

CS598HS Advanced Social & Information Networks

Information Diffusion in Grid-like Social Networks

Guangyu Dong, Randolph Hill, Vasileios Livanos

Department of Computer Science
University of Illinois at Urbana-Champaign

gdong2@illinois.edu, rwhill2@illinois.edu, livanos3@illinois.edu

December 13, 2017

Overview

1 Introduction

2 Theoretical Results

3 Simulation Results

Problem Statement

Problem Statement

- We study how fast information propagates through variants of grid-like social networks.

Problem Statement

- We study how fast information propagates through variants of grid-like social networks.
- We assume a fixed-weight, directed graph G representing the social network, with nodes as agents and edges that represent the interaction between two agents.

Problem Statement

- We study how fast information propagates through variants of grid-like social networks.
- We assume a fixed-weight, directed graph G representing the social network, with nodes as agents and edges that represent the interaction between two agents.
- Each agent i has a specific type $\theta_i \in [0, 1]$, and interacts with another agent j at a time-varying frequency $f_{ij}^*(t)$.

Problem Statement

- We study how fast information propagates through variants of grid-like social networks.
- We assume a fixed-weight, directed graph G representing the social network, with nodes as agents and edges that represent the interaction between two agents.
- Each agent i has a specific type $\theta_i \in [0, 1]$, and interacts with another agent j at a time-varying frequency $f_{ij}^*(t)$.
- In our model, the information can only be transmitted between agents of the same type, and that there exists a source of information for each different agent type.

Problem Statement

- We study how fast information propagates through variants of grid-like social networks.
- We assume a fixed-weight, directed graph G representing the social network, with nodes as agents and edges that represent the interaction between two agents.
- Each agent i has a specific type $\theta_i \in [0, 1]$, and interacts with another agent j at a time-varying frequency $f_{ij}^*(t)$.
- In our model, the information can only be transmitted between agents of the same type, and that there exists a source of information for each different agent type.
- Finally, there is a constant probability p that the information will leak through a single interaction. This implies that an agent j who interacts with frequency $f_{ij}^*(t)$ at time t with another agent i who has the information, has a probability $pf_{ij}^*(t)$ of getting the information.

Motivation

Motivation

- All people interact with other people in real social networks, and most of the time we procure information through this interaction.

Motivation

- All people interact with other people in real social networks, and most of the time we procure information through this interaction.
- This information could be for example which individual is a good doctor, or a good car mechanic, and procuring this information could drastically affect our quality of life.

- All people interact with other people in real social networks, and most of the time we procure information through this interaction.
- This information could be for example which individual is a good doctor, or a good car mechanic, and procuring this information could drastically affect our quality of life.
- Our problem is thus motivated by these examples, and we assume that there exist k external service providers, who provide services of different quality to agents of different type, but of the same quality to agents of the same type.

Motivation

- All people interact with other people in real social networks, and most of the time we procure information through this interaction.
- This information could be for example which individual is a good doctor, or a good car mechanic, and procuring this information could drastically affect our quality of life.
- Our problem is thus motivated by these examples, and we assume that there exist k external service providers, who provide services of different quality to agents of different type, but of the same quality to agents of the same type.
- Thus, the information that is propagated through the network is assumed to be the identity of the highest quality service provider for a specific type of agents.

Preliminaries

Preliminaries

- Our analysis focuses on 3 different graph structures:

Preliminaries

- Our analysis focuses on 3 different graph structures:
 - 1 Plain Grid (PG): A 4-regular graph where vertices are arranged in a grid pattern.

Preliminaries

- Our analysis focuses on 3 different graph structures:
 - ① Plain Grid (PG): A 4-regular graph where vertices are arranged in a grid pattern.
 - ② Unbiased Grid (UG): Similar to PG, but every node u forms one additional edge with some other node v , which is picked randomly, with probability proportional to $\frac{1}{d^2}$, where d is the Manhattan distance of u and v in the grid.

- Our analysis focuses on 3 different graph structures:
 - ① Plain Grid (PG): A 4-regular graph where vertices are arranged in a grid pattern.
 - ② Unbiased Grid (UG): Similar to PG, but every node u forms one additional edge with some other node v , which is picked randomly, with probability proportional to $\frac{1}{d^2}$, where d is the Manhattan distance of u and v in the grid.
 - ③ Biased Grid (BG): Similar to UG but the probability of an agent u forming an edge with another agent v of the same type is proportional to $\frac{b}{d^2}$. b is called the *bias* of the graph.

- Our analysis focuses on 3 different graph structures:
 - ① Plain Grid (PG): A 4-regular graph where vertices are arranged in a grid pattern.
 - ② Unbiased Grid (UG): Similar to PG, but every node u forms one additional edge with some other node v , which is picked randomly, with probability proportional to $\frac{1}{d^2}$, where d is the Manhattan distance of u and v in the grid.
 - ③ Biased Grid (BG): Similar to UG but the probability of an agent u forming an edge with another agent v of the same type is proportional to $\frac{b}{d^2}$. b is called the *bias* of the graph.
- We seek to compare the **Diffusion Rate (DR)** of information between these graphs, which is defined as the expected time it will take for the information to spread to all agents in the graph who can potentially learn it.

- Our analysis focuses on 3 different graph structures:
 - ① Plain Grid (PG): A 4-regular graph where vertices are arranged in a grid pattern.
 - ② Unbiased Grid (UG): Similar to PG, but every node u forms one additional edge with some other node v , which is picked randomly, with probability proportional to $\frac{1}{d^2}$, where d is the Manhattan distance of u and v in the grid.
 - ③ Biased Grid (BG): Similar to UG but the probability of an agent u forming an edge with another agent v of the same type is proportional to $\frac{b}{d^2}$. b is called the *bias* of the graph.
- We seek to compare the **Diffusion Rate (DR)** of information between these graphs, which is defined as the expected time it will take for the information to spread to all agents in the graph who can potentially learn it.
- We seek to both develop a model and obtain some theoretical results about the DR between these graphs, as well as perform several simulations that possibly confirm our theoretical analysis.

Overview

1 Introduction

2 Theoretical Results

3 Simulation Results

Plain Grid

- We model our system as a **Time Inhomogeneous Markov Chain**. While TIMCs are extremely important, not many theoretical results are known about them.

- We model our system as a **Time Inhomogeneous Markov Chain**. While TIMCs are extremely important, not many theoretical results are known about them.
- To make the problem tractable, we assume that any non-zero interaction between two agents is lower-bounded by a constant $\delta > 0$, meaning that agents cannot have an arbitrarily small interaction.

- We model our system as a **Time Inhomogeneous Markov Chain**. While TIMCs are extremely important, not many theoretical results are known about them.
- To make the problem tractable, we assume that any non-zero interaction between two agents is lower-bounded by a constant $\delta > 0$, meaning that agents cannot have an arbitrarily small interaction.

C_t : Possible Expansion Set

$$C_t = \{\{i, j\} \in E(G) \mid i \in \mathcal{I}(t), j \in \mathcal{F}(t), \theta_i = \theta_j\}$$

Plain Grid

- We model our system as a **Time Inhomogeneous Markov Chain**. While TIMCs are extremely important, not many theoretical results are known about them.
- To make the problem tractable, we assume that any non-zero interaction between two agents is lower-bounded by a constant $\delta > 0$, meaning that agents cannot have an arbitrarily small interaction.

C_t : Possible Expansion Set

$$C_t = \{\{i, j\} \in E(G) \mid i \in \mathcal{I}(t), j \in \mathcal{F}(t), \theta_i = \theta_j\}$$

Diffusion Rate

For any graph G

$$DR \leq n \sum_{t=1}^{\infty} \left(t \left(1 - (1 - \delta)^{|C_t|} \right) \prod_{k=1}^{t-1} (1 - \delta)^{|C_k|} \right)$$

Unbiased and Biased Grids

Unbiased and Biased Grids

Expected increase in $|C_t|$ in UG

$$\mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right] = \frac{\left(\sum_{k=2}^{2n} \frac{1}{k^2} \right) |\mathcal{I}(t)| \left(1 - \frac{|\mathcal{I}(t)|}{n} \right)}{N_\theta}$$

Unbiased and Biased Grids

Expected increase in $|C_t|$ in UG

$$\mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right] = \frac{\left(\sum_{k=2}^{2n} \frac{1}{k^2} \right) |\mathcal{I}(t)| \left(1 - \frac{|\mathcal{I}(t)|}{n} \right)}{N_\theta}$$

- We observe that the increase in DR between PG and UG is exponential!

Unbiased and Biased Grids

Expected increase in $|C_t|$ in UG

$$\mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right] = \frac{\left(\sum_{k=2}^{2n} \frac{1}{k^2} \right) |\mathcal{I}(t)| \left(1 - \frac{|\mathcal{I}(t)|}{n} \right)}{N_\theta}$$

- We observe that the increase in DR between PG and UG is exponential!

Expected increase in $|C_t|$ in BG

$$\mathbb{E} \left[|C_t^{BG}| - |C_t^{PG}| \right] = b \cdot \mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right]$$

Unbiased and Biased Grids

Expected increase in $|C_t|$ in UG

$$\mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right] = \frac{\left(\sum_{k=2}^{2n} \frac{1}{k^2} \right) |\mathcal{I}(t)| \left(1 - \frac{|\mathcal{I}(t)|}{n} \right)}{N_\theta}$$

- We observe that the increase in DR between PG and UG is exponential!

Expected increase in $|C_t|$ in BG

$$\mathbb{E} \left[|C_t^{BG}| - |C_t^{PG}| \right] = b \cdot \mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right]$$

- Similarly, the increase in DR between BG and UG is exponential, and is dependent on the bias b .

Unbiased and Biased Grids

Expected increase in $|C_t|$ in UG

$$\mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right] = \frac{\left(\sum_{k=2}^{2n} \frac{1}{k^2} \right) |\mathcal{I}(t)| \left(1 - \frac{|\mathcal{I}(t)|}{n} \right)}{N_\theta}$$

- We observe that the increase in DR between PG and UG is exponential!

Expected increase in $|C_t|$ in BG

$$\mathbb{E} \left[|C_t^{BG}| - |C_t^{PG}| \right] = b \cdot \mathbb{E} \left[|C_t^{UG}| - |C_t^{PG}| \right]$$

- Similarly, the increase in DR between BG and UG is exponential, and is dependent on the bias b .
- Specifically, for $b = 2$ we expect the difference in DR between BG and UG to be larger than the difference in DR between UG and PG.

Overview

- 1 Introduction
- 2 Theoretical Results
- 3 Simulation Results**

Diffusion Rate Simulations

QUESTIONS ?

