

# Cheat Sheet: Building Apps with RAG



**Skills**  
Network

**Estimated Reading Time: 5 minutes**

Gradio is an open-source Python package that allows for the quick building of an application interface. No JavaScript, CSS, or web hosting experience is required!

## Interface class core arguments

Gradio's Interface class wraps any arbitrary Python function. The interface class has the following three core arguments:

| Term    | Definition                                                                                                                                                                                                                                  |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fn      | Fn is the function to wrap. Each function parameter represents an input component, and the function's output should be either a single value or a tuple. Each element within the tuple corresponds directly to a specific output component. |
| inputs  | The Gradio component(s) to use for the inputs of the function. The number of inputs should match the number of arguments in the function.                                                                                                   |
| outputs | Outputs are the Gradio component(s) to use for the outputs of the function.                                                                                                                                                                 |

## Common input types

| Term          | Definition                                                                                                                                                                                                                                                                                                                    |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| checkbox      | A checkbox that can be set to True or False only.                                                                                                                                                                                                                                                                             |
| checkboxGroup | An input type that allows users to select multiple values from a predefined checkbox list.                                                                                                                                                                                                                                    |
| dropdown      | An input type that provides a dropdown list where, by default, one value can be selected. If <code>multiselect</code> is set to True, then one or more values can be selected.                                                                                                                                                |
| file          | An input type that allows a user to upload a file.                                                                                                                                                                                                                                                                            |
| image         | An input type that allows the user to select or upload an image.                                                                                                                                                                                                                                                              |
| radio         | An input type that forces the user to choose one value.                                                                                                                                                                                                                                                                       |
| slider        | An input type that provides a slider where a value must be selected between a minimum and a maximum range. The <code>value</code> parameter defines the default value, and <code>step</code> provides the increment value. Setting the minimum, maximum, and <code>step</code> values to integers will select integer values. |
| textbox       | An expandible text box that allows the user to type in text.                                                                                                                                                                                                                                                                  |

## Common output types

| Term    | Definition                                                                                                                                                                                                       |
|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| textbox | An expandible text box that allows the user to type in text.                                                                                                                                                     |
| label   | A type typically used for classification models. Can output the classes along with their predicted probabilities. You can control the number of output classes using the <code>num_top_classes</code> parameter. |

## Launching the application

Use the `launch()` method to launch the application. This method starts a simple web server that serves the interface. If you set `share=True` in `launch()`, you can share the application with the rest of the world. The system will set up a public URL allowing anyone worldwide to access your application. Users can interact with your app through this URL, while all computations run on your local machine.

## Author

[Wojciech "Victor" Fulmyk](#)



**Skills** Network