

Capturing from Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

udp

No.	Time	Source	Destination	Protocol	Length	Info
259	4.177635600	172.25.53.2	239.255.255.250	SSDP	179	M-SEARCH * HTTP/1.1
262	4.254781300	fe80::a617:52ff:fe1...	ff02::1:2	DHCPv6	116	Solicit XID: 0x9ee620 [ROOT-ONLY DOMAIN NAME]CID: 00030001a41752114b01
264	4.255186100	172.25.55.130	255.255.255.255	UDP	82	63842 → 1947 Len=40
265	4.255237300	172.25.55.130	172.25.63.255	UDP	82	63841 → 1947 Len=40
269	4.356931300	172.25.55.16	224.2.2.2	UDP	72	64039 → 8995 Len=30
270	4.357558000	172.25.54.240	224.77.77.77	UDP	155	53845 → 12177 Len=113
277	4.492887700	172.25.50.69	239.255.255.250	SSDP	212	M-SEARCH * HTTP/1.1
278	4.492889500	172.25.50.69	239.255.255.250	SSDP	212	M-SEARCH * HTTP/1.1
279	4.492891300	172.25.51.35	224.0.0.251	MQMS	110	Standard query 0x0000 A Android_WQ6U7WC2.local, "QM" question AAAA Android_WQ6U7WC2.local, "QM" question
280	4.492892500	172.25.50.126	239.255.255.250	SSDP	179	M-SEARCH * HTTP/1.1
284	4.512151700	172.25.48.216	224.0.0.252	LLMNR	64	Standard query 0x4082 ANY UDAY
287	4.512438400	172.25.48.216	239.255.255.250	SSDP	540	NOTIFY * HTTP/1.1
288	4.512439700	172.25.48.216	224.0.0.252	LLMNR	64	Standard query 0x4082 ANY UDAY
296	4.708125400	172.25.48.216	239.255.255.250	SSDP	548	NOTIFY * HTTP/1.1
297	4.708126200	172.25.51.239	239.255.255.250	UDP	207	10151 → 42974 Len=165
301	4.770050800	172.25.55.130	172.25.63.255	UDP	82	63841 → 1947 Len=40
309	5.044633500	172.25.55.85	20.202.41.0	STUN	62	Binding Indication
325	7.857331800	172.25.55.85	20.202.41.16	STUN	62	Binding Indication
329	10.057411300	172.25.55.85	20.202.41.0	STUN	62	Binding Indication

> Frame 270: Packet, 155 bytes on wire (1240 bits), 155 bytes captured (1240 bits) on interface \Device\NPF...
> Ethernet II, Src: AzureWaveTec_ad:b2:1d (b4:8c:94:ad:b2:1d), Dst: IPv4cast_Ad:4d:4d (01:00:5e:4d:4d:4d)
> Internet Protocol Version 4, Src: 172.25.54.240, Dst: 224.77.77.77
> User Datagram Protocol, Src Port: 53845, Dst Port: 12177
> Data (113 bytes)

0000 01 00 5e 4d 4d 4d b4 8c 9d ad b2 1d 08 00 45 00 --MM... ..E-
0010 00 8d 25 ee 00 00 01 11 82 ce ac 19 36 f0 e0 4d --%.....6..M
0020 4d 4d d2 55 2f 91 00 79 a7 a9 3c 41 53 55 53 5f MM-U/..y...KASUS-
0030 41 52 4d 4f 55 52 59 5f 43 52 41 54 45 3e 0a 20 ARNDURY_CRATE>
0040 20 20 20 3c 4c 41 4e 20 50 6f 72 74 3d 22 31 32 <LAN Port="12
0050 31 37 37 22 20 43 75 73 49 44 3d 22 42 37 37 39 177" Cus ID="B779
0060 35 32 35 44 2d 31 33 34 34 2d 34 31 35 32 2d 38 5250-134 4-4152-8
0070 34 31 32 2d 46 42 36 35 46 44 35 38 42 41 46 43 412-FB65 F098BAFC
0080 22 2f 3e 0a 3c 2f 41 53 55 53 5f 41 52 4d 4f 55 */></AS US_ARNDU
0090 52 59 5f 43 52 41 54 45 3e 0a 00 RY_CRATE >

Capturing from Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

tcp

No.	Time	Source	Destination	Protocol	Length	Info
4710	47.909136700	146.59.55.107	172.25.55.85	TCP	60	443 → 51498 [RST] Seq=1 Win=6364672 Len=0
4719	47.942154400	172.25.55.85	20.195.85.193	TCP	54	51435 → 443 [ACK] Seq=150 Ack=421 Win=252 Len=0
4750	48.639979900	172.64.148.235	172.25.55.85	TLSv1.2	78	Application Data
4751	48.640466300	172.25.55.85	172.64.148.235	TLSv1.2	82	Application Data
4760	48.678432100	172.64.148.235	172.25.55.85	TCP	60	443 → 55907 [ACK] Seq=73 Ack=85 Win=16 Len=0
4795	48.954881000	172.25.55.85	51.222.43.134	TCP	66	51499 → 443 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
4808	49.262604300	51.222.43.134	172.25.55.85	TCP	66	443 → 51499 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
4809	49.262668500	172.25.55.85	51.222.43.134	TCP	54	51499 → 443 [ACK] Seq=1 Ack=1 Win=65280 Len=0
4810	49.266893200	172.25.55.85	51.222.43.134	TLSv1	492	Client Hello (SNI=ultraviewer)
4811	49.276518500	51.222.43.134	172.25.55.85	TCP	60	443 → 51499 [RST] Seq=1 Win=6364672 Len=0
4881	50.218928200	172.25.55.85	142.251.43.35	TCP	66	51500 → 80 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
4882	50.225652500	142.251.43.35	172.25.55.85	TCP	66	80 → 51500 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=1412 SACK_PERM WS=256
4883	50.225738700	172.25.55.85	142.251.43.35	TCP	54	51500 → 80 [ACK] Seq=1 Ack=1 Win=65280 Len=0
4884	50.226382600	172.25.55.85	142.251.43.35	HTTP	254	GET /r/r4.cr1 HTTP/1.1
4885	50.226256100	142.251.43.35	172.25.55.85	TCP	60	80 → 51500 [ACK] Seq=1 Ack=201 Win=269568 Len=0
4886	50.240625900	142.251.43.35	172.25.55.85	HTTP	276	HTTP/1.1 304 Not Modified
4887	50.286161400	172.25.55.85	142.251.43.35	TCP	54	51500 → 80 [ACK] Seq=201 Ack=223 Win=65280 Len=0
4888	50.303102600	172.25.55.85	42.56.32.170	TCP	66	51501 → 443 [SYN] Seq=0 Win=65535 Len=0 MSS=1460 WS=256 SACK_PERM
4896	50.424759200	172.25.55.85	172.217.116.4	TCP	55	[TCP Keep-Alive] 64439 → 443 [ACK] Seq=517 Ack=6319 Win=255 Len=1

> Frame 4885: Packet, 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface \Device\NPF...
> Ethernet II, Src: Cisco_6d:c0:d7 (24:d5:e4:6d:c0:d7), Dst: LiteonTechno_7f:cb:95 (14:b5:cd:7f:cb:95)
> Internet Protocol Version 4, Src: 142.251.43.35, Dst: 172.25.55.85
> Transmission Control Protocol, Src Port: 80, Dst Port: 51500, Seq: 1, Ack: 201, Len: 0

0000 14 b5 cd 7f cb 95 24 d5 e4 6d c0 d7 08 00 45 00\$.m...E-
0010 00 28 25 45 00 00 7a 06 7d 7e 8e fb 2b 23 ac 19 (NE.z.)...+..
0020 37 55 00 50 c9 2c f6 6a d7 af 1e 83 28 5d 50 10 7U P...j...[P-
0030 04 1d 2f b3 00 00 00 00 00 00 00 00 00 00 00 00 ..//.....