Response to the reviewers for the article entitled *Algorithmic aspects of data-driven computational damage mechanics and introduction of Lipschitz regularization*

October 19, 2026

We thank the reviewers for their careful reading of the manuscript and for the constructive comments. The feedback has led to significant improvements in both the depth and clarity of the work through the addition of new sections and appendices. We have addressed all the points raised, and provide a point-by-point response below. For ease of reference, Reviewer comments are reproduced in black, followed by our responses in blue. All changes in the revised manuscript are highlighted: additions are shown in blue and deletions in red.

Common response regarding Section 3.1

The reviewers' comments indicate that Section 3.1 was insufficiently motivated in the submitted version. Accordingly, the section has been rewritten with an explicit statement of its purpose and scope.

Before a length scale is introduced, it must be established that any localization-band width observed in the regularized formulation of Sections 4,5 is a consequence of the regularization itself and not of the DDCM algorithm. The DDCM algorithm, when driven by a local database, must therefore reproduce the characteristic behaviors of local damage models - mesh dependence of the localization width, and softening-induced instabilities such as snapback. Both must be shown to be handled correctly by the DDCM algorithm before a regularized formulation is proposed. This is the purpose of Section 3.1, now stated explicitly at lines 132–137 of the unmarked manuscript.

A second concern is that the performance of the DDCM solver also depends on the resolution of the database, particularly under non-homogeneous strain increments within a load step. It is therefore necessary to determine whether a given pathology observed in a DDCM setting with a local model is a consequence of the algorithm itself or of insufficient database resolution. One way to isolate algorithmic effects from database sampling artifacts, and to make an analytical treatment tractable, is to replace the database by the underlying constitutive model. This is the motivation for using the model directly during the material update, now stated at lines 138–141 of the unmarked manuscript. On this basis, three cases are studied in Section 3.1 to analyze the effect of the hyperparameter and of the choice of solver (arc-length vs. direct displacement control): the hyperparameter choice under continuous evolution, the hyperparameter choice under snapback, and the continuation strategy under snapback. These three cases together establish the ingredients required for DDCM to inherit the correct behavior of a local damage model.

Other general modifications

In addition to the items detailed below, the revision includes the following clarifications, made at our own initiative to support the arguments of Section 3.1 and the 2D examples:

- The three cases of Section 3.1 are now summarized in Table 1, which gathers the regime, hyper-parameter choices, and outcomes in one place.
- The behavior under arc-length control without snapback (case 1 driven by arc length) is now treated explicitly: $C_2 > -E/N$ is required for convergence, so both $C_2 = m$ and $C_2 = E$ converge under arc length, with $C_2 = E$ approaching a spectral radius close to one. This closes the (snapback vs. no snapback) $\times$ (arc-length vs. displacement control) grid.
- Section 6.1 and the Discussion now acknowledge that the formulation does not include a tension-compression split of the strain energy, with references to [1, 4]. For the notched bar this is immaterial because the loading produces a purely tensile stress state along the crack path; the implementation of a tension-compression split in the data-driven setting is identified as an open problem in the Discussion.
- In the lip-mesh representation in Figure 12 of the revised manuscript, the strains on the lip-mesh read $\epsilon_1, \epsilon_2, \ldots \epsilon_{n-2}, \epsilon_{n-1}$ as opposed to $\epsilon_1, \epsilon_2, \ldots \epsilon_{n-1}, \epsilon_n$ in the old manuscript.

Reviewer 1

In this paper, the authors adopt the framework of data-driven damage mechanics in which the solution to a boundary value problem is the minimization of a distance between strain and stress pairs with respect to a database subject to the stress-strain pairs satisfying equilibrium. Specifically for this paper, the authors consider the case of damage mechanics in which the stress-strain pairs in the database are history dependent and can exhibit softening. Authors show that the distance function must account for the softening in order to converge. Additionally, the paper tackles the problem of localization. Damage mechanics problems are known to localize to a single element. The regularization introduced is to restrict the norm of the strain to a certain interval. This Lipschitz regularization operates on the strain field because of the nature of the data-driven framework (which must work on the stress-strain field rather than on the elements of the material database), and introduces a length scale that prevents localization of the damage field. The paper is meritorious but some of the details are cumbersome to read and understand and the figure layout is also cumbersome.

1. The role of stress-strain history is not well defined. For example in Eqs. 10, 11 the constitutive model assumes a simple function between strain and stress, no history dependence.

   Response. We agree, and have revised the opening of Section 3 to make history dependence explicit at the level of the general equations, with pointers to the sections where its content is given. Specifically, the material update is now written as

   $$(\epsilon^*, \sigma^*) = \arg \min_{(\tilde{\epsilon^*}, \tilde{\sigma^*})} d(\boldsymbol{\epsilon}, \boldsymbol{\sigma}, \tilde{\epsilon^*}, \tilde{\sigma^*}) \quad \text{s.t.} \quad \tilde{\sigma^*} = f(\tilde{\epsilon^*}; \mathcal{H}),$$

   where $\mathcal{H}$ is a history variable carried from the converged solution of the previous load step, whose role is to encode irreversibility and to select the appropriate branch of the (multi-valued) softening response. The content of $\mathcal{H}$ and the branch-selection logic implemented by $f(\cdot; \mathcal{H})$ depend on the setting:

   - In the analytical study of Section 3.1, $\mathcal{H}$ is held fixed within a load step through the *branch restriction* (Definition 1): the mechanical and material iterates are confined to the branch each element occupies at the beginning of the step, so that the fixed-point behavior of the alternating minimization on an already bifurcated branch can be isolated. Equations 10 and 11 of the original submission describe this restricted setting.
   - In 1D (Section 3.2), $\mathcal{H} = (d^n, \epsilon^n_{\max})$ is updated at convergence of each load step and selects, through $f(\cdot; \mathcal{H})$, among the elastic (degraded) branch, the softening branch, and saturation at $d_{\max}$.
   - In 2D (Section 3.3.1), $\mathcal{H} = (d^n, \mathcal{H}^n)$ with $\mathcal{H}^n = \max_{k \le n} \psi_0(\boldsymbol{\epsilon}^k)$, and the branch selection is given there and specified algorithmically in Algorithm 2 (Appendix B).

   History dependence is therefore no longer hidden in the equations preceding Section 3.1, and the restricted character of the analytical study is stated where it is used.

2. 1D example Fig 1 also shows no history dependence. Shouldn't unloading fall back on a line with reduced slope like Fig 10? It seems that this is what is meant by 'elements are forced to stay in the elastic or softening branches' thereby removing any history dependence in this example.

   Response. The reviewer is correct. The intention of Section 3.1 is to isolate the fixed-point behavior of the alternating minimization on a given bifurcated branch; to do so, elements are restricted to the branch they occupy at the beginning of the load step. This is now stated explicitly as the *branch restriction* together with two admissibility constraints (irreversibility and peak cap, Definition 1). Branch restriction is used only for the analytical study in Section 3.1 and is removed from Section 3.2 onward, where the branch is selected freely by Algorithm 2.

3. Fig 2, Fig 3, Fig 4: There is no need to introduce a figure with just a legend, there is also no need to have figure which is just the zoomed in of a panel in Fig 3. These three figures can easily be consolidated in one. Please see below for the response.

4. Similar comment for figs 5 and 6.

   Response. We thank the reviewer. The figure structure of Section 3.1 has been reorganized as follows:

   - Two figures now present the evolution of the normalized distance functional with iterations (Figures 3 and 6), together covering the four cases studied in Section 3.1 and the additional starting point of Appendix D. The distance functional is now the primary vehicle for conveying convergence behavior, as also suggested by the reviewer in a later comment.
   - Three figures in the main text present the trajectories of the iterates on the σ–ϵ plane, as a complementary view that exposes the mechanism underlying each case (direction of the first increments, saturation at the peak or irreversibility bound).
   - The legend-only figure (former Figure 2) has been removed. Its content - mechanical states as crosses, material states as circles, elastic branch in blue, damage branch in red (matching Figure 2) - is now stated in the text of Section 3.1 before the first trajectory figure.
   - The two zoom figures (former Figures 4 and 6) have been removed. The information they carried - the direction of the first strain increments and the near-coincidence of successive iterates - is now described in prose, together with the distance-evolution plots.

   A common color scheme is used throughout: elements on the elastic branch in blue and the element on the damage branch in red, matching Figure 2. Mechanical and material states are distinguished by markers (crosses and circles), and the initial point is marked with a black asterisk.

5. Fig 9 has barely any information.

   Response. We have removed this figure. The loading and the geometry are directly described in the prose in Section 3.2, lines 405–407.

6. Overall I had a very hard time following the argument surrounding the convergence plots in Figs 3-6 and corresponding text in the article. It seems that a more direct visualization of Eq. 15 and 16 would work better. Also, normalizing with respect to the true value would help seeing when is the algorithm pushing the softening branch toward lower strains (below the max stress strain). How are the branches forced to stay within their respective branches? That's not clear at all from Eq 12. To be frank, I had a really hard time with this example and corresponding plots. To me, this example is almost better as supplemental material, as it distracts from the more valuable core of the paper stemming from the 1D problem with body force and the 2D problems.

   Response. We thank the reviewer for this suggestion. Section 3.1 has been substantially rewritten, both to clarify the *branch restriction* and the admissibility constraints that complement it (Definition 1), and to change the way convergence is reported. The convergence behavior for each case is now first conveyed through the evolution of the distance functional governed by the iterates from Eq. 17 (Figures 3 and 6), which is the direct visualization the reviewer suggested. We normalize the distance by the first-iteration value, so that all cases start at one and their decay rates can be compared on a single plot. The trajectory plots are retained as a complementary view that exposes the underlying mechanism (direction of the first mechanical and material increments, saturation at the peak or irreversibility bound), but they are no longer the primary vehicle for conveying convergence.

Regarding the question of iterates pushing below the maximum-stress strain: the admissibility constraints in Definition 1 (irreversibility and the peak cap) explicitly prevent this (it prevents the material state of the damaging element from assuming strain levels smaller than the initial point). Section 3.1 now shows that, when either constraint becomes active, the AM iteration leaves the regime governed by the matrix $\boldsymbol{AC}$, and that this constraint-saturation mechanism is precisely what causes the displacement-controlled snapback case to stagnate at a finite distance rather than diverge.

The analysis is separated into three cases to isolate the role of the hyper-parameter choice and of the continuation strategy. As shown in Section 3.3, the absence of either ingredient produces a diffuse damage profile in 2D even with a local database, i.e. a spurious algorithmic effect that would otherwise be indistinguishable from a true regularization length. For this reason we have kept the convergence study in the main text rather than moving it to supplementary material: without it, a localization width observed in Sections 4 and 5 could not be attributed unambiguously to the regularization. The common response at the top of this document states this motivation up front.

7. 1D Problem with body force. This problem actually introduces the history dependence, as evidenced from Fig 10. However, how is the history dependence handled still not clear. As mentioned before in comment [1], this is a major problem with the current expositon of the method.

   Response. We agree, and this concern is tied to our response to comment [1]. As noted there, the opening of Section 3 now writes the constitutive relation as $\tilde{\sigma}^* = f(\tilde{\epsilon}^*; \mathcal{H})$, with $\mathcal{H}$ a history variable carried from the converged solution of the previous load step. The present comment prompted us to make the content of $\mathcal{H}$ and the logic encoded in $f(\cdot; \mathcal{H})$ explicit in the main text, in two dedicated subsubsections:

   - Section 3.2 (*Material update*, 1D). The state variables are $(d^n, \epsilon^n_{\max})$, updated at convergence of each load step; the three-case classification (unloading, reloading below the yield point, damaging) is detailed in Section 3.3.1 with the 2D treatment and reduces to the 1D case through Eqs. 25-26.
   - Section 3.3.1 (*Material update*, 2D). The state variables are $(d^n, \mathcal{H}^n)$ with $\mathcal{H}^n = \max_{k \le n} \psi_0(\boldsymbol{\epsilon}^k)$. The classification follows the same three cases. When neither the elastic nor the damage branch is feasible, the cusp at the intersection of the elastic branch with the damage branch is returned, together with the tangent corresponding to the damage branch.

   The full per-Gauss-point procedure, including the Newton iteration on the softening branch and the admissibility checks (irreversibility and the peak cap of Definition 1), is given as Algorithm 2 in Appendix B. Together, the revised Section 3 opening and these two subsubsections make the handling of history dependence explicit in the main text, as the reviewer suggested.

8. The rest of the paper is actually much easier to follow, in particular it is clear how the Lipschitz regularization is introduced as a constraint on the norm of the strain gradient. The arc-length is not discussed in detail in the main text but it is well described in Appendix E, where Eq. 61 expresses the constraint in terms of the strain mechanical field. Thus, these extra constraints and regularizations are in terms of the mechanical strain field. The question about how to handle the history dependence on the material stress-strain pairs still bothers me because it is not well covered in the main text.

   Response. Beyond the Section 3.2 and 3.3 material-update subsections discussed in our response to comment [7], an introductory paragraph has been added at the start of Appendix A that links Algorithm 2 to those sections. Together with the state variables $(d^n, \mathcal{H}^n)$ carried across load steps, this makes the handling of history dependence explicit.

Reviewer 2

The paper presents a discussion of the data driven computational approach in the presence of damage localization. To simplify the analysis, instead of material databases, the Authors employ the simple elastic-damage constitutive model. This assumption weakens a bit the paper and the extension of the findings to the real DD method is quite questionable. Still there is an interest in the developed analysis. However, in the reviewer opinion, there are some points that deserve further improvements before possible publication. Hereafter my critical remarks/questions.

We thank the reviewer for the comment. The motivation for substituting the database with an underlying model has now been presented in Section 3.1. As stated in the common response, the intent of this substitution is to analyze the convergence properties of the DDCM algorithm analytically in a simple 1D setting, which cannot be carried out directly with a finite database.

The case of the explicit model is a "best case scenario" check for DDCM: failure of the DDCM algorithm (for instance, to properly localize) with the substitution will necessarily imply its eventual failure with a finite database, since a finite database introduces further sources of error (sampling, limited coverage of the state space) that can only degrade the behavior observed here. The three cases examined in Section 3.1 therefore establish the ingredients necessary in the DDCM setting, and these conclusions are verified first in Section 3.2 (1D bar with body force, with branch restriction removed) and then in the 2D setting of Section 3.3.

The algorithmic criteria identified in this work are therefore expected to carry over to the finite-database setting; the only remaining source of discrepancy between the two settings is the database itself (sampling density, phase-space coverage), whose systematic study is left as future work.

1. A first major concern is about the structure of the paper which in my opinion should be significantly revised and improved. In the main test, reference is made to equations coming several pages after. Similarly, the appendices are not sequentially arranged according to their use in the test. Figure 10 is referenced at the beginning of the paper, etc... Algorithm 1 suddenly appears at page 20 without any explanation. At page 24 the values of Yc and k are given, but the model was not introduced at this point of the paper. These are some examples of the inconsistency of the structure of the manuscript.

   Response. We thank the reviewer and agree that the structure needed revision. Section 3 has been substantially reorganized:

   - Algorithm 1 is now presented together with Section 3.2, where it is first exercised.

- The 1D linear-softening model, serving here as the implicit database, is introduced at the beginning of Section 3, with its parameters stated in Section 3.1 before the convergence study. The corresponding figure (Figure 1, formerly Figure 10) is also brought forward to this point.
- The 2D degradation function and damage-driving energy density are introduced in Section 3.3, where the 2D case is first considered, so that Y_c and k are no longer referenced before definition.
- The appendices have been reordered to follow their first citation in the text.

2. Another crucial point concerns the first 1D example (page 8 and 9). In the test it is explained that the procedure converges at slow rate, however there is no common point between mechanical and material states (see figure 3a). What does this mean? It seems a proof of failure of the procedure: please explain.

   Response. We thank the reviewer for raising this point; it allows us to clarify what Section 3.1 is designed to establish and what Figure 4a (formerly Figure 3a) is showing.

   Section 3.1 performs a spectral analysis of the AM fixed-point map on an already-bifurcated branch. Its central deliverable is an analytical relation between the pair (hyper-parameter, continuation strategy) and the rate at which the mechanical and material states approach each other.

   Figure 4a corresponds to the case ($C_2 = E$, displacement control, no snapback). For this case the analysis predicts that the composed update operator **AC** has spectral radius $\rho \approx 0.9994$: the iteration is formally contractive, but at a rate indistinguishable from stagnation on the time scale of a load step. Figure 4a is the empirical confirmation of this prediction. The mechanical and material states would eventually meet, but only after a prohibitive number of iterations. This is therefore not a failure of the DDCM procedure, but a predicted diagnostic for a specific hyper-parameter choice. In fact, the figure exposes a practical pitfall: standard DDCM implementations declare convergence when successive iterates cease to move, and under $C_2 = E$ with the analytical database used here, the iterates become near-stationary long before the mechanical–material gap has closed. In a finite-database implementation, this behavior would be even more subtle: since $\rho \approx 0.9994$ implies a slow variation of the mechanical state between iterations, the nearest-neighbor material projection would select the same database point for many consecutive iterations, and the stopping criterion would then falsely declare convergence well before the distance functional decreases to close to zero. This diagnosis is only visible when the exact spectral radius is known. To make this explicit, the normalized distance functional has been added in Figure 3, with a zoomed panel (Figure 3b) showing the residual decaying at a slope consistent with $\rho \approx 0.9994$.

   The same spectral analysis delivers the complete picture across the (hyper-parameter, continuation strategy) combinations examined in Section 3.1 and summarized in Table 1:

   - *No snapback, displacement control,* $C_2 = E$: $\rho \approx 0.9994$. Converges, unusably (Figure 3a).
   - *No snapback, displacement control,* $C_2 = m$: $\rho = 1/2$. Converges in a handful of iterations.
   - *Snapback, arc-length,* $C_2 = E$: $\rho \approx 1.029 > 1$. The iteration is non-contractive. It does not diverge, but freezes at a finite mechanical–material gap, because the material projection saturates at the peak stress (constraint 2) and the iteration leaves the regime governed by **AC**.
   - *Snapback, arc-length,* $C_2 = m$: $\rho = 1/2$. Converges in a handful of iterations.

   Beyond these four cases, the characteristic polynomial of **AC** in the arc-length setting yields a closed-form bound equation (24), a derivation made possible by the substitution of the discrete database by the underlying analytical model: under snapback, the AM fixed-point map is contractive only when C_2 is strictly negative ($< -E/N$). No positive hyper-parameter is admissible, and $C_2 = m$ is the unique interpretable derivative of the constitutive response that lies in the admissible range. Figure 3a is therefore one entry in a complete analytical map, and the behavior it displays is the predicted signature of the only $C_2 > 0$ case that even converges in principle.

3. Figures 3, 4, 5, 6 are unclear. If they represent the global response of the whole bar, one would expect just one blue curve of material states and one red of mechanical states. If they refer to the different elements (purple or teal inside the bar), this must be visible. Also, the initial and final points should be marked.

   Response. In Section 3.1, the 1D bar is meshed with $N + 1$ elements, each carrying its own mechanical and material state. Figures 4, 5 and 7 of the revised manuscript present the trajectories of these mechanical and material states during the DDCM iterations within a single load step. Since the damage is localized to one element and all remaining elements unload uniformly, each figure shows the trajectory of two representative elements: one on the elastic branch and the damaging one. These trajectories therefore characterize the local convergence behavior of the DDCM algorithm, not the global response of the bar. The former Figures 4 and 6 (zoom panels of the trajectory figures) have been removed; the information they carried - the direction of the first strain increments and the near-coincidence of successive iterates - is now summarized in prose and in the normalized distance plot (Figure 3), introduced in the response to the previous comment.

   The trajectory figures now use a single, uniform color scheme: states associated with elements on the elastic branch in blue, states associated with the damaging element in red, matching Figure 2. Mechanical states are drawn as crosses and material states as circles. Initial iterates are marked with black asterisks. Final iterates are not separately marked, since a meaningful final state is defined only when the algorithm converges; in that case it coincides with the intersection of the mechanical and material trajectories and is directly visible in the figure. For the non-converging cases, no distinct final state exists. This convention is stated in the text of Section 3.1 before the first trajectory figure.

4. The 2D example selected exhibits an extremely brittle behaviour which prevents to follow the evolution of damage with some detail (see figure 12 and 13). Maybe another geometry would help to appreciate the mesh dependence and the following regularization. The sentence at page 16 (line 445) is not justified by the comparison between fig 12d and 12e.

   Response. We thank the reviewer for the suggestion. The 2D notch example in Section 3.3 is designed to verify, in a 2D setting, the necessity conditions established analytically in 1D in Section 3.1; it is a complement to the 1D analysis, not a stand-alone 2D study. The severe snapback it produces is in fact what makes it the appropriate test case: according to the 1D analysis, the choice of hyper-parameter and continuation strategy matters most precisely

in the snapback regime, so a sufficiently brittle 2D example is required to expose the differences between scenarios. A gentler geometry would simply hide the behavior that this section is intended to isolate.

To make this role explicit, three *Scenarios* are now defined (Definition 3), each corresponding to a case from Section 3.1, and the discussion of Figure 11 is structured scenario by scenario. In Scenarios 1 and 2 the algorithm fails before damage has had the opportunity to evolve significantly, consistent with the loss of contractivity derived in Section 3.1. In Scenario 3, the full load-displacement response (Figure 10) and the mesh-dependent localized damage band (Figure 11c,d) are tracked all the way through the snapback; the damage evolution is in fact fully visible once the appropriate hyper-parameter and arc-length continuation are used. The symbols on each load–displacement curve in Figure 10 (circle, square, star, triangle) mark the final converged load step for the corresponding scenario, and the same symbols appear at the bottom of each panel of Figure 11, so that each damage distribution can be read directly against the load step at which it was obtained. The former panel 12d of the submitted version has been removed as part of this restructuring, and the sentence that depended on comparing 12d with 12e has been rewritten accordingly.

5. Section 4 - Why is the mesh adopted for the strain called "dual" with respect to the one used for displacements? The same order of interpolation is used for displacement and strain, does this ensure the fulfilment of the Babuska-Brezzi conditions? What are the consequences of these interpolations?

   Response. We thank the reviewer. Following the terminology of [2], the auxiliary mesh is now called the *lip-mesh* throughout. The term "dual" was used only because its vertices are the centroids of the primal mesh; it carries no further meaning. A stability analysis of the displacement-strain pairing is provided in Appendix F.1: writing the compatibility constraint $\boldsymbol{\epsilon} = \boldsymbol{B}\boldsymbol{u}$ in weak form, $\int \mu(\varepsilon - Bu)\, dx = 0$ with μ chosen as a sum of Diracs at the centroids of the primal mesh, recovers the discrete system in use. The resulting inf-sup constant then satisfies

$$\beta = \inf_{\boldsymbol{\Lambda}} \sup_{\boldsymbol{U}} \frac{b^h(\boldsymbol{U}, \boldsymbol{\Lambda})}{\|\boldsymbol{U}\|\, \|\boldsymbol{\Lambda}\|} \geq 1$$

   independently of the mesh, so the displacement-strain pairing satisfies the Babuska-Brezzi condition and no spurious modes arise from this interpolation choice. A separate inf-sup condition arises from the active-set multipliers that enforce the Lipschitz inequality; a formal analysis of this active-set formulation is beyond the scope of this article, and the stability of the discretized problem is instead assessed numerically through mesh refinement, as reported in Sections 4 and 5.

6. The removal of the constraint in order to reach failure (zero force), see fig 15, is artificial and put in evidence a non-physical behavior of the model. Also, in the L shape example failure cannot be reached. What is the reason of this?

   Response. We agree that the deactivation of the constraint at $d = 1$ is an artificial numerical device rather than a physical statement, and this is now stated plainly in Section 4.2. The deactivation is tractable in 1D because failure is contained in a single element and the discontinuity it introduces does not propagate; in 2D it causes convergence difficulties, and it has been replaced in Section 5 by a principled alternative: a damage-dependent weakening of the constraint combined with a log-barrier formulation. The 2D results reported in Sections 5 and 6 therefore rely on this smooth alternative, not on the hard deactivation.

   Regarding why the L-beam simulation cannot be driven to complete failure: the L-beam develops a compressive region on the right side of the beam under the applied loading. The present formulation does not include a tension-compression split of the strain energy (see [1, 4]), so under purely compressive stress the model allows the damage variable to grow, which is unphysical. The simulation is therefore terminated at the load step where damage in the compressive zone begins to increase. This is now stated explicitly in Section 6.2. By contrast, the notched bar of Section 6.1 is a pure tension problem; no compressive region develops there, and the simulation can therefore be driven all the way to failure. The implementation of a tension-compression split in the data-driven setting is identified as an open problem in the Discussion.

7. *The length lc is fixed in an arbitrary way: could you please discuss the issue?*

   Response. We agree that the choice of ℓ_c warranted more discussion. ℓ_c sets the width of the regularized localization band and plays the same role as the length-scale parameter in gradient-damage and phase-field formulations. In the DDCM-Lipschitz setting considered here, it has in addition a direct energetic interpretation: as reported in [3, eq. 55],

$$G_c = Y_c \ell_c,$$

   so that ℓ_c is determined by the pair (peak stress through Y_c/k, dissipated energy from damage initiation to complete failure). This relation is now stated in Section 4.1.

   The specific values of ℓ_c used in the examples were chosen for illustration rather than calibrated against a specific fracture energy; in practice, ℓ_c would be fixed by the measured G_c and peak stress of the material. We also note that in the 2D case the effective regularization length is smaller than ℓ_c itself, because the constraint is weakened by the damage-dependent function g (Section 6.1), so that the observed band width is narrower than ℓ_c alone would predict.

8. *The claim at page 28, line 713 that oscillation are reduced is not justified by the results.*

   Response. We agree. The unsupported claim has been removed. The Discussion now states that the comparison with the strict-inequality formulation is not tested here (lines 738–740):

   > "Whether the log-barrier reduces the oscillation amplitude relative to the strict-inequality formulation is not tested here. It is nevertheless plausible that alternative choices of the barrier parameter may further smooth the global response, a possibility that was not explored here."

Minor remarks:

1. In figure 2 one cannot distinguish the two arrows

   Response. The former Figure 2 has been removed (see our response to Reviewer 1, comments 3 and 4). The conventions it illustrated are now stated in the text of Section 3.1.

2. At page 7, line 214, Blue should be purple

   Response. We thank the reviewer. The color scheme has been unified throughout Section 3.1: blue for the elastic branch and red for the damage branch, matching Figure 2. The sentence in question has been rewritten.

3. At page 22, line 577 the elements cannot be called constant strain triangles since the strain is linearly interpolated

   Response. We agree. The lip-mesh elements are now described as piecewise-affine triangles. The term "constant strain triangles" is kept only for the primal displacement mesh, where the strain is indeed constant.

4. Pag 23, line 607, the name of appendix lacks

   Response. Corrected. The references at L923 now explicitly name the appendices: "Appendix B" for the tangent matrix and "Appendix E" for the arc-length solver.

5. Ref 31 is incomplete

   Response. Corrected. Reference 31 is now Ref. 33, and includes the full publication details (URL, ISBN).

References

[1] Hanen Amor, Jean-Jacques Marigo, and Corrado Maurini. "Regularized formulation of the variational brittle fracture with unilateral contact: Numerical experiments". In: *Journal of the Mechanics and Physics of Solids* 57.8 (2009), pp. 1209–1229.

[2] N. Chevaugeon and N. Moes. "Lipschitz regularization for fracture: the Lip-field approach". In: *Computer Methods in Applied Mechanics and Engineering* 160 (2021), p. 115644. DOI: 10.1016/j.cma.2022.115644.

[3] Vasudevan Kamasamudram and Laurent Stainier. "A strain based Lipschitz regularization for materials undergoing damage". In: *Comptes Rendus - Mecanique* 351 (2023), pp. 125–149. DOI: 10.5802/CRMECA.176/.

[4] Christian Miehe, Martina Hofacker, and Fabian Welschinger. "A phase field model for rate-independent crack propagation: Robust algorithmic implementation based on operator splits". In: *Computer Methods in Applied Mechanics and Engineering* 199.45-48 (2010), pp. 2765–2778.