

Exam Questions CWNA-107

Certified Wireless Network Administrator (CWNA)

<https://www.2passeasy.com/dumps/CWNA-107/>



NEW QUESTION 1

You are planning for PoE in a standard office deployment. Which one of these devices is least likely to be a PoE PD?

- A. Video camera
- B. Access point
- C. VoIP phone
- D. Ethernet switch

Answer: A

NEW QUESTION 2

You are evaluating access points for use in the 5 GHz frequency band. What PHY supports this band and supports 80 MHz channels?

- A. OFDM
- B. HT
- C. VHT
- D. ERP

Answer: C

Explanation:

Reference <https://www.cwnp.com/802-11ac-vht-just-the-facts/>

NEW QUESTION 3

What primary metric of scanning can stations use to select the best AP for connectivity to the desired BSS?

- A. Signal strength of AP beacons received.
- B. PING latency when testing against an Internet server.
- C. FCS errors in frames transmitted to and from the AP.
- D. Throughput speed in Mbps.

Answer: A

NEW QUESTION 4

The requirements for a WLAN you are installing state that it must support unidirectional delays of less than 150 ms and the signal strength at all receivers can be no lower than -67 dBm. What application is likely used that demands these requirements?

- A. E-Mail
- B. RTLS
- C. VoIP
- D. FTP

Answer: B

NEW QUESTION 5

In which plane of the three networking planes is an access point configured by a WLAN controller?

- A. Control
- B. Management
- C. Security
- D. Data

Answer: B

Explanation:

Reference <https://books.google.com.pk/books?id=HQxhBgAAQBAJ&pg=PA343&lpg=PA343&dq=plane+of+the+three+n>

NEW QUESTION 6

What cipher suite is specified by the 802.11-2016 standard and is not deprecated?

- A. Temporal Key Integrity Protocol
- B. Extensible Authentication Protocol
- C. Counter Mode with CBC- MAC Protocol
- D. Wired Equivalent Privacy

Answer: C

NEW QUESTION 7

What is an advantage of using WPA2-Personal instead of WEP-128 as a security solution for 802.11 networks?

- A. WPA2-Personal uses CCMP for encryption, and WEP-128 uses TKIP for encryption
- B. WPA2-Personal uses dynamic encryption keys, and WEP-128 uses static keys
- C. WPA2-Personal uses 802.1X/EAP for authentication, and WEP-128 uses preshared keys
- D. WPA2-Personal is based on IEEE 802.11 industry standards, but WEP is not

Answer: B

NEW QUESTION 8

You are installing AP to be used by 23 laptops. All laptops will connect on the 5 GHz frequency band. A neighbor network uses channels 1 and 6. What channel should be used for this AP and why?

- A. Channel 6, because it is always best to use this channel
- B. A 5 GHz channel, because channels 1 and 6 are 2.4 GHz channels they have no impact on the decision
- C. Channel 1, because it is best to use the channel with the lowest frequency
- D. Channel 11, because channels 1 and 6 are in use nearby

Answer: D

NEW QUESTION 9

What fact is true regarding controllers and Aps in a split-MAC architecture?

- A. Using centralized data forwarding, frames leaving the Aps are never tagged Ethernet frames with VLAN identifiers
- B. An IP tunnel is established between the AP and controller for AP management and control functions
- C. With 802.1X/EAP security, the AP acts as the supplicant and the controller acts as the authenticator
- D. Management and data frames must be processed locally by the AP, while control frames are sent to the controller

Answer: B

NEW QUESTION 10

As an RF wave propagates through space, the wave front experiences natural expansion that reduces its signal strength in an area. What term describes the rate at which this expansion happens?

- A. Inverse square law
- B. Ohm's law
- C. Fresnel zone thinning
- D. MU-MIMO

Answer: A

NEW QUESTION 10

A standard PoE injector is use to power an access point requiring 802.3at. CAT6 cabling is in use. What is the maximum distance supported between the access point and the Ethernet switch with the use of a midspan power injector?

- A. 100 meters
- B. 300 meters
- C. 328 meters
- D. 200 meters

Answer: A

NEW QUESTION 15

The IEEE 802.11-2016 standard requires VHT capable devices to be backward compatible with devices using which other 802.11 physical layer specification (PHY)?

- A. ERP-PBCC
- B. DSSS
- C. OFDM
- D. HR/DSSS

Answer: C

NEW QUESTION 19

You are managing a wireless access point in autonomous mode using the Web based interface. You capture traffic during this management task and notice that you can see the HTML code of the Web pages for access point management. What error in administration could be the cause of the security concern?

- A. A VPN with the AP is not established
- B. WPA2 is disabled on the WLAN
- C. HTTP is in use instead of HTTPS
- D. IPsec is not in use of the management connection as recommended

Answer: C

NEW QUESTION 24

When using an RF splitter to connect one transceiver to sector antennas loss is incurred. What is this loss called?

- A. Conversion loss
- B. Intentional loss
- C. Through loss
- D. Active loss

Answer: C

NEW QUESTION 25

You are troubleshooting a client problem with a 2.4 GHz WLAN connection. The client is experiencing surprisingly low data rates during the work day. You analyze the workspace outside of business hours and detect a strong signal with a typical noise floor at the client location. During working hours, the user works with a laptop in the area and uses an external USB hard drive for continuous data access. The user also states that the laptop works as expected on her home network. The user working approximately 8 feet away from this client experiences no problems. Based on this information, what is the likely cause of the problem?

- A. The laptop has a failing wireless adapter
- B. the AP is overloaded during the work day
- C. The external hard drive is USB 3.0 and is causing a significant increase in the noise floor when in use
- D. The drives in the laptop are corrupt

Answer: B

NEW QUESTION 28

What statement describes the authorization component of a AAA implementation?

- A. Validating client device credentials against a database.
- B. Implementing a WIPS as a full-time monitoring solution to enforce policies.
- C. Granting access to specific network services or resources according to a user profile.
- D. Verifying that a user is who he says he is.

Answer: C

Explanation:

Reference
<http://searchsecurity.techtarget.com/definition/authentication-authorization-and-accounting>

NEW QUESTION 29

A natural disaster has occurred in a remote area that is approximately 40 miles from the response team headquarters. The response team must setup a local wireless network using 802.11 WLAN access points. What is the best method, of those listed, for implementation of a network backhaul for communications across the Internet in this scenario?

- A. Temporary wired cable
- B. 802.11 bridging
- C. Cellular/LTE
- D. Temporary wired DSL

Answer: C

NEW QUESTION 30

What is the final step in an effective troubleshooting process?

- A. Document the results
- B. Disable the WLAN
- C. Notify the users of problem resolution
- D. Verify the solution

Answer: A

NEW QUESTION 31

When antenna gain is reported in dBi, the gain of the antenna is compared to what theoretical antenna?

- A. Yagi
- B. Dipole
- C. Rubber ducky
- D. Isotropic radiator

Answer: D

Explanation:

Reference https://en.wikipedia.org/wiki/Antenna_gain

NEW QUESTION 35

What statement about the beamwidth of an RF antenna is true?

- A. Horizontal and vertical beamwidth are calculated at the point where the main lobe decreases power by 3 dB.
- B. Vertical beamwidth is displayed (in degrees) on the antenna's Azimuth chart.
- C. When antenna gain is lower, the beamwidth is also lower in both the horizontal and vertical dimensions.
- D. The beamwidth patterns on an antenna polar chart indicate the point at which the RF signal stops propagating.

Answer: A

NEW QUESTION 39

What statement about 802.11 WLAN performance is true?

- A. In modem networks, both centralized and distributed data forwarding work well for most standard office deployments
- B. In most WLANs, no special skill or tuning is required to get peak performance
- C. WLANs perform better as more wireless clients connect with each AP
- D. To get the best performance out of an AP, you should disable data rates of 72 Mbps and lower

Answer: D

NEW QUESTION 41

In which plane of the three networking planes is an access point configured by a WLAN controlled?

- A. Control
- B. Management
- C. Security
- D. Data

Answer: B

NEW QUESTION 44

What security method is commonly used for VoIP handsets when the infrastructure does not support OKC or FT roaming?

- A. WPA2-Enterprise with EAP-TTLS
- B. WPA2-Enterprise with EAP-TLS
- C. WPA2-Enterprise with PEAP
- D. WPA2 -Personal

Answer: B

NEW QUESTION 49

You are reporting on the RF environment in you facility. The manager asks you do describe the noise floor noted in the report. Which of the following is the best explanation:?

- A. The energy radiated by flooring materials that causes interference in the 2.4 GHz and 5 GHz bands.
- B. The noise caused by elevators, microwave ovens, and video transmitters.
- C. The RF energy that exists in the environment from intentional and unintentional RF radiators that forms the baseline above which the Intentional signal of your WLAN must exist.
- D. The extra energy radiated by access points and client devices beyond that intended for the signal.

Answer: B

Explanation:

Reference <http://blog.prosig.com/2008/04/14/what-is-db-noise-floor-dynamic-range/>

NEW QUESTION 53

Which one of the following channels can be used for VHT transmissions?

- A. 44
- B. 1
- C. 7
- D. 13

Answer: A

NEW QUESTION 58

A WLAN transmitter that emits a 50 mW signal is connected to a cable with 3 dB loss. If the cable is connected to an antenna with 9dBi gain, what is the EIRP at the antenna element?

- A. 23 dBm
- B. 26 dBm
- C. 13 dBm
- D. 10 dBm

Answer: A

NEW QUESTION 63

You are attempting to explain RF shadow and how it can cause lack of coverage. What common building item frequently causes RF shadow and must be accounted for in coverage plans?

- A. Wooden doors
- B. Carpeted floors
- C. Elevators
- D. Cubicle partitions

Answer: D

NEW QUESTION 65

When using a spectrum to look for non Wi-Fi interference sources, you notice significant interference across the entire 2.4 GHz band (not on a few select frequencies) within the desktop area of a user's workspace, but the interference disappears quickly after just 2 meters. What is the most likely cause of this interference?

- A. USB 3 devices in the user's work area
- B. Bluetooth devices in the user's work area
- C. Excess RF energy from a nearby AP
- D. Unintentional radiation from the PC power supply

Answer: D

Explanation:

https://www.reddit.com/r/electronics/comments/2i2s76/is_the_emf_of_a_pc_without_a_case_much_higher/?st=

NEW QUESTION 67

You are implementing a multi-AP WLAN and fast secure roaming is essential. Which one of the following methods is an IEEE 802.11 standard method for fast roaming?

- A. Band steering
- B. FT
- C. OKC
- D. Load balancing

Answer: B

Explanation:

Reference

<https://www.networkcomputing.com/wireless-infrastructure/wifi-fast-roaming-simplified/1993108957>

NEW QUESTION 70

An IEEE 802.11 amendment is in the draft state. What impact does this draft amendment have on the 802.11 standard?

- A. No impact: Until an amendment is ratified, it does not become part of the standard.
- B. Devices will be released based on the draft amendment and the draft amendment features are part of the standard.
- C. The standard is changed to reflect the new capabilities as soon as an amendment enters the draft stage.
- D. No impact: Draft amendments do not become part of the standard until a working group is formed.

Answer: A

NEW QUESTION 72

You are troubleshooting a problem with interference from a non-802.11 device. Given that the device is not a WLAN device, you cannot use a protocol analyzer and have chosen to use a spectrum analyzer. You want to view the signal from the interfering device over time to see the activity that is generating. What common spectrum analyzer view should you use for this analysis?

- A. Waterfall/Spectrogram
- B. Real-time FFT
- C. APs
- D. Clients

Answer: A

NEW QUESTION 73

An 802.11-based network uses an AP and has several connecting clients. The clients include iPhones, iPads, laptops and one desktop. What WLAN use case is represented?

- A. WPAN
- B. Ad-hoc
- C. BSS
- D. IBSS

Answer: C

NEW QUESTION 76

A standard PoE injector is used to power an access point requiring 802.3at. CAT6 cabling is in use. What is the maximum distance supported between the access point and the Ethernet switch with the use of a midspan power injector?

- A. 100 meters
- B. 300 meters
- C. 328 meters
- D. 200 meters

Answer: A

NEW QUESTION 78

When replacing the antenna of a WLAN device with a similar antenna type that has a higher passive gain, what antenna characteristic will decrease?

- A. Range
- B. Beam width
- C. Active gain
- D. Receive sensitivity

Answer: B

NEW QUESTION 83

In an 802.11 2.4 GHz system, what 22 MHz channels are considered non-overlapping?

- A. 11 and 6
- B. 7 and 11
- C. 1 and 5
- D. 2 and 8

Answer: A

NEW QUESTION 87

The BSA of an AP covers the area used by the sales and marketing department. Thirty-five stations operate in this space. The users indicate that they need more throughput and all stations are 5 GHz capable 802.11ac clients. The current AP configuration uses 20 MHz channels in both 2.4 GHz and 5 GHz. What is the least expensive solution available for increasing throughput for these users without implementing configuration options that are not recommended?

- A. Use a 160 MHz channel on the 5 GHz radio
- B. Use a 40 MHz channel on the 5 GHz radio
- C. Install a second AP in the coverage area
- D. Use a 40 MHz channel on the 2.4 GHz radio

Answer: C

NEW QUESTION 92

A dual-band 802.11ac AP must be powered by PoE. As a class 4 device, what power level should be received at the AP?

- A. 30 W
- B. 25.5 W
- C. 15.4 W
- D. 12.95 W

Answer: C

NEW QUESTION 95

In a WLAN security, what authentication method always creates Layer2 dynamic encryption keys?

- A. Shared Key
- B. WEP
- C. HTTPS captive portal
- D. EAP-TLS

Answer: B

NEW QUESTION 97

When an ACK frame is not received by the transmitting STA, what is assumed?

- A. The frame was correctly delivered
- B. The frame was not delivered and must be retransmitted
- C. The receiver is offline
- D. The receiver processed the frame, but did not respond with an ACK frame because 802.11w is enabled

Answer: B

NEW QUESTION 102

When performing a validation survey for a Multiple Channel Architecture (MCA) system in a multi-tenant building with five floors, what aspect should you, as the surveyor, keep in mind?

- A. The RF interference caused by passing airplanes supporting on-board Wi-Fi should be a prime consideration
- B. The channel reuse pattern should be three dimensional with the RF cell extending coverage of each access point to other floors
- C. The omni-directional antennas of the access points should be oriented parallel to the floor to maximize the coverage pattern across as many floors as possible
- D. The Fresnel Zone is completely blocked between floors so each floor is considered a separate site survey

Answer: B

NEW QUESTION 106

What statement about 802.11 WLAN performance is true?

- A. In modern networks, both centralized and distributed data forwarding work well for most standard office deployments
- B. In most WLANs, no special skill or tuning is required to get peak performance
- C. WLANs perform better as more wireless clients connect with each AP
- D. To get the best performance out of an AP, you should disable data rates of 72 Mbps and lower

Answer: D

NEW QUESTION 109

You are tasked with performing a throughput test on the WLAN. The manager asks that you use open source tools to reduce costs. What open source tool is designed to perform a throughput test?

- A. IxChariot
- B. Python
- C. PuTTY
- D. iPerf

Answer: D

NEW QUESTION 110

Which unit of measurement is an absolute unit that is used to quantify received signal power levels on a logarithmic scale?

- A. dBm
- B. SNR
- C. RSSI
- D. VSWR

Answer: A

NEW QUESTION 115

Lynne runs a small hotel, and as a value added for his customers he has implemented a Wi-Fi hot-spot. Lynne has read news articles about how hackers wait at hot-spots trying to take advantage of unsuspecting users. He wants to avoid this problem at his hotel.

What is an efficient and practical step that Lynne can take to decrease the likelihood of active attacks on his customers' wireless computers?

- A. Implement Network Access Control (NAC) and require antivirus and firewall software along with OS patches.
- B. Implement an SSL VPN in the WLAN controller that initiates after HTTPS login.
- C. Enable station-to-station traffic blocking by the access points in the hotel.
- D. Require EAP_FAST authentication and provide customers with a username/password on their receipt.

Answer: B

NEW QUESTION 119

You recently purchased four laptops containing dual-band 802.11ac adapters. The laptops can connect to your 2.4 GHz network, but they cannot connect to the 5 GHz network. The laptops do not show the 5 GHz SSIDs, which are different than the 2.4 GHz SSIDs. Existing devices can connect to the 5 GHz SSIDs with no difficulty. What is the likely problem?

- A. Interference from no-Wi-Fi sources
- B. Faulty drivers
- C. DoS attack
- D. Interference from other WLANs

Answer: D

NEW QUESTION 123

.....

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual CWNA-107 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the CWNA-107 Product From:

<https://www.2passeasy.com/dumps/CWNA-107/>

Money Back Guarantee

CWNA-107 Practice Exam Features:

- * CWNA-107 Questions and Answers Updated Frequently
- * CWNA-107 Practice Questions Verified by Expert Senior Certified Staff
- * CWNA-107 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * CWNA-107 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year