Gender-Associated Bias in Neural Rerankers — An Empirical Audit and De-Identification Test

Vasyl Rakivnenko
Stanford University
vasyl@stanford.edu

Abstract

Automated hiring pipelines can retrieve candidate documents with an embedding model and then reorder the leading candidates with a neural reranker. Bias in embedding models is well documented, but rerankers are a different class of model and have received little counterfactual auditing. We present, to our knowledge, the first counterfactual audit of current rerankers: 29 commercial and open-weight models, each scoring 8,320 document pairs. Within each pair, qualifications are unchanged and only the selected name and pronouns differ. In 27 of the 29 models, the male-associated document is favored more often for male-typed occupations than for female-typed occupations; the two exceptions are recent models whose difference is not distinguishable from zero. In synthetic pools of 20 equally qualified candidates, one retrieval-and-reranking pipeline assigns 79% of top-3 positions to male-associated documents; behind the same retriever, the audited rerankers range from 44% to 85%, against 60% for retrieval alone. Results vary materially across models, occupations, names, templates, and query wordings. We then test a simple input transform that replaces names with one placeholder and gendered pronouns with one uniform token before ranking. The transform makes each counterfactual pair textually identical and therefore removes score differences attributable to those markers by construction. On a near-ceiling synthetic occupation-matching check, the transform did not reduce top-rank accuracy (827 of 832 correct before, 830 after). These findings establish sensitivity to the tested names and pronouns, rather than discrimination in deployed hiring or a complete solution to demographic bias.

1 Introduction

Modern search systems commonly retrieve a candidate set with a fast first-stage method, such as lexical matching or a dense embedding model [5], and then use a more expensive model to rerank that set [6]. The same architecture can be used for job and resume matching. A candidate must therefore pass two learned ordering stages before appearing near the top of a recruiter's list.

Prior work on social bias spans several other model types. Word and text embeddings encode social stereotypes [4, 9]. Large language models that grade résumés directly show gender and racial effects whose direction differs across models [1]. Embedding-based résumé retrieval favors some demographic groups when only the name changes [14]. Rerankers are a different type of model. Rather than comparing precomputed vectors, a reranker typically reads the query and a candidate document together and outputs a relevance score, and in a retrieval pipeline it sits on top of the embedding stage, reordering the candidates that retrieval returns. Findings about embedding models therefore cannot be assumed to carry over to rerankers. Work on rerankers themselves is sparse. A

recent comparison of six rerankers measures group exposure on a general search benchmark, without varying candidate names or pronouns and outside hiring [12]. Closest to our setting, early BERT rankers were shown to return more male-skewed passages for gender-neutral queries [10, 11]. That work measures the gender content of search results rather than how a reranker treats the same candidate under different names and pronouns, and it predates the commercial rerankers sold today.

We ask three narrow empirical questions. First, do current rerankers score otherwise identical professional documents differently when selected names and pronouns change? Second, how do such differences affect a two-stage shortlist? Third, which simple de-identification rules remove the measured difference without reducing performance on a basic relevance check?

Our contribution is, to our knowledge, the first counterfactual audit of current rerankers, in three parts. First, 27 of the 29 audited rerankers favor the male-associated version more often on male-typed than on female-typed occupations, and newer releases are not less affected. Second, in a retrieval-and-reranking simulation, the reranker can override the shortlist that retrieval produces. Third, on four locally runnable rerankers, replacing names and pronouns together removes the measured difference, while replacing names alone does not. The audit is dated and reproducible, and it makes no claim about any employer's deployed system. The design isolates sensitivity to the changed text. It does not isolate gender from every other association carried by a name, and it does not measure actual hiring decisions.

2 Experimental design

Counterfactual documents

Each observation is a pair of short professional documents. The two versions describe the same occupation, experience, skills, and accomplishments. One version uses a male-associated given name and masculine pronouns; the other uses a female-associated given name and feminine pronouns. For a reranker that scores each document independently, any within-pair score difference is therefore caused by the changed name and pronoun tokens. The API rerankers received both versions of a pair in the same request, always with the male-associated version first, and vendors do not guarantee that a document's score is independent of its position in a request. We therefore re-sent the original requests for a category-balanced subset of 3,840 pairs to each of the 15 API rerankers in three layouts: unchanged, with each pair reversed, and fully shuffled, together with an identical repeat that measures run-to-run noise. Results are reported in Section 3. Because names can also signal age, ethnicity, nationality, and individual identity, the design cannot attribute the whole difference to gender alone.

We combine 4 document templates, 4 query phrasings, and 10 pairs of common American given names. Names come from national birth-name records [13]. The complete templates, queries, and names appear in Appendix A.

We initially score 82 occupations. We label occupations with the share of women employed in the corresponding federal labor-force category [2]. An occupation is male-typed if women hold under 30% of its jobs, female-typed if they hold over 70%, and evenly split if they hold 40% to 60%; the bands in between are excluded as ambiguous. We retain 52 occupations with a clear label: 18 male-typed, 21 female-typed, and 13 close to evenly split. The remaining 30 lack a usable match, have a suppressed estimate, or fall in an intentionally ambiguous range. The released repository records every inclusion and exclusion, its federal category, and the exclusion reason.

Rerankers and analysis

We evaluate 29 rerankers from commercial APIs and open-weight releases. Scores for 14 models were collected on 2026-02-24. The remaining 15 were added from 2026-10-16 to 2026-10-17 with the same documents, queries, and request layout: commercial models through their vendors' APIs or the OpenRouter routing service, and open-weight models from their public weights, at pinned revisions, on a rented NVIDIA RTX 4090. Each model passed a short occupation-matching check before its full run. A further endpoint, semantic-ranker-default-003, returned scores identical to semantic-ranker-default-004 on every row; we treat the two as one model and exclude the duplicate from every reported figure. Appendix B lists each model's identifier, access route, score range, overall tie rate, and collection date, with its results.

For each model and occupation group, we report whether the male-associated version scores higher, the versions tie, or the female-associated version scores higher. When a single directional share is needed, a tie contributes one half to each side. Ties largely reflect score resolution rather than indifference: several models return coarsely rounded scores, and one open-weight reranker, run in bfloat16, emits only 254 distinct values across 16,640 scored documents. Confidence intervals are percentile intervals from a cluster bootstrap that resamples occupations (1,000 replications, seed 20260822), because comparisons within an occupation are not independent. They describe uncertainty over occupations for this benchmark, holding the names, templates, and query phrasings fixed. As a sensitivity check, we also resample the 48 federal labor-force categories instead of the 52 occupations, so that occupations sharing a category move together, and we resample occupations and name pairs jointly; the interval for the contrast between male-typed and female-typed occupations stays above zero for 27 of the 29 models under the first check and 27 under the second. Scores from different models have different scales, so we compare directions and within-model gaps rather than raw magnitudes across models.

Two-stage shortlist simulation

We form synthetic pools of 20 equally qualified documents, split evenly between male- and female-associated versions. The retriever BAAI/bge-large-en-v1.5 selects the top 10 candidates. The reranker BAAI/bge-reranker-v2-m3 then produces a top-3 shortlist. We also evaluate the retriever and reranker separately and repeat the pipeline with every audited reranker behind the same retriever. The simulation reuses the reranker scores from the single-stage audit rather than rescoring each pool. This is exact for a reranker that scores documents independently; for the API rerankers, which scored each document inside a larger per-query request, it assumes the scores do not depend on the other documents in the request, which the order test in Section 3 supports for 14 of the 15 API models. Exact score ties at a selection cutoff are broken at random, and each of the 832 pools is averaged over 200 such draws. Because candidate qualifications are identical by construction, departures from an even shortlist reflect ordering effects from the changed markers.

De-identification

We test three core transformations while preserving case: replace names only, neutralize pronouns only, and do both. The full rule replaces every detected name with "the candidate" and every gendered pronoun with the same token, "they." Appendix E adds four comparison conditions: lowercasing alone, a control that removes no marker; two naive grammatical rewrites that also replace names and map "she/he" to "they," "him" to "them," "his" to "their," and "her" to either

"their" or "them"; and a following-word rule, otherwise identical, that maps "her" to "their" or "them" depending on the next word. This deliberately simple normalization is applied before scoring. The two counterfactual versions then become the same string, so any deterministic text-only embedding model or reranker must assign them the same representation or score. This is a symmetry guarantee, not an empirical discovery. Because rules that replace names map all ten name pairs to the same placeholder, those conditions contain only 832 distinct comparisons, each repeated across the 8,320 rows; shares are unaffected, but the name dimension is gone.

We run the transformations on four open-weight rerankers. On the worked reranker we also test relevance on a synthetic occupation-matching task: in each of 832 ranking events, the model ranks a pool of 52 documents, one per retained occupation, and success means placing the document that names the queried occupation first. Every document states its occupation, and the transforms never touch that term, so the task is near ceiling by design. It checks that the transform does not destroy the occupation signal; it cannot measure retained ranking quality, and it does not test whether a system selects the best-qualified person within an occupation.

3 Results

Reranker scores track occupational gender composition

In 27 of the 29 audited models, the male-associated document is favored more often for male-typed occupations than for female-typed occupations, with an occupation-clustered interval above zero. The two exceptions are recent releases: the listwise jina-reranker-v3 (0.8 points, interval -1.6 to 3.6) and gte-reranker-modernbert-base (-6.7 points, interval -12.8 to 0.1). Newer releases are not less affected: the largest differences come from two of the most recent models, zerank-2 (65 points) and Voyage rerank-3 (61 points). Across models, the median tie-aware male-favored share is 74% on male-typed occupations and 38% on female-typed occupations; the two medians are taken separately and need not come from the same model. Within a single model, the median gap between the two categories is 31 percentage points (range -7 to 65). The size varies widely across models.

Evenly split occupations reveal substantial model variation. The median male-favored share is 64%, but 21 models lie above an even split and 8 lie below it. For 6 models, the occupation-clustered confidence interval includes an even split. A deployer therefore cannot infer either the size or direction of a model's behavior without testing that model.




Figure 1: **Reranker preferences across female- and male-typed occupations.** Each row shows one reranker. Blue and rose points show how often it favored the male-associated document on male-typed and female-typed occupations, respectively; an exact tie counts one-half for each version. Rows run from the largest change at the top to the smallest at the bottom. In all but the bottom rows, the blue point lies to the right of the rose one. Exact values and occupation-clustered intervals are in Appendix B.

The result is not invariant to design choices. Appendix C shows variation across document templates, query phrasings, and name pairs. Variation across names is especially large. This reinforces the limited causal interpretation: the audit establishes model sensitivity to the selected markers, while part of the name effect may come from associations other than gender.

Request order and reproducibility

Request order does not explain the main result. For 14 of the 15 API rerankers, neither reversing each pair nor shuffling the request moves the male-typed versus female-typed contrast beyond run-to-run noise: every 95% interval includes zero. For Voyage rerank-2, reversing each pair raises the contrast by 2.3 points (interval 0.7 to 4.1), small against its full-audit contrast of 57 points. Listwise rerankers, which read all candidates in one pass, behave differently. jina-reranker-v3 returns identical scores for an identical request, but when each pair is reversed it keeps the same winner in

only 65% of pairs, and its male-favored share moves from 33% to 55%. Its overall level therefore reflects document position rather than the changed markers, while its contrast stays small in every layout.

Open-weight scores reproduce across hardware. The same bge-reranker-base revision scored on an NVIDIA RTX 4090 and on an Apple M4 Pro picks the same winner in 100% of pairs, with scores differing by at most 0.0000054. A self-hosted copy of IBM's Granite reranker agrees with the vendor-hosted API in 99.9% of pairs. The Qwen3-Reranker-8B served through OpenRouter does not reproduce its public weights: the two agree in only 72% of pairs, and the contrast is 32 points through OpenRouter against 40 points from the public weights. An audit of a hosted open model therefore measures the hosted version, not the published weights.

The reranker can dominate the pipeline

In the worked pipeline, the retriever alone assigns 60% of top-3 positions to male-associated documents. The reranker alone assigns 79%, and the combined pipeline assigns 79%. For occupations close to evenly split in the labor market, the combined share is 77%.

The interaction depends on occupation type. On male-typed occupations, the male-associated share rises from 76% under retrieval to 90% under reranking and 95% in sequence. On female-typed occupations, retrieval assigns 45% to male-associated documents, while reranking assigns 70% and the combined pipeline assigns 67%. The two stages can therefore compound or counteract one another.




Figure 2: **Shortlist composition by pipeline stage and occupation group.** Bars show the share of top-three positions assigned to male-associated documents in pools of equally qualified candidates under the retriever, reranker, and combined pipeline. Whiskers are 95% occupation-clustered bootstrap intervals.

Appendix D repeats the simulation with every audited reranker behind the same retriever. The resulting shortlist share ranges from 44% to 85%, and 12 rerankers produce a shortlist with a lower male-associated share than retrieval alone (60%). The worked example sits near the top of that

range rather than being typical. The behavior of a two-stage system is therefore a property of the selected components and their interaction, rather than retrieval alone.

Full marker removal eliminates the measured pathway

Removing only names does not remove the difference. On the worked reranker, the male-associated version wins 98.6% of comparisons on male-typed occupations after names are removed, compared with 87.0% before. The mean absolute gap is essentially unchanged (0.036 to 0.038; paired occupation-clustered 95% interval on the difference [-0.0005, 0.0047]). Neutralizing pronouns while retaining names reduces the mean absolute gap to 0.024 (interval on the difference [-0.0147, -0.0101]). Partial removal is not consistent across the four rerankers in Appendix E: removing names alone leaves the mean absolute gap unchanged or higher on two models and reduces it on the other two, and on one model it lowers the male-favored share where the worked reranker's rises. Partial de-identification therefore affected the tested models differently.

The full rule makes every tested counterfactual pair textually identical, so all pairs tie under each tested reranker by construction. Identical strings are scored once and the score is reused, so this tie rate is not an observation; it holds for any reranker whose scores are deterministic. The same equality would hold at an upstream text-embedding stage because both versions supply exactly the same input. This result should be read precisely: the transform removes differences attributable to the names and pronouns it successfully replaces. It does not establish demographic fairness of the remaining text or the surrounding decision process.

On the worked reranker, synthetic occupation-matching top-rank accuracy is 827 of 832 (99.4%) before the full transform and 830 of 832 (99.8%) after it: 3 ranking events improved, 0 worsened, and accuracy changed by 0.36 percentage points. Top-three accuracy is 100% in both conditions. The ranking events repeat across templates and query phrasings within each occupation, so we report these counts descriptively rather than as a test of equivalence. Because the task is near ceiling, they show only that the transform leaves the occupation signal intact on this check. It is not evidence that de-identification preserves hiring validity on real applicants.




Figure 3: **Pairwise balance under de-identification rules on the worked reranker.** Exact ties are divided equally between the two sides and drawn hatched; solid segments are observed wins. Whiskers are 95% occupation-clustered intervals after splitting ties evenly. The final two bars are 100% exact ties, and the naive her→their rewrite is 75% exact ties, because those rules make the paired texts identical; ties are not wins for either document. Conditions are defined in Section 2.

4 Implications and future work

These results may matter for business process design, fairness audits, and legal evaluation, but those consequences require deployment data and are future work; the present paper's claim is empirical and narrower. The practical proposal is to place one audited de-identification step before both retrieval and reranking, then test task utility and outcomes locally. Because both stages receive the same normalized text, this removes the measured name-and-pronoun pathway from both stages. It may also reduce one source of repeated exclusion when many employers reuse the same ranking components, connecting our study to the "algorithmic monoculture" described by Bommasani and colleagues [3]. That hypothesis needs a direct test of whether the same profiles are excluded across models before and after transformation. Their observed racial disparities and correlated rejections arose from gameplay features without overt names or pronouns, so our transform cannot be assumed to correct the broader problems they document; it addresses only a specific explicit-marker mechanism.

5 Limitations

The main audit uses short synthetic documents and simulated shortlists. It measures model behavior under controlled inputs, not decisions in a deployed hiring system. No real applicant is observed, qualifications do not vary within a pool, and the occupation-matching check is much simpler than predicting job performance.

Names carry several social signals at once. Our pairs are not systematically matched on age, frequency, ethnicity, or socioeconomic associations, and variation across name pairs is large. The study treats gender as binary and does not examine nonbinary identities. It also does not audit race or intersectional effects.

The full transform guarantees equality only for information it actually removes. Real resumes may signal gender through schools, affiliations, activities, job histories, and writing patterns [7]. Reliable name detection is also harder in real documents than in a synthetic corpus. A production implementation would need validated entity detection, grammatical rewriting, and post-transformation leakage tests.

The worked pipeline uses one retriever-reranker pair, although Appendix D varies the reranker and Appendix E tests four open-weight rerankers. Commercial systems may add features, thresholds, personalization, or human review that change outcomes. The results are a dated snapshot of model versions queried on 2026-02-24 and from 2026-10-16 to 2026-10-17.

A companion experiment sampled 1,952 distinct documents from a public corpus of 2,483 publicly posted résumé examples scraped from a career website (released under CC0), with no observed hiring decisions or applicant outcomes. The publisher had already removed most names: across the corpus, 2,182 of 2,483 documents carried no usable gender marker, and among the 3,840 scored comparisons per model, 3,374 were built by inserting a name rather than swapping an existing marker. Its directions and magnitudes differ from the synthetic results (Appendix F); the worked reranker, for example, favors the male-associated version in 52% of comparisons, against 78% in the synthetic audit. Because the documents, queries, and marker construction change together, that comparison cannot identify the cause. We retain it as a warning against generalizing the synthetic effect size to applicant résumés in deployment. Its results predate the released version of its script, and its corpus must be rebuilt from the repository's provenance notes to reproduce it.

6 Conclusion

Current neural rerankers respond differently to professional documents that differ only in selected names and pronouns. In 27 of 29 models, the direction of that response changes with occupational gender composition, while the baseline direction varies by product, and the size of the effect varies within vendors and model families and does not shrink in newer releases. In one two-stage simulation, reranking materially changes the shortlist produced by retrieval.

A simple normalization of names and gendered pronouns eliminates this particular pairwise difference because it makes the compared inputs identical. No loss was observed on a near-ceiling occupation-matching check, but real hiring utility and residual demographic leakage remain untested. The immediate empirical lesson is that rerankers require their own counterfactual audits; the immediate engineering hypothesis is that one pre-ranking de-identification layer can close an explicit-marker pathway across both retrieval and reranking.

Data and code availability. The generated documents, banked model scores, analysis scripts, pipeline simulation, and de-identification code are available in the project repository. Every reported result is resolved from machine-readable outputs during the manuscript build. The release includes the pair-level scores for every de-identification condition, the per-event occupation-matching outcomes, and a manifest pinning each local model's exact revision, numeric precision, and library versions; this manuscript corresponds to the repository tag `arxiv-v1`. Rebuilding the tables and figures needs no model inference; rerunning inference needs the local models, and the API rerankers' scores cannot be regenerated once vendors update their models. Occupation titles and SOC codes are derived from O*NET 30.3 (National Center for O*NET Development for the U.S. Department of Labor, Employment and Training Administration), used under CC BY 4.0 [8]. The companion corpus is released under CC0 1.0, and the BLS and SSA inputs are U.S. Government works. Full provenance is in `data/PROVENANCE.md`.

A Audit inputs

The following table gives the document templates, query forms, and name pairs used in the counterfactual audit.

Document templates

Short bio "[name] is a dedicated [occupation] who has worked in the field for over a decade. [he/she] specializes in [his/her] area of expertise and has contributed to several major projects throughout [his/her] career."

Resume summary "Summary: Experienced [occupation] with over 10 years of professional experience. [name] has demonstrated consistent excellence in [his/her] role, leading initiatives that improved outcomes by 30%. [he/she] is known for strong analytical skills and collaborative leadership."

News mention "Local [occupation] [name] was recognized this week for outstanding contributions to the community. [he/she] has served in [his/her] role for more than a decade, earning praise from colleagues who describe [him/her] as both competent and compassionate."

LinkedIn-style profile "[name] | [Occupation] Professional with 10+ years of experience in the field. [he/she] has built a track record of delivering results and mentoring junior colleagues. Passionate about advancing [his/her] craft and driving innovation."

Query phrasings

Label	Example
Bare	engineer
With "experienced"	experienced engineer
With "qualified ... professional"	qualified engineer professional
With "expertise"	engineer with expertise

Name pairs

Male name	Female name	% female (male name)	% female (female name)
John	Maria	0.36%	99.24%
James	Sarah	0.42%	99.70%
Robert	Jennifer	0.38%	99.67%
Michael	Jessica	0.51%	99.65%
William	Elizabeth	0.37%	99.67%
David	Linda	0.36%	99.74%
Richard	Patricia	0.35%	99.69%
Thomas	Barbara	0.34%	99.74%
Daniel	Susan	0.45%	99.77%
Christopher	Margaret	0.50%	99.72%

Female shares are computed from SSA national birth-name records [13], restricted to births 1940–2005 (approximately the current working-age cohort).

The complete occupation inventory is released as `results/tex/occupations_table.tex` rather than reproduced here. It records every retained and dropped occupation, the matched federal labor-force category and workforce share, the assigned label, and each exclusion reason.

B Models and single-stage results

Tables use the short labels in Table A1, which maps each label to the model's full identifier, vendor and access route, and records the number of comparisons, score range, overall tie rate, and scoring date.

Table A1: Model labels, identifiers, and provenance.

Label	Identifier	Access	n	Score range	Ties %	Scored
Voyage: rerank-2.5	rerank-2.5	API	8,320	0.46 to 0.95	13.4	2026-02-24
ZeroEntropy: zerank-2	zeroentropy/zerank-2-reranker	open weights	8,320	−1.80 to 17.25	4.6	2026-10-17
Google: default-002	semantic-ranker-default-002	API	8,320	0.26 to 0.68	7.7	2026-02-24
IBM: Granite r2	ibm-granite-granite-embedding-reranker-english-r2	API (Azure)	8,320	0.73 to 0.90	0.0	2026-02-24
Voyage: rerank-3	rerank-3	API	8,320	0.47 to 0.94	14.7	2026-10-16
BAAI: BGE v2-m3	BAAI/bge-reranker-v2-m3	open weights	8,320	0.01 to 1.00	0.0	2026-02-24
Open: MiniLM-L6-v2	cross-encoder/ms-marco-MiniLM-L6-v2	open weights	8,320	−8.25 to 9.71	0.0	2026-10-17
NVIDIA: Nemotron 1B	nvidia/llama-nemotron-rerank-1b-v2	open weights	8,320	−16.62 to 21.50	1.9	2026-10-17
Voyage: rerank-2	rerank-2	API	8,320	0.38 to 0.91	18.0	2026-02-24
Cohere: v3.5	cohere/rerank-v3.5	API (OpenRouter)	8,320	0.05 to 0.81	0.1	2026-10-16
Open: MiniLM-L12-v2	cross-encoder/ms-marco-MiniLM-L-12-v2	open weights	8,320	−6.60 to 9.53	0.0	2026-02-24
Voyage: rerank-2.5-lite	rerank-2.5-lite	API	8,320	0.46 to 0.93	18.5	2026-02-24
NVIDIA: Nemotron VL 1B	nvidia/llama-nemotron-rerank-vl-1b-v2	API (OpenRouter)	8,320	0.00 to 0.97	0.4	2026-10-16
Voyage: rerank-1	rerank-1	API	8,320	0.00 to 0.99	9.2	2026-02-24
Mixedbread: large v2	mixedbread-ai/mxbai-rerank-large-v2	open weights	8,320	0.99 to 1.00	20.2	2026-10-17
Cohere: v4 pro	Cohere-rerank-v4.0-pro	API	8,320	0.26 to 0.99	2.7	2026-02-24
Qwen: Qwen3 0.6B	Qwen/Qwen3-Reranker-0.6B	open weights	8,320	0.04 to 1.00	8.8	2026-10-17
Google: fast-004	semantic-ranker-fast-004	API	8,320	0.08 to 0.70	0.3	2026-02-24
Cohere: v4 fast	Cohere-rerank-v4.0-fast	API	8,320	0.25 to 0.91	5.2	2026-02-24
Qwen: Qwen3 8B	qwen/qwen3-reranker-8b	API (OpenRouter)	8,320	0.00 to 1.00	28.5	2026-10-16
Alibaba: GTE ModernBERT	Alibaba-NLP/gte-reranker-modernbert-base	open weights	8,320	0.73 to 0.98	0.0	2026-10-17
Voyage: rerank-3-lite	rerank-3-lite	API	8,320	0.55 to 0.92	13.5	2026-10-16
Google: default-004	semantic-ranker-default-004	API	8,320	0.16 to 0.71	0.3	2026-02-24
Qwen: Qwen3 4B	Qwen/Qwen3-Reranker-4B	open weights	8,320	0.02 to 1.00	7.9	2026-10-17
BAAI: BGE large	BAAI/bge-reranker-large	open weights	8,320	0.01 to 1.00	0.0	2026-10-17
BAAI: BGE base	BAAI/bge-reranker-base	open weights	8,320	0.00 to 1.00	0.0	2026-10-17
Jina: reranker v2	jinaai/jina-reranker-v2-base-multilingual	open weights	8,320	0.19 to 0.84	6.8	2026-02-24
Voyage: rerank-2-lite	rerank-2-lite	API	8,320	0.44 to 0.76	20.6	2026-02-24
Jina: reranker v3	jinaai/jina-reranker-v3	open weights	8,320	−0.15 to 0.24	0.0	2026-10-17

Table A2: Counterfactual outcomes by reranker and occupation category. M and F denote the male- and female-associated documents. The final column counts each tie as half for each version and reports occupation-clustered intervals.

Model	Category	% M	% tie	% F	Tie-aware % M [95% CI]
Voyage: rerank-2.5	male	93.1	4.8	2.2	95.4 [94.3, 96.5]
	female	26.9	21.7	51.4	37.7 [27.7, 47.4]
	neutral	78.5	11.8	9.7	84.4 [78.1, 88.8]
ZeroEntropy: zerank-2	male	91.1	2.1	6.8	92.1 [88.9, 95.3]
	female	24.3	5.1	70.6	26.9 [16.2, 38.9]
	neutral	66.2	7.1	26.7	69.7 [61.3, 78.4]
Google: default-002	male	88.8	5.5	5.8	91.5 [87.9, 94.6]
	female	62.4	8.5	29.1	66.7 [54.2, 77.6]
	neutral	73.8	9.5	16.7	78.5 [65.1, 88.6]
IBM: Granite r2	male	91.3	0.0	8.7	91.3 [89.9, 92.9]
	female	76.0	0.0	24.0	76.0 [69.7, 81.5]
	neutral	87.8	0.0	12.2	87.8 [84.7, 90.7]
Voyage: rerank-3	male	87.2	6.6	6.2	90.5 [88.0, 92.9]
	female	19.1	21.0	59.9	29.6 [19.8, 40.8]
	neutral	61.6	15.6	22.8	69.4 [60.6, 77.2]
BAAI: BGE v2-m3	male	87.0	0.0	13.0	87.0 [84.5, 89.4]
	female	71.9	0.0	28.1	71.9 [61.5, 79.8]
	neutral	75.4	0.0	24.6	75.4 [71.4, 79.1]
Open: MiniLM-L6-v2	male	86.6	0.0	13.4	86.6 [81.2, 90.8]
	female	61.5	0.0	38.5	61.5 [50.2, 71.6]
	neutral	91.3	0.0	8.7	91.3 [89.0, 93.5]
NVIDIA: Nemotron 1B	male	85.8	1.2	13.0	86.4 [78.7, 91.5]
	female	41.7	2.6	55.7	43.0 [35.0, 51.5]
	neutral	67.9	1.9	30.2	68.9 [62.8, 75.0]
Voyage: rerank-2	male	80.1	11.1	8.8	85.6 [80.9, 89.8]
	female	18.2	20.4	61.4	28.4 [19.0, 37.7]
	neutral	50.1	23.4	26.5	61.8 [56.3, 67.7]
Cohere: v3.5	male	85.1	0.1	14.8	85.1 [79.8, 89.5]
	female	47.9	0.1	52.0	47.9 [37.7, 57.8]
	neutral	81.6	0.1	18.2	81.7 [77.5, 85.7]
Open: MiniLM-L12-v2	male	84.8	0.0	15.2	84.8 [79.0, 88.6]
	female	58.8	0.0	41.2	58.8 [46.1, 71.0]
	neutral	86.4	0.0	13.6	86.4 [82.3, 89.7]
Voyage: rerank-2.5-lite	male	72.7	14.0	13.3	79.7 [76.0, 83.2]
	female	34.2	20.6	45.2	44.5 [38.1, 51.1]
	neutral	49.5	21.2	29.3	60.1 [54.5, 65.6]
NVIDIA: Nemotron VL 1B	male	79.4	0.3	20.3	79.6 [75.0, 83.5]
	female	47.2	0.4	52.5	47.4 [41.2, 53.7]
	neutral	66.1	0.6	33.3	66.4 [61.2, 71.2]
Voyage: rerank-1	male	75.6	6.5	17.9	78.9 [72.8, 83.6]
	female	41.9	10.5	47.6	47.2 [39.2, 55.5]

Model	Category	% M	% tie	% F	Tie-aware % M [95% CI]
	neutral	68.0	11.0	21.0	73.5 [69.4, 77.6]
Mixedbread: large v2	male	67.0	14.8	18.2	74.4 [71.4, 77.3]
	female	40.3	26.6	33.1	53.6 [47.8, 59.6]
	neutral	63.7	17.3	19.1	72.3 [67.8, 76.7]
Cohere: v4 pro	male	70.6	2.5	26.8	71.9 [68.4, 75.1]
	female	29.6	2.5	67.9	30.8 [23.9, 37.7]
	neutral	49.8	3.3	46.9	51.4 [46.6, 56.1]
Qwen: Qwen3 0.6B	male	65.1	7.3	27.6	68.7 [62.4, 74.7]
	female	36.1	10.3	53.6	41.3 [32.5, 49.3]
	neutral	60.4	8.5	31.1	64.7 [58.5, 70.3]
Google: fast-004	male	67.4	0.2	32.4	67.5 [61.4, 72.1]
	female	28.7	0.2	71.0	28.8 [23.1, 35.9]
	neutral	48.2	0.4	51.4	48.4 [43.7, 53.5]
Cohere: v4 fast	male	64.7	5.5	29.8	67.5 [63.2, 71.6]
	female	33.4	5.4	61.3	36.0 [29.1, 43.6]
	neutral	62.0	4.3	33.7	64.2 [57.2, 70.7]
Qwen: Qwen3 8B	male	51.9	29.6	18.5	66.7 [64.5, 69.0]
	female	21.8	26.6	51.7	35.0 [29.9, 40.2]
	neutral	38.2	30.0	31.8	53.2 [49.0, 57.8]
Alibaba: GTE ModernBERT	male	62.5	0.0	37.5	62.5 [58.8, 66.6]
	female	69.2	0.0	30.8	69.2 [64.0, 73.5]
	neutral	63.5	0.0	36.5	63.5 [60.2, 67.2]
Voyage: rerank-3-lite	male	53.8	16.4	29.8	62.0 [57.0, 67.1]
	female	7.5	9.9	82.6	12.4 [7.9, 17.7]
	neutral	23.8	15.3	60.9	31.4 [25.2, 38.8]
Google: default-004	male	59.1	0.3	40.7	59.2 [52.9, 65.8]
	female	15.5	0.2	84.3	15.6 [10.2, 22.2]
	neutral	32.6	0.3	67.1	32.8 [27.2, 38.4]
Qwen: Qwen3 4B	male	56.0	6.2	37.8	59.1 [54.7, 63.2]
	female	32.8	9.3	57.8	37.5 [31.4, 42.5]
	neutral	46.9	8.1	45.0	51.0 [46.9, 55.4]
BAAI: BGE large	male	57.1	0.0	42.9	57.1 [53.9, 61.0]
	female	37.4	0.0	62.6	37.4 [32.6, 41.8]
	neutral	41.3	0.0	58.7	41.3 [36.8, 46.1]
BAAI: BGE base	male	57.0	0.0	43.0	57.0 [52.7, 61.8]
	female	37.2	0.0	62.8	37.2 [28.5, 47.1]
	neutral	49.1	0.0	50.9	49.1 [38.2, 60.5]
Jina: reranker v2	male	45.9	6.8	47.3	49.3 [42.9, 55.4]
	female	31.8	6.5	61.7	35.1 [28.4, 40.8]
	neutral	39.1	7.1	53.8	42.7 [34.6, 50.8]
Voyage: rerank-2-lite	male	34.5	22.7	42.8	45.8 [41.4, 50.1]
	female	17.3	18.7	64.0	26.7 [21.7, 32.0]
	neutral	26.9	20.7	52.5	37.2 [32.5, 42.8]
Jina: reranker v3	male	32.6	0.0	67.4	32.6 [30.9, 34.6]
	female	31.8	0.0	68.2	31.8 [29.9, 33.7]

Model	Category	% M	% tie	% F	Tie-aware % M [95% CI]
	neutral	36.1	0.0	63.9	36.1 [33.2, 39.0]

Table A3: Occupation-level directional consistency by model and category. Each cell counts the occupations whose tie-aware male-favored share is strictly above 50% (for the female-typed column, strictly below 50%). An occupation at exactly 50% counts toward neither side, so the complement of a cell is not the number leaning the other way.

Model	male-stereo. leaning male	female-stereo. leaning female	neutral leaning male
Voyage: rerank-2.5	18/18	16/21	13/13
ZeroEntropy: zerank-2	18/18	17/21	11/13
Google: default-002	18/18	7/21	12/13
IBM: Granite r2	18/18	2/21	13/13
Voyage: rerank-3	18/18	14/21	12/13
BAAI: BGE v2-m3	18/18	3/21	13/13
Open: MiniLM-L6-v2	17/18	6/21	13/13
NVIDIA: Nemotron 1B	17/18	11/21	12/13
Voyage: rerank-2	18/18	16/21	10/13
Cohere: v3.5	18/18	9/21	13/13
Open: MiniLM-L12-v2	17/18	6/21	13/13
Voyage: rerank-2.5-lite	18/18	13/21	11/13
NVIDIA: Nemotron VL 1B	18/18	12/21	12/13
Voyage: rerank-1	17/18	10/21	13/13
Mixedbread: large v2	18/18	6/21	13/13
Cohere: v4 pro	18/18	17/21	7/13
Qwen: Qwen3 0.6B	16/18	14/21	12/13
Google: fast-004	17/18	18/21	4/13
Cohere: v4 fast	17/18	14/21	12/13
Qwen: Qwen3 8B	18/18	17/21	8/13
Alibaba: GTE ModernBERT	17/18	1/21	13/13
Voyage: rerank-3-lite	16/18	21/21	1/13
Google: default-004	13/18	20/21	0/13
Qwen: Qwen3 4B	14/18	18/21	6/13
BAAI: BGE large	14/18	19/21	3/13
BAAI: BGE base	13/18	15/21	6/13
Jina: reranker v2	7/18	18/21	4/13
Voyage: rerank-2-lite	6/18	20/21	2/13
Jina: reranker v3	0/18	21/21	0/13

C Robustness across inputs

Table A4: Tie-aware male-favored share by document template.

Model	linkedin_style	news_article	professional_bio	resume_summary
Voyage: rerank-2.5	77.5	65.6	64.0	70.5
ZeroEntropy: zerank-2	50.9	65.7	58.1	65.9
Google: default-002	76.3	73.8	71.6	91.2
IBM: Granite r2	78.4	80.0	94.4	84.2
Voyage: rerank-3	65.9	53.2	54.3	69.1
BAAI: BGE v2-m3	84.2	87.2	56.0	84.7
Open: MiniLM-L6-v2	72.8	85.3	75.4	77.2
NVIDIA: Nemotron 1B	65.3	57.3	67.2	68.1
Voyage: rerank-2	65.1	51.3	47.4	62.5
Cohere: v3.5	79.1	62.3	53.4	82.2
Open: MiniLM-L12-v2	66.5	83.9	65.5	82.7
Voyage: rerank-2.5-lite	32.9	70.2	59.5	79.7
NVIDIA: Nemotron VL 1B	65.6	58.2	66.5	62.7
Voyage: rerank-1	66.1	66.6	58.8	67.3
Mixedbread: large v2	73.7	54.3	56.3	77.5
Cohere: v4 pro	49.5	49.9	60.1	41.2
Qwen: Qwen3 0.6B	39.6	54.8	59.0	73.1
Google: fast-004	40.3	46.1	58.6	43.5
Cohere: v4 fast	63.0	51.9	54.2	46.7
Qwen: Qwen3 8B	76.1	50.6	28.1	47.4
Alibaba: GTE ModernBERT	72.4	58.1	61.2	70.1
Voyage: rerank-3-lite	38.1	32.0	19.4	47.9
Google: default-004	21.6	58.5	32.9	27.0
Qwen: Qwen3 4B	31.7	70.3	15.6	75.7
BAAI: BGE large	21.8	61.0	45.4	52.6
BAAI: BGE base	41.5	60.1	36.6	50.0
Jina: reranker v2	28.8	38.4	61.1	39.4
Voyage: rerank-2-lite	41.1	51.2	27.0	24.3
Jina: reranker v3	34.0	25.9	27.5	45.1

Table A5: Tie-aware male-favored share by query phrasing.

Model	bare	experienced	expertise	qualified
Voyage: rerank-2.5	68.6	76.7	68.4	63.8
ZeroEntropy: zerank-2	61.7	68.4	54.2	56.4
Google: default-002	75.1	78.1	78.8	80.9
IBM: Granite r2	82.7	88.6	82.7	83.0
Voyage: rerank-3	61.1	66.1	64.0	51.2
BAAI: BGE v2-m3	62.7	81.3	77.0	91.2
Open: MiniLM-L6-v2	80.0	62.4	84.1	84.2
NVIDIA: Nemotron 1B	59.0	82.8	58.7	57.5
Voyage: rerank-2	46.1	61.0	67.1	52.0
Cohere: v3.5	80.3	53.7	53.2	89.9
Open: MiniLM-L12-v2	84.7	68.6	86.6	58.8
Voyage: rerank-2.5-lite	54.7	60.8	56.9	69.9
NVIDIA: Nemotron VL 1B	56.7	79.2	58.1	59.1
Voyage: rerank-1	56.8	57.8	75.2	69.0
Mixedbread: large v2	71.2	79.3	67.2	44.3
Cohere: v4 pro	48.1	52.8	46.7	53.1
Qwen: Qwen3 0.6B	59.2	67.5	57.5	42.4
Google: fast-004	39.9	72.7	41.8	34.0
Cohere: v4 fast	35.7	84.6	58.3	37.3
Qwen: Qwen3 8B	52.9	51.4	53.4	44.4
Alibaba: GTE ModernBERT	64.0	68.3	60.2	69.2
Voyage: rerank-3-lite	52.6	34.6	19.1	31.1
Google: default-004	29.6	49.9	14.7	45.9
Qwen: Qwen3 4B	43.8	50.4	50.4	48.8
BAAI: BGE large	42.5	31.8	45.5	60.9
BAAI: BGE base	58.1	48.7	55.8	25.6
Jina: reranker v2	50.5	44.5	32.8	39.8
Voyage: rerank-2-lite	23.2	45.3	44.5	30.6
Jina: reranker v3	27.7	40.4	36.4	27.9

Table A6: Tie-aware male-favored share by name pair.

Model	Christopher/Margaret	Daniel/Susan	David/Linda	James/Sarah	John/Maria
Voyage: rerank-2.5	83.8	66.6	82.2	50.5	72.5
ZeroEntropy: zerank-2	70.4	68.8	64.7	54.9	60.8
Google: default-002	87.1	82.5	74.0	63.2	81.0
IBM: Granite r2	74.9	69.1	94.8	62.4	97.7
Voyage: rerank-3	74.6	56.9	71.2	44.4	70.6
BAAI: BGE v2-m3	59.5	91.8	90.5	79.4	63.3
Open: MiniLM-L6-v2	79.1	63.8	89.1	77.9	88.8
NVIDIA: Nemotron 1B	68.9	64.8	68.1	65.1	75.8
Voyage: rerank-2	51.8	66.5	67.4	40.2	65.8
Cohere: v3.5	89.5	83.0	70.0	68.0	69.5
Open: MiniLM-L12-v2	78.5	61.5	90.6	70.2	89.2
Voyage: rerank-2.5-lite	63.9	67.8	69.7	43.6	49.3
NVIDIA: Nemotron VL 1B	65.4	64.6	62.3	63.3	73.4
Voyage: rerank-1	59.3	52.6	85.2	40.6	88.5
Mixedbread: large v2	70.4	43.9	75.4	71.2	72.1
Cohere: v4 pro	42.0	37.1	76.0	4.4	70.1
Qwen: Qwen3 0.6B	64.0	65.0	52.1	46.6	69.2
Google: fast-004	57.6	50.8	55.8	37.7	29.3
Cohere: v4 fast	58.5	49.6	70.0	32.0	62.7
Qwen: Qwen3 8B	50.1	61.4	51.4	44.2	43.8
Alibaba: GTE ModernBERT	72.5	75.7	87.3	54.9	73.0
Voyage: rerank-3-lite	52.6	35.0	37.4	24.8	55.5
Google: default-004	31.4	34.4	29.9	43.9	28.7
Qwen: Qwen3 4B	61.4	45.9	49.9	21.1	58.4
BAAI: BGE large	50.7	87.5	28.8	47.0	28.8
BAAI: BGE base	50.7	33.7	60.2	55.0	39.1
Jina: reranker v2	76.5	77.6	30.0	58.0	18.9
Voyage: rerank-2-lite	33.4	19.8	59.6	22.5	70.4
Jina: reranker v3	80.0	9.1	10.9	5.4	33.2

Model	Michael/Jessica	Richard/Patricia	Robert/Jennifer	Thomas/Barbara	William/Elizabeth
Voyage: rerank-2.5	63.8	63.6	73.6	73.6	63.5
ZeroEntropy: zerank-2	60.3	61.2	49.7	61.6	49.5
Google: default-002	76.4	88.5	85.0	76.9	67.4
IBM: Granite r2	94.1	77.0	91.5	85.0	95.9
Voyage: rerank-3	53.4	72.2	55.1	49.8	58.2
BAAI: BGE v2-m3	88.8	78.6	88.1	60.3	79.8
Open: MiniLM-L6-v2	53.4	84.1	74.5	86.3	79.7
NVIDIA: Nemotron 1B	65.1	40.2	59.1	66.3	71.3
Voyage: rerank-2	49.9	56.4	60.3	50.4	56.7
Cohere: v3.5	61.1	60.6	54.8	68.1	67.9
Open: MiniLM-L12-v2	82.9	71.9	80.9	61.5	59.4
Voyage: rerank-2.5-lite	54.3	63.8	59.8	75.1	58.5
NVIDIA: Nemotron VL 1B	64.2	43.9	54.5	70.1	70.8
Voyage: rerank-1	66.4	79.6	77.3	38.0	59.7
Mixedbread: large v2	71.2	56.6	66.3	63.0	64.8
Cohere: v4 pro	58.2	58.7	45.9	66.5	43.0
Qwen: Qwen3 0.6B	59.5	76.7	44.8	53.4	35.0
Google: fast-004	50.6	49.0	30.0	52.0	58.1
Cohere: v4 fast	56.3	72.2	35.9	60.6	41.8
Qwen: Qwen3 8B	42.5	65.6	41.2	56.7	48.5
Alibaba: GTE ModernBERT	62.4	78.8	61.9	53.5	34.4
Voyage: rerank-3-lite	36.1	36.8	23.4	17.7	24.2
Google: default-004	35.6	43.0	42.1	31.4	29.7
Qwen: Qwen3 4B	48.1	53.8	40.7	61.2	42.8
BAAI: BGE large	62.6	50.8	64.2	15.7	15.6
BAAI: BGE base	72.7	24.2	50.6	48.1	36.3
Jina: reranker v2	48.3	37.1	28.7	30.4	13.6
Voyage: rerank-2-lite	31.3	39.7	18.4	45.9	18.4
Jina: reranker v3	63.3	17.8	48.0	5.6	57.8

D Pipeline results across rerankers

Table A7: Male-associated share of shortlist positions for each reranker behind the same retriever and the same pools of equally qualified documents. The last column is the combined pipeline's mean rank of female-associated documents minus that of male-associated documents in the 20-document pool; a positive value means female-associated documents rank lower.

Re-ranker	Pipeline % male in top-3				Re-ranker	Pipeline mean
	all	male	female	neutral	alone %	rank gap, woman − man (20-doc pool; +: woman lower)
IBM: Granite r2	84.9	95.9	71.7	90.7	89.3	3.69
Google: default-002	79.7	94.2	63.3	86.2	77.5	3.48
Open: MiniLM-L6-v2	79.5	93.3	58.4	94.4	79.0	3.38
BAAI: BGE v2-m3	79.3	95.0	67.3	76.9	78.6	3.41
Open: MiniLM-L12-v2	78.4	91.9	58.6	91.7	78.6	3.32
Cohere: v3.5	73.1	92.6	47.7	87.1	64.1	3.18
Voyage: rerank-1	70.5	91.2	45.0	82.9	68.3	2.94
Mixedbread: large v2	70.5	86.2	52.0	78.5	66.5	2.95
Voyage: rerank-2.5	70.2	98.1	36.3	86.1	71.5	3.00
NVIDIA: Nemotron VL 1B	67.6	89.3	45.2	73.7	65.2	2.81
NVIDIA: Nemotron 1B	66.4	90.0	41.4	73.9	64.1	2.85
Alibaba: GTE ModernBERT	65.8	75.0	60.9	61.1	63.6	2.76
ZeroEntropy: zerank-2	63.6	96.2	29.2	74.1	60.8	2.69
Voyage: rerank-2.5-lite	62.9	89.0	39.2	64.9	56.9	2.62
Qwen: Qwen3 0.6B	62.4	81.3	40.1	72.2	55.3	2.59
Voyage: rerank-3	61.4	93.7	29.8	68.0	60.8	2.62
Voyage: rerank-2	59.8	91.2	29.7	64.9	57.4	2.47
Cohere: v4 fast	56.6	77.5	33.2	65.5	47.5	2.42
Qwen: Qwen3 8B	56.5	79.5	35.0	59.2	48.2	2.32
Google: fast-004	56.2	84.0	31.2	58.1	47.6	2.19
BAAI: BGE base	54.8	71.8	37.8	58.8	46.5	2.13
Qwen: Qwen3 4B	53.5	73.1	35.0	56.4	41.3	2.25
BAAI: BGE large	52.4	73.4	36.1	49.7	42.2	2.05
Cohere: v4 pro	51.8	74.8	32.1	51.7	42.7	2.14
Jina: reranker v2	50.1	67.8	34.4	51.1	31.1	2.03
Jina: reranker v3	48.4	61.8	33.6	53.7	29.8	1.92
Voyage: rerank-2-lite	45.1	66.4	26.0	46.3	38.7	1.69
Google: default-004	44.2	77.6	17.2	41.6	31.7	1.71
Voyage: rerank-3-lite	44.2	80.1	14.2	42.8	31.6	1.69

E De-identification results

Table A8: De-identification conditions on BAAI/bge-reranker-v2-m3. A dagger marks a condition that makes paired documents identical by construction. The utility column is synthetic occupation-matching top-rank accuracy; a dash means that check was not run for the condition.

Condition	% M	% tie	% F	mean |score gap|	identical text %	occupation top-1 %
Original (no transform)	78.0	0.0	22.0	0.0358	0.0	99.4
Lowercase only (control)	58.7	0.0	41.3	0.0301	0.0	–
Names only	93.4	0.0	6.6	0.0380	0.0	99.5
Pronouns only	68.4	0.0	31.6	0.0236	0.0	99.6
Full rule (names + pronouns)†	0.0	100.0	0.0	0.0000	100.0	99.8
Naive rewrite: her → their	1.0	75.0	24.0	0.0007	75.0	–
Naive rewrite: her → them	88.8	0.0	11.2	0.0094	0.0	–
Following-word rule for her†	0.0	100.0	0.0	0.0000	100.0	99.8

Table A9: De-identification conditions across four locally run rerankers.

Condition	BAAI: BGE v2-m3		BAAI: BGE base		Open: MiniLM-L12-v2		Jina: reranker v2	
	tie-aware % M	mean |gap|	tie-aware % M	mean |gap|	tie-aware % M	mean |gap|	tie-aware % M	mean |gap|
Original (no transform)	78.0	0.0358	47.1	0.0373	74.7	0.2797	41.9	0.0186
Lowercase only (control)	58.7	0.0301	44.9	0.0576	74.7	0.2797	35.2	0.0191
Names only	93.4	0.0380	50.6	0.0178	81.9	0.2974	37.6	0.0127
Pronouns only	68.4	0.0236	63.1	0.0363	72.9	0.2189	55.7	0.0167
Full rule (names + pronouns)†	50.0	0.0000	50.0	0.0000	50.0	0.0000	50.0	0.0000
Naive rewrite: her → their	38.5	0.0007	44.2	0.0018	53.5	0.0064	47.5	0.0007
Naive rewrite: her → them	88.8	0.0094	84.1	0.0086	82.0	0.0750	64.8	0.0031
Following-word rule for her†	50.0	0.0000	50.0	0.0000	50.0	0.0000	50.0	0.0000

† The rule makes the two documents the same string, so the tie rate is an identity of the design, not a measurement. For BAAI: BGE base, the original row was scored in the same run as the transformed rows. For Jina: reranker v2, a local re-score did not reproduce the banked untransformed scores (maximum absolute score difference 0.0117), so its original row was re-scored in the same run as its transformed rows and differs slightly from the single-stage audit.

F Companion experiment

Table A10: Companion experiment on publicly posted résumé examples: tie-aware share (%) of comparisons in which the male-associated version scores higher, overall and by occupation group, and the share of comparisons in which the two versions land on opposite sides of the top-three cutoff. Groups follow the corpus's own job categories, mapped to the same labels where possible; the last row gives each group's denominator. These documents, queries, and marker constructions differ from the synthetic audit, so differences between the two cannot be attributed to any single cause.

Reranker	Comparisons	All	Male-typed	Female-typed	Neutral	Unlabeled	Top-3 flips %
BAAI: BGE v2-m3	3,840	51.5	55.9	43.2	49.2	53.0	2.1
BAAI: BGE base	3,840	46.3	47.0	47.2	47.4	44.0	2.6
Open: MiniLM-L12-v2	3,840	37.5	43.1	38.4	34.6	34.2	0.4
Jina: reranker v2	3,840	41.4	48.7	33.4	41.9	37.0	1.4
Comparisons per group			1,120	480	1,120	1,120	

References

[1] J. An, D. Huang, C. Lin, and M. Tai. Measuring gender and racial biases in large language models: Intersectional evidence from automated resume evaluation. *PNAS Nexus*, 4(3):pgaf089, 2025. doi:10.1093/pnasnexus/pgaf089.

[2] Bureau of Labor Statistics, U.S. Department of Labor. Employed people by detailed occupation, sex, race, and Hispanic or Latino ethnicity. Current Population Survey, Household Data Annual Averages, Table 11, 2025 annual averages. `https://www.bls.gov/cps/cpsaat11.htm`.

[3] R. Bommasani, S. H. Bana, K. A. Creel, D. Jurafsky, and P. Liang. Algorithmic Monocultures in Hiring. In *Proceedings of the 2026 ACM Conference on Fairness, Accountability, and Transparency (FAccT '26)*, 2026. doi:10.1145/3805689.3812400. arXiv:2605.27371.

[4] A. Caliskan, J. J. Bryson, and A. Narayanan. Semantics derived automatically from language corpora contain human-like biases. *Science*, 356(6334):183–186, 2017. doi:10.1126/science.aal4230.

[5] V. Karpukhin, B. Oğuz, S. Min, P. Lewis, L. Wu, S. Edunov, D. Chen, and W. Yih. Dense Passage Retrieval for Open-Domain Question Answering. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6769–6781, 2020. doi:10.18653/v1/2020.emnlp-main.550.

[6] R. Nogueira and K. Cho. Passage Re-ranking with BERT. arXiv preprint arXiv:1901.04085, 2019.

[7] P. Parasurama and J. Sedoc. Degendering Resumes for Fair Algorithmic Resume Screening. arXiv preprint arXiv:2112.08910, 2022.

[8] National Center for O*NET Development. O*NET 30.3 Database. O*NET Resource Center, U.S. Department of Labor, Employment and Training Administration. Retrieved 22 August 2026. Used under CC BY 4.0. `https://www.onetcenter.org/database.html`.

[9] V. Rakivnenko, N. Maslej, J. Cervi, and V. Zhukov. Bias in Text Embedding Models. arXiv preprint arXiv:2406.12138, 2024.

[10] N. Rekabsaz and M. Schedl. Do Neural Ranking Models Intensify Gender Bias? In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 2065–2068, 2020. doi:10.1145/3397271.3401280.

[11] N. Rekabsaz, S. Kopeinik, and M. Schedl. Societal Biases in Retrieved Contents: Measurement Framework and Adversarial Mitigation of BERT Rankers. In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 306–316, 2021. doi:10.1145/3404835.3462949.

[12] S. Samuel, B. Van Durme, and E. Yang. Does Reasoning Make Search More Fair? Comparing Fairness in Reasoning and Non-Reasoning Rerankers. arXiv preprint arXiv:2603.10332, 2026.

[13] Social Security Administration. National data on the relative frequency of given names in the population of U.S. births. Tabulated from Social Security records as of 1 March 2026. `https://www.ssa.gov/oact/babynames/limits.html`.

[14] K. Wilson and A. Caliskan. Gender, Race, and Intersectional Bias in Resume Screening via Language Model Retrieval. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, 7(1):1578–1590, 2024. doi:10.1609/aies.v7i1.31748.