

# STAT3191/6191: Group Project Submission

Group Number: Group 17

(Group Leader) Vathana Khun (48302031)  
Sadiqun Nur Ayan (48920959)      Raja Pedapudi (46562753)

2025-09-26

## Part A: Natural Variation in Completion Times

```
# Load required library
library(matrixStats)
library(kableExtra)
```

```
# Simulation-Based Inference: Estimating Completion Time for Security Training
# Set seed for reproducibility
set.seed(42)
```

```
# Parameters
n <- 250           # Sample size per simulation
lambda <- 1        # Rate parameter for Exponential(1)
n_sim <- 1000      # Number of simulations
```

```
## Section 1, Part A : Natural Variation in Completion Times ##
```

```
# Step 1: Generate 1000 samples of size 250 from Exponential(1)
samples <- replicate(n_sim, rexp(n, rate = lambda))
```

```
# Step 2: Compute estimators for each sample
sample_means <- colMeans(samples)
sample_medians <- apply(samples, 2, median)
sample_trimmed_means <- apply(samples, 2, function(x) mean(x, trim = 0.1))
```

```
# Step 3: Calculate Bias, Monte Carlo Standard Deviation (MCSD), and Mean Squared Error (MSE)
true_mean <- 1 # Theoretical mean of Exponential(1)
```

```

# Bias = mean of estimates - true mean
bias_mean <- mean(sample_means) - true_mean
bias_median <- mean(sample_medians) - true_mean
bias_trimmed <- mean(sample_trimmed_means) - true_mean

# Monte Carlo Standard Deviation = standard deviation of estimates
mcsd_mean <- sd(sample_means)
mcsd_median <- sd(sample_medians)
mcsd_trimmed <- sd(sample_trimmed_means)

# Mean Squared Error = mean squared difference from true mean
mse_mean <- mean((sample_means - true_mean)^2)
mse_median <- mean((sample_medians - true_mean)^2)
mse_trimmed <- mean((sample_trimmed_means - true_mean)^2)

# Step 4: Summarise results in a table
results_partA <- data.frame(
  Estimator = c("Mean", "Median", "Trimmed Mean (10%)"),
  Bias = c(bias_mean, bias_median, bias_trimmed),
  MCSD = c(mcsd_mean, mcsd_median, mcsd_trimmed),
  MSE = c(mse_mean, mse_median, mse_trimmed)
)
results_partA %>%
  kable() %>%
  kable_classic(full_width = F, html_font = "Cambria")

```

Estimator	Bias	MCSD	MSE
Mean	-0.0017348	0.0641395	0.0041128
Median	-0.3068622	0.0637944	0.0982301
Trimmed Mean (10%)	-0.1701139	0.0587640	0.0323885

## Section 1, Part B: Logging Error Introduces Outliers #

```

# Step 1: Generate 1000 contaminated samples:
# 90% from Exp(1), 10% from Exp(0.02) to simulate contamination
lambda1 <- 1
lambda2 <- 0.02
contamination_rate <- 0.1

```

```

samples_contaminated <- matrix(NA, nrow = n, ncol = n_sim)

for (i in 1:n_sim) {
  n1 <- round(n * (1 - contamination_rate)) # number from main distribution
  n2 <- n - n1                             # number from contamination

  # Generate and combine samples
  samples_contaminated[, i] <- c(rexp(n1, rate = lambda1), rexp(n2, rate = lambda2))

  # Shuffle to mix contaminated values randomly
  samples_contaminated[, i] <- sample(samples_contaminated[, i])
}

# Step 2: Compute estimators for contaminated samples
sample_means_cont <- colMeans(samples_contaminated)
sample_medians_cont <- apply(samples_contaminated, 2, median)
sample_trimmed_means_cont <- apply(samples_contaminated, 2, function(x) mean(x, trim = 0.1))

# Step 3: Calculate Bias, MCSD, MSE for contaminated data
# True mean for mixture:  $0.9 * 1/\lambda_1 + 0.1 * 1/\lambda_2$ 
true_mean_cont <- 0.9 * (1 / lambda1) + 0.1 * (1 / lambda2) # = 5.9

bias_mean_cont <- mean(sample_means_cont) - true_mean_cont
bias_median_cont <- mean(sample_medians_cont) - true_mean_cont
bias_trimmed_cont <- mean(sample_trimmed_means_cont) - true_mean_cont

mcsd_mean_cont <- sd(sample_means_cont)
mcsd_median_cont <- sd(sample_medians_cont)
mcsd_trimmed_cont <- sd(sample_trimmed_means_cont)

mse_mean_cont <- mean((sample_means_cont - true_mean_cont)^2)
mse_median_cont <- mean((sample_medians_cont - true_mean_cont)^2)
mse_trimmed_cont <- mean((sample_trimmed_means_cont - true_mean_cont)^2)

# Step 4: Summarise contaminated results in a table
results_partB <- data.frame(
  Estimator = c("Mean", "Median", "Trimmed Mean (10%)"),
  Bias = c(bias_mean_cont, bias_median_cont, bias_trimmed_cont),
  MCSD = c(mcsd_mean_cont, mcsd_median_cont, mcsd_trimmed_cont),
  MSE = c(mse_mean_cont, mse_median_cont, mse_trimmed_cont)
)

```

```

results_partB%>%
  kable()%>%
  kable_classic(full_width = F, html_font = "Cambria")

```

Estimator	Bias	MCSD	MSE
Mean	-0.0017397	1.0242196	1.04798
Median	-5.0862454	0.0751779	25.87554
Trimmed Mean (10%)	-4.8103352	0.0771154	23.14527