
LINGUABRIDGE: AI-POWERED MULTILINGUAL TRANSLATION AND SENTIMENT ANALYSIS

Saumik Chakraborty^{1,2,*}, Tapomoy Adhikari^{1,3}, Vengatesan Krishnasamy^{1,4}, Abhisek Raj^{1,2}
saumik17rkl@gmail.com, tapomoy@cornit.com, vengicse2005@gmail.com, abhisek.raj.tiwari@gmail.com

¹ Finessefleet Foundation, Bengaluru, India

² NIST University, Berhampur, India

³ Cornit Research, Bengaluru, India

⁴ Sanjivani University, Kopargaon, India

* Corresponding author

ABSTRACT

India’s linguistic diversity presents a significant challenge to seamless communication and the effective delivery of digital services across regions. We introduce **LinguaBridge**, an AI-powered framework that enables robust multilingual translation and sentiment analysis for over 22 Indian languages. We utilize modern NLP technologies such as Google Translate, TextBlob, and Llama, so the system facilitates real-time text translation, emotion detection, and performance feedback. The architecture is designed to be modular, scalable, and adaptable, with integrated user feedback loops to refine model selection dynamically. Applications of this system span diverse domains including education, healthcare, governance, and social media.

Keywords Multilingual Machine Translation · Sentiment and Emotion Analysis · Indian Languages

1 Introduction

India’s extraordinary linguistic diversity, spanning 22 scheduled languages and over 1,500 dialects [1], enriches its cultural landscape but also creates significant barriers to inclusive digital access, education, healthcare, and governance. Despite rapid growth in digital infrastructure, large segments of the population remain underserved due to language constraints, which limit access to vital information and services.

Recent advances in Natural Language Processing (NLP), especially transformer-based models, have transformed machine translation and sentiment analysis. Yet, most tools remain optimized for high-resource languages such as English or Chinese, leaving Indian languages—often low-resource, morphologically rich, and code-mixed—underrepresented and underperforming in real-world multilingual systems.

To address this gap, we propose **LinguaBridge**: an AI-powered, modular framework that unifies multilingual translation and sentiment analysis across 22 Indian languages. **LinguaBridge** integrates multiple translation backends (e.g., Google Translate, Llama [2], LibreTranslate) with hybrid rule-based and deep learning sentiment pipelines. A distinctive feature is its real-time user feedback mechanism, which dynamically refines model selection to improve translation accuracy and sentiment inference over time. Designed for scalability and inclusivity, **LinguaBridge** targets applications ranging from education and governance to healthcare and social media analytics.

The rest of this paper details the system architecture, methodological approach, evaluation results, and practical applications, and concludes with discussion on limitations, future enhancements, and broader relevance to multilingual NLP.

2 Related Work

Multilingual Natural Language Processing (NLP) has witnessed substantial progress over the past decade, driven by innovations in deep learning, the availability of large multilingual corpora, and increasing demand for cross-lingual communication tools. The area of multilingual machine translation and sentiment analysis—especially for underrepresented languages such as those native to the Indian subcontinent—remains an active and evolving research frontier.

2.1 Multilingual Machine Translation

Historically, machine translation systems were developed using rule-based and statistical approaches [3, 4]. With the advent of deep learning, neural machine translation (NMT) architectures such as the encoder-decoder model [5] and the attention mechanism [6] revolutionized the field. The introduction of the Transformer architecture [6] provided a highly parallelizable and scalable solution, giving rise to models such as Google’s Multilingual Neural Machine Translation (MNMT) [7] and Facebook AI’s M2M-100 [8], both of which support dozens of languages including some Indic ones.

Despite these advancements, most general-purpose translation engines still struggle with Indian languages due to sparse training data, complex grammar, and significant code-switching in informal texts. To address this, dedicated initiatives have emerged. For example, **AI4Bharat**’s IndicTrans2 model [9] represents a milestone in Indian language translation, leveraging Transformer-based architecture fine-tuned on parallel corpora specific to Indian language pairs. Similarly, **Samanantar** [10] provides the largest publicly available parallel dataset for Indian languages, facilitating research in multilingual modeling.

Additionally, multilingual frameworks like **OPUS-MT** [11] and **LibreTranslate** offer open-source alternatives to proprietary systems, albeit with limited domain adaptation and uneven quality across language pairs. Several efforts have also been made to evaluate and benchmark Indian language translation systems, including the WAT (Workshop on Asian Translation) shared tasks [12], which continue to highlight the wide performance gap between high- and low-resource Indian languages.

2.2 Sentiment Analysis and Emotion Detection

Recent advancements in Indic NLP have sought to address persistent challenges in sentiment classification for Indian languages. Initiatives such as the **IJCNLP Sentiment Analysis Shared Task** [13] and the **DravidianLangTech** workshops have galvanized community efforts focused on languages including Hindi, Tamil, and Malayalam. Meanwhile, annotated resources like the **Hindi SentiWordNet** [14] and the **SentiMix** dataset [15] have provided valuable benchmarks, although the overall coverage across Indic languages remains limited.

To overcome these limitations and improve contextual understanding, there is a growing consensus on augmenting or replacing traditional lexicon-based tools such as TextBlob with transformer-based architectures, notably IndicBERT. These models are explicitly designed to capture the linguistic nuances inherent to Indian languages, significantly enhancing sentiment analysis performance. Hybrid approaches that combine rule-based lexicons with deep learning techniques—including convolutional neural networks (CNNs), long short-term memory networks (LSTMs), and transformer-based models such as mBERT and IndicBERT [16, 17]—have demonstrated promising results in capturing sentiment subtleties across diverse Indic scripts. Nonetheless, the presence of code-mixing and multilingual noise, which are prevalent in social media and user-generated content within India, continues to adversely affect system performance.

Addressing this challenge, recent research has specifically targeted the phenomenon of code-switching, wherein multiple languages co-occur within a single utterance or discourse, further complicating NLP tasks. The **GLUECoS** benchmark [18] provides an evaluation suite for code-switched NLP tasks involving English-Hindi and English-Spanish language pairs. It encompasses a range of tasks including language identification, part-of-speech tagging, named entity recognition, sentiment analysis, question answering, and natural language inference. Findings from this work reveal that multilingual models fine-tuned on artificially generated code-switched data outperform both standard cross-lingual and multilingual models across most evaluated tasks. This underscores the critical need for model adaptation to code-switching phenomena, which are especially pervasive in Indian social and conversational contexts. Incorporating such tailored approaches can substantially enhance the robustness and accuracy of sentiment and emotion detection systems in multilingual environments.

By integrating IndicBERT or similar transformer-based architectures, the emotional analysis module of the **LinguaBridge** system is poised to achieve more nuanced contextual understanding, enabling it to more accurately capture the emotional

tone of multilingual texts. This enhancement aims not only to improve overall system performance but also to enrich user experience through more insightful and expressive emotional analysis capabilities.

2.3 Language Technologies for Indian Contexts

Several national and academic initiatives have catalyzed progress in Indian language AI. The **Bhashini** initiative by the Indian government and the broader **National Language Translation Mission (NLTM)** aims to build scalable AI models for all 22 scheduled Indian languages. Research groups like AI4Bharat, IIT Madras, IIIT Hyderabad, and Microsoft Research, India have played pivotal roles in releasing datasets, pretrained models, and APIs tailored for local contexts.

Multilingual projects such as **Masakhane** in Africa and **BigScience BLOOM** [19] have further highlighted the global need for inclusive language modeling. The Indian NLP ecosystem, however, still lacks a unifying framework that integrates translation, sentiment analysis, and user-centered feedback mechanisms.

2.4 Gap Analysis and Research Motivation

While many translation engines and sentiment classifiers exist, few systems are designed to operate across 20+ Indian languages with a consistent user experience, modular architecture, and real-time feedback loop. Moreover, most studies treat translation and sentiment analysis as separate pipelines without examining the cascading effects of translation quality on downstream sentiment inference.

LinguaBridge attempts to fill this crucial gap by offering an integrated system where multiple translation engines can be compared and selected dynamically based on user feedback, and where sentiment analysis is sensitive to translation ambiguity, cultural nuance, and emotion preservation. To our knowledge, this is one of the first frameworks to unify these functionalities specifically for Indian languages in a modular, scalable, and user-centered manner.

3 System Design and Architecture

The LinguaBridge system is designed to tackle the complexities of multilingual sentiment analysis (MSA) in a linguistically diverse context like India. Key challenges addressed include managing morphologically rich languages, processing code-switched and mixed-script inputs, and coping with limited labeled data. This section outlines the system’s modular architecture, highlighting its core components and their integration to enable scalable, adaptive sentiment analysis.

Figure 6 presents an overview of the end-to-end workflow, illustrating the sequential processing of user input through translation, sentiment analysis, dynamic model selection, and visualization.



Figure 1: End-to-End Workflow of the LinguaBridge System: From user input to translated output with sentiment and visual analytics

3.1 Architectural Overview

LinguaBridge adopts a modular architecture comprising four main components:

1. Translation engine,
2. Sentiment analysis module and emotion detection,
3. Dynamic model selection mechanism driven by user feedback,
4. Visualization and analytics module.

The architecture separates the presentation layer from business logic, facilitating independent scaling and maintenance. The system is designed for scalability through containerization, asynchronous processing, and caching strategies to optimize performance and reduce latency.

3.1.1 Architectural Style

The system employs a layered design:

- **Presentation Layer:** User interface developed with Streamlit for intuitive interaction.
- **Application Layer:** Implements translation, sentiment analysis, model selection, and feedback handling.
- **Service Layer:** Integrates external APIs (e.g., Google Translate, Llama models) and internal microservices.
- **Data Layer:** Manages session state, user feedback, and analytics data.

This approach supports deployment as either a monolithic application or as distributed microservices based on scale requirements.

3.1.2 High-Level Architecture

Key modules include:

- **User Interface:** A web application with navigation for module selection.
- **Translation Service:** Routes text to appropriate translation models based on feedback and word based translation using Llama 3.3 model.
- **Sentiment Analysis Service:** Analyzes sentiment using TextBlob, afinn and vader using tokenization.
- **Emotional detection Service:** Analyzes the emotion of the sentence.
- **Feedback Engine:** Collects and analyzes user feedback to guide dynamic model selection.
- **Analytics Module:** Generates performance visualizations and confusion matrices.
- **External Datasets:** Use unstructured learning for tokenization for code-mix translations.
- **External APIs:** Includes Google Translate.




Figure 2: Line graph showing model performance (e.g., accuracy or F1-score) over time as user feedback increases, highlighting the system's adaptive behavior.

The user interface, implemented in Streamlit, enables text input and displays translated text with sentiment analysis. Translation primarily relies on Google Translate with fallback or supplementary use of TextBlob and AI4Bharat models. User feedback collected via a five-point scale informs a dynamic model selection mechanism that adapts translation strategies over time to improve accuracy and user satisfaction. Visualization tools built with Matplotlib and Seaborn provide insights into model and language-specific performance.

3.2 Core Modules

3.2.1 Translation Engine

Supporting 22 Indian languages alongside English, the translation engine employs a hybrid approach integrating multiple models. Google Translate serves as the primary model with automatic language detection to simplify user interaction. An internal mapping between language names and ISO codes ensures accurate routing of translation requests.

3.2.2 Sentiment Analysis Module

This module employs TextBlob, afinn, nltk and vader for token based evaluation the polarity of translated text, scoring sentiment on a scale from -1 (negative) to +1 (positive), with values near zero representing neutrality. This provides users with emotional context beyond literal translations. Multi-module analysis is done and average of all token and module are compared and provides the sentiment.

3.3 Emotional detection Module

This module uses nrclx for emotional detection

3.3.1 Visualization and Analytics




Figure 3: Line graph showing model performance (e.g., accuracy or F1-score) over time as user feedback increases, highlighting the system’s adaptive behavior.




Figure 4: Heatmap visualizing confusion matrix for emotion classification. For instance, showing how often happiness was confused with surprise, or negative with neutral sentiment.

3.3.2 Dynamic Model Selection

A novel component of LinguaBridge is the feedback-driven dynamic selection mechanism. User ratings on translations are aggregated to adjust the choice of translation models dynamically. This reinforcement-like approach enables the system to learn from user preferences and improve over time, adapting to evolving language use and quality expectations.

3.3.3 Visualization and Analytics

Comprehensive visualization modules provide transparency into system performance by displaying:

- Model-wise accuracy comparisons,
- Language-specific translation quality,




Figure 5: Bar charts comparing model accuracy across translation engines: Google Translate, AI4Bharat, and Gamma/LLaMa.

- Confusion matrices highlighting translation and language identification errors.

These visual insights support ongoing evaluation and system refinement.

3.4 User Interface Implementation

The frontend, built using Streamlit, offers four primary modules:

- **Translator** for direct text translation,
- **Code-Mix translator** for proper translation of code-mix languages(e.g., Hinglish, Banglish, Tanglish, etc.)
- **Sentiment Analysis** for emotional tone classification,
- **Accuracy Insights** for visualization of performance metrics.

This modular interface enhances usability and isolates frontend logic from backend processes.

3.5 Error Handling and Robustness

Robust error handling ensures system stability during unexpected inputs or service disruptions, maintaining usability and reliability.

3.6 Evaluation Methodology

Performance is assessed via multiple metrics:

- Model accuracy comparison,
- Language-specific translation quality,
- Confusion matrix analysis,
- User feedback evaluation.

This multifaceted evaluation framework enables targeted improvements.

3.7 Implementation Details

LinguaBridge is implemented in Python, utilizing:

- Streamlit for UI,
- Deep-Translator for Google Translate API access,
- TextBlob,afinn, vader for sentiment analysis,
- NRCLex for Emotional classification
- Matplotlib and Seaborn for visualization,
- NumPy and Scikit-learn for analytical support.

The system follows object-oriented, modular design principles to facilitate maintenance and future enhancements.




Figure 6: LLD of LinguaBridge

3.8 Preprocessing Layer

The preprocessing pipeline standardizes and cleans multilingual text before it enters downstream tasks. Given the noise in real-world user-generated content, this stage is critical for boosting the performance of translation and sentiment models.

- **Normalization:** We apply Unicode normalization (NFKC), remove special characters, HTML tags, URLs, and excessive whitespace using regular expressions.
- **Translation:** For uniform downstream processing, all input texts are normalized into English using multilingual neural machine translation (NMT) engines. We use Google Translate, AI4Bharat IndicTrans2, and LibreTranslate APIs as configurable backends.
- **Tokenization and Stemming:** We apply language-specific tokenizers and use the Porter stemmer or Snowball stemmer to reduce inflected words to their roots.

3.9 Feature Extraction and Embedding Layer

The aim of this layer is to convert raw text into semantically meaningful numerical representations that can be ingested by machine learning models. We utilize both classical and contextual embeddings:

- **TF-IDF Vectors:** For traditional ML models, term frequency-inverse document frequency vectors provide sparse, interpretable features.
- **Pre-trained Word Embeddings:** We use multilingual embeddings such as mBERT, XLM-RoBERTa, and IndicBERT for deep learning models. Each word is mapped to a high-dimensional vector $\vec{w}_i \in \mathbb{R}^d$ that captures contextual semantics across languages.
- **Document Embeddings:** Sentence-BERT or Mean-Pooling over word vectors is used to construct document-level embeddings:

$$\vec{d} = \frac{1}{n} \sum_{i=1}^n \vec{w}_i$$

where n is the number of tokens in the sentence.

- **Graph-based Encoding:** We utilize MSA-GCN, a graph convolutional approach where documents are represented as graphs $G = (V, E)$ with nodes as words and edges as co-occurrence or dependency links. The graph embeddings are learned via:

$$H^{(l+1)} = \sigma \left(\hat{D}^{-1/2} \hat{A} \hat{D}^{-1/2} H^{(l)} W^{(l)} \right)$$

where $\hat{A} = A + I$ is the adjacency matrix with self-loops, $H^{(l)}$ is the feature matrix at layer l , and $W^{(l)}$ is a trainable weight matrix.

3.10 Sentiment Classification Models

This is the core layer where transformed inputs are classified into sentiment categories — usually **positive**, **negative**, and **neutral**, though it can be extended to multi-label emotion classification (e.g., **joy**, **anger**, **fear**, etc.).

3.10.1 Traditional Machine Learning Models

- **Support Vector Machines (SVM):** A hyperplane-based model that maximizes the margin between classes. It is especially effective when trained with TF-IDF features on smaller datasets.
- **Naïve Bayes:** A probabilistic classifier based on Bayes' theorem:

$$P(C_k|X) = \frac{P(X|C_k)P(C_k)}{P(X)}$$

where X is the feature vector, and C_k denotes a sentiment class.

3.10.2 Deep Learning Models

- **LSTM/BiLSTM:** Recurrent models that capture sequential dependencies. The hidden and cell states are updated as:

$$h_t, c_t = \text{LSTM}(x_t, h_{t-1}, c_{t-1})$$

where x_t is the input at time t , h_{t-1} and c_{t-1} are the previous hidden and cell states, and h_t, c_t are the updated states.

Bidirectional LSTMs (BiLSTMs) process the sequence in both forward and backward directions:

$$h_t = [\vec{h}_t; \overleftarrow{h}_t]$$

where $\vec{h}_t$ and $\overleftarrow{h}_t$ are the hidden states from the forward and backward passes, respectively. This helps capture context from both directions.

- **CNN for Text:** 1D convolutional filters detect n-gram features:

$$c_i = \text{ReLU}(w \cdot x_{i:i+h-1} + b)$$

where $x_{i:i+h-1}$ is the input window, w is the filter, and b is the bias.

- **Hybrid CNN-LSTM Models:** These models extract local features with CNNs and sequence information with LSTMs, improving robustness on noisy multilingual texts.

3.10.3 Graph Convolutional Networks (GCN)

To enable cross-lingual sentiment modeling, we implement MSA-GCN, a multilingual graph-based model. Words and documents across languages are connected through a shared multilingual embedding space. This promotes knowledge transfer from high-resource to low-resource languages. GCNs propagate label and structure information using message passing:

$$H^{(l+1)} = \sigma(\tilde{A}H^{(l)}W^{(l)})$$

where $H^{(0)}$ is initialized with word/document embeddings, and $\tilde{A}$ is the normalized adjacency matrix.

3.11 Modular and Scalable Deployment

The entire system is encapsulated into microservices deployed using containerized infrastructure (e.g., Docker + Kubernetes), making the architecture horizontally scalable and domain-adaptable. The system follows a plug-and-play philosophy:

- **Translation Module:** Accepts input in any supported language and returns normalized English output.
- **Sentiment Module:** Classifies the translated text using the selected classifier.
- **Feedback Module:** Captures user ratings to fine-tune or select optimal models over time.

In essence, the LinguaBridge architecture is an end-to-end system for real-time, multilingual sentiment analysis, capable of adapting across domains, scaling across languages, and evolving through user feedback. The integration of GCNs, hybrid deep models, and multilingual embeddings marks a significant advancement over monolithic or mono-lingual sentiment analysis frameworks.

4 Methodology and Proposed Approach

This section presents the methodology and proposed approach for the LinguaBridge system, which integrates multilingual translation, sentiment analysis, and a feedback-driven evaluation framework. The design supports over 22 Indian regional languages and English. We describe the data collection process, core modules, implementation techniques, and evaluation metrics. The methodology is structured into five main components: data processing, model application, algorithmic translation, sentiment inference, and evaluation analytics.

4.1 Data Collection

The data used in LinguaBridge is compiled from high-quality multilingual sources such as AI4Bharat IndicCorp, IndicNLP Corpora, OpenSubtitles, and WMT shared tasks. This dataset includes over 50,000 sentence pairs across 22 Indian languages and English, enriched with sentiment annotations (Positive, Negative, Neutral, Angry, Sad, Fear). Additional contextual data is gathered via user interaction and feedback mechanisms embedded in the application.

4.2 System Workflow Overview

The implementation pipeline is divided into functional blocks:

- **User Interface:** A lightweight interface is built using Streamlit to collect input, provide translation, show sentiment analysis, and visualize metrics.
- **Translation Layer:** Google Translate, Gamma and LLaMa APIs are used to perform dynamic translations, augmented with 22+ language normalization via a custom dictionary.
- **Sentiment Layer:** TextBlob, afinn and vader are used for polarity computation to classify emotions.
- **Evaluation and Feedback Loop:** Real-time user feedback is collected and modeled to enhance decision-making regarding model selection.

4.3 Implementation Flow and Pseudocode Modules

Algorithm 1 Main Application Flow

```
1: Initialize: Load code-mix dictionary  $D \leftarrow \text{load\_code\_mix}()$ 
2: Define language set  $L \leftarrow \{l_1, l_2, \dots, l_{22}, \text{en}\}$ 
3: Display sidebar menu  $M \leftarrow \{\text{Translator, Sentiment, Chatbot, Insights}\}$ 
4:  $\text{choice} \leftarrow \text{user selection from } M$ 
5: if  $\text{choice} = \text{Translator}$  then
6:   Process translation input  $\rightarrow \text{process\_translation}(\text{input}, \text{target}, D)$ 
7: else if  $\text{choice} = \text{Code-Mix Translator}$  then
8:   Process Code-Mix Translation input  $\rightarrow \text{process\_Code-mix\_translation}(\text{input}, \text{target}, D)$ 
9: else if  $\text{choice} = \text{Sentiment}$  then
10:  Perform sentiment analysis  $\rightarrow \text{analyze\_sentiment}(\text{text})$ 
11: else if  $\text{choice} = \text{Chatbot}$  then
12:  Translate and respond with chatbot engine
13: else
14:  Display insights and visualizations
15: end if
```

4.4 Translation Algorithm

Translation handles line-wise user input, preserves formatting, and translates using external APIs.

Algorithm 2 Code-Mix Translation

```
1: Input:  $\text{code\_mixed\_text}$ ,  $\text{selected\_language\_pair}$ ,  $\text{scheme}$ 
2: Tokenize  $\text{code\_mixed\_text} \rightarrow \text{tokens}$ 
3: Load model/tokenizer for  $\text{selected\_language\_pair} \rightarrow (\text{model}, \text{tokenizer})$ 
4: for each token  $t \in \text{tokens}$  do
5:   Preprocess  $t$  (normalize, lower-case, strip)
6: end for
7: Construct  $\text{model\_input} \leftarrow \text{tokenizer}(\text{tokens})$ 
8: Generate  $\text{output\_ids} \leftarrow \text{model.generate}(\text{model\_input})$ 
9: Decode  $\text{output\_ids} \rightarrow \text{translated\_text}$ 
10: Transliterate  $\rightarrow \text{native\_script\_text} \leftarrow \text{transliterate}(\text{translated\_text}, \text{scheme})$ 
11: if model-based correction then
12:   Prepare  $\text{batch\_input} \leftarrow \text{IndicTrans2.preprocess}(\text{native\_script\_text})$ 
13:   Generate  $\text{output\_ids} \leftarrow \text{model.generate}(\text{batch\_input})$ 
14:   Decode and postprocess  $\rightarrow \text{final\_text}$ 
15: else
16:    $\text{final\_text} \leftarrow \text{native\_script\_text}$ 
17: end if
18: return  $\text{final\_text}$ 
```

4.5 Sentiment Polarity and Classification

We utilize TextBlob for computing sentiment polarity. The sentiment s is computed as:

$$\text{Polarity}(s) = \begin{cases} \text{Positive}, & \text{if } p > 0 \\ \text{Neutral}, & \text{if } p = 0 \\ \text{Negative}, & \text{if } p < 0 \end{cases}$$

Where $p \in [-1.0, +1.0]$ is the polarity score returned by `TextBlob(text).sentiment.polarity`.

4.6 Emotion Detection

For deeper understanding, we expand to multiclass emotion recognition:

Classes = Joy, Anger, Sadness, Fear, Surprise
Models = CNN-LSTM Hybrid / NRCLex

4.7 Confusion Matrix Evaluation

We measure the quality of predictions using the standard confusion matrix, defined as:

$$CM = \begin{bmatrix} TP & FP \\ FN & TN \end{bmatrix}$$

where:

- TP = True Positives,
- FP = False Positives,
- FN = False Negatives,
- TN = True Negatives.

This matrix is generated using:

```
from sklearn.metrics import confusion_matrix  
cm = confusion_matrix(y_true, y_pred)
```

4.8 Model Selection Based on Feedback

A dynamic scoring mechanism selects the most appropriate translation model:

$$\text{Bad Ratio} = \frac{\text{Score}_{\text{Bad}} + \text{Score}_{\text{Ok}}}{\text{Total Feedback}}$$

If Bad Ratio < 0.4, switch to AI4Bharat, else continue with Google Translate.

Algorithm 3 RL-Based Translation Quality Feedback

```
1: Initialize Dataset  $D$  and Model  $M$   
2: procedure ADDFEEDBACK( $s, t, f, l_s, l_t, m, c, q$ )  
3:   Extract features from  $s, t, l_s, l_t$   
4:    $D \leftarrow D \cup \{\text{features}, f, q\}$   
5: end procedure  
6: procedure PREDICTQUALITY( $s, t, l_s, l_t$ )  
7:   if  $|D| < 10$  then return 0.8  
8:   end if  
9:   return  $M.\text{predict}(\text{ExtractFeatures}(s, t, l_s, l_t))$   
10: end procedure  
11: procedure UPDATEWITHFEEDBACK( $f$ )  
12:   AddFeedback( $f$ )  
13:   if  $|D| \geq \text{batch\_size}$  and UpdateIntervalPassed() then  
14:     Train  $M$  using batch from  $D$   
15:     Save updated  $M$  and  $D$   
16:   end if  
17: end procedure
```

4.9 Accuracy Metrics and Visualization

Model performance is visualized using:

- **Bar Charts:** Translation accuracy across different languages.
- **Heatmaps:** Visual confusion matrices using Seaborn.
- **Line Graphs:** Performance change over time with feedback.

Accuracy Formula:

$$\text{Accuracy} = \frac{\text{Correct Predictions}}{\text{Total Predictions}} \times 100\%$$

4.10 Error Handling and Robustness

Robust exception handling is implemented for translation errors, network failures, and unsupported characters. Code-mix normalization ensures grammatical structure is preserved.

4.11 Application Adaptability

The application’s modular architecture allows easy inclusion of:

- **New Languages:** By extending dictionary D and updating API coverage.
- **Alternate APIs:** Plug-in support for Azure, Amazon Translate, or AI4Bharat enhancements.
- **Advanced Sentiment Models:** Replacement of TextBlob with transformer-based classifiers like BERT or IndicBERT.

The proposed approach integrates multiple components—translation, code-mix resolution, sentiment polarity detection, and feedback analytics—into a single framework that serves both academic evaluation and end-user deployment. The feedback loop ensures progressive improvement, and the modularity supports experimentation with multilingual NLP technologies.

5 Results and Discussion

This section presents a unified analysis of the experimental setup, quantitative results, user feedback, and interpretive discussion regarding the performance of the proposed LinguaBridge framework across multilingual NLP tasks in the Indian context. The evaluation highlights both the empirical strengths and current limitations of the system.

5.1 Experimentation Setup

The LinguaBridge system integrates several specialized libraries and APIs that support translation, sentiment analysis, multilingual handling, and interactive deployment. The components listed below were critical in enabling these core functionalities:

Table 1: Key Libraries and APIs Used in the LinguaBridge System

Component	Description
Streamlit	Used to develop an interactive web-based UI for testing multilingual translation and sentiment modules.
TextBlob	Applied for sentiment polarity and subjectivity detection in English texts.
deep_translator	Provides a unified interface to access multiple translation APIs, including Google Translate and AI4Bharat.
Scikit-learn	Used to compute classification performance metrics such as precision, recall, F1-score, and confusion matrices.
Google Translate API	Used as a baseline multilingual translation engine for comparison and fallback.
Gamma and LLaMa	Primary translation engine for high-quality English-to-Indic and Indic-to-English language conversion.




Figure 7: Pie chart summarizing user satisfaction metrics. For example, 78% rated their experience as Excellent, 15% as Good, and 7% as Average.

5.2 Baseline Models for Comparison

To evaluate the efficacy of the proposed system, several established baseline models were used for comparison in multilingual translation and sentiment inference tasks:

Table 2: Baseline Models and Reported Accuracy

Model	Description	Reported Accuracy
Google Translator	Industry-standard NMT system supporting wide language coverage.	95%
TextBlob	Rule-based model for grammatical parsing and sentiment inference.	85%
Deep Learning Indic Translators	Deep learning-based translation system trained on IndicCorp.	92%

Our hybrid system combines these tools in a feedback-driven architecture to balance fluency, adaptability, and performance under real-time constraints.

5.3 Mean Translation Accuracy Summary

The average translation accuracy across 18 Indian languages was computed as:

$$\text{Mean Accuracy} = 85.94\%$$

This indicates solid general performance, particularly in linguistically diverse settings. Languages with rich digital corpora (e.g., Hindi, Marathi) achieved the highest scores, while low-resource languages (e.g., Konkani, Manipuri) faced degradation in translation quality.

Table 3: Language-wise Translation Accuracy

Language	Accuracy (%)
Assamese	90
Bengali	88
Gujarati	85
Hindi	92
Kannada	86
Konkani	80
Maithili	83
Malayalam	84
Manipuri (Meitei)	82
Marathi	90
Nepali	87
Odia	85
Punjabi	89
Sanskrit	85
Sindhi	81
Tamil	85
Telugu	87
Urdu	88

The findings reaffirm that translation accuracy correlates positively with the richness of language-specific training data, emphasizing the need for expanded linguistic datasets in underrepresented languages.

5.4 Qualitative Sentiment and Emotion Classification Results

Sentiment classification yielded the following quantitative results:

- **Overall Accuracy:** 88%
- **Precision:** 83.33%
- **Recall:** 80.56%
- **F1-Score:** 80.24%

Classification Categories:

- **Polarity-Based:** Positive, Negative, Neutral
- **Emotion-Specific:** Anger, Sadness, Fear, Joy, Surprise

While the system performed well in general, it struggled with pragmatically nuanced inputs such as sarcasm (e.g., “Just what I needed!”), short texts lacking emotional context (e.g., “Meh”), and regional sentiment expressions not captured by standard lexicons.

5.5 User Evaluation and Feedback

Over 300 users interacted with the application through the Streamlit interface. Feedback analysis revealed the following:

- **78%** rated their experience as *very good* or *excellent*.
- Key positive feedback included intuitive UI and contextual fluency in responses.
- Limitations noted included occasional lags and lack of support for slang and voice input.

Real-time feedback was instrumental in updating model parameters and refining the hybrid selection strategy, demonstrating the value of human-in-the-loop adaptation.

5.6 Notable Observations and Patterns

- **Best Translation Pair:** English–Hindi achieved peak fluency and syntactic fidelity.
- **Sentiment Accuracy:** Improved in long-form text due to richer contextual cues.
- **Keyword Robustness:** Frequent detection of terms like *happy*, *angry*, *love*, and *fear*.
- **Underrepresented Languages:** Languages like Konkani and Sindhi underperformed due to limited annotated corpora.

5.7 Challenges, Anomalies, and Limitations

Despite the promising results, several challenges persist:

- **Ambiguity and Sarcasm:** Sentiment analysis misclassified syntactically positive but contextually negative phrases.
- **Structural Divergence:** Sentence reordering issues arose due to grammatical variations across languages.
- **Round-Trip Translation Errors:** Notable discrepancies appeared when translating cyclically (e.g., English → Hindi → English).
- **Data Scarcity:** Accuracy dropped significantly for low-resource languages, underscoring the importance of inclusive dataset development.

5.8 Interpretation and Implications

The integrated hybrid system dynamically adapted to user needs through a feedback-aware architecture, significantly improving contextual relevance and user satisfaction. However, to reach broader deployment in settings like multilingual customer service or education platforms, the system must evolve to handle code-mixed content, sarcasm, and informal language more effectively. Incorporating transformer-based sarcasm detectors and crowdsourced corpus expansion for underrepresented languages are key next steps.

The LinguaBridge framework demonstrates that a hybrid, feedback-driven multilingual NLP system can effectively navigate the complexities of Indian language diversity. While high-resource languages benefit most from current model capabilities, the path forward requires targeted improvements in low-resource support, pragmatic understanding, and latency optimization to deliver inclusive, context-sensitive, and emotionally aware language technologies.

6 Future Work

The development of LinguaBridge marks a significant step toward enhancing natural language processing capabilities for low-resource Indian languages. However, several promising directions remain to be explored. One immediate area for enhancement is the incorporation of morphosyntactic features such as part-of-speech (POS) tagging into the sentiment and emotion analysis pipeline. As shown in [20], the application of POS tagging techniques—even with minimal resources—can substantially improve syntactic understanding in low-resource languages like Angika, Magahi, and Bhojpur. Integrating such annotations into LinguaBridge could increase the system’s robustness when interpreting syntactically complex or morphologically diverse inputs, potentially improving classification accuracy and making the sentiment engine more linguistically aware.

Another vital extension involves improving LinguaBridge’s ability to handle code-switched and multilingual content, which is pervasive in informal and digital communication in India. Code-mixed language poses unique challenges due to its syntactic fluidity and semantic ambiguity. [21] address this through linguistically grounded synthetic data generation for code-mixed language modeling. Adopting similar techniques could enable LinguaBridge to process such inputs more effectively. Additionally, it is essential to assess the fairness and inclusivity of multilingual systems. As pointed out by [22], current multilingual pre-trained language models may exhibit systemic biases or performance disparities across languages. Future research should thus include a fairness audit of LinguaBridge’s outputs, ensuring balanced performance across supported Indic languages and dialects.

Lastly, improving evaluation strategies for low-resource contexts remains a critical need. Traditional benchmarks often fail to capture the challenges unique to Indian languages. The PARIKSHA platform introduced by [23] offers a scalable and democratic framework for evaluating Indic language models and could be adapted to assess translation and sentiment systems like LinguaBridge. Furthermore, expanding the system’s capabilities to include speech processing would significantly enhance accessibility, especially for non-literate users or those with speech-based interaction needs.

[24] demonstrate the feasibility of multilingual speech synthesis in navigation tasks, suggesting that similar methods could extend LinguaBridge into multimodal or spoken applications, thus broadening its reach and impact across diverse user demographics.

7 Ethical and Societal Considerations

7.1 Fairness and Bias in Low-Resource Languages

Machine translation and emotion analysis system increases the risk and increases prejudice, especially for Indian languages. Synthetic oversampling, transfer learning, and careful dataset partially reduces these risks but does not completely eliminate inequalities. For example, representation inequalities can lead to the performance of the uneven system, resulting in preference to major language groups keeping others marginalized. This challenge is well documented in recent studies focused on prejudice and fairness in multilingual pre-influential models. The ongoing fairness audit is important.

7.2 Privacy and Data Governance

Linguabridge model uses user response loops to customize the selection and improve performance. To align with the best practices and India's Digital Personal Data Protection Act (DPDP, 2023), all individual identified information is unknown, and the response is stored only in overall form. The data is encrypted in both transit and comfort. The system prevents the translation material from storing beyond operating requirement.

7.3 Risks of Misuse (Profiling/Surveillance)

While Linguabridge is designed to democratizing access to language technologies, there are significant risks related to misuse, especially as profiling and monitoring:

Profiling: AI-powered profiling can eliminate social prejudices found in underlying data. Trained systems on biased or unprotected dataset risk the green signal or targeting specific communities, which often enhance social inequalities. The future policing and risk evaluation algorithm, as seen globally, can cause monitoring and inappropriate treatment of some groups if not managed carefully.[2]

Monitoring: AI-operated systems enable user to monitor interaction and communication patterns on a large scale. Without strong moral and legal safety measures in place, violations of rights of privacy and freedom of expression are likely to have a cold effect.[25][2] Even routine system logs or feedback loops can unknowingly assemble and maintain sensitive personal data, increase the risk of misuse of data or unauthorized access.[26]

Opportunity and accountability: Many AI models serve as "black boxes", making it difficult to make decisions based on their predictions. Lack of transparency destroys public belief and prevents meaningful support if the system is misused.[2]

Technology misuse: Increasing access to devices such as Deepfake generator and AI-driven bots increases the widespread capacity for political manipulation, social engineering, misinformation and unauthorized outline or monitoring.[27]

Recommended mitigations include regular fairness and privacy audit, technical safety measures (such as data minimization, strong encryption, transparent logging), and alignment with moral AI guidelines to ensure accountability and public trust.[25][2][27]

7.4 Alignment with Natural AI Process

The architecture and deployment of Linguabridge is closely aligned with India's national AI strategy as expressed by Niti Aayog. The solution emphasizes inclusive digital public goods, multilingual access and responsible AI Stewardship:

Alignment with Bhashini and NLTM initiatives: Linguabridge adopted the standards and guidelines proposed by India's Bhashini and National Language Translation Mission (NLTM) projects, which advocate for all citizens, accessible open, modular and scalable language technologies.

Interoperability and Evolution: The system is designed for interoperability with government-supported platforms such as Pariksha for ongoing evaluation and benchmarking.

Ethical and social objectives: reflecting the priorities mentioned in the National AI policy - such as inclusion, transparency and accountability - platform transparency mechanisms, user data the data secrecy protocol and the participation response mechanism during their life cycle appointments.

Policy Reference: Recent policy documents and technical standard low-resources insist on supporting Indian languages, prejudice mitigation and open-source cooperation. These are integrated fundamental principles in the Lingubridge project.

This active policy alignment not only facilitates compliance and wealth, but also ensures widespread social impacts and stability of multilingual AI technologies in India.

8 Visual and Accessibility Enhancements

8.1 Captions and Numbering for Figures

Figure 1: This figure presents the complete workflow of the LinguaBridge system. It visually maps the entire process from the initial user input (such as the text presented for translation and emotion analysis), including translated results and emotion analysis. Various modules included in the workflow have been highlighted -language detection, translation, emotion classification, and reaction collection - how information flows between components. Additionally, it shows the points where the system incorporates the user response to increase translation and emotion accurate over time. This relevant, step-by-step structure helps readers to understand how the system ensures accurate, accessible and user-manual AI services in its pipeline.

Figure 2: This diagram gives a description of the internal architecture of the Lingubridge. This major project shows modular design of components, such as translation engines, emotion analysis modules and supporting services for data security and aggregation. The figure shows how these modules interact and are functionally separated, reflecting the design options for Extension, reliability and safe data flow. The use of separate modules also underlines how the system supports integration with large platforms, such as supported by government or research initiative.




Figure 8: Confusion Matrix for Multilingual Sentiment Analysis.

Figure 3: The third figure displays a sample confusion matrix for emotion analysis in Hindi-English translation pairs. Each cell explains how often a emotion class (eg, positive, neutral, negative) is correctly identified (diagonal) versus miscarriage (off-diagonal). The matrix visually gives a surface to strength and weaknesses in models’ predictions, which helps researchers to identify which emotion categories require further tuning or additional training data-especially relevant in multilingual or code-survived texts, where the specifics are often lost.

9 Conclusion

The LinguaBridge system advances multilingual NLP by unifying translation and sentiment analysis in a context-aware, adaptive framework. Combining rule-based, statistical, and neural approaches—including Google Translate, AI4Bharat, and TextBlob—it delivers real-time translation across 18+ Indian languages with emotion-sensitive sentiment detection.

Notably, its dynamic model-switching driven by user feedback improves accuracy over time. Evaluation with 300 users yielded a 78% satisfaction rate, underscoring its practical utility in domains like mental health, education, and governance.

Despite these strengths, challenges remain in handling low-resource languages, code-mixed texts, and complex expressions like sarcasm. Addressing these requires richer datasets and more linguistically nuanced models. Future work will explore transformer-based enhancements, deeper emotion detection, and multimodal analysis, moving toward AI systems that not only translate, but also understand and connect with human emotion across diverse cultural contexts.

Metric	Value	Description
Mean Translation Accuracy	85.94%	Across 18 Indian languages (higher for Hindi/Marathi, lower for Konkani/Manipuri)
Highest Language Accuracy	92%	Hindi
Lowest Language Accuracy	80%	Konkani
Sentiment Analysis Accuracy	88%	Overall sentiment polarity classification
Sentiment Precision	83.33%	
Sentiment Recall	80.56%	
Sentiment F1-Score	80.24%	
User Satisfaction ("Good" or above)	78%	Portion of 300 users rating the system favorably

Table 4: Performance Metrics for the LinguaBridge System

References

- [1] India Office of the Registrar General & Census Commissioner. Census of india 2011: Provisional population totals, 2011. <https://censusindia.gov.in>.
- [2] Iliyan Kuzmanov. Ai and psychological profiling for violence risk assessment: Enhancing accuracy and addressing ethical challenges. *Criminology and Psychopathology at London Metropolitan University*, 2024. Accessed: 2025-07-30.
- [3] Peter F Brown, Stephen A Della Pietra, Vincent J Della Pietra, and Robert L Mercer. The mathematics of statistical machine translation: Parameter estimation. *Computational linguistics*, 19(2):263–311, 1993.
- [4] Philipp Koehn, Franz Josef Och, and Daniel Marcu. Statistical phrase-based translation. In *2003 Conference of the North American Chapter of the Association for Computational Linguistics on Human Language Technology (HLT-NAACL 2003)*, pages 48–54. Association for Computational Linguistics, 2003.
- [5] Ilya Sutskever, Oriol Vinyals, and Quoc V Le. Sequence to sequence learning with neural networks. *Advances in neural information processing systems*, 27, 2014.
- [6] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.
- [7] Roei Aharoni, Melvin Johnson, and Orhan Firat. Massively multilingual neural machine translation. *arXiv preprint arXiv:1903.00089*, 2019.
- [8] Angela Fan, Shruti Bhosale, Holger Schwenk, Zhiyi Ma, Ahmed El-Kishky, Siddharth Goyal, Mandeep Baines, Onur Celebi, Guillaume Wenzek, Vishrav Chaudhary, et al. Beyond english-centric multilingual machine translation. *Journal of Machine Learning Research*, 22(107):1–48, 2021.
- [9] Jay Gala, Pranjal A Chitale, Raghavan AK, Varun Gumma, Sumanth Doddapaneni, Aswanth Kumar, Janki Nawale, Anupama Sujatha, Ratish Puduppully, Vivek Raghavan, et al. Indictrans2: Towards high-quality and accessible machine translation models for all 22 scheduled indian languages. *arXiv preprint arXiv:2305.16307*, 2023.
- [10] Gowtham Ramesh, Sumanth Doddapaneni, Aravinth Bheemaraj, Mayank Jobanputra, Raghavan Ak, Ajitesh Sharma, Sujit Sahoo, Harshita Diddee, Divyanshu Kakwani, Navneet Kumar, et al. Samanantar: The largest publicly available parallel corpora collection for 11 indic languages. *Transactions of the Association for Computational Linguistics*, 10:145–162, 2022.
- [11] Jörg Tiedemann and Santhosh Thottingal. Opus-mt—building open translation services for the world. In *Annual Conference of the European Association for Machine Translation*, pages 479–480. European Association for Machine Translation, 2020.
- [12] Wat 2024: The 11th workshop on asian translation. <https://lotus.kuee.kyoto-u.ac.jp/WAT/WAT2024/index.html#task.html>, 2024. Accessed: 2025-04-20.

- [13] Chao-Hong Liu, Preslav Nakov, and Nianwen Xue, editors. *Proceedings of the IJCNLP 2017, Shared Tasks*, Taipei, Taiwan, December 2017. Asian Federation of Natural Language Processing.
- [14] Aditya Joshi, AR Balamurali, Pushpak Bhattacharyya, et al. A fall-back strategy for sentiment analysis in hindi: a case study. *Proceedings of the 8th ICON*, 2010.
- [15] Parth Patwa, Gustavo Aguilar, Sudipta Kar, Suraj Pandey, Srinivas Pykl, Björn Gambäck, Tanmoy Chakraborty, Thamar Solorio, and Amitava Das. Semeval-2020 task 9: Overview of sentiment analysis of code-mixed tweets. *arXiv preprint arXiv:2008.04277*, 2020.
- [16] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 conference of the North American chapter of the association for computational linguistics: human language technologies, volume 1 (long and short papers)*, pages 4171–4186, 2019.
- [17] Divyanshu Kakwani, Anoop Kunchukuttan, Satish Golla, Gokul NC, Avik Bhattacharyya, Mitesh M Khapra, and Pratyush Kumar. Indicnlp suite: Monolingual corpora, evaluation benchmarks and pre-trained multilingual language models for indian languages. In *Findings of the association for computational linguistics: EMNLP 2020*, pages 4948–4961, 2020.
- [18] Simran Khanuja, Sandipan Dandapat, Anirudh Srinivasan, Sunayana Sitaram, and Monojit Choudhury. Gluecos: An evaluation benchmark for code-switched nlp. *arXiv preprint arXiv:2004.12376*, 2020.
- [19] BigScience Workshop, Teven Le Scao, Angela Fan, Christopher Akiki, Ellie Pavlick, Suzana Ilić, Daniel Hesslow, Roman Castagné, Alexandra Sasha Luccioni, François Yvon, et al. Bloom: A 176b-parameter open-access multilingual language model. *arXiv preprint arXiv:2211.05100*, 2022.
- [20] Sanjeev Kumar, Preethi Jyothi, and Pushpak Bhattacharyya. Part-of-speech tagging for extremely low-resource indian languages. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 14422–14431, 2024.
- [21] Adithya Pratapa, Gayatri Bhat, Monojit Choudhury, Sunayana Sitaram, Sandipan Dandapat, and Kalika Bali. Language modeling for code-mixing: The role of linguistic theory based synthetic data. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1543–1553, 2018.
- [22] Monojit Choudhury and Amit Deshpande. How linguistically fair are multilingual pre-trained language models? In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pages 12710–12718, 2021.
- [23] Ishaan Watts, Varun Gumma, Aditya Yadavalli, Vivek Seshadri, Manohar Swaminathan, and Sunayana Sitaram. Pariksha: A large-scale investigation of human-llm evaluator agreement on multilingual and multi-cultural data. *arXiv preprint arXiv:2406.15053*, 2024.
- [24] Khyathi Raghavi Chandu, Sai Krishna Rallabandi, Sunayana Sitaram, and Alan W Black. Speech synthesis for mixed-language navigation instructions. In *INTERSPEECH*, pages 57–61, 2017.
- [25] Christoph Lütge Ellen Hohma, Caitlin C. Corrigan. Ai-powered public surveillance systems: why we (might) need them and how we want them. *ScienceDirect*, 2022. Accessed: 2025-07-30.
- [26] Isabel BARBERÁ. Ai privacy risks and mitigations in llms. *European Data Protection Board*, 2025. Accessed: 2025-07-30.
- [27] WebAsha Technologies. The most dangerous ai tools no one’s talking about: Risks, examples, protection. *Webasha Blog*, Year. Accessed: 2025-07-30.