PRACTICAL – 2

Implementation and Time Analysis of Linear and Binary Search Algorithm

Objective:

The objective of this practical is to implement ***Linear Search*** and ***Binary Search*** algorithms and compare their performance based on ***time complexity***, ***space complexity***, and ***execution time***. This helps in understanding the efficiency of both searching techniques and selecting the appropriate algorithm for different applications.

1.Linear Search

Algorithm:

START

INPUT A
INPUT X

FOR i ← 0 TO len(A) - 1
IF A[i] == X THEN

PRINT "Element found at index", i
EXIT
END IF
END FOR

PRINT "Element not found"

STOP


PythonCode:

```
import time
# Linear Search Function
def linear_search(arr, n, key):
    for i in range(n):
        if arr[i] == key:
            return i
    return -1
# Take input from the user
n = int(input("Enter the number of elements: "))
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))
key = int(input("Enter the element to search: "))
# Measure execution time
start_time = time.perf_counter()
result = linear_search(arr, n, key)
```

```
end_time = time.perf_counter()
# Display result
if result != -1:
    print("\nElement found at position:", result + 1)
else:
    print("\nElement not found")
# Display execution time
execution_time = end_time - start_time
print("Execution Time: {:.10f} seconds".format(execution_time))

#Enter your EN.No
print("EN.No:
92460118673")
```

OUTPUT:



Time Complexity:

Case	*Time Complexity*	*Description*
Best Case	*O(1)*	*Element is at the first position.*
Average Case	*O(n)*	*Element is in the middle or random position.*
Worst case	*O(n)*	*Element is at the last position or absent.*

Space Complexity:

Space Complexity	***Description***
O(1)	***Uses only a few variables; no extra memory is required.***

2.Binary Search

Algorithm:

START

INPUT sorted list A

INPUT X

low ← 0

high ← len(A)-1

WHILE low <=high

mid ← (low+high)//2

IF A[mid]==XTHEN

PRINT"Elementfoundatindex",mid

EXIT

ELSEIFA[mid]<XTHEN

low←mid+1

ELSE

high←mid-1

END IF

ENDWHILE

PRINT "Element not found"

STOP

Python Code


```
import time
# Binary Search Function
def binary_search(arr, n, key):
    low = 0
    high = n - 1
    while low <= high:
```

```
        mid = (low + high) // 2
        if arr[mid] == key:
            return mid
        elif arr[mid] < key:
            low = mid + 1
        else:
            high = mid - 1
    return -1
# Take input from the user
n = int(input("Enter the number of elements: "))
arr = []
print("Enter the elements:")
for i in range(n):
    arr.append(int(input()))
key = int(input("Enter the element to search: "))
# Sort the array
arr.sort()
# Measure execution time
start_time = time.perf_counter()
result = binary_search(arr, n, key)
end_time = time.perf_counter()
# Display sorted array
print("\nSorted Array:", arr)
# Display result
if result != -1:
    print("Element found at position:", result + 1)
else:
    print("Element not found")

# Display execution time
execution_time = end_time - start_time
print("Execution Time: {:.10f} seconds".format(execution_time))

#Enter your EN.No
print("EN.No:
92460118673")
```

OUTPUT:



Time Complexity:

Case	*Time Complexity*	*Description*
Best Case	*O(1)*	*Element is found at the middle.*
Average Case	*O(log n)*	*Search space is halved repeatedly.*
Worst case	*O(log n)*	*Maximum divisions before finding or rejecting the element.*

Space Complexity:

Space Complexity	*Description*
O(1)	*Uses only a few variables (low, high, mid); no extra memory is required.*