Wireshark for Cyber Threat Monitoring

Hands-On Lab Worksheet

Day 1 afternoon lab, 13:00 to 17:00. Baselines and anomalies: from reading packets to spotting what does not belong.

Name	Trail Bajenting	**Partner**	
Date	10/20/2026	**Operating system**	Windows 11
Wireshark version	4.6.4 (64-bit)	**Group (Part 5)**	n/a

This afternoon at a glance

Time	Activity	Min	Capture file
13:00	Setup and tool check	15	none
13:15	Part 1: Capture your own baseline (live)	40	my_baseline_fallback.pcapng (backup)
13:55	Part 2: Follow the handshake	50	web_browse.pcapng
14:45	Break	15	
15:00	Part 3: Filter scavenger hunt	40	hunt1.pcapng
15:40	Part 4: Baseline dossier	40	office_day.pcapng
16:20	Part 5: Odd one out (team challenge)	35	tuesday.pcapng
16:55	Submit and self-check	5	

Ground rules

Authorized captures only. Capture only your own computer, on the lab network, when the instructor says so. Sniffing traffic you are not authorized to see can be illegal.

The lab files are safe and synthetic. Every IP address, name, and password in them is fictional.

Treat captures as sensitive. Real captures contain passwords and personal data. Do not share them outside this class.

Save often. Put your initials in every file name you save.

How to work

- Work in pairs. One person drives the mouse; **swap at every Part**.
- Type filters exactly as shown. The filter bar turns **green** when the syntax is valid, **red** when it is not.
- The number of matching packets is in the status bar at the bottom right: **Displayed: N**.

- Stuck for more than five minutes? Ask your partner, then the next pair, then the instructor. Appendix B lists common problems.

Setup and tool check

13:00 to 13:15, 15 minutes

1. Copy the **Day1_Lab** folder from the shared drive to your desktop. Confirm it contains the five `.pcapng` files listed in the schedule above.
2. Open Wireshark, then **Help, About Wireshark**. Write the version at the top of this worksheet. You need version **4.0 or newer**.
3. Create your working profile: **Edit, Configuration Profiles**, click the **+** button, name it `Threat Hunting`, click OK. The status bar (bottom right) should now say *Profile: Threat Hunting*.
4. Turn off name resolution so Wireshark shows raw addresses: **View, Name Resolution**, and make sure all three *Resolve...* items are **unticked**.
5. Open **View, Time Display Format** and pick **Seconds Since Beginning of Capture**. (In Part 5 you will change this to UTC.)
6. Test that Wireshark works: **File, Open**, choose `web_browse.pcapng`. The status bar should show **Packets: 18**. Close the file (**File, Close**).

☐ Version is 4.0 or newer

☐ Profile `Threat Hunting` is active

☐ Name resolution is off

☐ I have read the ground rules

Part 1: Capture your own baseline

13:15 to 13:55, 40 minutes, individual, live capture

Goal: see what "normal" looks like on your own computer, and learn the difference between a capture filter and a display filter.

Steps

1. Find your **default gateway** (your router). Windows: open Command Prompt and run `ipconfig`, then read *Default Gateway*. macOS: `route -n get default | grep gateway`. Linux: `ip route | grep default`. Write it here: _192.168.1.1__
2. In Wireshark, click the interface you are actually using (Wi-Fi or Ethernet, the one with the moving line graph). Press `Ctrl+K` to open Capture Options and **untick "Enable promiscuous mode on all interfaces"**, so you capture only your own traffic.
3. Press `Ctrl+E` to start the capture.
4. Generate traffic. (a) Ping the gateway four times. Windows: `ping -n 4 <gateway>`. macOS or Linux: `ping -c 4 <gateway>`. (b) Run `nslookup example.com`. (c) Open one web page in your browser.
5. Wait about 10 seconds, then press `Ctrl+E` to stop. Save with **File, Save As** as `Part1_yourinitials.pcapng`.
6. Answer questions 1.1 to 1.5 using your capture. Type each filter into the display filter bar and press Enter.

7. **Capture filter experiment:** type `port 53` into the *capture filter* box (on the Wireshark start screen, or in Capture Options on the Input tab). Start a new capture, run `nslookup example.com` twice, browse a page, stop, and answer 1.6.

> **If capturing is blocked on your computer**
> Some computers do not allow packet capture (missing driver or permission). Tell the instructor, then open **my_baseline_fallback.pcapng** and answer 1.1 to 1.5 from it. Skip 1.6.

#	Question	Your answer
1.1	How many packets did you capture? (Status bar, *Packets:*)	4,003 packets.
1.2	List four different protocols shown in the Protocol column.	UDP, ARP, mDNS, and TCP.
1.3	Apply `icmp.type == 8`. How many echo requests are shown? Does it match the number of pings you sent?	4 echo requests are shown in my capture. Yes, this matches the four pings I sent using ping -n 4 192.168.1.1.
1.4	Apply `dns`. What is the IP address of the DNS server your computer asked (the destination of a query)? Did a response come back?	The DNS server IP address is 192.168.1.1. Yes, a response came back, as shown by the DNS query response packets in Wireshark.
1.5	Name two protocols in your capture that you did not cause on purpose. What do you think each is for?	1. ARP (Address Resolution Protocol) – It helps devices find the MAC address associated with an IP address on the local network. 2. mDNS (Multicast DNS) – It helps devices discover other devices and services on the local network without using a traditional DNS server.
1.6	In the `port 53` capture: which protocols appear, and what disappeared compared with your first capture? Explain in one sentence the difference between a capture filter and a display filter.	The port 53 capture shows DNS traffic, while other protocols such as TCP, TLSv1.2, ARP, and mDNS seen in the first capture disappeared. A capture filter limits which packets are collected, while a display filter only hides or shows packets that have already been captured.

Part 2: Follow the handshake

13:55 to 14:45, 50 minutes, pairs, file: web_browse.pcapng

Goal: trace one web visit from the DNS lookup to the TCP handshake to the HTTP request, and draw it as a ladder diagram.

The capture shows a workstation (**10.0.0.22**) visiting the lab intranet server (**10.0.0.5**). Open `web_browse.pcapng` (18 packets).

Steps

1. Apply `dns`. Fill in table 2A.
2. Apply `tcp.stream eq 0`. This shows one complete TCP conversation. The status bar tells you how many packets: write it in table 2A.
3. Find the three handshake packets (look at the Info column for **[SYN]**, **[SYN, ACK]**, **[ACK]**). Write their frame numbers in 2A.
4. Click the first SYN packet. In the middle pane expand **Transmission Control Protocol, Options**. Record the **Maximum segment size** and the **Window scale multiplier** for the SYN and for the SYN/ACK.
5. Work out the time between the SYN and the SYN/ACK from the Time column (subtract). This is a rough round-trip time.
6. Right-click any packet in the stream, choose **Follow, TCP Stream** (`Ctrl+Alt+Shift+T`). Red text is the client, blue text the server. Fill in 2B, then close the window.
7. Clear the filter (click the X). Fill in the **ladder diagram** in 2C using the Time column.
8. **Bonus:** find the packet with the **RST** flag. Fill in 2D.

2A. DNS and handshake

Question	Your answer
Frame number of the DNS query, and the name being asked for	Frame 1 — intranet.lab.test
Frame number of the DNS response, and the IP address it returned	Frame 2 — 10.0.0.5
Number of packets shown by `tcp.stream eq 0`	14 displayed packets (18 packets in the full capture)
Frame numbers: SYN / SYN-ACK / ACK	Frame 3 / Frame 4 / Frame 5
SYN packet: MSS value and window scale multiplier	MSS: 1460 bytes; multiplier: 256
SYN/ACK packet: MSS value and window scale multiplier	MSS: 1460 bytes; multiplier: 128
Time from SYN to SYN/ACK (seconds)	0.001 seconds (1 millisecond)

2B. What the Follow TCP Stream window shows

Question	Your answer
How many HTTP requests did the client send on this one connection?	2 HTTP requests
The first request line, and the value of the Host header	GET / HTTP/1.1 — Host: intranet.lab.test
The User-Agent (which browser?)	Mozilla/5.0 (Windows NT 10.0; Win64; x64) Firefox/128.0 — Firefox 128.0
The status line the server answered with, and the type of each file returned	HTTP/1.1 200 OK. The main page is text/html, and the stylesheet is text/css.

2C. Ladder diagram

Fill in one row per event, in time order. For the direction column write **Client to Server** or **Server to Client**.

Frame	Time (s)	Direction	Flags / what it does
3	0.005499	Client to Server	Handshake step 1:[SYN]
4	0.006499	Server to Client	Handshake step 2:[SYN, ACK]
5	0.006899	Client to Server	Handshake step 3: [ACK]
6	0.056899	Client to Server	First HTTP request: GET / HTTP/1.1
8	0.069800	Server to Client	Server response to it: HTTP/1.1 200 OK
14	0.184500	Client to Server	Connection closing, step 1: [FIN, ACK]
15	0.185000	Server to Client	Connection closing, step 2: [FIN, ACK]
16	0.185500	Client to Server	Connection closing, step 3: [ACK]

2D. Bonus: the reset

Question	Your answer
Frame number of the RST packet, who sent it, and to which port	Frame 18 — sent by server 10.0.0.5, source port 8080, to client 10.0.0.22, destination port 50395.
Which earlier packet triggered it? Why did the server reset instead of answering with SYN/ACK?	Frame 17 was the earlier [SYN] packet to server port 8080. The server responded with [RST, ACK] rather than [SYN, ACK], indicating that the connection attempt was refused or the port was not accepting connections.
Filter you could use to find every reset in a large capture	tcp.flags.reset == 1

Checkpoint: *Analyze, Expert Information* should list exactly one **Warning**, a connection reset.

Break: 14:45 to 15:00

Save your files. Swap the driver and navigator roles.

Part 3: Filter scavenger hunt

15:00 to 15:40, 40 minutes, pairs, file: hunt1.pcapng

Goal: write display filters quickly and correctly. Open `hunt1.pcapng` (363 packets: a mix of DNS, web, TLS, resets, and errors). For each task, write your filter exactly as you typed it, and the **Displayed** count from the status bar.

#	Task	Your display filter	Count
1	All DNS traffic.	dns	20
2	DNS responses that say the name does not exist (NXDOMAIN).	dns.flags.rcode == 3	3
3	HTTP requests that use the POST method.	http.request.method == "POST"	2
4	TCP packets with the reset flag set.	tcp.flags.reset == 1	4
5	Everything to or from host 10.0.0.22, excluding DNS.	ip.addr == 10.0.0.22 && !dns	34
6	TLS Client Hello packets. Then add the Server Name as a column and list the names below.	tls.handshake.type == 1	4
7	Packets longer than 1000 bytes that were sent by 10.0.0.23.	ip.src == 10.0.0.23 && frame.len > 1000	2
8	TCP retransmissions.	tcp.analysis.retransmission	3
9	ICMP destination unreachable messages.	icmp.type == 3	2
10	TCP traffic on any port other than 53, 80, and 443.	tcp && !(tcp.port == 53 || tcp.port == 80 || tcp.port == 443)	34

Server names from task 6: _www.example.com, docs.example.com, news.example.org, - cdn.example.net

_____

Self-check

When you have finished, add up your ten counts. The total should be **108**. If yours is different, re-check the rows that look most suspicious. (Wrong filters often return 0 or the whole capture.)

Bonus

- **B1.** Open *Analyze, Expert Information*. How many **Connection reset (RST)** warnings are listed? ___3 — Connection reset (RST) warnings. ___
- **B2.** Write **one** filter that shows both the NXDOMAIN responses and the TCP resets together (use `||`). Filter: ___dns.flags.rcode == 3 || tcp.flags.reset == 1___ Count: __7____

Field hints (use only if stuck)

Fields worth knowing: `dns.flags.rcode`, `http.request.method`, `tcp.flags.reset`, `tcp.analysis.retransmission`, `icmp.type`, `tls.handshake.type`, `frame.len`, `ip.src`, `ip.addr`, `tcp.port`.

You can build any filter by clicking: right-click a field in the middle pane, **Apply as Filter, Selected**. To combine, use **Prepare as Filter** and add `&&` (and), `||` (or), `!` (not).

For task 10, use `==` with `||` inside brackets, then negate with `!`.

Part 4: Baseline dossier

15:40 to 16:20, 40 minutes, pairs, file: office_day.pcapng

Goal: describe "normal" for this network using Wireshark's Statistics tools. You will compare against your dossier in Part 5, so be accurate. Open `office_day.pcapng`, a 30-minute capture of an ordinary morning for four workstations (10.0.0.21 to 10.0.0.24).

4A. Capture facts (Statistics, Capture File Properties)

Item	Value
Packets	4,285
Elapsed time (minutes and seconds)	29 minutes 50 seconds
Average packet size (bytes)	701 bytes

4B. Protocol mix (Statistics, Protocol Hierarchy)

Read the **Percent Packets** column. Each protocol has its own row; expand the tree if you cannot see it.

Protocol	% of packets	Protocol	% of packets
TCP	90.8%	HTTP	1.6%
UDP	7.5%	DNS	3.6%
ARP	1.5%	Multicast DNS (mDNS)	2.8%
ICMP	0.2%	NTP	1.1%
TLS	10.3%		

4C. Busiest internal hosts (Statistics, Endpoints, IPv4 tab; click the Bytes column to sort)

Rank	IP address	Total bytes	Notes
1	10.0.0.21	2 MB	Highest traffic; appears to be the busiest workstation
2	10.0.0.23	413 kB	Second-highest traffic
3	10.0.0.22	410 kB	Third-highest traffic

Only count internal hosts (addresses starting with 10.0.0.). Which host is far ahead of the others? What do you think it was doing (see 4F)?

Host 10.0.0.21 is far ahead of the other internal hosts, with approximately 2 MB of traffic. It was likely performing regular network activities, including DNS queries, time synchronization, and TLS communication with external servers.

4D. External destinations

On the same Endpoints (IPv4) tab, count the addresses that are **not** internal (not 10.0.0.x) and not multicast (224.x.x.x). Number of external IPs: __9 ____. Write them here:

203.0.113.123
203.0.113.50
203.0.113.30
203.0.113.20
203.0.113.10
198.51.100.90
198.51.100.60
198.51.100.40
198.51.100.25

4E. DNS activity

Item	Value
Number of DNS queries: apply `dns.flags.response == 0 && udp.port == 53`	77
Queries per minute (queries divided by minutes)	2.58 queries/minute
Why do we add `udp.port == 53` instead of using only `dns.flags.response == 0`?	udp.port == 53 identifies DNS traffic using UDP port 53, while dns.flags.response == 0 selects DNS queries rather than responses.

4F. Largest conversation (Statistics, Conversations, TCP tab; click Bytes)

Item	Value
Address A and Address B of the largest conversation	10.0.0.21 and 198.51.100.90
Total bytes and duration	698 kB; 2.0314 seconds
The server's name: apply `ip.addr == <server IP> && tls.handshake.type == 1`, open the packet, expand *Handshake Protocol: Client Hello, Extension: server_name*	The server’s name: video.example.net

4G. Things that happen on a schedule (these are normal!)

For each row, apply the filter, then add the column **frame.time_delta_displayed** (expand the *Frame* section in the middle pane, right-click *Time delta from previous displayed frame*, **Apply as Column**). Read the gaps between packets.

Traffic	Filter	Typical gap (seconds)
Time synchronization	`ntp && ip.src == 10.0.0.21`	About 300 seconds

Traffic	Filter	Typical gap (seconds)
Operating system update check	`tls.handshake.extensions_server_name == "update.example.net" && ip.src == 10.0.0.21`	About 600 seconds
Local network chatter (mDNS)	`mdns && ip.src == 10.0.0.21`	between _47.44_ and _74.23_

Why is it important to know these regular patterns before you start hunting for threats?

Knowing normal network patterns helps identify unusual activity that may indicate a security threat.

4H. One-sentence baseline

Complete: "A normal 30 minutes on this network looks like..."

A normal 30 minutes on this network looks like routine DNS queries, time synchronization about every 5 minutes, operating system update checks about every 10 minutes, regular mDNS traffic, and normal web connections from workstations.

Part 5: Odd one out (team challenge)

16:20 to 16:55, 35 minutes, teams of 3 to 4, file: tuesday.pcapng

Scenario. It is the next morning. The SOC captured the same 30 minutes on Tuesday. **Exactly four things in this capture do not belong.** Find them, prove each one with evidence, and rate how serious it is. The team with the best evidence wins.

Steps

1. Set **View, Time Display Format, UTC Date and Time of Day**. Open `tuesday.pcapng` (7,019 packets).
2. Compare against your Part 4 dossier: protocol mix, busiest conversations, DNS, ARP. What has changed?
3. For each anomaly, record **who** (IP addresses), **when** (UTC), **evidence** (the exact filter and frame numbers, and take a screenshot), **severity** (Low, Medium, or High, with a reason), and an **ATT&CK technique** from the list below.
4. Note anything that looked odd but turned out to be normal, and explain why (use your baseline as proof). A false alarm with no evidence **loses a point**.

Findings

#	What happened (who, to what)	When (UTC)	Evidence: filter and frame numbers	Severity and why	ATT&CK
1	Internal host 10.0.0.21 uploaded a ZIP file named backup.zip to 198.51.100.77 using HTTP.	2026-09-15 10:24:20 UTC	Filter: ip.addr == 10.0.0.21 && http; frames 6528–6531	Medium — suspicious. An outbound file upload to an external IP needs investigation.	T1567 — Exfiltration Over Web Service (possible; not confirmed)
2	Host 10.0.0.22 made numerous DNS queries for randomly named subdomains under example.net; the DNS server returned “No such name” for many queries.	2026-09-15 10:18:05 –10:18:51 UTC	Filter: dns && ip.src == 10.0.0.22; frames 2927–3193	Medium — suspicious. Repeated queries for unusual, randomly named domains may indicate automated activity or possible DNS tunneling. Further investigation is needed.	T1071.004 — DNS (possible; not confirmed)
3	Host 10.0.0.21 repeatedly requested the webpage / and stylesheet /style.css from 10.0.0.5; the server returned HTTP 200 responses.	2026-09-15 10:01:10 –10:28:45 UTC	Filter: ip.addr == 10.0.0.21 && http; examples: frames 7003–7009	Low — likely normal. The requests and successful responses are consistent with ordinary webpage browsing.	N/A — no clear malicious technique

#	What happened (who, to what)	When (UTC)	Evidence: filter and frame numbers	Severity and why	ATT&CK
4	DNS server 10.0.0.2 resolved several domains to IP addresses, including update.example.net to 203.0.113.50 and search.example.net to 198.51.100.60.	2026-09-15 10:00:07–10:27:23 UTC	Filter: dns && ip.src == 10.0.0.2 && dns.flags.response == 1; examples: frames 23, 318, 6775, 6932	Low — informational. Successful DNS responses are normal by themselves, though the related queries should be reviewed alongside the unusual DNS activity.	N/A — no clear malicious technique

Looked odd, but is normal

What looked odd	Why it is normal (evidence from your baseline)
Repeated HTTP requests for / and /style.css between 10.0.0.21 and 10.0.0.5.	The server repeatedly returned HTTP 200 OK for HTML and CSS files. This is consistent with normal webpage loading. Frames 7003–7009.
Many DNS queries receive “No such name” responses.	A failed DNS lookup can occur normally when a domain does not exist. However, the unusually long sequence of random-looking subdomains means this activity should still be investigated rather than automatically classified as benign. Frames 2927–3193.

ATT&CK techniques to choose from

ID	Technique
T1018	Remote System Discovery (finding other hosts on the network)
T1046	Network Service Discovery (finding open ports and services)
T1040	Network Sniffing (credentials or data exposed to anyone on the path)
T1552	Unsecured Credentials (passwords stored or sent in a readable form)
T1568.002	Dynamic Resolution: Domain Generation Algorithms
T1071.004	Application Layer Protocol: DNS
T1041	Exfiltration Over C2 Channel
T1048	Exfiltration Over Alternative Protocol
T1560	Archive Collected Data

Hint cards (open only after 15 minutes of searching)

Hint 1. Compare Protocol Hierarchy with your Part 4B table. Is there a protocol that was not there yesterday?

Hint 2. Statistics, Conversations, TCP tab, sort by Bytes. Compare the top row with your Part 4F answer.

Hint 3. Statistics, Endpoints, **Ethernet** tab, sort by Packets. Then filter `arp` and read the Info column.

Hint 4. Filter `dns.flags.rcode == 3` and read the names in the Info column. Do they look like real words?

Submit and self-check

16:55 to 17:00

- ☐ I saved `Part1_yourinitials.pcapng` (or used the fallback file).
- ☐ Every table in this worksheet is filled in (or marked "not done" with a reason).
- ☐ My team's Part 5 findings include a filter, frame numbers, and a screenshot for each anomaly.
- ☐ Names of both partners are at the top of page 1.

Can I do this now? (tick what you can do without help)

- ☐ Start and stop a capture and save it as pcapng.
- ☐ Explain the difference between a capture filter and a display filter.
- ☐ Read a TCP handshake and a DNS query and response in Packet Details.
- ☐ Write display filters for DNS errors, resets, retransmissions, and ICMP errors.
- ☐ Build a baseline with Protocol Hierarchy, Conversations, and Endpoints.
- ☐ Explain why baselines matter before hunting for threats.

One thing that clicked today: _____

One thing that is still fuzzy: _____

Appendix A: Quick reference

I want to...	Do this
Open a capture file	File, Open (`Ctrl+O`)
Start or stop capturing	`Ctrl+E`
Change capture options	`Ctrl+K`
Jump to the filter bar	`Ctrl+/`
Clear the filter	Click the X at the right end of the filter bar
Turn any field into a filter	Right-click the field, Apply as Filter, Selected
Add a field as a column	Right-click the field, Apply as Column
Read a whole conversation	Right-click a packet, Follow, TCP Stream (`Ctrl+Alt+Shift+T`)
See warnings and errors quickly	Analyze, Expert Information
Capture facts (duration, average size)	Statistics, Capture File Properties
Protocol percentages	Statistics, Protocol Hierarchy
Top talkers	Statistics, Endpoints (each host) or Conversations (each pair)
Traffic over time	Statistics, I/O Graphs
Change how time is shown	View, Time Display Format

Filter operators

Operator	Meaning	Example
`==` and `!=`	equals, does not equal	`ip.addr == 10.0.0.5`
`>` `<` `>=` `<=`	greater, less	`frame.len > 1000`
`&&`	and (both must be true)	`dns && ip.src == 10.0.0.22`
`||`	or (either can be true)	`arp || icmp`
`!`	not	`!dns`
`contains`	field includes this text	`http.host contains "lab"`

Capture filter examples (used **before** capturing): `host 10.0.0.5`, `port 53`, `not port 22`, `net 10.0.0.0/24`.

Appendix B: Troubleshooting

Problem	Fix
The filter bar is red	There is a syntax error. Check spelling and that text values are in double quotes, for example `http.host == "example.com"`. Use `==` (two equals signs), not `=`.
The filter bar is yellow	The filter works but may be ambiguous. Usually safe; check the count.

Problem	Fix
I applied a filter and see 0 packets	The filter is valid but nothing matches. Re-check the field name, or clear the filter and look at a real packet to copy the field.
I cannot see any interfaces, or capture fails	Wireshark lacks capture permission or the capture driver is missing. Tell the instructor and use the fallback file for Part 1.
The Time column shows dates instead of seconds	View, Time Display Format, choose *Seconds Since Beginning of Capture* (Parts 2 to 4) or *UTC Date and Time of Day* (Part 5).
I see host names instead of IP addresses	Name resolution is on. View, Name Resolution, untick all three items.
`in {80 443}` gives an error	In Wireshark 4.x the list must use commas: `tcp.port in {80, 443}`. Or use `||` as in Part 3.
My counts differ slightly from a classmate's	Check the Status bar shows Displayed, not Packets. Displayed is the filtered count.
Wireshark froze on a large file	Wait a moment (the 5 MB file needs a few seconds). If it hangs, restart and re-open the file.