# F

A complete system integration of stream-based IP flow-record querier

## VAIBHAV BAJPAI

**Masters Thesis** 

School of Engineering and Science Jacobs University Bremen Bremen, Germany

June 2012

## ABSTRACT

Short summary of the contents in English. . .

### **CONTENTS**

Ι	INTR	ODUCT	ION	1	
1	TRA	RAFFIC MEASUREMENT APPROACHES			
	1.1	Captu	ring Packets	3	
	1.2		ring Flows	3	
	1.3	Remot	e Monitoring	3	
	1.4	Remot	re Metering	3	
2	FLO	W EXPO	ORT PROTOCOLS	5	
	2.1	NetFlo	ow	5	
	2.2	IPFIX		5	
	2.3	sFlow		5	
3	LAN	LANGUAGES AND TOOLS			
	3.1	SQL-b	ased Query Languages	7	
			NetFlow exports as relational DBMS	7	
		3.1.2	Data Stream Management System	7	
			Gigascope	7	
		3.1.4	Tribeca	7	
	3.2	Filteri	ng Languages	7	
		3.2.1	flow-tools	7	
		3.2.2	nfdump	7	
	3.3	Proced	lural Languages	7	
		3.3.1	FlowScan	7	
		3.3.2	Clustering NetFlow Exports	7	
		3.3.3	SiLK Analysis Suite	7	
4	LEG	AL CON	NSIDERATION	9	
п	STAT	TE OF T	THE ART	11	
5				 13	
J	5.1			13	
	<i>J</i> ••=	5.1.1		- <i>)</i> 13	
		5.1.2		14	
		_		 14	
		5.1.4	C	 14	
		5.1.5		 14	
		5.1.6		 15	
	5.2	D .1	-	-5 15	
	<i>J</i>	5.2.1	5 - 11	15	
		_		-5 15	
				-5 15	
		5.2.4		15	
6	FLO	•	,	17	
7		FLOWY 2.0			

8 FLOWY: APPLICATIONS	21		
8.1 IPv6 Transition Failure Identification	21		
8.2 Cybermetrics: User Identification	21		
8.3 Application Identification using Flow Signatures	21		
8.4 TCP level Spam Detection	21		
III MOTIVATION	23		
IV WORK PLAN			
9 DESIGN			
10 IMPLEMENTATION			
11 PERFORMANCE EVALUATION			
12 CONCLUSION	33		
V IMPLEMENTATION AND EVALUATION	35		
13 DESIGN			
14 IMPLEMENTATION			
15 PERFORMANCE EVALUATION			
16 FUTURE WORK			
17 CONCLUSION	45		
VI APPENDIX	47		
A APPENDIX			
BIBLIOGRAPHY	50		

#### LIST OF FIGURES

Figure 1 Flowy: Processing Pipeline [4] ..... 13

LIST OF TABLES

#### LISTINGS

#### **ACRONYMS**

IPFIX Internet Protocol Flow Information Export

**HDF** Hierarchical Data Format

LALR Look-Ahead LR Parser

PLY Python Lex-Yacc

# Part I

# INTRODUCTION

You can put some informational part preamble text here

TRAFFIC MEASUREMENT APPROACHES

- 1.1 CAPTURING PACKETS
- 1.2 CAPTURING FLOWS
- 1.3 REMOTE MONITORING
- 1.4 REMOTE METERING

# FLOW EXPORT PROTOCOLS

- 2.1 NETFLOW
- 2.2 IPFIX
- 2.3 SFLOW

#### LANGUAGES AND TOOLS

- 3.1 SQL-BASED QUERY LANGUAGES
- 3.1.1 *NetFlow exports as relational DBMS*
- 3.1.2 Data Stream Management System
- 3.1.3 Gigascope
- 3.1.4 Tribeca
- 3.2 FILTERING LANGUAGES
- 3.2.1 *flow-tools*
- 3.2.2 *nfdump*
- 3.3 PROCEDURAL LANGUAGES
- 3.3.1 FlowScan
- 3.3.2 Clustering NetFlow Exports
- 3.3.3 SiLK Analysis Suite

# LEGAL CONSIDERATION

# Part II

# STATE OF THE ART

You can put some informational part preamble text here

Flowy [1][2] is the first prototype implementation of a stream-based flow record query language [3][4][5]. The query language allows to describe patterns in flow-records in a declarative and orthogonal fashion, making it easy to read and flexible enough to describe complex relationships among a given set of flows.

#### 5.1 PROCESSING PIPELINE




Figure 1: Flowy: Processing Pipeline [4]

The pipeline consists of a number of independent processing elements that are connected to one another using UNIX-based pipes. Each element receives the content from the previous pipe, performs an operation and pushes it to the next element in the pipeline. Figure 1 shows an overview of the processing pipeline. The flow record attributes used in this pipeline exactly correlate with the attributes defines in the Internet Protocol Flow Information Export (IPFIX) Information Model specified in RFC 5102 [6]. A complete description on the semantics of each element in the pipeline can be found in [3]

#### 5.1.1 Splitter

The splitter takes the flow-records data as input in the flow-tools compatible format. It is responsible to duplicate the input data out to several branches without any processing whatsoever. This allows each of the branches to have an identical copy of the flow data to process it independently.

#### 5.1.2 *Filter*

The filter performs *absolute* filtering on the input flow-records data. The flow-records that pass the filtering criterion are forwarded to the grouper, the rest of the flow-records are dropped. The filter compares separate fields of a flow-record against either a constant value or a value on a different field of the *same* flow-record. The filter cannot *relatively* compare two different incoming flow-records

#### 5.1.3 Grouper

The grouper performs aggregation of the input flow-records data. It consists of a number of rule modules that correspond to a specific subgroup. A flow-record in order to be a part of the group should be a part of at-least one subgroup. A flow-record can be a part of multiple subgroups within a group. In addition a flow-record cannot be part of multiple groups. The grouping rules can be either absolute or relative. The newly formed groups which are passed on to the group filter can also contain meta-information about the flow-records contained within the group using the aggregate clause defined as part of the grouper query.

#### 5.1.4 Group-Filter

The group-filter performs *absolute* filtering on the input group-records data. The group-records that pass the filtering criterion are forwarded to the merger, the rest of the group-records are dropped. The group-filter compares separate fields (or aggregated fields) of a flow-record against either a constant value or a value on a different field of the *same* flow-record. The group-filter cannot *relatively* compare two different incoming group-records

#### 5.1.5 Merger

The merger performs relative filtering on the N-tuples of groups formed from the N stream of groups passed on from the group-filter as input. The merger rule module consists of a number of a submodules, where the output of the merger is the set difference of the output of the first submodule with the union of the output of the rest of the submodules. The relative filtering on the groups are applied to express timing and concurrency constraints using Allen interval algebra [7]

#### 5.1.6 Ungrouper

The ungrouper unwraps the tuples of group-records into individual flow-records, ordered by their timestamps. The duplicate flow-records appearing from several group-records are eliminated and are sent as output only once.

#### 5.2 PYTHON FRAMEWORK

The Python framework is subdivided into two main modules: the validator module and the execution module. The validator module is used for syntax checking and interconnecting of all the stages of the processing pipeline and the execution module is used to perform actions at each stage of the runtime operation.

#### 5.2.1 PyTables and PLY

Flowy uses PyTables [8] to store the flow-records. PyTables is built on top of the Hierarchical Data Format (HDF) library and can exploit the hierarchical nature of the flow-records to efficiently handle large amounts of flow data. In addition, Flowy uses Python Lex-Yacc (PLY) for generating a Look-Ahead LR Parser (LALR) parser and providing extensive input validation, error reporting and validation on the execution module.

#### 5.2.2 Records

Flow-records are the principal unit of data exchange throughout Flowy's processing pipeline. The prototype implementation allows the Record class to be dynamically generated allowing future implementations to easily plug in support for IPFIX or even newer versions of NetFlow [9] exports. The Record handles the reading of the flow-records and saving them in PyTables for future processing.

#### 5.2.3 Filters and Rules

#### 5.2.4 Branches and Branch Masks

# FLOWY IMPROVEMENTS USING MAP/REDUCE

#### FLOWY: APPLICATIONS

- 8.1 IPV6 TRANSITION FAILURE IDENTIFICATION
- 8.2 CYBERMETRICS: USER IDENTIFICATION
- 8.3 APPLICATION IDENTIFICATION USING FLOW SIGNATURES
- 8.4 TCP LEVEL SPAM DETECTION

# Part III MOTIVATION

# Part IV

# WORK PLAN

You can put some informational part preamble text here

# DESIGN

#### **IMPLEMENTATION**

PERFORMANCE EVALUATION

# Part V

## IMPLEMENTATION AND EVALUATION

You can put some informational part preamble text here

## DESIGN

#### **IMPLEMENTATION**

## PERFORMANCE EVALUATION

# Part VI

# APPENDIX



#### APPENDIX

Put your appendix here.

[1] Vladislav Marinov and Jürgen Schönwälder. Design of a Stream-Based IP Flow Record Query Language. In *Proceedings of the 20th* 

IFIP/IEEE International Workshop on Distributed Systems: Operations and Management: Integrated Management of Systems, Services, Processes and People in IT, DSOM '09, pages 15–28, Berlin, Heidelberg, 2009. Springer-Verlag.

- [2] Kaloyan Kanev. Flowy Network Flow Analysis Application. Master's thesis, Jacobs University Bremen, Campus Ring 1, 28759 Bremen, Germany, 2009.
- [3] Kaloyan Kanev, Nikolay Melnikov, and Jürgen Schönwälder. Implementation of a stream-based IP flow record query language. In *Proceedings of the Mechanisms for autonomous management of networks and services, and 4th international conference on Autonomous infrastructure, management and security*, AIMS'10, pages 147–158, Berlin, Heidelberg, 2010. Springer-Verlag.
- [4] Vladislav Marinov. Design of an IP Flow Record Query Language. Master's thesis, Jacobs University Bremen, Campus Ring 1, 28759 Bremen, Germany, 2009.
- [5] Vladislav Marinov and Jürgen Schönwälder. Design of an IP Flow Record Query Language. In *Proceedings of the 2nd international conference on Autonomous Infrastructure, Management and Security: Resilient Networks and Services*, AIMS '08, pages 205–210, Berlin, Heidelberg, 2008. Springer-Verlag.
- [6] J. Quittek, S. Bryant, B. Claise, P. Aitken, and J. Meyer. Information Model for IP Flow Information Export. RFC 5102 (Proposed Standard), January 2008. Updated by RFC 6313.
- [7] James F. Allen. Maintaining knowledge about temporal intervals. *Communications of the ACM*, 26:832–843, November 1983.
- [8] Francesc Alted and Mercedes Fernández-Alonso. PyTables: Processing And Analyzing Extremely Large Amounts Of Data In Python. 2003.
- [9] B. Claise. Cisco Systems NetFlow Services Export Version 9. RFC 3954 (Informational), October 2004.

DECLARATION	
Put your declaration here.	
Bremen, Germany, June 2012	
	 Vaibhav Bajpai