

Client Script Cheat Sheet

client script, cheat sheet

Server loopups

It is important to minimize server calls, especially you should NOT use a direct GlideRecord lookup nor a `g_form.getReference()` (if you use the `getReference()`, remember to use a callback). Instead you should use `g_scratchpad` or the asynchronous `GlideAjax`.

g_scratchpad client script Copy

Use the `g_scratchpad` to pass information to the client side, when the form loads, to reduce the load time.

```
/** Client script **/  
if(g_scratchpad.hasAttachments && g_scratchpad.instance == "production") {  
    var comment = "Something is attached to a child of " + parentCaller + "'s record.";  
    g_form.setValue('comments', comment);  
}
```

g_scratchpad business rule Copy

An `onDisplay` business rule to prepare all the data for client side on `g_scratchpad`

```
/** onDisplay business rule **/  
g_scratchpad.hasAttachments = current.hasAttachments(); //Does this record have attachments  
g_scratchpad.instance = gs.getProperty('instance_name'); //Get the name of the instance  
g_scratchpad.parentCaller = current.parent.caller_id.name; //Get parent's caller's name
```

GlideAjax client script Copy

Call the asynchronous script include from the client script, and also receive the answer back from the server after processing

```

function onChange(control, oldValue, newValue, isLoading) {
    if (isLoading) {
        return;
    }

    var ga = new GlideAjax('serverCheck');
    ga.addParam('sysparm_name', 'serverFunctionName'); //sysparm_name is reserved for the
    ga.addParam('sysparm_group', g_form.getValue('assignment_group'));
    ga.addParam('sysparm_other_variable', g_form.getValue('short_description')); //Any var
    ga.getXML(clientCallback); //Use getXML rather than getXMLWait. Input is your callba
}

function clientCallback(response) {
    var answer = response.responseXML.documentElement.getAttribute("answer"); //Ge
    //Do something with answer
    g_form.setValue('short_description', answer);
}

```

GlideAjax script include Copy

Asynchronous GlideAjax script include, called from the client script with the script include name and the sysparm_name of the function.

```

var serverCheck = Class.create();
serverCheck.prototype = Object.extendObject(AbstractAjaxProcessor, {
    serverFunctionName: function() {
        var assignment_group = this.getParameter('sysparm_group');
        var short_desc = this.getParameter('sysparm_other_variable');
        var returnValue = "";

        var groups = new GlideRecord('sys_user_group');
        if(groups.get(assignment_group)) {
            returnValue = groups.name + ":" + short_desc;
        }
        return returnValue;
    }
});

```

setValue() Copy

When setting a reference value, remember to include the display value, otherwise ServiceNow will make another call to the server

```
//Reference field
var group_name = 'IT Support';
var group_id = '86e8d203ff833100ba13ffffffff70';
g_form.setValue('assignment_group', group_id, group_name); //No server call required

//Other fields
var short_desc = "This is my new short description";
g_form.setValue('short_description', short_desc);
```



(mailto:?subject=Client Script Cheat Sheet&body=http://servicehow.com/client-script-cheat-sheet)