

```

root@0c99d06523d2:/# aws ec2 describe-instances \
--instance-ids i-05670b53c5fc7b822 \
--query "Reservations[0].Instances[0].[State.Name,PublicIpAddress]" \
--output table \
--region us-east-2
-----
| DescribeInstances |
+-----+
| running          |
| 18.225.249.203   |
+-----+
root@0c99d06523d2:/#

```

service: e2 operation: describe-instances parameters: the rest of the command, each one starting in --param

← → ↻ ⚠ Not secure 18.216.26.30

Hello from ip-172-31-34-59.us-east-2.compute.internal

```

root@0c99d06523d2:/cct1# git status
On branch main

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
    .gitignore
    cct1

nothing added to commit but untracked files present (use "git add" to track)
root@0c99d06523d2:/cct1#

```

```

root@0c99d06523d2:/cct1# cat .gitignore
.env
root@0c99d06523d2:/cct1#

```

```

root@0c99d06523d2:/cct1# ./create_instances.sh
Launching 1 instance(s) in us-east-2...
Launched instance IDs:
i-001b358bf385801d6
Instance IDs saved to instance_ids.txt
root@0c99d06523d2:/cct1#

```

```
root@0c99d06523d2:/cct1# ./delete_instances.sh
Terminating instances: i-001b358bf385801d6
{
  "TerminatingInstances": [
    {
      "InstanceId": "i-001b358bf385801d6"
      "CurrentState": {
        "Code": 32,
        "Name": "shutting-down"
      },
      "PreviousState": {
        "Code": 16,
        "Name": "running"
      }
    }
  ]
}
Waiting for instances to terminate...
All instances terminated successfully.
```

Environment variables must be excluded from Git, even in a private repo. This is because it directly places the access control into Git's hand, which is 3rd-party. It's better to keep these in the virtual environment so that there is no other access point for you to monitor for attackers.