

---

```

% Created by Vansh Bhavsar
% Shannon-Fano Coding
clear;
clc;

% Define symbols and corresponding frequencies
symbols = {'0-30', '31-59', '60-63', '64-100', '101-127', '128-150',
'151-200', '201-255'};
frequencies = [2048, 2048, 2048, 2048, 819, 819, 3277, 3277];

% Calculate and sort probabilities in descending order
probabilities = frequencies / sum(frequencies);
[probabilities, idx] = sort(probabilities, 'descend');
symbols = symbols(idx);

% Initialize variables
codes = cell(size(symbols));
code_lengths = zeros(size(symbols));
stack = {{symbols, probabilities, ''}}; % Stack for iterative Shannon-Fano

while ~isempty(stack)
    % Extract top element from stack
    data = stack{end};
    stack(end) = [];

    s = data{1};
    p = data{2};
    pre = data{3};

    % Assign final code if only one symbol remains
    if numel(s) == 1
        idx = strcmp(symbols, s{1});
        codes{idx} = pre;
        code_lengths(idx) = length(pre);
        continue;
    end

    % Find optimal split point where cumulative probability is closest to half
    split = find(cumsum(p) >= sum(p) / 2, 1);

    % Push the two partitions onto the stack as separate elements
    stack{end+1} = {s(1:split), p(1:split), strcat(pre, '0')};
    stack{end+1} = {s(split+1:end), p(split+1:end), strcat(pre, '1')};
end

% Display results
fprintf('Symbol\tCode\tLength\n');
for i = 1:length(symbols)
    fprintf('%s\t%s\t%d\n', symbols{i}, codes{i}, code_lengths(i));
end

Symbol      Code      Length
151-200     000       3

```

---

---

201-255	001	3
0-30	01	2
31-59	100	3
60-63	101	3
64-100	110	3
101-127	1110	4
128-150	1111	4

*Published with MATLAB® R2024b*