


This issue was moved to a discussion.

You can continue the conversation there. [Go to discussion →](#)

# Date: 2024-03-06 #4557

New issue

Closed

 13 of 34 tasks

chang330 opened this issue on Mar 20 · 0 comments



chang330 commented on Mar 20

Date: 2024-03-06

Administrative

- [Previous meeting minutes](#)
- [API WG project board](#)
- [API WG Roadmap](#)

Participants:

- ☒ David Cole (DanLaw)
- ☒ Daniel Shih (Tier4/NTU)
- ☒ Ryohsuke Mitsudome (TSC Chair)
- ☒ Bonolo Mathibela (AUTOWARE)
- ☐ Abinesh Lingeswaran (Danlaw)
- ☒ David Walmroth
- ☒ Huei-Ru Tseng (ITRI)
- ☒ Isamu-takagi
- ☐ Jaiden
- ☒ Pedro
- ☒ Rohit
- ☐ Rojer
- ☐ Sudharsan Srikanthan
- ☐ Sujith (Interpl.ai)
- ☐ Tanishq
- ☐ Venkat
- ☐ Yu Asabe

Assignees

No one assigned

Labels

None yet

Projects

None yet

Milestone

No milestone

Development

No branches or pull requests

1 participant



- ☐ Christian John (SPC/Tier 4)
- ☐ Weilin Yao (Whaledynamic)
- ☐ Ram (Interpl.ai)
- ☐ Mark (Interpl.ai)
- ☐ Armagan (Leodrive)
- ☐ Lingzi (Whaledynamic)
- ☐ Heewon Kim (AWF korea)
- ☒ Shreekant Marwadi (Leidos)
- ☐ Hidenaga Ushijima
- ☐ Yu Zhigang
- ☒ CY
- ☐ Ziri
- ☐ Will Martin
- ☐ Chang
- ☐ Joao Amaral
- ☒ Samet Kutuk
- ☒ Jon Smet

## Agenda

---

- AW-V2X Traffic Signal ID Mapping Update Logic Proposal from Rohit (30-40 mins)
- Discussion on the above

## Notes

---

### AW-V2X Traffic Signal ID Mapping Update Logic Proposal from Rohit

---

- Recap from the previous meeting.

### Discussion

---

- Mitsudome) Can't the vehicle receive the traffic light info from the nearest RSU, and map the relevant IDs to the Lanelet2 traffic signal IDs? All the traffic light information from V2X can be published. Do we need the RSU\_Mapping module to receive the predicted path of the ego vehicle from the Planning module?
  - A table that matches the Lane IDs in the MAP message and the traffic\_signal\_id in the LL2 map is necessary. Then, the SPaT information can be matched to the traffic signal information used in Autoware.
  - The ego-vehicle's path information can be used to make the matching process more efficient. (But is

it necessary?)

- Daniel) Should the traffic\_light\_arbiter be placed there? Should the V2X output be put directly into the traffic\_light\_arbiter?
  - The traffic\_light\_arbiter will take in a TrafficSignalArray, arbitrate the information, and output the final traffic light information that will be fed to the planner. The SPaT message only includes the signal phase information and does not have the physical location information of the lights. Therefore, the MAP message needs to be used simultaneously to know the coordinates of the specific traffic lights.
- Rohit) Can the map matching of the IDs happen prior? Or should it happen at run-time?
- Can the predicted path of the ego-vehicle be used as a way to optimize? For example, out of all the V2X traffic light information received, only the traffic light information that is related to the trajectory of the ego-vehicle needs to be published.
  - Both ways are probably possible. Which is better to align with other Autoware modules?
  - Any input from @mitsudome-r -san?
- [https://github.com/autowarefoundation/autoware.universe/tree/main/perception/traffic\\_light\\_map\\_based\\_detector](https://github.com/autowarefoundation/autoware.universe/tree/main/perception/traffic_light_map_based_detector): there is an option to use the route as a way to filter the traffic lights that are published.
- Huei-Ru) In ITRI, only V2X was used for traffic light detection for the bus project.
  - We can maybe hold another meeting to discuss possible ways to proceed and to also share previous work.
- Rohit) The map matching may also fail if the stop line location in the Autoware Lanelet2 map and V2X map are not aligned.

## Next Steps

---

- Possibly another meeting to discuss the above before the next API meeting.
- Especially the topic of whether to use the ego-vehicle trajected path in the traffic signal detection process.

Overall, we want to discuss the following over the next few meetings.

- Consider various use-cases and identify what kind of communication will take place between Autoware and the V2X stack.
- Requirements on the handshake between the V2X software and autonomous driving stack (creating

sequence diagrams)

- Requirements for the interfaces/APIs
- Interface between V2X software and AD stack (not only APIs, any means of communication)
- HMI (both in-cabin and external) of Autoware and V2X applications

Originally posted by [@yuasabe](#) in [#4201](#)



**autowarefoundation** locked and limited conversation to collaborators on Apr 2



**mitsudome-r** converted this issue into discussion [#4586](#) on Apr 2

**This issue was moved to a discussion.**

You can continue the conversation there. [Go to discussion](#)

