

CS 380 - GPU and GPGPU Programming

Lecture 4: GPU Architecture, Pt. 1

Markus Hadwiger, KAUST

Reading Assignment #2 (until Sep 13)



Read (required):

- Orange book (GLSL), chapter 4 (*The OpenGL Programmable Pipeline*)
- Brief overviews of GLSL and legacy assembly shading language

https://en.wikipedia.org/wiki/OpenGL_Shading_Language

https://en.wikipedia.org/wiki/ARB_assembly_language

- GPU Gems 2 book, chapter 30 (*The GeForce 6 Series GPU Architecture*)

http://download.nvidia.com/developer/GPU_Gems_2/GPU_Gems2_ch30.pdf

OpenGL Tutorial (Attendance Optional)




With Amani

Tomorrow, 15:00 – 16:30, Room 3223

Come with your conceptual or coding questions!

Graphics Hardware



ROPs = raster operations
(render output units)

Direct3D 10 Pipeline (~OpenGL 3.2)




New geometry shader stage:

- Vertex -> geometry -> pixel shaders
- Stream output after geometry shader

fixed

programmable

memory



Courtesy David Blythe, Microsoft

Direct3D 11 Pipeline (~OpenGL 4.x)




New tessellation stages

- Hull shader
(OpenGL: *tessellation control*)
- Tessellator
(OpenGL: *tessellation primitive generator*)
- Domain shader
(OpenGL: *tessellation evaluation*)

Outside this pipeline


- Compute shader
- (Ray tracing cores, D3D 12)
- (Mesh shader pipeline, D3D 12.2)



Direct3D 12 Traditional Geometry Pipeline



- First version 2015 (Windows 10)
- New from March 2018: DXR (DX12 ray tracing)
- DX 12 Ultimate (March 2020; PC and Xbox Series X)



Direct3D 12 Mesh Shader Pipeline




Reinventing the Geometry Pipeline

- Mesh and amplification shaders: new high-performance geometry pipeline based on compute shaders (DX 12 Ultimate / feature level 12.2)
- Compute shader-style replacement of IA/VS/HS/Tess/DS/GS

Legacy D3D12 graphics pipeline




Mesh shader pipeline



See talk by Shawn Hargreaves: <https://www.youtube.com/watch?v=CFXKTXti134>

Vulkan 1.1/1.2



Some Vulkan commands specify geometric objects to be drawn or computational work to be performed, while others specify state controlling how objects are handled by the various pipeline stages, or control data transfer between memory organized as images and buffers. Commands are effectively sent through a processing pipeline, either a **graphics pipeline** or a **compute pipeline**.

- Fixed Function Stage
- Shader Stage
- Storage Images

Vulkan 1.1/1.2




- Mesh and task shaders: new high-performance geometry pipeline based on compute shaders
(Mesh and task shaders also available as OpenGL 4.5/4.6 extension: GL_NV_mesh_shader)


TRADITIONAL PIPELINE



TASK/MESH PIPELINE



GPU Structure *Before Later Unified Shaders*




Example
NVIDIA GeForce 6/7,
2004, 2005

Legacy Vertex Shading Unit (1)




Geforce 3 (NV20), 2001

- floating point
4-vector
vertex engine
- still very
instructive for
understanding
GPUs in general



Lindholm et al., A User-Programmable Vertex Engine, SIGGRAPH 2001

Vertex Processor



Legacy Vertex Shading Unit (2)



Input
attributes

Vertex Attribute Register	Conventional Per-vertex Parameter	Conventional Per-vertex Parameter Command	Conventional Component Mapping
0	Vertex position	glVertex	<i>x,y,z,w</i>
1	Vertex weights	glVertexWeightEXT	<i>w,0,0,1</i>
2	Normal	glNormal	
3	Primary color	glColor	<i>r,g,b,a</i>
4	Secondary color	glSecondaryColorEXT	<i>r,g,b,1</i>
5	Fog coordinate	glFogCoordEXT	<i>f,0,0,1</i>
6	-	-	-
7	-	-	-
8	Texture coord 0	glMultiTexCoordARB (GL_TEXTURE0...)	<i>s,t,r,q</i>
9	Texture coord 1	glMultiTexCoordARB (GL_TEXTURE1...)	<i>s,t,r,q</i>
10	Texture coord 2	glMultiTexCoordARB (GL_TEXTURE2...)	<i>s,t,r,q</i>
11	Texture coord 3	glMultiTexCoordARB (GL_TEXTURE3...)	<i>s,t,r,q</i>
12	Texture coord 4	glMultiTexCoordARB (GL_TEXTURE4...)	<i>s,t,r,q</i>
13	Texture coord 5	glMultiTexCoordARB (GL_TEXTURE5...)	<i>s,t,r,q</i>
14	Texture coord 6	glMultiTexCoordARB (GL_TEXTURE6...)	<i>s,t,r,q</i>
15	Texture coord 7	glMultiTexCoordARB (GL_TEXTURE7...)	<i>s,t,r,q</i>

Code
examples

```

DP4 o[HPOS].x, c[0], v[OPOS];
MUL R1, R0.zxyw, R2.yzxw ;
MAD R1, R0.yzxw, R2.zxyw, -R1;
    
```

swizzling!

Legacy Vertex Shading Unit (3)




Vector instruction set, very few instructions; **no branching** yet!

OpCode	Full Name	Description
MOV	Move	vector -> vector
MUL	Multiply	vector -> vector
ADD	Add	vector -> vector
MAD	Multiply and add	vector -> vector
DST	Distance	vector -> vector
MIN	Minimum	vector -> vector
MAX	Maximum	vector -> vector
SLT	Set on less than	vector -> vector
SGE	Set on greater or equal	vector -> vector
RCP	Reciprocal	scalar-> replicated scalar
RSQ	Reciprocal square root	scalar-> replicated scalar
DP3	3 term dot product	vector-> replicated scalar
DP4	4 term dot product	vector-> replicated scalar
LOG	Log base 2	miscellaneous
EXP	Exp base 2	miscellaneous
LIT	Phong lighting	miscellaneous
ARL	Address register load	miscellaneous

GPU Structure *Before Later Unified Shaders*



Example
NVIDIA GeForce 6/7,
2004, 2005




Fast Forward to Programm. Fragment Shading



Core OpenGL Fragment Texturing & Coloring

< 1999



NVIDIA Proprietary


Courtesy Mark Kilgard

Fast Forward to Programm. Fragment Shading



NV10 OpenGL Fragment Texturing & Coloring

GeForce 256,
1999



NVIDIA Proprietary


Courtesy Mark Kilgard

Fast Forward to Programm. Fragment Shading



NV20 OpenGL Fragment Texturing & Coloring

GeForce 3,
2001



NVIDIA Proprietary


Courtesy Mark Kilgard

Fast Forward to Programm. Fragment Shading



NV30 OpenGL Fragment Texturing & Coloring

GeForce FX (5),
2003



NVIDIA Proprietary

Courtesy Mark Kilgard

Legacy Fragment Shading Unit (1)




GeForce 6 (NV40), 2004

- dynamic branching

Texture Filter
Bi / Tri / Aniso
1 texture @ full speed
4-tap filter @ full speed
16:1 Aniso w/ Trilinear (128-tap)
FP16 Texture Filtering

L2 Texture
Cache

SIMD Architecture
Dual Issue / Co-Issue
FP32 Computation
Shader Model 3.0



Shader Unit 1
4 FP Ops / pixel
Dual/Co-Issue
Texture Address Calc
Free fp16 normalize
+ mini ALU

Shader Unit 2
4 FP Ops / pixel
Dual/Co-Issue
+ mini ALU

Legacy Fragment Shading Unit (2)



Example code

```
!!ARBfp1.0

ATTRIB unit_tc = fragment.texcoord[ 0 ];
PARAM  mvp_inv[] = { state.matrix.mvp.inverse };
PARAM  constants = {0, 0.999, 1, 2};

TEMP pos_win, temp;

TEX pos_win.z, unit_tc, texture[ 1 ], 2D;

ADD pos_win.w, constants.y, -pos_win.z;
KIL pos_win.w;

MOV result.color.w, pos_win.z;

MOV pos_win.xyw, unit_tc;
MAD pos_win.xyz, pos_win, constants.a, -constants.b;


DP4 temp.w, mvp_inv[ 3 ], pos_win;
RCP temp.w, temp.w;

MUL pos_win, pos_win, temp.w;

DP4 result.color.x, mvp_inv[ 0 ], pos_win;
DP4 result.color.y, mvp_inv[ 1 ], pos_win;
DP4 result.color.z, mvp_inv[ 2 ], pos_win;

END
```


Fragment Processor



Per-Pixel(Fragment) Lighting




Simulating smooth surfaces by calculating illumination for each fragment

Example: specular highlights (Phong illumination/shading)

**fragment
shader!** Phong shading:
per-fragment evaluation

Gouraud shading:
linear interpolation from vertices

**vertex
shader!**



Per-Pixel Phong Lighting (Cg)



```
void main(float4 position : TEXCOORD0,  
          float3 normal   : TEXCOORD1,  
  
          out float4 oColor : COLOR,  
  
          uniform float3 ambientCol,  
          uniform float3 lightCol,  
          uniform float3 lightPos,  
          uniform float3 eyePos,  
          uniform float3 Ka,  
          uniform float3 Kd,  
          uniform float3 Ks,  
          uniform float  shiny)  
{
```

Per-Pixel Phong Lighting (Cg)



```
float3 P = position.xyz;
float3 N = normal;
float3 V = normalize(eyePosition - P);
float3 H = normalize(L + V);

float3 ambient = Ka * ambientCol;

float3 L          = normalize(lightPos - P);
float  diffLight = max(dot(L, N), 0);
float3 diffuse    = Kd * lightCol * diffLight;

float  specLight = pow(max(dot(H, N), 0), shiny);
float3 specular  = Ks * lightCol * specLight;

oColor.xyz = ambient + diffuse + specular;
oColor.w = 1;
}
```

Thank you.