

Quiz navigation



Show one page at a time

Finish notes

Status: Finished
Started: Monday, 23 December 2024, 5:53 PM
Completed: Thursday, 27 November 2024, 11:26 AM
Duration: 30 days 5 hours

Question 1

Correct
Marked out of 1.00
Flag question

Write a program that determines the name of a shape from its number of sides. Read the number of sides from the user and then report the appropriate name as part of a meaningful message. Your program should support shapes with anywhere from 3 up to (and including) 10 sides. If a number of sides outside of this range is entered then your program should display an appropriate error message.

Sample Input 1

3

Sample Output 1

Triangle

Sample Input 2

7

Sample Output 2

Heptagon

Sample Input 3

11

Sample Output 3

The number of sides is not supported.

Answer: (generally regime: 0 %)

```
#include <stdio.h>
int main()
{
    int sides;
    printf("Enter sides: ");
    scanf("%d", &sides);
    switch(sides)
    {
        case 3:
            printf("Triangle");
            break;
        case 4:
            printf("Quadrilateral");
            break;
        case 5:
            printf("Pentagon");
            break;
        case 6:
            printf("Hexagon");
            break;
        case 7:
            printf("Heptagon");
            break;
        case 8:
            printf("Octagon");
            break;
        case 9:
            printf("Nonagon");
            break;
        case 10:
            printf("Decagon");
            break;
    }
}
```

Input	Expected	Got
✓ 3	Triangle	Triangle ✓
✓ 7	heptagon	heptagon ✓
✓ 11	The number of sides is not supported.	The number of sides is not supported. ✓

Passed all tests: ✓

Question 2

Correct
Marked out of 1.00
Flag question

The Chinese zodiac assigns animals to years in a 12-year cycle. One 12-year cycle is shown in the table below. The pattern repeats from there, with 2012 being another year of the Dragon, and 1999 being another year of the Horse.

Year

Animal

2009	Dragon
2001	Snake
2002	Horse
2003	Sheep
2004	Monkey
2005	Rooster
2006	Dog
2007	Pig
2008	Rat
2009	Ox
2010	Tiger
2011	Hare

Write a program that reads a year from the user and displays the animal associated with that year. Your program should work correctly for any year greater than or equal to zero, not just the ones listed in the table.

Sample Input 1

2004

Sample Output 1

Monkey

Sample Input 2

2010

Sample Output 2

Tiger

Answer: (generally regime: 0 %)

```
#include <stdio.h>
int main()
{
    int year;
    printf("Enter year: ");
    scanf("%d", &year);
    switch((year - 2009) % 12)
    {
        case 0:
            printf("Ox");
            break;
        case 1:
            printf("Tiger");
            break;
        case 2:
            printf("Rabbit");
            break;
        case 3:
            printf("Dragon");
            break;
        case 4:
            printf("Snake");
            break;
        case 5:
            printf("Horse");
            break;
        case 6:
            printf("Sheep");
            break;
        case 7:
            printf("Monkey");
            break;
        case 8:
            printf("Rooster");
            break;
        case 9:
            printf("Dog");
            break;
        case 10:
            printf("Pig");
            break;
        case 11:
            printf("Rat");
            break;
    }
}
```


Input	Expected	Got
✓ 2009	Ox	Ox ✓
✓ 2010	Tiger	Tiger ✓

Passed all tests: ✓

Question 3

Correct
Marked out of 1.00
Flag question

Positions on a chess board are identified by a letter and a number. The letter identifies the column, while the number identifies the row, as shown below.



Write a program that reads a position from the user. Use an if statement to determine if the column begins with a black square or a white square. Then use modular arithmetic to report the color of the square in that row. For example, if the user enters a then your program should report that the square is black. If the user enters d then your program should report that the square is white. Your program may assume that a valid position will always be entered. It does not need to perform any error checking.

Sample Input 1

a 1

Sample Output 1

The square is black.

Sample Input 2

d 5

Sample Output 2

The square is white.

Answer: (generally regime: 0 %)

```
#include <stdio.h>
int main()
{
    char col;
    int row;
    printf("Enter column: ");
    scanf("%c", &col);
    printf("Enter row: ");
    scanf("%d", &row);
    if ((col - 'a') % 2 == 0)
    {
        printf("The square is black.");
    }
    else
    {
        printf("The square is white.");
    }
}
```

Input	Expected	Got
✓ a 1	The square is black.	The square is black. ✓
✓ d 5	The square is white.	The square is white. ✓

Passed all tests: ✓

Save the state of the flags

Finish review