

Week 5 A03

Reading Discussion

- **Tidy Data**

By Hadley Wickham

Tidy Data:

- 1) Structure: Most statistical datasets are rectangular tables made up of *rows* and *columns*
- 2) Definition: A dataset is a collection of values, usually either numbers (if quantitative) or strings (if qualitative).
- 3) Values are organized in two ways. Every value belongs to a *variable* and an *observation*.

Example

Variable1	Variable2	Variable3
person	treatment	result
John Smith	a	—
Jane Doe	a	16
Mary Johnson	a	3
John Smith	b	2
Jane Doe	b	11
Mary Johnson	b	1

Variables in columns and observations in rows

Therefore, in tidy data:

- Each variable forms a column.
- Each observation forms a row.
- Each type of observational unit forms a table.

The five most common issues with messy datasets

- Column headers are values, not variable names.
- Multiple variables are stored in one column.
- Variables are stored in both rows and columns.
- Multiple types of observational units are stored in the same table.
- A single observational unit is stored in multiple tables.

Column headers are values, not variable names

row	a	b	c
A	1	4	7
B	2	5	8
C	3	6	9

(a) Raw data

row	column	value
A	a	1
B	a	2
C	a	3
A	b	4
B	b	5
C	b	6
A	c	7
B	c	8
C	c	9

(b) Molten data

Table 5: A simple example of melting. (a) is melted with one colvar, row, yielding the molten dataset (b). The information in each table is exactly the same, just stored in a different way.

Multiple variables stored in one column

country	year	column	cases
AD	2000	m014	0
AD	2000	m1524	0
AD	2000	m2534	1
AD	2000	m3544	0
AD	2000	m4554	0
AD	2000	m5564	0
AD	2000	m65	0
AE	2000	m014	2
AE	2000	m1524	4
AE	2000	m2534	4
AE	2000	m3544	6
AE	2000	m4554	5
AE	2000	m5564	12
AE	2000	m65	10
AE	2000	f014	3

(a) Molten data

country	year	sex	age	cases
AD	2000	m	0–14	0
AD	2000	m	15–24	0
AD	2000	m	25–34	1
AD	2000	m	35–44	0
AD	2000	m	45–54	0
AD	2000	m	55–64	0
AD	2000	m	65+	0
AE	2000	m	0–14	2
AE	2000	m	15–24	4
AE	2000	m	25–34	4
AE	2000	m	35–44	6
AE	2000	m	45–54	5
AE	2000	m	55–64	12
AE	2000	m	65+	10
AE	2000	f	0-14	3

(b) Tidy data

Table 10: Tidying the TB dataset requires first melting, and then splitting the `column` column into two variables: `sex` and `age`.

Variables are stored in both rows and columns

id	date	element	value
MX17004	2010-01-30	tmax	27.8
MX17004	2010-01-30	tmin	14.5
MX17004	2010-02-02	tmax	27.3
MX17004	2010-02-02	tmin	14.4
MX17004	2010-02-03	tmax	24.1
MX17004	2010-02-03	tmin	14.4
MX17004	2010-02-11	tmax	29.7
MX17004	2010-02-11	tmin	13.4
MX17004	2010-02-23	tmax	29.9
MX17004	2010-02-23	tmin	10.7

(a) Molten data

id	date	tmax	tmin
MX17004	2010-01-30	27.8	14.5
MX17004	2010-02-02	27.3	14.4
MX17004	2010-02-03	24.1	14.4
MX17004	2010-02-11	29.7	13.4
MX17004	2010-02-23	29.9	10.7
MX17004	2010-03-05	32.1	14.2
MX17004	2010-03-10	34.5	16.8
MX17004	2010-03-16	31.1	17.6
MX17004	2010-04-27	36.3	16.7
MX17004	2010-05-27	33.2	18.2

(b) Tidy data

Multiple types in one table

year	artist	time	track	date	week	rank
2000	2 Pac	4:22	Baby Don't Cry	2000-02-26	1	87
2000	2 Pac	4:22	Baby Don't Cry	2000-03-04	2	82
2000	2 Pac	4:22	Baby Don't Cry	2000-03-11	3	72
2000	2 Pac	4:22	Baby Don't Cry	2000-03-18	4	77
2000	2 Pac	4:22	Baby Don't Cry	2000-03-25	5	87
2000	2 Pac	4:22	Baby Don't Cry	2000-04-01	6	94
2000	2 Pac	4:22	Baby Don't Cry	2000-04-08	7	99
2000	2Ge+her	3:15	The Hardest Part Of ...	2000-09-02	1	91
2000	2Ge+her	3:15	The Hardest Part Of ...	2000-09-09	2	87
2000	2Ge+her	3:15	The Hardest Part Of ...	2000-09-16	3	92
2000	3 Doors Down	3:53	Kryptonite	2000-04-08	1	81
2000	3 Doors Down	3:53	Kryptonite	2000-04-15	2	70
2000	3 Doors Down	3:53	Kryptonite	2000-04-22	3	68
2000	3 Doors Down	3:53	Kryptonite	2000-04-29	4	67
2000	3 Doors Down	3:53	Kryptonite	2000-05-06	5	66