

6

5

4

3

2

1

Rev

AWO #

Description

Date

Appr

-

RELEASED

6/1/16

APPROVED: _____

DATE: _____ TITLE: _____

Ø.551
[14.00]

1.728 [43.90]

L

SD-PMAXXX-MMTBL-CXX-XFT
7=IP67 A=UL2464

PART NO.		L
SD-PMAXXX-MMTBL-CXX-3FT		36"±1.80" [914.4±45.72mm]
SD-PMAXXX-MMTBL-CXX-6FT		72"±3.60" [1828.8±91.44mm]
SD-PMAXXX-MMTBL-CXX-10FT		120"±6.000" [3048±152.4mm]

MOLDING	PU	BLACK
RING NUT	BRASS, NICKEL PLATED	
CONTACT	BRASS, MALE PIN, GOLD FLASH	
CONNECTOR	M12 MALE CONNECTOR	BLACK
PART NAME	DESCRIPTION	COLOR

02B

03B

04B

05B

06B

08A

10A

12A

PIN ASSIGNMENT FRONT VIEW

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES

.X ± .10 Ø.X ± .10
.XX ± .020 Ø.XX ± .015
.XXX ± .015 Ø.XXX ± .010

APPROVALS

DATE

DRAWN

HR

6/1/16

CHECKED

CK

6/1/16

APPROVED

ADAM TECH

909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

TITLE

WATERPROOF CONNECTOR, MALE, M12
ASSEMBLY CABLE, STRAIGHT

SIZE

PART NO.

REV.

X

SD-PMAXXX-MMTBL-CXX-XFT

-

REF: S00200T

SCALE: NTS

SHEET 1 OF 1

SPECIFICATIONS:

Electrical:

Current rating: XXA=2A, XXB=5A

Dielectric withstanding voltage: 500 VAC for 1 minute

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant.

RoHS
COMPLIANT