


Artificial Intelligence

Decision Trees



Reminder: Features

- Features, aka attributes
 - Sometimes: TYPE=French
 - Sometimes: $f_{\text{TYPE=French}}(x) = 1$

Example	Attributes										Target
	<i>Alt</i>	<i>Bar</i>	<i>Fri</i>	<i>Hun</i>	<i>Pat</i>	<i>Price</i>	<i>Rain</i>	<i>Res</i>	<i>Type</i>	<i>Est</i>	<i>WillWait</i>
X_1	<i>T</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Some</i>	<i>\$\$\$</i>	<i>F</i>	<i>T</i>	<i>French</i>	<i>0–10</i>	<i>T</i>
X_2	<i>T</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Full</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Thai</i>	<i>30–60</i>	<i>F</i>
X_3	<i>F</i>	<i>T</i>	<i>F</i>	<i>F</i>	<i>Some</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Burger</i>	<i>0–10</i>	<i>T</i>
X_4	<i>T</i>	<i>F</i>	<i>T</i>	<i>T</i>	<i>Full</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Thai</i>	<i>10–30</i>	<i>T</i>
X_5	<i>T</i>	<i>F</i>	<i>T</i>	<i>F</i>	<i>Full</i>	<i>\$\$\$</i>	<i>F</i>	<i>T</i>	<i>French</i>	<i>>60</i>	<i>F</i>
X_6	<i>F</i>	<i>T</i>	<i>F</i>	<i>T</i>	<i>Some</i>	<i>\$\$</i>	<i>T</i>	<i>T</i>	<i>Italian</i>	<i>0–10</i>	<i>T</i>
X_7	<i>F</i>	<i>T</i>	<i>F</i>	<i>F</i>	<i>None</i>	<i>\$</i>	<i>T</i>	<i>F</i>	<i>Burger</i>	<i>0–10</i>	<i>F</i>
X_8	<i>F</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Some</i>	<i>\$\$</i>	<i>T</i>	<i>T</i>	<i>Thai</i>	<i>0–10</i>	<i>T</i>
X_9	<i>F</i>	<i>T</i>	<i>T</i>	<i>F</i>	<i>Full</i>	<i>\$</i>	<i>T</i>	<i>F</i>	<i>Burger</i>	<i>>60</i>	<i>F</i>
X_{10}	<i>T</i>	<i>T</i>	<i>T</i>	<i>T</i>	<i>Full</i>	<i>\$\$\$</i>	<i>F</i>	<i>T</i>	<i>Italian</i>	<i>10–30</i>	<i>F</i>
X_{11}	<i>F</i>	<i>F</i>	<i>F</i>	<i>F</i>	<i>None</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Thai</i>	<i>0–10</i>	<i>F</i>
X_{12}	<i>T</i>	<i>T</i>	<i>T</i>	<i>T</i>	<i>Full</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Burger</i>	<i>30–60</i>	<i>T</i>


Decision Trees

- Compact representation of a function:

- Truth table
- Conditional probability table
- Regression values

- True function


- Realizable: in H



Expressiveness of DTs

- Can express any function of the features

A	B	A xor B
F	F	F
F	T	T
T	F	T
T	T	F



$$P(C|A, B)$$

- However, we hope for compact trees

Comparison: Perceptrons

- What is the expressiveness of a perceptron over these features?

Example	Attributes										Target
	<i>Alt</i>	<i>Bar</i>	<i>Fri</i>	<i>Hun</i>	<i>Pat</i>	<i>Price</i>	<i>Rain</i>	<i>Res</i>	<i>Type</i>	<i>Est</i>	<i>WillWait</i>
X_1	<i>T</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Some</i>	<i>\$\$\$</i>	<i>F</i>	<i>T</i>	<i>French</i>	<i>0-10</i>	<i>T</i>
X_2	<i>T</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Full</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Thai</i>	<i>30-60</i>	<i>F</i>

- For a perceptron, a feature's contribution is either positive or negative
 - If you want one feature's effect to depend on another, you have to add a new conjunction feature
 - E.g. adding "PATRONS=full \wedge WAIT = 60" allows a perceptron to model the interaction between the two atomic features
- DTs automatically conjoin features / attributes
 - Features can have different effects in different branches of the tree!
- Difference between modeling relative evidence weighting (NB) and complex evidence interaction (DTs)
 - Though if the interactions are too complex, may not find the DT greedily


Decision Tree Learning

- Aim: find a small tree consistent with the training examples
- Idea: (recursively) choose “most significant” attribute as root of (sub)tree

```
function DTL(examples, attributes, default) returns a decision tree
  if examples is empty then return default
  else if all examples have the same classification then return the classification
  else if attributes is empty then return MODE(examples)
  else
    best ← CHOOSE-ATTRIBUTE(attributes, examples)
    tree ← a new decision tree with root test best
    for each value  $v_i$  of best do
      examplesi ← {elements of examples with best =  $v_i$ }
      subtree ← DTL(examplesi, attributes − best, MODE(examples))
      add a branch to tree with label  $v_i$  and subtree subtree
  return tree
```

Choosing an Attribute

- Idea: a good attribute splits the examples into subsets that are (ideally) “all positive” or “all negative”



- So: we need a measure of how “good” a split is, even if the results aren’t perfectly separated out

Entropy and Information

- **Information** answers questions

- The more uncertain about the answer initially, the more information in the answer

- Scale: bits

- Answer to Boolean question with prior $\langle 1/2, 1/2 \rangle$? 1
- Answer to 4-way question with prior $\langle 1/4, 1/4, 1/4, 1/4 \rangle$? 2
- Answer to 4-way question with prior $\langle 0, 0, 0, 1 \rangle$? 0
- Answer to 3-way question with prior $\langle 1/2, 1/4, 1/4 \rangle$? $3/2$

Bits on average:

Coding scheme:

Distribution: $\langle 1/2, 1/4, 1/4 \rangle$

Code words: 0, 10, 11

Bits on average = $1 \cdot 1/2 + 2 \cdot 1/4 + 2 \cdot 1/4 = 3/2$

Distribution: $\langle 1/2, 1/4, 1/4 \rangle$

- A probability p is typical of:

- A uniform distribution of size $1/p$
- A code of length $\log 1/p$


The average number of bits is $\sum_i p_i \log_2 \frac{1}{p_i}$

Entropy


- General answer: if prior is $\langle p_1, \dots, p_n \rangle$:
 - Information is the expected code length

$$\begin{aligned} H(\langle p_1, \dots, p_n \rangle) &= E_p \log_2 1/p_i \\ &= \sum_{i=1}^n -p_i \log_2 p_i \end{aligned}$$


- Also called the **entropy** of the distribution
 - More uniform = higher entropy
 - More values = higher entropy
 - More peaked = lower entropy



1 bit



0 bits



0.5 bit

Information Gain

- Back to decision trees!
- For each split, compare entropy before and after
 - Difference is the **information gain**
 - Problem: there's more than one distribution after split!

$$IG = \text{Entropy}(\text{Parent}) - \text{WeightedAverage}(\text{Entropy}(\text{Children}))$$

$$H(\text{Parent}) = -\frac{1}{2}\log_2\frac{1}{2} - \frac{1}{2}\log_2\frac{1}{2} = 1$$



$$H(\text{None}) = -1\log_2 1 = 0$$

$$H(\text{Some}) = -1\log_2 1 = 0$$


$$H(\text{Full}) = -\frac{1}{3}\log_2\frac{1}{3} - \frac{2}{3}\log_2\frac{2}{3} = 0.92$$

$$IG = H(\text{Parent}) - \frac{2}{12}H(\text{None}) - \frac{4}{12}H(\text{Some}) - \frac{6}{12}H(\text{Full})$$

$$IG = 0.54$$




- Solution: use **expected entropy**, weighted by the number of examples



Next Step: Recurse


- Now we need to keep growing the tree!
- Two branches are done (why?)
- What to do under “full”?
 - See what examples are there...



Example	Attributes										Target
	<i>Alt</i>	<i>Bar</i>	<i>Fri</i>	<i>Hun</i>	<i>Pat</i>	<i>Price</i>	<i>Rain</i>	<i>Res</i>	<i>Type</i>	<i>Est</i>	<i>WillWait</i>
X_1	<i>T</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Some</i>	<i>\$\$\$</i>	<i>F</i>	<i>T</i>	<i>French</i>	<i>0-10</i>	<i>T</i>
X_2	<i>T</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Full</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Thai</i>	<i>30-60</i>	<i>F</i>
X_3	<i>F</i>	<i>T</i>	<i>F</i>	<i>F</i>	<i>Some</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Burger</i>	<i>0-10</i>	<i>T</i>
X_4	<i>T</i>	<i>F</i>	<i>T</i>	<i>T</i>	<i>Full</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Thai</i>	<i>10-30</i>	<i>T</i>
X_5	<i>T</i>	<i>F</i>	<i>T</i>	<i>F</i>	<i>Full</i>	<i>\$\$\$</i>	<i>F</i>	<i>T</i>	<i>French</i>	<i>>60</i>	<i>F</i>
X_6	<i>F</i>	<i>T</i>	<i>F</i>	<i>T</i>	<i>Some</i>	<i>\$\$</i>	<i>T</i>	<i>T</i>	<i>Italian</i>	<i>0-10</i>	<i>T</i>
X_7	<i>F</i>	<i>T</i>	<i>F</i>	<i>F</i>	<i>None</i>	<i>\$</i>	<i>T</i>	<i>F</i>	<i>Burger</i>	<i>0-10</i>	<i>F</i>
X_8	<i>F</i>	<i>F</i>	<i>F</i>	<i>T</i>	<i>Some</i>	<i>\$\$</i>	<i>T</i>	<i>T</i>	<i>Thai</i>	<i>0-10</i>	<i>T</i>
X_9	<i>F</i>	<i>T</i>	<i>T</i>	<i>F</i>	<i>Full</i>	<i>\$</i>	<i>T</i>	<i>F</i>	<i>Burger</i>	<i>>60</i>	<i>F</i>
X_{10}	<i>T</i>	<i>T</i>	<i>T</i>	<i>T</i>	<i>Full</i>	<i>\$\$\$</i>	<i>F</i>	<i>T</i>	<i>Italian</i>	<i>10-30</i>	<i>F</i>
X_{11}	<i>F</i>	<i>F</i>	<i>F</i>	<i>F</i>	<i>None</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Thai</i>	<i>0-10</i>	<i>F</i>
X_{12}	<i>T</i>	<i>T</i>	<i>T</i>	<i>T</i>	<i>Full</i>	<i>\$</i>	<i>F</i>	<i>F</i>	<i>Burger</i>	<i>30-60</i>	<i>T</i>

Example: Learned Tree

- Decision tree learned from these 12 examples:




- Substantially simpler than “true” tree
 - A more complex hypothesis isn't justified by data
- Also: it's reasonable, but wrong

Example: Play Tennis?


Training examples

Day	Outlook	Temp.	Humidity	Wind	Play Tennis
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rain	Mild	High	Weak	Yes
D5	Rain	Cool	Normal	Weak	Yes
D6	Rain	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rain	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rain	Mild	High	Strong	No

Selecting the Next Attribute




$$\begin{aligned}\text{Gain}(S, \text{Humidity}) &= 0.940 - (7/14) * 0.985 \\ &\quad - (7/14) * 0.592 \\ &= 0.151\end{aligned}$$




$$\begin{aligned}\text{Gain}(S, \text{Wind}) &= 0.940 - (8/14) * 0.811 \\ &\quad - (6/14) * 1.0 \\ &= 0.048\end{aligned}$$

Selecting the Next Attribute




$$\begin{aligned} \text{Gain}(S, \text{Outlook}) &= 0.940 - (5/14) * 0.971 \\ &\quad - (4/14) * 0.0 - (5/14) * 0.971 \\ &= 0.247 \end{aligned}$$

ID3 Algorithm



Converting a Tree to Rules



- R_1 : If (Outlook=Sunny) \wedge (Humidity=High) Then PlayTennis=No
 R_2 : If (Outlook=Sunny) \wedge (Humidity=Normal) Then PlayTennis=Yes
 R_3 : If (Outlook=Overcast) Then PlayTennis=Yes
 R_4 : If (Outlook=Rain) \wedge (Wind=Strong) Then PlayTennis=No
 R_5 : If (Outlook=Rain) \wedge (Wind=Weak) Then PlayTennis=Yes


Example: Miles Per Gallon

40 Examples


mpg	cylinders	displacement	horsepower	weight	acceleration	modelyear	maker
good	4	low	low	low	high	75to78	asia
bad	6	medium	medium	medium	medium	70to74	america
bad	4	medium	medium	medium	low	75to78	europa
bad	8	high	high	high	low	70to74	america
bad	6	medium	medium	medium	medium	70to74	america
bad	4	low	medium	low	medium	70to74	asia
bad	4	low	medium	low	low	70to74	asia
bad	8	high	high	high	low	75to78	america
:	:	:	:	:	:	:	:
:	:	:	:	:	:	:	:
:	:	:	:	:	:	:	:
bad	8	high	high	high	low	70to74	america
good	8	high	medium	high	high	79to83	america
bad	8	high	high	high	low	75to78	america
good	4	low	low	low	low	79to83	america
bad	6	medium	medium	medium	high	75to78	america
good	4	medium	low	low	low	79to83	america
good	4	low	low	medium	high	79to83	america
bad	8	high	high	high	low	70to74	america
good	4	low	medium	low	medium	75to78	europa
bad	5	medium	medium	medium	medium	75to78	europa

Find the First Split


- Look at information gain for each attribute
- Note that each attribute is correlated with the target!
- What do we split on?




Result: Decision Stump




Second Level



Final Tree



Final Tree



Information gains using the training set (2 records)

mpg values: bad good

Input	Value	Distribution	Info Gain
cylinders	3		0
	4		
	5		
	6		
	8		
displacement	low		0
	medium		
	high		
horsepower	low		0
	medium		
	high		
weight	low		0
	medium		
	high		
acceleration	low		0
	medium		
	high		
modelyear	70to74		0
	75to78		
	79to83		
maker	america		0
	asia		
	europe		

Reminder: Overfitting

- Overfitting:
 - When you stop modeling the patterns in the training data (which generalize)
 - And start modeling the noise (which doesn't)
- We had this before:
 - Naïve Bayes: needed to smooth
 - Perceptron: early stopping

MPG Training Error

mpg values: bad good

root
22 18
pchance = 0.001

	Num Errors	Set Size	Percent Wrong
Training Set	1	40	2.50
Test Set	74	352	21.02

epower = high

ict bad

horsepower = low

horsepower = medium

horsepower = high

acceleration = low

acceleration = medium

acceleration = high

0

Pr

ad

1

Predict bad

(unexpandable)

Predict bad

Predict good

Predict bad

Predict bad

= 0.717


= 79to83

The test set error is much worse than the training set error...

...why?

Significance of a Split

- Starting with:
 - Three cars with 4 cylinders, from Asia, with medium HP
 - 2 bad MPG
 - 1 good MPG
- What do we expect from a three-way split?
 - Maybe each example in its own subset?
 - Maybe just what we saw in the last slide?
- Probably shouldn't split if the counts are so small they could be due to chance
- A chi-squared test can tell us how likely it is that deviations from a perfect split are due to chance*
- Each split will have a **significance value**, p_{CHANCE}



**The Asterix stands for "You don't need to know the details in this course"*

Keeping it General

■ Pruning:



- Build the full decision tree
- Begin at the bottom of the tree
- Delete splits in which

$$p_{\text{CHANCE}} > \text{Max} p_{\text{CHANCE}}$$

- Continue working upward until there are no more prunable nodes


$$y = a \text{ XOR } b$$

a	b	y
0	0	0
0	1	1
1	0	1
1	1	0



Pruning example

- With $\text{MaxP}_{\text{CHANCE}} = 0.1$:




Note the improved test set accuracy compared with the unpruned tree

	Num Errors	Set Size	Percent Wrong
Training Set	5	40	12.50
Test Set	56	352	15.91




Regularization

- $\text{MaxP}_{\text{CHANCE}}$ is a regularization parameter
- Generally, set it using held-out data (as usual)





A few important points about learning

- Data: labeled instances, e.g. emails marked spam/ham
 - Training set
 - Held out set
 - Test set
- Features: attribute-value pairs which characterize each x
- Experimentation cycle
 - Learn parameters (e.g. model probabilities) on training set
 - (Tune hyperparameters on held-out set)
 - Compute accuracy of test set
 - Very important: never “peek” at the test set!
- Evaluation
 - Accuracy: fraction of instances predicted correctly
- Overfitting and generalization
 - Want a classifier which does well on *test* data
 - Overfitting: fitting the training data very closely, but not generalizing well
 - Underfitting: fits the training set poorly




A few important points about learning

- What should we learn where?
 - Learn parameters from training data
 - Tune hyperparameters on different data
 - Why?
 - For each value of the hyperparameters, train and test on the held-out data
 - Choose the best value and do a final test on the test data
- What are examples of hyperparameters?




Inductive Learning




Inductive Learning (Science)

- Simplest form: learn a function from examples
 - A target function: g
 - Examples: input-output pairs $(x, g(x))$
 - E.g. x is an email and $g(x)$ is spam / ham
 - E.g. x is a house and $g(x)$ is its selling price
- Problem:
 - Given a hypothesis space H
 - Given a training set of examples x_i
 - Find a hypothesis $h(x)$ such that $h \sim g$
- Includes:
 - Classification (outputs = class labels)
 - Regression (outputs = real numbers)
- How do perceptron and naïve Bayes fit in? (H, h, g , etc.)



Inductive Learning

- Curve fitting (regression, function approximation):



- Consistency vs. simplicity
- Ockham's razor

Consistency vs. Simplicity

- Fundamental tradeoff: bias vs. variance
- Usually algorithms prefer consistency by default (why?)
- Several ways to operationalize “simplicity”
 - Reduce the **hypothesis space**
 - Assume more: e.g. independence assumptions, as in naïve Bayes
 - Have fewer, better features / attributes: feature selection
 - Other structural limitations (decision lists vs trees)
 - **Regularization**
 - Smoothing: cautious use of small counts
 - Many other generalization parameters (pruning cutoffs today)
 - Hypothesis space stays big, but harder to get to the outskirts