	DLogo √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √ √	
atechicsel	STUDENT REPORT CENTER OF STUDENT	)
DETA	STUDENT REPORT  SELON TEMPETE CHOCSELON STUDENT REPORT  LEMPETE CHOCSELON TEMPETE CH	TEN
Nan	ne Rekshitha V	en' est
6 VII	Number MR Section On Set Section MR Section Se	
TE	MPBTech-CSE027	, PR
	RIMENT LOVI TEMP BIECH SELOVI	FM
27	ON RAIL  Cription In 18 Test 2 1 1 Temperate of the Security of Temperature of Te	CSEON
ਹੋਂ Th	nere is a ant on your balcony. It wants to leave the rail so sometimes it moves right and sometimes it moves left until it gets chausted. Given an integer array A of size N which consists of integer 1 and -1 only representing ant's moves.	NPBTE
obje M	here 1 means ant moved unit distance towards the right side and -1 means it moved unit distance towards the left .Your task to find and return the integer value representing how many times the ant reaches back to original starting position.	^
	ote:	,£02,
2027	<ul> <li>Assume 1-based indexing</li> <li>Assume that the railing extends infinitely on the either sides</li> </ul>	rech.
	put Format:	b`
	put1 : An integer value N representing the number of moves made by the ant.	
	put2: An integer array A consisting of the ant's moves towards either side	ZIZEN
5 5 1		
1	-11-11	echi ces
, Se	ampie ()utput	
2 Se		, Q. 8
Sou	rce Code: Story Linkers Story Linkers Loston Loston States Company	SEPTI
KEN.	The Code:  The Code of the Cod	CEEN CONTRACTOR
	THREFE TO THE SECON TEMPS TO SECOND TEMPS TO S	AR EW
	TEMPETER STOOT	K PEK

```
def count_returns_to_start(N, A):
    current_position = 0
    return_count = 0

for move in A:
        current_position += move
    if current_position == 0:
        return_count += 1

    return return_count

# Example usage:
N = int(input())
A = list(map(int,input().split())) # Example moves
    result = count_returns_to_start(N, A)
    print(result) # Output: 3

RESULT

Fig. 10

RESULT

S/5 Test Cases Passed | 100 %
```