Deep Learning for Recommender Systems

Jakub Macina
Deep Learning Vienna Meetup
September 24th 2019

EXPONEA

About me - Jakub Macina

@dmacjam

Machine Learning Engineer

Teaching assistant & PeWe research lab member

Open source contributor

Agenda

1. Motivation
2. Traditional Approaches
3. Deep Learning Approaches
4. Case study for Fashion E-commerce
5. Conclusions

Information overload

400+ hours of videos are uploaded every minute

50+ million songs available

Recommendations are everywhere







What is the goal of recommender system?

Help customers find content to **maximize their satisfaction** and **retention**

“Our recommender system is used on most screens of the Netflix product beyond the homepage, and in total **influences choice for about 80% of hours** streamed at Netflix. [...]

NETFLIX

Carlos A Gomez-Uribe and Neil Hunt. 2016. The netflix recommender system: Algorithms, business value, and innovation. ACM Transactions on Management Information Systems (TMIS) 6, 4 (2016), 13.

"35% of what consumers purchase on Amazon come from product recommendations [...]

https://www.mckinsey.com/industries/retail/our-insights/how-retailers-can-keep-up-with-consumers

Everything is a recommendation

- ranking of products
  - recall@N, N < 20
  - mean average precision (MAP)
  - normalized discounted cumulative gain (NDCG)

Exponea Personalization as a Service for 100+ e-commerce businesses

- Customer Data Platform
- Personalization platform - Product recommendations
- Various quality and big diversity of client's data



Typical flow of a customer in e-commerce

Product metadata



II. Traditional **approaches**

Recommendations task

- **Goal:** Provide suggestions to users for items to maximize their satisfaction

- Set of users $U = (u_1, \ldots, u_n)$
- Set of items $I = (i_1, \ldots, i_n)$
- Set of interactions $(u, i, R_{u,i}) \in U \times I \times R^+$

- **Task**: Estimate a utility function that automatically predicts how a user will like an item.

R

The ***ratings matrix***
(n_users x n_items)

1				
0				1
	?		0	
		1		
	1	0		
				1

Challenges

- Extremely large matrix
- Very sparse (0.01% - 1%)
- Cold-start problem

Dataset	**Users**	**Items**	**Matrix density**
Movielens 10M	69 878	10 681	1.340%
Average fashion e-commerce	100K - 50M	1K - 500K	0.012% - 0.155 %

Collaborative filtering - nearest neighbours



Matrix factorization

R

The ***ratings matrix***
(n_users, n_items)

P

The ***user matrix***
(n_users, k)

Q

The ***item matrix***
(n_item, k)



Matrix factorization

$$R_{ui} \approx p_u \cdot q_i$$



$$\text{Minimize } L = (R_{ui} - p_u \cdot q_i)^2 + \lambda\, |Q|^2 + \lambda |P|^2$$

III. Deep learning **approaches**

Framing with Deep learning

- **Matrix factorization extensions**
  - Predicting interaction by feed forward neural network
  - Autoencoders
  - *2vec approaches
- **Next event prediction**
  - Sequence predictions
- **Content-based recommendations**
  - CNNs

Neural matrix factorization



Neural matrix factorization - not big benefit



Justin Basilico, Yves Raimond: GPU Tech Conference, March 28, 2018 in San Jose, CA

Youtube recommendations - DL is useful when adding side features



COVINGTON, Paul; ADAMS, Jay; SARGIN, Emre. Deep neural networks for youtube recommendations. In: Proceedings of the 10th ACM Conference on Recommender Systems. ACM, 2016. p. 191-198.

Youtube recommendations - 1) retrieval part



COVINGTON, Paul; ADAMS, Jay; SARGIN, Emre. Deep neural networks for youtube recommendations. In: Proceedings of the 10th ACM Conference on Recommender Systems. ACM, 2016. p. 191-198.

Youtube recommendations



COVINGTON, Paul; ADAMS, Jay; SARGIN, Emre. Deep neural networks for youtube recommendations. In: Proceedings of the 10th ACM Conference on Recommender Systems. ACM, 2016. p. 191-198.

Youtube recommendations - 2) ranking part



COVINGTON, Paul; ADAMS, Jay; SARGIN, Emre. Deep neural networks for youtube recommendations. In: Proceedings of the 10th ACM Conference on Recommender Systems. ACM, 2016. p. 191-198.

Session-based recommendations - recurrent neural networks (RNN)

- GRU4REC
- Model temporal dependencies
- Predict next item clicked in a session



HIDASI, Balázs, et al. Session-based recommendations with recurrent neural networks. arXiv preprint arXiv:1511.06939, 2015.

Session-based recommendations - hierarchical RNN

Session RNN

- short term preferences

User RNN

- long term preferences



Quadrana, Massimo, et al. "Personalizing session-based recommendations with hierarchical recurrent neural networks." Proceedings of the Eleventh ACM Conference on Recommender Systems. ACM, 2017.

IV. Case study **for fashion e-commerce**

Fashion e-commerce business

- Fashion domain
- Challenges:
  - Fast changing customer intents
  - Most of the customers visits site few times a year
  - Metadata in product catalogs are usually in poor quality
  - Rarely buys the same product twice

Fashion e-commerce domain

- Product detail and homepage
- Challenges:
  - Fast changing customer intents → **no MF, real-time adaptable approach**
  - Most of the customers visits site few times a year → **prefer latest information**
  - Metadata in product catalogs are usually in poor quality → **prefer behavioural data**
  - Rarely buys the same product twice
- **Solution**: Session personalization by prod2vec

GRBOVIC, Mihajlo, et al. E-commerce in your inbox: Product recommendations at scale. In: Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. ACM, 2015. p. 1809-1818.

Co-occurrence modelling

Intent: I would like to buy formal business shirt.

?



Inspiration in the NLP domain

- Extent the idea of Word2vec (Mikolov 2013)
    - “You shall know a word by the company it keeps” (J. R. Firth 1957)
    - unsupervised learning
    - capture similarity between words, analogies, general syntactic and semantic information
    - representing each word as a numeric vector = embedding
        - dense vectors - size is usually from 20 to 300



Inspiration in NLP domain

- neural network trained to reconstruct a word context

Given a sequence of training words $w_1, w_2, \cdots, w_T$, maximize:

$$\frac{1}{T}\sum_{t=1}^{T}\sum_{-c\leq j\leq c, j\neq 0}\log p(w_{t+j} \mid w_t)$$

where c is the size of the training context

$$p(w_O \mid w_I) = \frac{exp(v'^{T}_{w_O} v_{w_I})}{\sum_{w=1}^{W} exp(v'^{T}_{w} v_{w_I})}$$

Mikolov, Tomas, et al. "Distributed representations of words and phrases and their compositionality." Advances in neural information processing systems. 2013.

General idea



Prod2vec training

- Customer product views within a sessions ordered in time



$= 8011 \quad 1239 \quad 2310$

$= 5846 \quad 8743 \quad 9635 \quad 8745$

$= 3324 \quad 9803$

$= 6798 \quad 7129 \quad 5989$

Prod2vec training - Skip-gram model

t - 2 t - 1 t + 1 t + 2

0.1	...	0.3	...	0.6	....	0.4

|P|

Dense (hidden layer)

0	0	...	1	0	...

|P|

t = central product

At each step:

$$\boxed{\underset{\theta}{\operatorname{argmax}} \sum_{(a,c)\in D} \log \frac{1}{1+e^{-v_c \cdot v_a}} + \sum_{(a,c)\in D_r} \log \frac{1}{1+e^{v_c \cdot v_a}}}$$

uses neighbors (context) as **positives**

uses random listings as **negatives**

Prod2vec training - Skip-gram model intuition

Prod2vec training - Skip-gram model intuition

Prod2vec training - Skip-gram model intuition

Prod2vec training - Skip-gram model intuition



Prod2vec training - Skip-gram model intuition



Prod2vec training - Skip-gram model intuition

After training - Calculate similarity between products

0.6	2.1	1.4	0.1	4.2	...	3.3

$|100|$

$$\text{Cosine similarity} = 0.823$$

0.4	1.7	0.7	0.3	5.6	...	2.1

$|100|$

After training - analyse and understand clusters

- PCA

After training - analyse and understand clusters

- PCA



After training - understand dimensions



Product space

- has great properties for real-time personalization and scalable architecture
- ~1M of products



Product space - similar products by k-nearest neighbours

Session:



Results

```
most_similar_terms_images(["372402"], topn=12)
```



Results


Vínové unisex kotníkové tenisky s logem Converse Chuck Taylor All Star Seasonal
Tmavě modré dámské tenisky Converse
Béžové dámské tenisky Vans Peanuts

Results


Černé květované midišaty s odhalenými rameny Dorothy Perkins


Růžovo-černé květované šaty s odhalenými ram
šaty s odhalenými rameny Dorothy
é šaty s odhalenými rameny Mela Lon
né květované midišaty s mašlí Dorothy Perkins
Tmavě modré šaty s výstřihem na zádech Chi Chi London
větší kabelka French Connection Core
Šedé šaty s ozdobným živůtkem Little Mistr
avě modré šaty s tylovou sukní Chi Chi London Nisha
Černé krajkové šaty s výšivkami růží M&Co
Starorůžové šaty na ramínka Chi Chi London Kia

Product space - representation of a customer

Session:



Results



Vínové unisex kotníkové tenisky s logem Converse Chuck Taylor
tričko s potiskem Converse Line
Černá pánská mikina na zip bez kapuce Broadway Neely
Modré pánské tenisky
kožené kotníkové tenisky s banánem
s vložkou Converse Chuck Taylor Lunarlon
Béžové dámské kožené kotníkové tenisky Converse Chuck Taylor
modré dámské tenisky Converse
Tmavě modrá unisex crossbody taška
tenisky s bílou podrážkou Converse Chuck Taylor All Star
Bílé pánské kožené perforované tenisky
kotníkové tenisky Converse Chuck Taylor
Icon Brand Doin´werk
Bílé dámské tričko Vans Tropic Skateful
Bílé unisex kožené kotníkové tenisky s logem
kotníkové tenisky Converse Chuck Taylor
kožené kotníkové tenisky Bullboxer
pánské triko se zeleno-černým potiskem Rip Curl

Product space - directions in the space

Session:



Model tuning

- quality of data - filter out short clicks and have an open feedback loop
- negative sampling - random sampling by default - use products from the same category
- customers who viewed this then bought



GRBOVIC, Mihajlo; CHENG, Haibin. Real-time Personalization using Embeddings for Search Ranking at Airbnb. In: Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining. ACM, 2018. p. 311-320.

Comparison with matrix factorization

TABLE 2: A COMPARISON BETWEEN SVD AND ITEM2VEC ON GENRE CLASSIFICATION TASK FOR VARIOUS SIZES OF TOP POPULAR ARTIST SETS

Top (q) popular artists	**SVD accuracy**	**item2vec accuracy**
2.5k	85%	**86.4%**
5k	83.4%	**84.2%**
10k	80.2%	**82%**
15k	76.8%	**79.5%**
20k	73.8%	**77.9%**
10k unpopular (see text)	58.4%	**68%**

BARKAN, Oren; KOENIGSTEIN, Noam. Item2vec: neural item embedding for collaborative filtering. In: Machine Learning for Signal Processing (MLSP), 2016 IEEE 26th International Workshop on. IEEE, 2016. p. 1-6.

Conclusions

1. Recommendations engines are instruments of e-commerce business
2. Lots of applications and open research questions
3. Deep learning is helping when leveraging additional data
4. Word2vec is actually a recommender engine

If interested, **talk to us or visit us in Bratislava office**

JAKUB MACINA
Machine Learning Engineer

jakub.macina@exponea.com
+421 910 926 484

www.exponea.com

EXPONEA

Resources

- Balász Hidasi. Deep Learning for Recommender Systems. RecSys summer school 2017
- https://multithreaded.stitchfix.com/blog/2018/06/28/latent-style/

Inspiration in NLP domain





Mikolov, Tomas, et al. "Distributed representations of words and phrases and their compositionality." Advances in neural information processing systems. 2013.

Prod2vec

- represent each product as a dense numeric vector
- products in similar contexts to have similar vectors

-0.6	0.1	0.3	0.6	-0.3	...	0.7

$|100|$

GRBOVIC, Mihajlo, et al. E-commerce in your inbox: Product recommendations at scale. In: Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. ACM, 2015. p. 1809-1818.

End-to-End solution

Google Cloud

Data Preprocessing → Training → Serving

kafka
Google BigQuery
jupyter
TensorFlow
Google Kubernetes Engine

Product space - new product

- cold start problem - find similar by metadata



Other challenges

- help customers find what they want when they’re not sure what they want
- biased data by existing recommender
- context dependent content
- cold start problems
- diversity, novelty, freshness