

# Module 3 Day 2

CSS: Selectors and The Box Model

PO #

ITEM #

DESCRIPTION

# Module 3 Day 2

## Can You ... / Do You ... ?

- Utilize the following selectors to apply CSS styles:
  - element
  - id
  - class
  - universal
  - attribute
  - pseudo (hover, focus)
  - descendant combinator
- Understand and utilize selector specificity and cascading to apply styles
- Describe the box model (padding, margin, border)
- Understand and demonstrate the use of `block`, `inline` and `inline-block`
- Understand the effect of "normal flow" on the positioning of elements on a page
- Describe and use the different positioning styles: `static`, `fixed`, `absolute`, and `relative`
- Understand the difference between common units of measure (px, %, rem) and be able to choose an appropriate unit for CSS styles

# CSS: Cascading Style Sheets

- CSS allows us to define how an element appears on a website through the use of style rules.
- These rules can control everything from colors and fonts, to positioning and behavior.
- For the purposes of layout and design, every element is thought of as a box, and a style rule is meant to format that box (and its contents).

# CSS: Using Stylesheets

## Internally:

CSS can be used by declaring a `<style>...rules...</style>` element within the `<head></head>`

## Externally:

CSS files are linked, related, to a webpage (HTML) using the `<link/>` element within the `<head></head>`. Link elements should have three attributes:

`href` = "*path\_to\_the\_stylesheet.css*"

`rel` = "stylesheet"

`type` = "text/css"

# CSS: The Box Model

When you look at a website, learn to “see” every element as a box.

This box surrounds both **BLOCK** level and **IN-LINE** level elements.

The box has four (4) parts:

Margin - Outside Edge

Border - Outline

Padding - Surrounds Content

Content - Inner HTML & Text



## Block:

(Start on a new line)

<div>

<h1-6>

<p>

## In-line:

(Flow with text)

<span>

<b> & <i>

<img>

# CSS: Application of Style Rules

## **Boxes:**

Background - Color and Image

Border - Width, Style ( Solid, Dashes, Dots), Color  
Position

## **Text:**

Font ( Typeface)

Color

Size

Format ( Bold, Italic, Upper\Lower Case)

## **Special Element-Specific Styling Attributes Exist For:**

Forms

Lists

Tables

# CSS: Anatomy of a Style Rule

Style rules have four parts:

**Selector**

**Declaration**

**Properties**

**Values**

**div**

**{** border-style: solid; border-width: 2px; **}**

**{** **border-style:** solid; **border-width:** 2px; **}**

**{** border-style: **solid**; border-width: **2px**; **}**

---

**div** **{** border-style: **solid**; border-width: **2px**; **}**

# CSS: Selectors - The Basics

- Universal:       \* {}                   Targets all elements on a page
- Element:        h1 {}               Targets all *h1* elements on a page
- ID:             #userphone {}       Targets the element whose ID="userphone"
- Class:          .info  
                  div.info           Targets any element with a class attribute with a value "info"  
                                     Targets only *div* elements with a class attribute value "info"
- Descendent:     div ul {}           Targets any *ul* elements inside a *div* element **regardless** of other elements in the *div*
- Child:          li>a {}           Targets any *a* element that is the **direct child** of an *li* element
- Siblings:
  - Adjacent:     h1+p {}           Targets the next *p* element after an *h1* element under the same Parent element
  - General:      h1~p {}           Targets all *p* elements that are siblings of an *h1* without regard to its position



# CSS: Selectors - Beyond The Basics

- Attributes

- Existence: `h1[class]` Targets all h1 tags with a class attribute
- Equality `h1[class="note"]` Targets all h1 tags with a class attribute value equal to "note"
- Space `h1[class~="note"]` Targets all h1 tags with space delimited attributes in which one value is equal to "note"
- Prefix `div[attr^n]` Targets all div tags with an attribute value beginning with "n"
- Substring `div[attr*ot]` Targets all div tags with attribute values containing the letters "ot"
- Suffix `div[attr$e]` Targets all div tags with an attribute value ending in "e"

- Pseudo

- `:hover` `input[type="text"]:hover` Applies when the cursor or pointer is over an element
- `:focus` `input[type="text"]:focus` Applies when an element has the focus (is ready for and the focus of user interaction)
- `:active` `input[type="text"]:active` Applies when a user is interacting with the element