

IDU REST (v1)

Download OpenAPI specification: [Download](#)

Overview

LexisNexis® IDU® offers a flexible approach to identity management, helping you confirm identities online, comply with anti-money laundering requirements and protect your business from the threat of fraud.

The IDU (REST) API suite of services allow you to screen individuals against a bespoke scorecard tailored to your risk appetite - helping to verify and authenticate recognised identity documents and identify potential risks.

IDU has a variety of use-cases including AML compliance, fraud prevention and customer due diligence.

Authentication

Requests to the IDU (REST) API must be accompanied by a valid bearer token acquired via the SSO API.

Generate bearer token

REQUEST BODY SCHEMA: application/json		
client_id required	string	
client_secret required	string	

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 422 Validation error

POST /oauth/token

Request samples

Payload

Content type
application/json

Copy

```
{
  "client_id": "941059b8-d2d2-45be-b0ea-736bbac30c34",
  "client_secret": "i8dJQESmz7kqKuRFnyY9k2fBQIeDZ3GXlqphs04P"
}
```

Response samples

200

401

422

Content type

application/json

Copy

```
{
  "token_type": "Bearer",
  "expires_in": 1800,
  "access_token": "string"
}
```

Address lookup

Look up an address by using a full address, partial address or just a postcode.

Search addresses

The IDU address lookup service can be used to find one or more addresses matching the search criteria.

AUTHORIZATIONS: > *Production or Sandbox*

REQUEST BODY SCHEMA: application/json

Any of	Address lines	Full address	Postcode only
house	string <= 64 characters	House/flat name or number	
street	string <= 64 characters	Street name	
town	string <= 64 characters	Town/city name	
postcode	string <= 8 characters	Postcode	

Responses

> 200 Ok

> **401** Unauthorized response

> **403** Forbidden

> **422** Validation error

POST /address-lookup

Request samples

Payload

Content type

application/json

Example

Address lines

Copy

```
{
  "house": "200",
  "street": "JULIUS ROAD",
  "town": "BRISTOL",
  "postcode": "BS7 8EU"
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": [
    + { ... }
  ]
}
```

Reports

In IDU you can create a report on an individual to validate, verify and authenticate data that has been supplied. A report can be built up by adding one report action at a time or by running multiple report actions initially.

An example of a [report action](#) is address verification which verifies if there is evidence of the individual living at the current address they have provided.

For simplicity, IDU allows you to save a configuration of commonly used report actions as a [report type](#). For example, you may wish to save a configuration called "AML" (Anti-Money Laundering) as a report type which will run a specific collection of services. When you pass this report type into IDU, it will run all the services stored against that report type. You are able to run additional report actions after the AML report type has run.

For full flexibility, IDU allows you to simply specific the report actions you wish to run individually on the request if you so wish.

Finally, IDU allows you to set thresholds for an overall pass, refer or fail by utilising [scorecards](#).

Create a report

Create a report on an individual.

AUTHORIZATIONS: > *Production or Sandbox*

REQUEST BODY SCHEMA: application/json

One of	Search with report type	Search with inline config
report_type_id	string <uuid> required ID of the report type	
forename	string <= 64 characters required Subject forename	
middlename	string <= 64 characters Subject middle name(s)	
surname	string <= 64 characters required Subject surname	
dob	string <date> Subject date of birth	
address >	object To ensure accurate matching we recommended using the <code>address-lookup</code> service to retrieve a correctly formatted address	
reference	string <= 255 characters Custom reference field. Report collections can also be filtered by this reference. Report types may require a reference to be provided.	
enduser_agreement	boolean required Provide confirmation that the end-user has agreed for the identity check to be performed. Declining the agreement will restrict some actions and datasets.	
scorecard_id	string Specify a scorecard that will be used to score this report.	
test	boolean Tag a report as a test. Reports which have been tagged as "test" can be excluded from reporting and will not be subject to the usual retention policy.	

Responses

- > 201 Created
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

✓

Payload

```
application/json
```

Search with report type

Copy Expand all Collapse all

```
{
  - "data": {
      "id": "5516dc1b-1db6-475b-935c-3f80c5d93724",
      "created_at": "2021-08-10T08:32:28Z",
      "updated_at": "2021-08-10T08:32:28Z",
      "status": "COMPLETE",
      + "user": { ... },
      + "context": { ... },
      + "annotations": [ ... ],
      + "assessment": { ... },
      + "attributes": { ... },
      + "address_insights": { ... },
      + "address_verification": { ... },
      + "age_verification": { ... },
      + "bank_account_validation": { ... },
      + "bank account verification": { ... },
  }
}
```

201

401

403

422

```
application/json
```

Copy Expand all Collapse all

```
{
  - "data": {
      "id": "5516dc1b-1db6-475b-935c-3f80c5d93724",
      "created_at": "2021-08-10T08:32:28Z",
      "updated_at": "2021-08-10T08:32:28Z",
      "status": "COMPLETE",
      + "user": { ... },
      + "context": { ... },
      + "annotations": [ ... ],
      + "assessment": { ... },
      + "attributes": { ... },
      + "address_insights": { ... },
      + "address_verification": { ... },
      + "age_verification": { ... },
      + "bank_account_validation": { ... },
      + "bank account verification": { ... },
    }
  }
}
```

```

+ "ccj_screening": { ... },
+ "company_officer_screening": { ... },
+ "credit_active": { ... },
+ "death_screening": { ... },
+ "dob_verification": { ... },
+ "driving_licence_validation": { ... },
+ "email_risk": { ... },
+ "insolvency_screening": { ... },
+ "lexid_match": { ... },
+ "nfi_amberhill": { ... },
+ "ni_number_validation": { ... },
+ "otp_email": { ... },
+ "otp_sms": { ... },
+ "passport_validation": { ... },
+ "pep_screening": { ... },
+ "phone_match": { ... },
+ "prs_verification": { ... },
+ "remote_check": { ... },
+ "sanction_screening": { ... }
}
}

```

Retrieve report collection

A paginated collection of report summaries. Results can be filtered by a variety of factors using the query parameters below.

[AUTHORIZATIONS:](#) >

Production or Sandbox

QUERY PARAMETERS

date_from	string <date-time> Example: <code>date_from=2021-08-10T08:32:28Z</code> Filter results starting from (and including) the provided date
date_to	string <date-time> Example: <code>date_to=2021-08-10T08:32:28Z</code> Filter results up until (and including) the provided date
dob	string <date> <code><= 10 characters</code> Example: <code>dob=1985-07-17</code> Filter results by date of birth
forename	string <code><= 64 characters</code> Example: <code>forename=BELLA</code> Filter results by forename (includes partial matches)
page	integer <code>>= 1</code> Example: <code>page=2</code> Select which page of results to return
per_page	integer <code>[1 .. 100]</code> Example: <code>per_page=10</code> Set how many results to return per page
postcode	string Example: <code>postcode=BS7 8EU</code> Filter results by postcode
reference	string <code><= 255 characters</code> Example: <code>reference=1w1ref-4ffef-222</code> Filter results by reference (includes partial matches)

status

string

Enum: "STARTED" "PENDING" "COMPLETE"

Example: status=PENDING

Filter results by status

surname

string <= 64 characters

Example: surname=HENDERSON

Filter results by surname (includes partial matches)

uklexid

integer <int64>

Example: uklexid=12345678912

Filter results by uklexid

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 422 Validation error

GET /reports

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": [
    + { ... }
  ],
  - "links": {
    "first": "https://example.com/v1/users?page=1",
    "last": "https://example.com/v1/users?page=20",
    "prev": "https://example.com/v1/users?page=1",
    "next": "https://example.com/v1/users?page=2"
  },
  - "meta": {
    "current_page": 1,
    "last_page": 1,
    "from": 21,
    "to": 101,
    "per_page": 10,
    "total": 1000,
    "path": "https://example.com/v1/users",
    + "links": [ ... ]
  }
}
```

Retrieve a report

Retrieve a single report by ID.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId string <uuid>
required ID of the report

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found

GET /reports/{reportId}

Response samples

200 401 403 404

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "id": "5516dc1b-1db6-475b-935c-3f80c5d93724",
    "created_at": "2021-08-10T08:32:28Z",
    "updated_at": "2021-08-10T08:32:28Z",
    "status": "COMPLETE",
    "user": { ... },
    "context": { ... },
    "annotations": [ ... ],
    "assessment": { ... },
    "attributes": { ... },
    "address_insights": { ... },
    "address_verification": { ... },
    "age_verification": { ... },
    "bank_account_validation": { ... },
```

```
+ "bank_account_verification": { ... },
+ "ccj_screening": { ... },
+ "company_officer_screening": { ... },
+ "credit_active": { ... },
+ "death_screening": { ... },
+ "dob_verification": { ... },
+ "driving_licence_validation": { ... },
+ "email_risk": { ... },
+ "insolvency_screening": { ... },
+ "lexid_match": { ... },
+ "nfi_amberhill": { ... },
+ "ni_number_validation": { ... },
+ "otp_email": { ... },
+ "otp_sms": { ... },
+ "passport_validation": { ... },
+ "pep_screening": { ... },
+ "phone_match": { ... },
+ "prs_verification": { ... },
+ "remote_check": { ... },
+ "sanction_screening": { ... }
}
}
```

Delete a report

Reports that are no longer used can be deleted.

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

→ reportId
required

string <uuid>
ID of the report

Responses

— **204** Deleted

> **401** Unauthorized response

> **403** Forbidden

> **404** Not found

DELETE /reports/{reportId}

Response samples

401

403

404

Content type
application/json

Retrieve report audit logs

Retrieve a list of audit events for a specific report

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

- reportId required

string <uuid>
ID of the report

Responses

> 200 Ok

➤ **401** Unauthorized response

➤ 403 Forbidden

> **404** Not found

GET /reports/{reportId}/audit

Response samples

200

Content type	application/json
--------------	------------------

Copy

Expand all

[Collapse all](#)

Retrieve report input

Returns all input data associated with the report. Please note that some sensitive information may be redacted.

AUTHORIZATIONS: >	Production or Sandbox
PATH PARAMETERS	
reportId required	string <uuid> ID of the report

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found

GET /reports/{reportId}/input-data

Response samples

- 200
- 401
- 403
- 404

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "data": {
    "reference": "string",
    "forename": "string",
    "middlename": "string",
    "surname": "string",
    "gender": "string",
    "dob": "string",
    "address": { ... },
    "bank_details": { ... },
    "emails": [ ... ],
    "driving_licence_number": "string",
    "ni_number": "string",
    "nhs_number": "string",
    "id_card_number": "string",
    "travel_visa_number": "string",
    "passport": { ... },
    "phone_code": "+44",
    "phone_number": "07123456789",
    "email": "john.doe@example.com"
  }
}
```

Report actions

Add a report action to a report, such as address verification or mortality screening.

Address insights

Address insights provides information on addresses linked to the search subject.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId required	string <uuid> ID of the report
----------------------	-----------------------------------

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address
dob	string <date> Subject date of birth

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/address-insights

Request samples

Payload

Content type

application/json

{

"forename": "Bella"

```
    "forename": "BELLA",
    "middlename": "PATRICIA",
    "surname": "HENDERSON",
    - "address": {
      "address1": "204 JULIUS ROAD",
      "address2": "",
      "address3": "",
      "address4": "",
      "address5": "",
      "postcode": "BS7 8EU"
    },
    "dob": "1985-07-17"
  }
}
```

Response samples

200

401

403

422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    + "address_insights": { ... }
  }
}
```

Address verification

Verifies if the search subject has an association to the address provided.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the <code>address-lookup</code> service to retrieve a correctly formatted address
dob	string <date> Subject date of birth
config >	object

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/address-verification

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "dob": "1985-07-17",
  "config": {
    "full_er": true,
    "nfi_address": true
  }
}
```

Response samples

- 200
- 401
- 403
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "address_verification": { ... }
  }
}
```

Age verification

Verifies the age of the subject.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId required string <uuid>
ID of the report

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the <code>address-lookup</code> service to retrieve a correctly formatted address
dob	string <date> Subject date of birth
config >	object List of settings to override the default configuration for each report

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/age-verification

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  - "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "dob": "1985-07-17",
  - "config": {
    "age_min": 18,
    "age_max": 75
  }
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": {
    + "age_verification": { ... }
  }
}
```

Bank account validation

Validates the given bank details belong to the search subject.

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

→ reportId
required

string <uuid>
ID of the report

REQUEST BODY SCHEMA: application/json

→ bank_details >
required

object

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/bank-account-validation

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "bank_details": {
    "sort_code": "010101",
    "account_number": "11111111"
  }
}
```

Response samples

- 200
- 401
- 403
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    + "bank_account_validation": { ... }
  }
}
```

Bank account verification

Verifies the given bank details belong to the search subject.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId	string <uuid>
required	ID of the report

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address
dob	string <date> Subject date of birth
bank_details > required	object

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/bank-account-verification

Request samples

Payload

Content type
application/json

CopyExpand allCollapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "dob": "1985-07-17",
  "bank_details": {
    "sort_code": "010101",
    "account_number": "11111111"
  }
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": {
    + "bank_account_verification": { ... }
  }
}
```

CCJ screening

Screens the subject for any county court judgements from within the last 6 years.

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

reportId
required

string <uuid>
ID of the report

REQUEST BODY SCHEMA: application/json

One of

Person with address

Person with DOB

forename
required

string <= 64 characters
Subject forename

middlename

string <= 64 characters
Subject middle name(s)

surname
required

string <= 64 characters
Subject surname

address >
required

object
To ensure accurate matching we recommended using the `address-lookup` service to retrieve a correctly formatted address

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 422 Validation error

POST /reports/{reportId}/actions/ccj-screening

Request samples

Payload

Content type

application/json

Example

Person with address

Copy

Expand all

Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  }
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "data": {
    "ccj_screening": { ... }
  }
}
```

Company officer screening

Searches against company and directorship data to provide information on current and historic appointments.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId

required

string <uuid>

ID of the report

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address
dob	string <date> Subject date of birth

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST

/reports/{reportId}/actions/company-officer-screening

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "dob": "1985-07-17"
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "data": {
    "company_officer_screening": { ... }
  }
}
```

Credit active

Search across multiple credit bureaus to provide information on the subject's credit activity.

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

reportId	string <uuid>
required	ID of the report

REQUEST BODY SCHEMA: application/json

forename	string <= 64 characters
required	Subject forename
middleware	string <= 64 characters
	Subject middle name(s)
surname	string <= 64 characters
required	Subject surname
address >	object
required	To ensure accurate matching we recommended using the <code>address-lookup</code> service to retrieve a correctly formatted address
dob	string <date>
required	Subject date of birth

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 422 Validation error

POST /reports/{reportId}/actions/credit-active



Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "dob": "1985-07-17"
}
```

Response samples

- 200
- 401
- 403
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "credit_active": { ... }
  }
}
```

Mortality screening

Screen the search subject against death records from multiple sources.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId	string <uuid>
required	ID of the report

REQUEST BODY SCHEMA: application/json

One of Person with address Person with DOB

forename	string <= 64 characters
required	Subject forename
middlename	string <= 64 characters
	Subject middle name(s)

surname > required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/death-screening

Request samples

Payload

Content type
application/json

Example
Person with address

Copy Expand all Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  }
}
```

Response samples

200 401 403 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "death_screening": { ... }
  }
}
```

```
}  
}  
}
```

DOB verification

Verify the subject's DOB against multiple sources.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId required	string <uuid> ID of the report
----------------------	-----------------------------------

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address
dob required	string <date> Subject date of birth

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/dob-verification

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

{

```
"forename": "BELLA",
"middlename": "PATRICIA",
"surname": "HENDERSON",
- "address": {
  "address1": "204 JULIUS ROAD",
  "address2": "",
  "address3": "",
  "address4": "",
  "address5": "",
  "postcode": "BS7 8EU"
},
"dob": "1985-07-17"
}
```

Response samples

- 200
- 401
- 403
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
- "data": {
  + "dob_verification": { ... }
}
}
```

Driving licence validation

Driving licence validation in IDU checks the algorithmic logic of a UK driving licence number against the provided personal details to confirm its validity and prevent fraud.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
dob required	string <date> Subject date of birth
gender	string The gender of the person
driving_licence_number required	string [16 .. 18] characters Driving licence number

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/driving-licence-validation

Request samples

Payload

Content type

application/json

Copy

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "dob": "1985-07-17",
  "gender": "F",
  "driving_licence_number": "HENDE857175BP9AB"
}
```

Response samples

200 401 403 422

Content type

application/json

Copy Expand all Collapse all

```
{
  "data": {
    "driving_licence_validation": { ... }
  }
}
```

Email risk assessment

Provides a risk assessment of one or more email addresses and information relating to linked cases of fraud.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId string <uuid>

required	ID of the report
REQUEST BODY SCHEMA: application/json	
forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
emails > required	Array of objects <= 5

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/email-risk

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "emails": [
    + { ... }
  ]
}
```

Response samples

- 200
- 401
- 403
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    + "email_risk": { ... }
  }
}
```

Insolvency screening

Screens the subject for any insolvencies from within the last 6 years.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

One of Person with address Person with DOB

forename	string <= 64 characters
required	Subject forename
middlename	string <= 64 characters
	Subject middle name(s)
surname	string <= 64 characters
required	Subject surname
address >	object
required	To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST

/reports/{reportId}/actions/insolvency-screening

Request samples

Payload

Content type

application/json

Example

Person with address

Copy Expand all Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  - "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  }
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": {
    + "insolvency_screening": { ... }
  }
}
```

Lexid match

Matches to a unique LexId for the subject

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

→ reportId
required string <uuid>
ID of the report

REQUEST BODY SCHEMA: application/json

→ forename required	string <= 64 characters Subject forename
→ middlename	string <= 64 characters Subject middle name(s)
→ surname required	string <= 64 characters Subject surname
→ address > required	object To ensure accurate matching we recommended using the <code>address-lookup</code> service to retrieve a correctly formatted address
→ dob	string <date> Subject date of birth

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/lexid-match

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "dob": "1985-07-17"
}
```

Response samples

200 401 403 422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "data": {
    + "lexid_match": { ... }
  }
}
```

Search the National Fraud Initiative's Amberhill database for reported fraudulent use of a document, such as a driving licence, associated with the data subject.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

Any of **Driving licence** ID card NHS number NI number Passport Travel visa

forename string <= 64 characters
required Subject forename

middlename string <= 64 characters
Subject middle name(s)

surname string <= 64 characters
required Subject surname

dob string <date>
required Subject date of birth

driving_licence_number string [16 .. 18] characters
required Driving licence number

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 422 Validation error

POST /reports/{reportId}/actions/nfi-amberhill

Request samples

Payload

Content type
application/json

Example
Driving licence

Copy

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "dob": "1985-07-17",
```

```
"driving_licence_number": "HENDE857175BP9AB"
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": {
    + "nfi_amberhill": { ... }
  }
}
```

NI number validation

Validates a NI number

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

→ reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

→ ni_number string <= 255 characters
required National Insurance number

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 422 Validation error

POST /reports/{reportId}/actions/ni-number-validation

Request samples

Payload

Content type

application/json

Copy

```
{
  "ni_number": "AB 12 34 56 A"
}
```

Response samples

200

401

403

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": {
    + "ni_number_validation": { ... }
  }
}
```

OTP email

Sends a OTP code to the email address provided.

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

→ reportId
required

string <uuid>
ID of the report

REQUEST BODY SCHEMA: application/json

→ email
required

string <email>

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 422 Validation error

> 429 Too many requests

POST /reports/{reportId}/actions/otp-email



Request samples

Payload

Content type
application/json

Copy

```
{
  "email": "test@example.com"
}
```

Response samples

- 200
- 401
- 403
- 422
- 429

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    + "otp_email": { ... }
  }
}
```

OTP email verification

Verifies the OTP code sent to the email address provided.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

code string = 6 characters ^\d{6}\$
required

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 422 Validation error

POST /reports/{reportId}/actions/otp-email-verification



Request samples

Payload

Content type
application/json

Copy

```
{
  "code": "123456"
}
```

Response samples

200

401

403

422

Content type
application/json

Copy

Expand all

Collapse all

```
{
  - "data": {
    + "otp_email": { ... }
  }
}
```

OTP SMS

Sends an OTP code to the phone number provided.

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

reportId
required string <uuid>
ID of the report

REQUEST BODY SCHEMA: application/json

phone_code
required string [2 .. 4] characters ^\+[1-9]\d{0,2}\$
Country calling code in plus-prefixed international format

phone_number
required string [10 .. 13] characters ^\d{10,13}\$
Phone number using digits only

Responses

> 200 Ok

> 401 Unauthorized response

> **403** Forbidden

> **422** Validation error

> **429** Too many requests

POST /reports/{reportId}/actions/otp-sms

Request samples

Payload

Content type
application/json

Copy

```
{
  "phone_code": "+44",
  "phone_number": "07123456789"
}
```

Response samples

200

401

403

422

429

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    + "otp_sms": { ... }
  }
}
```

OTP sms verification

Verifies the OTP code sent to the mobile number provided.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

code string = 6 characters ^\d{6}\$
required

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/otp-sms-verification

Request samples

Payload

Content type
application/json

Copy

```
{  
  "code": "123456"  
}
```

Response samples

200

401

403

422

Content type
application/json

Copy

Expand all

Collapse all

```
{  
  "data": {  
    + "otp_email": { ... }  
  }  
}
```

Passport validation

Checks that a passport number is valid, not expired, and corresponds to the subject's date of birth and gender.

AUTHORIZATIONS:	>	Production or Sandbox
PATH PARAMETERS		
reportId	string <uuid>	
required	ID of the report	
REQUEST BODY SCHEMA: application/json		
passport	>	object

required	Passport number
dob	string <date> Subject date of birth
gender	string Enum: "M" "F" "<" The passport holder's gender

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/passport-validation

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  - "passport": {
    + "mrz_line2": { ... }
  },
  "dob": "1985-07-17",
  "gender": "M"
}
```

Response samples

200 401 403 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    + "passport_validation": { ... }
  }
}
```

PEP screening

Screens the subject against an international list of politically exposed persons.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId required	string <uuid> ID of the report
----------------------	-----------------------------------

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
dob	string <date> Subject date of birth
config >	object List of settings to override the default configuration for each report

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/pep-screening

Request samples

Payload

Content type
application/json

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "dob": "1985-07-17",
  "config": {
    "pep_threshold": 85
  }
}
```

Copy Expand all Collapse all

```
}
}
```

Response samples

- 200
- 401
- 403
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    + "pep_screening": { ... }
  }
}
```

Phone match

Provides all mobile and landline numbers linked to a given subject.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId
required string <uuid>
ID of the report

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address
phone_code	string [2 .. 4] characters ^\+[1-9]\d{0,2}\$ Country calling code in plus-prefixed international format
phone_number	string [10 .. 13] characters ^\d{10,13}\$ Phone number using digits only

Responses

- > 200 Ok
- > 401 Unauthorized response

> **403** Forbidden

> **422** Validation error

POST /reports/{reportId}/actions/phone-match

Request samples

Payload

Content type
application/json

CopyExpand allCollapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "phone_code": "+44",
  "phone_number": "07123456789"
}
```

Response samples

200

401

403

422

Content type
application/json

CopyExpand allCollapse all

```
{
  "data": {
    "phone_match": { ... }
  }
}
```

Phone number validation

Intelligence screening on the phone number provided

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

reportId	string <uuid>
required	ID of the report

REQUEST BODY SCHEMA: application/json

phone_code	string [2 .. 4] characters ^\+[1-9]\d{0,2}\$
required	Country calling code in plus-prefixed international format
phone_number	string [10 .. 13] characters ^\d{10,13}\$
required	Phone number using digits only

Responses

- > 201 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/phone-number-validation

Request samples

Payload

Content type
application/json

```
{
  "phone_code": "+44",
  "phone_number": "07123456789"
}
```

Copy

Response samples

201 401 403 422

Content type
application/json

```
{
  "data": {
    "phone_number_validation": { ... }
  }
}
```

Copy Expand all Collapse all

Verify property ownership for a given person.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId string <uuid>
required ID of the report

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
address > required	object To ensure accurate matching we recommended using the address-lookup service to retrieve a correctly formatted address

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /reports/{reportId}/actions/prs-verification

Request samples

Payload

Content type
application/json

Copy

Expand all

Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  }
}
```

Response samples

- 200
- 401
- 403
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "prs_verification": { ... }
  }
}
```

Remote check

Perform a remote check on an individual.

Optionally provide an `emails` array to have the invite link automatically sent to the specified email addresses.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId	string <uuid>
required	ID of the report

REQUEST BODY SCHEMA: application/json

forename	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname	string <= 64 characters Subject surname
address >	object To ensure accurate matching we recommended using the <code>address-lookup</code> service to retrieve a correctly formatted address
phone_code	string [2 .. 4] characters ^\+[1-9]\d{0,2}\$ Country calling code in plus-prefixed international format
phone_number	string [10 .. 13] characters ^\d{10,13}\$ Phone number using digits only
emails >	Array of objects <= 5
config >	object List of settings to override the default configuration for each report

Responses

> **200** Ok

> **401** Unauthorized response

> **403** Forbidden

> **422** Validation error

POST /reports/{reportId}/actions/remote-check



Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "forename": "BELLA",
  "middlename": "PATRICIA",
  "surname": "HENDERSON",
  - "address": {
    "address1": "204 JULIUS ROAD",
    "address2": "",
    "address3": "",
    "address4": "",
    "address5": "",
    "postcode": "BS7 8EU"
  },
  "phone_code": "+44",
  "phone_number": "07123456789",
  - "emails": [
    + { ... }
  ],
  - "config": {
    "flow_type": "doc_only"
  }
}
```

Response samples

200

401

403

422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    + "remote_check": [ ... ]
  }
}
```

Sanctioned entity screening

Screens the subject against an international list of sanctioned entities.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId required	string <uuid> ID of the report
----------------------	-----------------------------------

REQUEST BODY SCHEMA: application/json

forename required	string <= 64 characters Subject forename
middlename	string <= 64 characters Subject middle name(s)
surname required	string <= 64 characters Subject surname
dob	string <date> Subject date of birth
config >	object List of settings to override the default configuration for each report

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST

/reports/{reportId}/actions/sanction-screening

Request samples

Payload

Content type

application/json

CopyExpand allCollapse all

{
 "forename": "BELLA",
 "middlename": "PATRICIA",
 "surname": "HENDERSON",
 "dob": "1985-07-17",

```
- "config": {  
  "sanction_threshold": 85  
}
```

Response samples

200

401

403

422

Content type
application/json

Copy Expand all Collapse all

```
{  
  - "data": {  
    + "sanction_screening": { ... }  
  }  
}
```

Report types

Save a commonly used configuration (for example AML, KYC) as a report type, removing the need to specify these report actions on every request call.

Create a report type

AUTHORIZATIONS: > *Production or Sandbox*

REQUEST BODY SCHEMA: application/json

name required	string <= 255 characters Name of the report type. Must be unique per user account.
description	string <= 512 characters Optional description
scorecard_id >	string or null
age_min >	integer or null [18 .. 114] Minimum age threshold used by age verification
age_max >	integer or null [18 .. 114] Maximum age threshold used by age verification
reference_required	boolean Whether the reference is required when creating a report
primary_actions	Array of strings (ReportActionName) Defines report actions to be performed when a new report is created. You can see a full list of report actions in the appendix.
secondary_actions	Array of strings (ReportActionName) Defines report actions to be shown as follow-up actions when a new report is created. You can

Responses

- > 201 Created
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

POST /report-types

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "name": "AML",
  "description": "Anti-money laundering report",
  "scorecard_id": "a3f779f1-f22d-4608-bc09-74d2f9a48bc8",
  "age_min": 18,
  "age_max": 75,
  "reference_required": true,
  "primary_actions": [
    "lexid-match"
  ],
  "secondary_actions": [
    "lexid-match"
  ]
}
```

Response samples

201 401 403 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "id": "7a9ee450-6a8e-4174-a1bf-80e0fb7b2112",
    "name": "AML",
    "description": "Anti-money laundering report",
    "username": "Username01",
    "scorecard_id": "a3f779f1-f22d-4608-bc09-74d2f9a48bc8",
    "scorecard": { ... },
    "age_min": 18,
    "age_max": 75
  }
}
```

```
    "age_max": 75,  
    "reference_required": true,  
+   "primary_actions": [ ... ],  
+   "secondary_actions": [ ... ],  
    "created_at": "2021-08-10T08:32:28Z",  
    "updated_at": "2021-08-10T08:32:28Z",  
    "is_default": false,  
    "category": "CUSTOM"  
  }  
}
```

Retrieve report type collection

AUTHORIZATIONS: >

Production or Sandbox

QUERY PARAMETERS

username	string Example: <code>username=myUsername</code> Filter by IDU username
per_page	integer Example: <code>per_page=10</code> Set how many results to return per page
page	integer Example: <code>page=2</code> Select which page of results to return
order	string Enum: <code>"asc"</code> <code>"desc"</code> Example: <code>order=desc</code> Sort order (asc or desc)
order_by	string Example: <code>order_by=created_at</code> Sort by a specific field

Responses

> 200 Ok

- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

GET /report-types

▼

Response samples

- 200
- 401
- 403
- 422

Content type

application/json

Copy Expand all Collapse all

```
{
  - "data": [
    + { ... }
  ],
  - "links": {
    "first": "https://example.com/v1/users?page=1",
    "last": "https://example.com/v1/users?page=20",
    "prev": "https://example.com/v1/users?page=1",
    "next": "https://example.com/v1/users?page=2"
  },
  - "meta": {
    "current_page": 1,
    "last_page": 1,
    "from": 21,
    "to": 101,
    "per_page": 10,
    "total": 1000,
    "path": "https://example.com/v1/users",
    + "links": [ ... ]
  }
}
```

Retrieve a report type

Retrieve a single report type by ID.

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS


→ reportTypeId

required

string <uuid>

ID of the report type

Responses



> **200** Ok

> **401** Unauthorized response

> **403** Forbidden

> **404** Not found

GET /report-types/{reportTypeId}

Response samples

200

401

403

404

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "id": "7a9ee450-6a8e-4174-a1bf-80e0fb7b2112",
    "name": "AML",
    "description": "Anti-money laundering report",
    "username": "Username01",
    "scorecard_id": "a3f779f1-f22d-4608-bc09-74d2f9a48bc8",
    "scorecard": { ... },
    "age_min": 18,
    "age_max": 75,
    "reference_required": true,
    "primary_actions": [ ... ],
    "secondary_actions": [ ... ],
    "created_at": "2021-08-10T08:32:28Z",
    "updated_at": "2021-08-10T08:32:28Z",
    "is_default": false,
    "category": "CUSTOM"
  }
}
```

Update a report type

AUTHORIZATIONS: >

Production or Sandbox

PATH PARAMETERS

reportTypeId	string <uuid>
required	ID of the report type

REQUEST BODY SCHEMA: application/json

name	string <= 255 characters Name of the report type. Must be unique per user account.
description	string <= 512 characters Optional description
scorecard_id >	string or null
age_min >	integer or null [18 .. 114] Minimum age threshold used by age verification
age_max >	integer or null [18 .. 114] Maximum age threshold used by age verification
reference_required	boolean Whether the reference is required when creating a report
primary_actions	Array of strings (ReportActionName) Defines report actions to be performed when a new report is created. You can see a full list of report actions in the appendix.
secondary_actions	Array of strings (ReportActionName) Defines report actions to be shown as follow-up actions when a new report is created. You can see a full list of report actions in the appendix.

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found
- > 422 Validation error

PATCH

/report-types/{reportTypeId}

Request samples

Payload

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "name": "AML",
  "description": "Anti-money laundering report",
  "scorecard_id": "a3f779f1-f22d-4608-bc09-74d2f9a48bc8",
  "age_min": 18,
  "age_max": 75,
  "reference_required": true,
  - "primary_actions": [
    "lexid-match"
  ],
  - "secondary_actions": [
    "lexid-match"
  ]
}
```

Response samples

200

401

403

404

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "data": {
    "id": "7a9ee450-6a8e-4174-a1bf-80e0fb7b2112",
    "name": "AML",
    "description": "Anti-money laundering report",
    "username": "Username01",
    "scorecard_id": "a3f779f1-f22d-4608-bc09-74d2f9a48bc8",
    + "scorecard": { ... },
    "age_min": 18,
    "age_max": 75,
    "reference_required": true,
    + "primary_actions": [ ... ],
    + "secondary_actions": [ ... ],
    "created_at": "2021-08-10T08:32:28Z",
    "updated_at": "2021-08-10T08:32:28Z",
    "is_default": false,
    "category": "CUSTOM"
  }
}
```

Delete a report type

Report types that are no longer used can be deleted.

PATH PARAMETERS

→ reportTypeId
required

string <uuid>
ID of the report type

Responses

— **204** Deleted

> **401** Unauthorized response

> **403** Forbidden

> **404** Not found

DELETE /report-types/{reportTypeId} 

Response samples

401

403

404

Content type
application/json

Copy

```
{
  "message": "Unauthenticated"
}
```

Scorecards

Scorecards allow each user to create a scorecard that is used to score against attributes.

Create a scorecard

AUTHORIZATIONS: > *Production or Sandbox*

REQUEST BODY SCHEMA: application/json

 name required	string <= 255 characters Name of the scorecard. Must be unique per user account.
 pass_threshold	integer or null The score required to achieve a pass result
 fail_threshold	integer or null The score required to achieve a failure result
 groups >	Array of objects The defined rule groups

Responses

> **201** Created

> **401** Unauthorized response

> **403** Forbidden

> **422** Validation error

POST /scorecards



Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "name": "Test",
  "pass_threshold": 100,
  "fail_threshold": 80,
  "groups": [
    + { ... }
  ]
}
```

Response samples

201

401

403

422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    "id": "5516dc1b-1db6-475b-935c-3f80c5d93724",
    "name": "Test",
    "pass_threshold": 100,
    "fail_threshold": 80,
    + "groups": [ ... ],
    "username": "test-username",
    "created_at": "2021-08-10T08:32:28Z"
  }
}
```

Retrieve a collection of scorecards

AUTHORIZATIONS: >

Production or Sandbox

QUERY PARAMETERS

username

string <= 64 characters

Example: username=myUsername

	Filter by IDU username
per_page	integer [1 .. 100] Example: per_page=20 Set how many results to return per page
page	integer >= 1 Example: page=1 Select which page of results to return
order	string Enum: "asc" "desc" Example: order=desc Sort order (asc or desc)
order_by	string Example: order_by=created_at Sort by a specific field

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

GET /scorecards

Response samples

200

401

403

422

Content type

application/json

CopyExpand allCollapse all

```
{
  - "data": [
    + { ... }
  ],
  - "links": {
    "first": "https://example.com/v1/users?page=1",
    "last": "https://example.com/v1/users?page=20",
    "prev": "https://example.com/v1/users?page=1",
    "next": "https://example.com/v1/users?page=2"
  },
  - "meta": {
    "current_page": 1,
    "last_page": 1,
    "from": 21,
    "to": 101,
    "per_page": 10,
    "total": 1000,
```

```
    "path": "https://example.com/v1/users",
    + "links": [ ... ]
  }
}
```

Retrieve a scorecard

Retrieve a single scorecard by ID

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

→ scorecardId required	string <uuid> ID of the scorecard
---------------------------	--------------------------------------

Responses

> **200** Ok

> **401** Unauthorized response

> **403** Forbidden

> **404** Not found

GET /scorecards/{scorecardId}

Response samples

200

401

403

404

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    "id": "5516dc1b-1db6-475b-935c-3f80c5d93724",
    "name": "Test",
    "pass_threshold": 100,
    "fail_threshold": 80,
    + "groups": [ ... ],
    "username": "test-username",
    "created_at": "2021-08-10T08:32:28Z"
  }
}
```

Update a scorecard

Update a single scorecard by id

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

scorecardId	string <uuid>
required	ID of the scorecard

REQUEST BODY SCHEMA: application/json

name	string <= 255 characters> Name of the scorecard. Must be unique per user account.
pass_threshold	integer or null The score required to achieve a pass result
fail_threshold	integer or null The score required to achieve a failure result
groups >	Array of objects The defined rule groups

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found
- > 422 Validation error

PATCH /scorecards/{scorecardId}

Request samples

Payload

Content type
application/json

CopyExpand allCollapse all

```
{
  "name": "Test",
  "pass_threshold": 100,
  "fail_threshold": 80,
  "groups": [
    + { ... }
  ]
}
```

Response samples

- 200
- 401
- 403
- 404
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "id": "5516dc1b-1db6-475b-935c-3f80c5d93724",
    "name": "Test",
    "pass_threshold": 100,
    "fail_threshold": 80,
    "groups": [ ... ],
    "username": "test-username",
    "created_at": "2021-08-10T08:32:28Z"
  }
}
```

Delete a scorecard

Scorecards that are no longer used can be deleted.

PATH PARAMETERS

scorecardId
required

string <uuid>
ID of the scorecard

Responses

- 204 Deleted
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found
- > 422 Validation error

DELETE /scorecards/{scorecardId}

Response samples

- 401
- 403
- 404
- 422

Content type
application/json

[Copy](#)

```
{  
  "message": "Unauthenticated"  
}
```

Users

Manage users within your organisation.

Retrieve current user

Retrieve the authenticated user's profile.

AUTHORIZATIONS: >

Production or Sandbox

Responses

> **200** Ok

> **401** Unauthorized response

> **403** Forbidden

GET /users/self



Response samples

200

401

403

Content type
application/json

[Copy](#) [Expand all](#) [Collapse all](#)

```
{  
  - "data": {  
    "id": "f515868c-1777-4d81-974a-ece150c4f472",  
    "username": "myUsername",  
    "forename": "Jane",  
    "surname": "Doe",  
    "status": 1,  
    "email": "jane.doe@example.com",  
    "telephone": "01234555666",  
    "extension": "123",  
    "mobile": "07123456789",  
    "active": true,  
    "role": "standard"  
  }  
}
```

Retrieve user company

Retrieve the authenticated user's company information.

AUTHORIZATIONS: > *Production or Sandbox*

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden

GET /users/self/company

Response samples

200 401 403

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "name": "Company Ltd",
    "account_manager": { ... }
  }
}
```

Get user activity logs

AUTHORIZATIONS: > *Production or Sandbox*

QUERY PARAMETERS

page	integer >= 1 Example: page=2 Select which page of results to return
per_page	integer [1 .. 100] Example: per_page=10 Set how many results to return per page

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

GET /users/self/activity-logs

Response samples

- 200
- 401
- 403
- 422

Content type

application/json

Copy Expand all Collapse all

```
{
  - "data": [
    + { ... }
  ],
  - "links": {
    "first": "https://example.com/v1/users?page=1",
    "last": "https://example.com/v1/users?page=20",
    "prev": "https://example.com/v1/users?page=1",
    "next": "https://example.com/v1/users?page=2"
  },
  - "meta": {
    "current_page": 1,
    "last_page": 1,
    "from": 21,
    "to": 101,
    "per_page": 10,
    "total": 1000,
    "path": "https://example.com/v1/users",
    + "links": [ ... ]
  }
}
```

Get user options

AUTHORIZATIONS: >

Production or Sandbox

Responses

- > 200 Ok

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden

GET

/users/self/options

▼

Response samples

200

401

403

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "data": {
    "bridger_client_id": "my-bridger-client-id",
    "bridger_client_secret": "my-bri*****",
    "bridger_customer_toggle": false,
    "bridger_predefined_search": "my-predefined-search",
    "bridger_user_id": "my-bridger-user-id"
  }
}
```

Update user options

AUTHORIZATIONS: > *Production or Sandbox*

REQUEST BODY SCHEMA: application/json

bridger_client_id >	string or null
bridger_client_secret >	string or null
bridger_customer_toggle	boolean
bridger_predefined_search >	string or null
bridger_user_id >	string or null

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

PATCH /users/self/options



Request samples

Payload

Content type
application/json

Copy

```
{
  "bridger_client_id": "my-bridger-client-id",
  "bridger_client_secret": "my-bridger-client-secret",
  "bridger_customer_toggle": false,
  "bridger_predefined_search": "my-predefined-search",
  "bridger_user_id": "my-bridger-user-id"
}
```

Response samples

200

401

403

422

Content type
application/json

Copy

Expand all

Collapse all

```
{
  "data": {
    "bridger_client_id": "my-bridger-client-id",
    "bridger_client_secret": "my-bri*****",
    "bridger_customer_toggle": false,
    "bridger_predefined_search": "my-predefined-search",
    "bridger_user_id": "my-bridger-user-id"
  }
}
```

Notifications

Access notifications relating to your use of the IDU (REST) API.

Retrieve notification collection

List all notifications for the authenticated user.

AUTHORIZATIONS: >

Production or Sandbox

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden

GET /users/self/notifications

Response samples

200401403

Content type

application/json

CopyExpand allCollapse all

```
{
  "data": [
    { ... }
  ]
}
```

Retrieve notification

Retrieve a single notification by ID.

AUTHORIZATIONS: >	Production or Sandbox
PATH PARAMETERS	
notificationId required	integer ID of the user notification

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found

GET /users/self/notifications/{notificationId}

Response samples

- 200
- 401
- 403
- 404

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    "id": "4f8c6a9e-1234-4d2b-8c2d-9a7e6c5b1a2f",
    "read_at": "2021-08-10T08:32:28Z",
    "created_at": "2021-08-10T08:32:28Z",
    + "data": { ... }
  }
}
```

Delete notification

Delete a single notification by ID.

AUTHORIZATIONS: > Production or Sandbox

PATH PARAMETERS

notificationId required	integer ID of the user notification
---	---

Responses

- 204 Deleted
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found

DELETE /users/self/notifications/{notificationId}

Response samples

- 401
- 403
- 404

Content type
application/json

Copy

```
{
  "message": "Unauthenticated"
}
```

Update notification

Mark a notification as read or unread.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

notificationId integer
required ID of the user notification

REQUEST BODY SCHEMA: application/json

read boolean
Set to true to mark as read, false to mark as unread

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found
- > 422 Validation error

PATCH

/users/self/notifications/{notificationId}

Request samples

Payload

Content type

application/json

Copy

```
{  
  "read": true  
}
```

Response samples

200

401

403

404

422

Content type

application/json

Copy

Expand all

Collapse all

```

{
  - "data": {
    "id": "4f8c6a9e-1234-4d2b-8c2d-9a7e6c5b1a2f",
    "read_at": "2021-08-10T08:32:28Z",
    "created_at": "2021-08-10T08:32:28Z",
    + "data": { ... }
  }
}

```

Webhooks

Some event notifications can be sent to webhook endpoints on your own public web services.

Remote Check completed Webhook

This message type is sent when a user completes a remote check

AUTHORIZATIONS: >

WebhookSignature

HEADER PARAMETERS

webhook-id <i>required</i>	string <uuid> Unique identifier for the webhook message, can be used as an idempotency key
webhook-timestamp <i>required</i>	integer <int64> Unix timestamp when the webhook message was sent
webhook-signature <i>required</i>	string ^{^v1,[a-zA-Z0-9+/=]+(v1,[a-zA-Z0-9+/=]+)*\$} Example: <code>v1,g0hM9SsE+OTpJTgt/tmIKtSyZlE3uFJELV1NIOLJ1OE=</code> Space-separated list of versioned signatures for verification. Format: <code>v1,<base64_signature> v1,<base64_signature_2></code>

REQUEST BODY SCHEMA: application/json

type <i>required</i>	string Value: <code>"remote-check.check-completed"</code> Event type identifier
timestamp <i>required</i>	string <date-time> ISO 8601 timestamp when the event occurred
data > <i>required</i>	object

Responses

— **200** Webhook received successfully

— **400** Bad request - invalid signature, malformed payload, etc.

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "type": "remote-check.check-completed",
  "timestamp": "2025-12-05T10:30:00Z",
  "data": {
    "report_id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c5d",
    "remote_check_id": "f1e2d3c4-b5a6-4978-8c9d-0e1f2a3b4c5d",
    "status": "COMPLETED"
  }
}
```

Remote Check invite expired Webhook

This message type is sent when a remote check invite has expired without completion

AUTHORIZATIONS: > WebhookSignature

HEADER PARAMETERS

webhook-id required	string <uuid> Unique identifier for the webhook message, can be used as an idempotency key
webhook-timestamp required	integer <int64> Unix timestamp when the webhook message was sent
webhook-signature required	string ^v1,[a-zA-Z0-9+/=]+(v1,[a-zA-Z0-9+/=]+)*\$ Example: v1,g0hM9SsE+OTPJTGT/tmIKtSyZlE3uFJELV1NIOLJ1OE= Space-separated list of versioned signatures for verification. Format: v1,<base64_signature> v1,<base64_signature_2>

REQUEST BODY SCHEMA: application/json

type required	string Value: remote-check.invitation-expired Event type identifier
timestamp required	string <date-time> ISO 8601 timestamp when the event occurred
data > required	object

Responses

— 200 Webhook received successfully

— 400 Bad request - invalid signature, malformed payload, etc.

Request samples

Payload

Content type
application/json

Copy Expand all Collapse all

```
{
  "type": "remote-check.invitation-expired",
  "timestamp": "2025-12-05T10:30:00Z",
  "data": {
    "report_id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c5d",
    "remote_check_id": "f1e2d3c4-b5a6-4978-8c9d-0e1f2a3b4c5d",
    "status": "EXPIRED"
  }
}
```

Generate webhook secret

Generate a new webhook secret for authenticating webhook notifications. Requires a webhook URL to be configured first.

AUTHORIZATIONS: > Production or Sandbox

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error
- > 428 Precondition required

PUT /users/self/webhook-secret

Response samples

- 200
- 401
- 403
- 422
- 428

Content type
application/json

Copy

```
{
  "secret": "string"
}
```

List webhooks

Retrieve a paginated list of webhook messages that we've attempted to deliver to you, within a time window that you specify

AUTHORIZATIONS: > *Production or Sandbox*

QUERY PARAMETERS

date_from <i>required</i>	string <date-time> Example: <code>date_from=2021-08-10T08:32:28Z</code> Date of earliest webhook event to include; must be a valid ISO 8601 date-time value
date_to	string <date-time> Example: <code>date_to=2021-08-10T08:32:28Z</code> Date of last webhook event to include; defaults to the current time when omitted
page	integer <code>>= 1</code> Example: <code>page=2</code> Select which page of results to return
per_page	integer <code>[1 .. 100]</code> Example: <code>per_page=10</code> Set how many results to return per page

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error

GET /webhooks

Response samples

200 401 403 422

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": [
    + { ... }
  ],
  - "links": {
    "first": "https://example.com/v1/users?page=1",
    "last": "https://example.com/v1/users?page=20",
    "prev": "https://example.com/v1/users?page=1",
```

```
    "next": "https://example.com/v1/users?page=2"
  },
  - "meta": {
    "current_page": 1,
    "last_page": 1,
    "from": 21,
    "to": 101,
    "per_page": 10,
    "total": 1000,
    "path": "https://example.com/v1/users",
    + "links": [ ... ]
  }
}
```

Get webhook details

Inspect the payload and delivery attempts for a single webhook message

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

webhookId required	string <uuid> ID of the webhook event instance
--	--

Responses

> 200 Ok

> 401 Unauthorized response

> 403 Forbidden

> 404 Not found

GET /webhooks/{webhookId}

Response samples

200

401

403

404

Content type
application/json

Copy Expand all Collapse all

```
{
  - "data": {
    "webhook_id": "a1b2c3d4-e5f6-4a7b-8c9d-0e1f2a3b4c5d",
    "type": "remote-check.check-completed",
    "status": "SUCCESS",
    + "payload": { ... },
    + "attempts": [ ... ]
  }
}
```

Retry webhook delivery

Retry a failed webhook delivery. This endpoint accepts a POST request to retry sending a webhook that previously failed. The webhook must be in a "failed" status to be retried.

The retry operation is asynchronous - the webhook will be queued for delivery and processed in the background.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

webhookId	string <uuid>
required	ID of the webhook event instance

Responses

— **202** Accepted - Request has been accepted for processing

> **401** Unauthorized response

> **403** Forbidden

> **404** Not found

> **422** Validation error

POST /webhooks/{webhookId}/retry

Response samples

401

403

404

422

Content type
application/json

Copy

```
{
  "message": "Unauthenticated"
}
```

Send a test webhook message

Send a dummy webhook message to verify your webhook integration. Parameters allow you to control aspects of the dummy message, so you can test specific success and failure scenarios.

We'll attempt to immediately deliver the test webhook message to your configured webhook URL. Your server will have 15 seconds to respond to our request. If successful, we'll return details of the response from your server, including the status code, HTTP headers, and the message body. We'll return a 500 status code in the event of a connection failure or timeout.

The webhook message will be sent with the normal `webhook-*` headers, plus a `webhook-test` header, which will have the value `true`. Your implementation should use this header to distinguish between test and real webhook messages.

Test webhooks are not logged in your webhook message history.

This endpoint has high latency and is not intended for use in production.

AUTHORIZATIONS: > *Production or Sandbox*

REQUEST BODY SCHEMA: application/json

valid_signature	boolean Default: <code>true</code> Set this to false to have the test webhook message be sent with a signature created from an invalid secret. Your webhook processor is expected to reject the message in this scenario.
event_type	string Enum: <code>"remote-check.check-completed"</code> <code>"remote-check.invitation-expired"</code> The event type you want to test. If not provided, this will be randomly selected from the supported event types. Other contents of the webhook message payload will be auto-generated with dummy data.

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 422 Validation error
- 500

This status code denotes we had a problem delivering the webhook message to your server, perhaps due to a connection issue or timeout.

POST

/webhooks/test

Request samples

Payload

Content type

application/json

Copy

```
{
  "valid_signature": true,
  "event_type": "remote-check.check-completed"
}
```

Response samples

200401403422

Content type

application/json

CopyExpand allCollapse all

```
{
  "data": {
    "http_status_code": 200,
    "http_headers": { },
    "http_message_payload": { }
  }
}
```

Remote check

Manage "Remote Check" identity verification sessions.

Cancel transaction link

Cancel the transaction link for the report.

AUTHORIZATIONS: >	Production or Sandbox
PATH PARAMETERS	
reportId required	string <uuid> ID of the report

Responses

- 202 Accepted - Request has been accepted for processing
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found
- > 422 Validation error

POST /reports/{reportId}/remote-check/cancel

Response samples

401403404422

Content type
application/json

Copy

```
{  
  "message": "Unauthenticated"  
}
```

Resend invitation link via SMS

Resend the Remote Check invitation link via SMS for this report. A `202 Accepted` response indicates the resend request was accepted for processing, it does not confirm that the recipient has received the message.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId required	string <uuid> ID of the report
----------------------	-----------------------------------

Responses

— **202 Accepted** - Request has been accepted for processing

> **401 Unauthorized** response

> **403 Forbidden**

> **404 Not found**

> **409 Conflict** - Remote Check is not in progress

> **422 Validation error**

> **429 Too many requests**

— **500**

This status code denotes we had a problem requesting the resend link, perhaps due to a connection issue or timeout.

POST /reports/{reportId}/remote-check/resend/sms

Response samples

401

403

404

409

422

429

Content type
application/json

Copy

```
{
  "message": "Unauthenticated"
}
```

Resend invitation link via email

Resend the Remote Check invitation link via email for this report.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId	string <uuid>
required	ID of the report

Responses

- 202 Accepted - Request has been accepted for processing
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found
- > 409 Conflict - Remote Check is not in progress
- > 422 Validation error
- 500
This status code denotes we had a problem requesting the resend link, perhaps due to a connection issue or timeout.

POST /reports/{reportId}/remote-check/resend/email

Response samples

401 403 404 409 422

Content type
application/json

```
{
  "message": "Unauthenticated"
}
```

Copy

Get remote check results

Retrieve the results of a remote check performed on an individual report.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

reportId	string <uuid>
required	ID of the report

Responses

- > 200 Ok
- > 401 Unauthorized response
- > 403 Forbidden
- > 404 Not found

GET /reports/{reportId}/remote-check/results

Response samples

- 200
- 401
- 403
- 404

Content type

application/json

Copy Expand all Collapse all

```
{
  "data": {
    "id": "5516dc1b-1db6-475b-935c-3f80c5d93724",
    "created_at": "2021-08-10T08:32:28Z",
    "updated_at": "2021-08-10T08:32:28Z",
    "status": "COMPLETE",
    "user": { ... },
    "context": { ... },
    "annotations": [ ... ],
    "assessment": { ... },
    "attributes": { ... },
    "address_insights": { ... },
    "address_verification": { ... },
    "age_verification": { ... },
    "bank_account_validation": { ... },
    "bank_account_verification": { ... },
    "ccj_screening": { ... },
    "company_officer_screening": { ... },
    "credit_active": { ... },
    "death_screening": { ... },
    "dob_verification": { ... },
    "driving_licence_validation": { ... },
    "email_risk": { ... },
    "insolvency_screening": { ... }
```

```
+ "insolvency_screening": { ... },
+ "lexid_match": { ... },
+ "nfi_amberhill": { ... },
+ "ni_number_validation": { ... },
+ "otp_email": { ... },
+ "otp_sms": { ... },
+ "passport_validation": { ... },
+ "pep_screening": { ... },
+ "phone_match": { ... },
+ "prs_verification": { ... },
+ "remote_check": { ... },
+ "sanction_screening": { ... }
}
}
```

Get remote check PDF results

Retrieve the PDF results of a remote check performed on an individual report.

AUTHORIZATIONS: > *Production or Sandbox*

PATH PARAMETERS

→ reportId	string <uuid>
required	ID of the report

Responses

> **200** Ok

> **401** Unauthorized response

> **403** Forbidden

> **404** Not found

GET /reports/{reportId}/remote-check/results/pdf

Response samples

200

401

403

404

Content type
application/json

Copy Expand all Collapse all

```
{
  "data": {
    "pdf": "string"
  }
}
```

Health

Check the health of the IDU REST API service.

Check service status

Check if the IDU REST API service is currently available.

AUTHORIZATIONS: > *Production or Sandbox*

Responses

- > **200** Ok
- > **401** Unauthorized response
- > **503** Service Unavailable

GET /up

Response samples

200

401

503

Content type

application/health+json

Copy

```
{
  "status": "pass",
  "version": "1.0.0"
}
```

Appendix

List of report actions

This is the complete list of report actions that can be used to add services and datasets to a report.

Name
address-insights
address-verification
age-verification
bank-account-validation
bank-account-verification
ccj-screening
company-officer-screening
credit-active
death-screening
dob-verification
driving-licence-validation
email-risk
insolvency-screening
lexid-match
nfi-amberhill
ni-number-validation
otp-email
otp-email-verification
otp-sms
otp-sms-verification
passport-validation
pep-screening
phone-match
phone-number-validation
prs-verification
remote-check
sanction-screening

List of report attributes

This is the complete list of report attributes that can be used to create scorecard rules when scoring risk on a report.

You can also see a short explanation of what each return value means.

Attribute	Report action	Match (<code>true</code>)	No match (<code>false</code>)
<code>address_companies_house</code>	address-verification	Address verified by companies house	Address not verified by companies house
<code>address_current_elector</code>	address-verification	On the current electoral register	Not on the current electoral register

address_gone_away_high	address-verification	High probability that the individual no longer lives at the address	No indication of a high gone away
address_gone_away_very_high	address-verification	Very high probability that the individual no longer lives at the address	No indication of a very high goneaway
address_historic_er	address-verification	On previous electoral registers	Not on previous electoral registers
address_insolvency_service	address-verification	Address verified by the insolvency service	Address not verified by the insolvency service
address_council_tax	address-verification	NFI address council tax source found	NFI address council tax source not found
address_council_tax_reduction_scheme	address-verification	NFI address council tax reduction scheme source found	NFI address council tax reduction scheme source not found
address_deferred_pensions	address-verification	NFI address deferred pensions source found	NFI address deferred pensions source not found
address_housing_tenants	address-verification	NFI address housing tenants source found	NFI address housing tenants source not found
address_housing_benefits	address-verification	NFI address NFI housing benefits source found	NFI address NFI housing benefits source not found
address_payroll	address-verification	NFI address payroll source found	NFI address payroll source not found
address_pensions	address-verification	NFI address pensions source found	NFI address pensions source not found
address_pensions_gratuities	address-verification	NFI address pensions gratuities source found	NFI address pensions gratuities source not found
address_personal_budgets	address-verification	NFI address personal budgets source found	NFI address personal budgets source not found
address_personal_licence	address-verification	NFI address personal licence source found	NFI address personal licence source not found
address_right_to_buy	address-verification	NFI address right to buy source found	NFI address right to buy source not found
address_state_benefits	address-verification	NFI address state benefits source found	NFI address state benefits source not found
address_student_loans	address-verification	NFI address student loans source found	NFI address student loans source not found
address_nfi_sources (INTEGER)	address-verification	NFI address sources found	NFI address sources not found
address_taxi_drivers	address-verification	NFI address taxi drivers source found	NFI address taxi drivers source not found
address_transport_pass	address-verification	NFI address transport pass source found	NFI address transport pass source not found
address_waiting_list	address-verification	NFI address waiting list source found	NFI address waiting list source not found
address_registry_trust	address-verification	Address verified by the registry trust	Address not verified by the registry trust
address_telephone_directory	address-verification	Address verified by telephone directory	Address not verified by telephone directory
address_tracesmart_register	address-verification	On the Tracesmart register	Not on the Tracesmart register

address_verified	address-verification	Address verified	Address not verified
age_max	age-verification	Younger than the maximum age	Older than the maximum age
age_min	age-verification	Older than the minimum age	Younger than the minimum age
bank_account_valid	bank-account-validation	Bank account details are valid	Bank account details are not valid
bank_account_verified	bank-account-verification	Bank account verified	Bank account not verified
ccj	ccj-screening	Has record of CCJs	Has no record of CCJs
company_officer_current	company-officer-screening	Current company officer	Not a current company officer
company_officer_historic	company-officer-screening	Former company officer	Not a former company officer
credit_lenders (INTEGER)	credit-active	Has credit activity	Has no credit activity
death_ddri	death-screening	DDRI mortality alert	No DDRI mortality alert
death_gro	death-screening	GRO mortality alert	No GRO mortality alert
death_halo	death-screening	HALO mortality alert	No HALO mortality alert
dob_count (INTEGER)	dob-verification	DOB verified	DOB not verified
driving_licence_validation	driving-licence-validation	Driving Licence Number has been validated against input data	Driving Licence Number has not been validated against input data
email_risk_high	email-risk	High risk email address	N/A
email_risk_low	email-risk	Low risk email address	N/A
email_risk_moderate	email-risk	Moderate risk email address	N/A
email_risk_review	email-risk	Review needed for email address	N/A
email_risk_very_high	email-risk	Very high risk email address	N/A
email_risk_very_low	email-risk	Very low risk email address	N/A
insolvency	insolvency-screening	Has record of insolvency	Has no record of insolvency
lexid_match	lexid-match	LexID has been validated against input data	LexID has not been validated against input data
nfi_amberhill_driving_licence	nfi-amberhill	Driving licence number found in Amberhill database	Driving licence number not found in Amberhill database
nfi_amberhill_id_card	nfi-amberhill	Id card number found in Amberhill database	Id card number not found in Amberhill database
nfi_amberhill_ni_number	nfi-amberhill	NI number found in Amberhill database	NI number not found in Amberhill database
nfi_amberhill_nhs_number	nfi-amberhill	NHS number found in Amberhill database	NHS number not found in Amberhill database
nfi_amberhill_passport	nfi-amberhill	Passport number found in Amberhill database	Passport number not found in Amberhill database
nfi_amberhill_travel_visa	nfi-amberhill	Travel visa number found in Amberhill database	Travel visa number not found in Amberhill database

<code>ni_number_validation</code>	ni-number-validation	NI number has been validated against input data	NI number has not been validated against input data
<code>otp_email_verified</code>	otp-email-verification	Email address has been verified successfully	Email address has not been verified successfully
<code>otp_sms_verified</code>	otp-sms-verification	Mobile phone number has been verified successfully	Mobile phone number has not been verified successfully
<code>passport_number_validation_expiry_date</code>	passport-validation	Passport number validation expiry date has been validated against input data	Passport number validation expiry date has not been validated against input data
<code>passport_number_validation_mrz</code>	passport-validation	Passport number validation MRZ has been validated against input data	Passport number validation MRZ has not been validated against input data
<code>pep</code>	pep-screening	Has PEP alert	Has no PEP alert
<code>phone_match_landline</code>	phone-match	Landline number has been validated successfully	Landline number has not been validated successfully
<code>phone_match_mobile</code>	phone-match	Mobile number has been validated successfully	Mobile number has not been validated successfully
<code>phone_number_validation</code>	phone-number-validation	Phone number has been validated successfully	Phone number has not been validated successfully
<code>prs_verified</code>	prs-verification	Owner verified on property register search	Owner not verified on property register search
<code>remote_check_verified</code>	remote-check-get-results	Remote check verification passed	Remote check verification failed
<code>sanction</code>	sanction-screening	Has sanction alert	Has no sanction alert

List of error codes

Each validation error returns a unique error code that corresponds with a specific input field and can be used in your integration to enhance the user-experience.

The human-readable error text returned alongside the error code will give more detail about the violation.

Code	Message
1000	The <code>name</code> must be a string
1001	The <code>name</code> field is required
1002	The <code>name</code> must not be greater than X characters
1003	The <code>description</code> must be a string
1004	The <code>description</code> must not be greater than X characters
1005	The <code>report_type_id</code> field is required
1006	The <code>report_type_id</code> must be a string
1007	The <code>forename</code> field is required
1008	The <code>forename</code> must be a string
1009	The <code>middlename</code> must be a string
1010	The <code>surname</code> field is required
1011	The <code>surname</code> must be a string
1012	The <code>dob</code> field is required

1013	The <code>dob</code> is not a valid date
1014	The <code>address.address1</code> field is required
1015	The <code>address.address1</code> must be a string
1016	The <code>address.address2</code> must be a string
1017	The <code>address.address3</code> must be a string
1018	The <code>address.address4</code> must be a string
1019	The <code>address.address5</code> must be a string
1020	The <code>address.postcode</code> field is required
1021	The <code>address.postcode</code> must be a string
1022	The <code>address</code> field must be true or false
1023	The <code>lexid</code> field must be true or false
1024	The <code>full_address</code> must be a string
1025	The <code>full_address</code> must not be greater than X characters
1026	The <code>house</code> must be a string
1027	The <code>house</code> must not be greater than X characters
1028	The <code>street</code> must be a string
1029	The <code>street</code> must not be greater than X characters
1030	The <code>town</code> must be a string
1031	The <code>town</code> must not be greater than X characters
1032	The <code>postcode</code> must be a string
1033	The <code>postcode</code> must not be greater than X characters
1034	The <code>fuzzy</code> field must be true or false
1035	The <code>alias</code> field must be true or false
1036	The <code>primary_actions</code> must be an array
1037	The X report action does not exist
1038	The <code>primary_actions</code> field has a duplicate value
1039	The X report action is not enabled for your user
1040	The <code>fuzzy_matching</code> field must be true or false
1042	The <code>alias_matching</code> field must be true or false
1044	The <code>date_from</code> is not a valid date
1045	The <code>date_to</code> is not a valid date
1046	The <code>full_er</code> field must be true or false
1047	The <code>dob</code> field must be true or false
1048	The <code>credit_activity</code> field must be true or false
1049	The <code>reference</code> must be a string
1050	The <code>death</code> field must be true or false
1051	The <code>ddri</code> field must be true or false
1052	The <code>dob</code> field is required when X is not present
1053	The <code>address.address1</code> field is required when X is not present
1054	The <code>address.postcode</code> field is required when X is not present
1055	The <code>enduser agreement</code> field is required

1056	The <code>enduser_agreement</code> field must be true or false
1057	The <code>ccj</code> field must be true or false
1058	The <code>insolvency</code> field must be true or false
1074	The <code>experian</code> field must be true or false
1075	The <code>equifax</code> field must be true or false
1076	The <code>director</code> field must be true or false
1077	The <code>per_page</code> must be an integer
1078	The <code>per_page</code> must be at least X
1079	The <code>per_page</code> must not be greater than X
1080	The <code>page</code> must be an integer
1081	The <code>page</code> must be at least X
1082	The <code>credit_active_mode</code> is not valid
1083	The <code>credit_active_primary</code> is not valid
1085	The <code>sanction</code> field must be true or false
1086	The <code>pep</code> field must be true or false
1093	The <code>bank_details.sort_code</code> field is required
1094	The <code>bank_details.sort_code</code> must be a string
1095	The <code>bank_details.sort_code</code> must be X digits
1096	The <code>bank_details.account_number</code> field is required
1097	The <code>bank_details.account_number</code> must be a string
1098	The <code>bank_details.account_number</code> must be X digits
1099	The <code>bankaccount</code> field must be true or false
1100	The <code>td</code> field must be true or false
1101	The <code>xd</code> field must be true or false
1104	The <code>email_risk</code> field must be true or false
1105	The <code>emails</code> must be an array
1106	The <code>emails</code> must not be greater than X characters
1107	The <code>emails.email</code> field is required
1108	The <code>emails.email</code> must be a valid email address
1109	The <code>emails.email</code> field has a duplicate value
1110	The <code>emails</code> field is required
1111	The <code>role</code> value is not a valid role
1113	The <code>age_min</code> must be an integer
1114	The <code>age_min</code> must be at least X
1115	The <code>age_min</code> must be less than X
1116	The <code>age_max</code> must be an integer
1117	The <code>age_max</code> must be at least X
1118	The <code>age_max</code> must be less than X
1119	The <code>age_min</code> must be less than or equal X
1120	The <code>age</code> field must be true or false

1121	The <code>path_identifier</code> must be a string
1122	The <code>method</code> must be a string
1123	The <code>path</code> must be a string
1124	The <code>ip</code> must be a string
1125	The <code>status</code> must be an integer
1126	The <code>user_id</code> must be an integer
1127	The <code>company_id</code> must be an integer
1128	The <code>forename</code> must not be greater than X characters
1129	The <code>middlename</code> must not be greater than X characters
1130	The <code>surname</code> must not be greater than X characters
1131	The <code>address.address1</code> must not be greater than X characters
1132	The <code>address.address2</code> must not be greater than X characters
1133	The <code>address.address3</code> must not be greater than X characters
1134	The <code>address.address4</code> must not be greater than X characters
1135	The <code>address.address5</code> must not be greater than X characters
1136	The <code>address.postcode</code> must not be greater than X characters
1137	The <code>reference</code> must not be greater than X characters
1138	The <code>username</code> must not be greater than X characters
1139	The <code>path_identifier</code> must not be greater than X characters
1140	The <code>method</code> must not be greater than X characters
1141	The <code>path</code> must not be greater than X characters
1142	The <code>ip</code> must not be greater than X characters
1143	The <code>server_name</code> must not be greater than X characters
1145	The <code>include_empty_postcode</code> must be between X and X characters
1146	The <code>include_empty_dob</code> must be between X and X characters
1147	The <code>include_empty_postcode</code> must be an integer
1148	The <code>include_empty_dob</code> must be an integer
1149	The <code>report_type_id</code> field prohibits X from being present
1150	The <code>actions</code> must be an array
1151	The <code>actions</code> field has a duplicate value
1152	The X report action does not exist
1153	The X report action is not enabled for your user
1154	The <code>application</code> must be a string
1155	The <code>application</code> must not be greater than X characters
1156	The <code>level</code> must be a string
1157	The <code>level</code> must not be greater than X characters
1158	The <code>channel</code> must be a string
1159	The <code>channel</code> must not be greater than X characters
1160	The <code>config.full_er</code> field must be true or false
1161	The <code>config.full_er</code> is a setting you do not have permission to use
1162	The <code>pass_threshold</code> must be an integer

1162	The <code>pass_threshold</code> must be an integer
1163	The scorecard pass threshold must be greater than the failure threshold
1164	The <code>fail_threshold</code> must be an integer
1165	The <code>groups</code> must be an array
1166	The <code>groups.group_name</code> field has a duplicate value
1167	The <code>groups.group_name</code> must be a string
1168	The <code>groups.min_score</code> must be an integer
1169	The <code>groups.rules</code> must be an array
1170	The <code>groups.rules.attribute</code> field is required
1171	The <code>groups.rules.attribute</code> is not a valid report attribute
1172	The <code>groups.rules.attribute</code> contains a report attribute that you do not have permission to use
1173	The <code>groups.rules</code> contains a duplicate rule
1174	The <code>groups.rules.match_score</code> must be an integer
1175	The <code>groups.rules.no_match_score</code> must be an integer
1176	The <code>groups.group_name</code> must be at least X characters
1177	The <code>groups.group_name</code> must not be greater than X characters
1178	The <code>scorecard_id</code> must be a string
1179	The <code>scorecard_id</code> is invalid
1180	The <code>address_insights</code> field must be true or false
1181	The <code>address_lookup</code> field must be true or false
1182	The <code>report_id</code> must be a string
1183	The <code>report_id</code> must not be greater than X characters
1184	The <code>url</code> must be a string
1185	The <code>url</code> must not be greater than X characters
1186	The <code>username</code> must be a string
1187	The <code>resource</code> must be a valid UUID
1190	The <code>message</code> must be a string
1191	The <code>message</code> must not be greater than X characters
1192	The <code>message</code> field is required
1193	The <code>config.age_min</code> must be at least X characters
1194	The <code>config.age_min</code> must be less than X characters
1195	The <code>config.age_max</code> must be at least X characters
1196	The <code>config.age_max</code> must be less than X characters
1197	The <code>config.age_min</code> must be less than the X
1198	The <code>config.age_max</code> must be greater than the X
1199	The <code>bank_account_validation</code> field must be true or false
1200	The <code>driving_licence_validation</code> field must be true or false
1201	The <code>ni_number_validation</code> field must be true or false
1202	The <code>passport_validation</code> field must be true or false
1203	The <code>ni_number</code> field is required
1204	The <code>ni_number</code> must be a string

1205	The <code>config.age_min</code> must be an integer
1206	The <code>config.age_max</code> must be an integer
1207	The <code>scorecard_id</code> must be a valid UUID
1208	The <code>gender</code> field is required
1209	The <code>gender</code> must be a string
1210	The selected <code>gender</code> is invalid
1211	The <code>passport.mrz_line2.part1</code> field is required
1212	The <code>passport.mrz_line2.part1</code> must be a string
1213	The <code>passport.mrz_line2.part1</code> must be X characters
1214	The <code>passport.mrz_line2.part2</code> field is required
1215	The <code>passport.mrz_line2.part2</code> must be a string
1216	The <code>passport.mrz_line2.part2</code> must be X characters
1217	The <code>passport.mrz_line2.part3</code> field is required
1218	The <code>passport.mrz_line2.part3</code> must be a string
1219	The <code>passport.mrz_line2.part3</code> must be X characters
1220	The <code>passport.mrz_line2.part4</code> field is required
1221	The <code>passport.mrz_line2.part4</code> must be a string
1222	The <code>passport.mrz_line2.part4</code> must be X characters
1223	The <code>passport.mrz_line2.part5</code> field is required
1224	The <code>passport.mrz_line2.part5</code> must be a string
1225	The <code>passport.mrz_line2.part5</code> must be X characters
1226	The <code>passport.mrz_line2.part6</code> field is required
1227	The <code>passport.mrz_line2.part6</code> must be a string
1228	The <code>passport.mrz_line2.part6</code> must be X characters
1229	The <code>passport.mrz_line2.part7</code> field is required
1230	The <code>passport.mrz_line2.part7</code> must be a string
1231	The <code>passport.mrz_line2.part7</code> must be X characters
1232	The <code>passport.mrz_line2.part8</code> field is required
1233	The <code>passport.mrz_line2.part8</code> must be a string
1234	The <code>passport.mrz_line2.part8</code> must be X characters
1235	The <code>dob</code> must be a string
1236	The <code>driving_licence_number</code> field is required
1237	The <code>driving_licence_number</code> must be a string
1238	The <code>driving_licence_number</code> must be at least X characters
1239	The <code>driving_licence_number</code> must not be greater than X characters
1240	The <code>dob</code> does not match the format X
1241	The scorecard is attached to a report type - please remove from report type before deleting
1242	The incoming data cannot overwrite existing input
1243	The <code>report_type_id</code> field is prohibited
1245	The <code>uklexid</code> must be an integer

1246	The <code>dob</code> must represent an age of 18 or over
1247	The <code>include_deleted</code> must be an integer
1248	The <code>include_deleted</code> must be between X and X characters
1249	The request returned too many records - please refine your search
1250	The <code>reference</code> field is required
1251	The <code>reference_required</code> field must be true or false
1252	The <code>dob</code> must represent an age of less than 115
1253	The <code>nfi_address</code> field must be true or false
1254	The <code>nfi_amberhill</code> field must be true or false
1255	The <code>driving_licence_number</code> field is required when none of X are present
1257	The <code>config.nfi_address</code> field must be true or false
1258	The <code>nfi_address_avt</code> must be an integer
1259	The <code>nfi_amberhill_avt</code> must be an integer
1260	The <code>id_card_number</code> must not be greater than X characters
1261	The <code>nhs_number</code> must not be greater than X characters
1262	The <code>ni_number</code> must not be greater than X characters
1263	The <code>passport.number</code> must not be greater than X characters
1264	The <code>travel_visa_number</code> must not be greater than X characters
1265	The <code>remote_check</code> field must be true or false
1266	The <code>property_register_search</code> field must be true or false
1267	The <code>transactionId</code> field is required
1268	The <code>event</code> field is required
1269	The selected <code>event</code> is invalid
1270	The user has already been migrated
1271	Subuser migration is not supported
1272	The <code>phone_code</code> format is invalid
1273	The <code>phone_code</code> must not be greater than X characters
1274	The <code>phone_number</code> format is invalid
1275	The <code>phone_number</code> must be at least X characters
1276	The <code>phone_number</code> must not be greater than X characters
1277	The <code>phone_code</code> field is required when X is present
1278	The <code>phone_number</code> field is required when X is present
1279	The selected <code>config.flow_type</code> is invalid
1280	The <code>config.flow_type</code> field is required
1281	The <code>read</code> field is required
1282	The <code>read</code> field must be true or false
1283	The <code>otp_email</code> field must be true or false
1284	The <code>phone_code</code> field is required
1285	The <code>phone_number</code> field is required
1286	The <code>forename</code> contains invalid characters
1287	The <code>surname</code> contains invalid characters

1288	The <code>middleware</code> contains invalid characters
1289	The <code>email</code> field is required
1290	The <code>email</code> must be a valid email address
1291	The <code>otp_sms</code> field must be true or false
1292	The <code>code</code> field is required
1293	The <code>code</code> must be X digits
1294	An OTP code must be generated first
1295	The <code>notification_webhook_url</code> format is invalid
1296	The <code>notification_webhook_url</code> is invalid
1297	The <code>notification_webhook_url</code> must have a valid SSL certificate
1298	The <code>phone_match</code> field must be true or false
1299	The <code>date_from</code> field is required
1300	The <code>date_to</code> must be a date after or equal to X
1301	The webhook URL is not configured for this user
1302	The <code>phone_number_validation</code> field must be true or false
1303	A webhook must be in a failed or retrying state to retry it
1304	The <code>telephone</code> must be a string
1305	The <code>extension</code> must be a string
1306	The <code>mobile</code> must be a string
1307	The <code>telephone</code> must not be greater than X characters
1308	The <code>extension</code> must not be greater than X characters
1309	The <code>mobile</code> must not be greater than X characters
1310	The <code>email</code> must not be greater than X characters
1311	The <code>webdev_email</code> must be a valid email address
1312	An active remote check journey exists - please cancel it first before creating a new one
1313	You cannot add another remote check to this report as one has already been completed
1314	The <code>username</code> format is invalid
1315	The <code>telephone</code> format is invalid
1316	The <code>extension</code> format is invalid
1317	The <code>mobile</code> format is invalid
1318	The username has already been taken
1319	The request contains invalid parameters
1320	The <code>username</code> field is required
1321	There is no active remote check transaction that can be cancelled
1322	The <code>notification_webhook_url</code> field is required
1323	The <code>notification_webhook_secret</code> field is required
1324	The <code>status</code> must be between X and X characters
1325	The report is closed for additional follow-up actions
1326	This template name is already taken. Please choose another name
1327	The report type name has already been taken
1328	The <code>bridger_client_id</code> must be a string

1329	The <code>bridger_client_id</code> must not be greater than X characters
1330	The <code>bridger_client_secret</code> must be a string
1331	The <code>bridger_client_secret</code> must not be greater than X characters
1332	The <code>bridger_predefined_search</code> must be a string
1333	The <code>bridger_predefined_search</code> must not be greater than X characters
1334	The <code>bridger_user_id</code> must be a string
1335	The <code>bridger_user_id</code> must not be greater than X characters
1336	The <code>bridger_customer_toggle</code> field must be true or false
1337	The <code>bridger_client_secret</code> must be at least X characters
1338	You cannot resend as the remote check transaction is no longer in progress
1339	The <code>search</code> must be a string
1340	The <code>search</code> must not be greater than X characters
1341	The <code>phone_number</code> must be a string
1342	The <code>phone_code</code> must be a string
1343	The <code>secondary_actions</code> must be an array
1344	The X report action does not exist
1345	The <code>secondary_actions</code> field has a duplicate value
1346	The X report action is not enabled for your user
1347	The X report action cannot appear in both primary and secondary actions
1348	The X report action cannot appear in both primary and secondary actions