NET NAMING

internal junctions are named for what they join

U<ref>_<PIN> node at that IC pin e.g. UIVOA_VINP

R<stem>_M midpoint of a series pair e.g. RBALTA_M

R<stem>_<nm> tap between R<stem>n/m e.g. RV1D_01

all others are explicit design nets

SHEET INDEX

30 kW DC-DC (upper) - 2 of 3

OUTPUT-SENSING - 6 sections
LLC-LEGS - 4 sections
LLC-TANKS - 3 sections
BANKS-SP - 4 sections
CONTROL - 3 sections
COMMS-HMI - 2 sections

rev D.4 - 22 sections - 309 components

MAGNETICS CONSTRUCTION

identity per docs/magnetics.md (turns, gap, litz, acceptance lines live there)

D3 T1-T3: 3x PQ50/50 PC95 stack, 9:9:9, litz 1350/660x0.1 TIW, Lm gap-ground +/-7%

tank Cr/trim-bin values printed at the TANK sections

D2 L1T-L3T: gapped 2x PQ50/50, N=4, bins ~4.0uH, gap ground per bin

DC-Modules 30 kW — DC-DC board (3-phase LLC)

DC-Modules 30 kW - board DC-DC (upper), sheet 2 of 3

2026-09-06 · rev D.4