

12 CHANNEL ECG

Model No. CMS 1200G



Technical Specifications

- 8" LCD Display with Touch screen
- Power Supply
 - AC : 100 – 240V, 50/60 Hz
 - DC:14.8V, 3700 mAh rechargeable lithium battery
- Input way Floating and defibrillation protection
- Lead : Standard 12 leads
- Patient leak current: $\leq 10\mu\text{A}$
- Input impedance $\geq 50\text{M}\Omega$
- Frequency response : 0.05Hz~150Hz (-3 dB~0.4 dB)
- Time Constant Time $\geq 3.2\text{s}$
- CMRF2: $\geq 60\text{ dB}$, $\geq 100\text{ dB}$ (add filter)
- EMG interference filter : 35Hz (~3dB)
- Recording papers : 210mm (W) X 20 m(L)
- Recording : Auto, Manual and Rhythm
- Recording way Thermal printing system
- Paper Speed :
 - Auto record : 25mm/s, 50mm/s, error $\pm 5\%$
(Record setup according to auto record format and mode, automatically measuring and analyzing)
 - Manual record : 5mm/s, 6.25mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50mm/s, error $\pm 5\%$
[Record setup according to auto record format and mode, manual changing leads.]
 - Rhythm Record : 25mm/s, 50mm/s, error $\pm 5\%$
(Record setup according to auto record format and mode, automatically measuring and analyzing)
- Sensitivity choice : 5, 10, 20, 40 mm/mV, {Error: $\pm 5\%$ }
- Standard sensitivity is 10mm/mV $\pm 0.2\%$

General Features

AC/ DC Operated with Rechargeable Lithium Battery
Battery backup : **Approx.90 minutes continuous printing, Up to 4 hours in standby mode**
Display 3/6/12 leads ECG waveform and can remark the lead sign, sensitivity paper speed and filter state
Data interpretation
Storage capacity up to 1000 of patient's data, more convenient for data review & statistics
Portable, light weight and sturdy design
Modes of printing :Automatic/ Manual

Printing Modes

- 12*1
- 6*2 + 1
- 6*2
- Rhythm row 12, row 10, row 8, row 6 etc with multiple formats
- Measurement parameter : HR, P-R interval P Duration, ORS Duration, T Duration, O-T interval, Q-Tc, P Axis, QRS Axis, T Axis, R(V5),S(V1), R(V5)+ S(V1)
- Product safety type Class I CF applied part, with defibrillation and pacing protection circuit in it
- Enduring polarization voltage: $\pm 500\text{mV}$
Noise level : $\leq 15\mu\text{Vp-p}$
- Machine Size: 334 (L) x 320 (W) x 85(H) mm
- Machine Net Weight : 2.25Kg

Optional :

- PC Interface software via RS 232 interface / USB / Ethernet
- Basic software : For data transfer & print
- Advance software : For cardiac analysis



We support service...