

## Database text:

```
use flightmanagementsystem;
```

```
show tables;
```

```
select * from login;
```

```
create table passenger (name varchar(20), nationality varchar(20), phone  
varchar(15), address varchar(50), aadhar varchar(20), gender varchar(20));
```

```
select * from passenger;
```

```
create table flight(f_code varchar(20), f_name varchar(20), source varchar(40),  
destination varchar(40));
```

```
describe flight;
```

```
insert into flight values("1001", "AI-1212", "Delhi", "Mumbai");
```

```
insert into flight values("1002", "AI-1435", "Delhi", "Goa");
```

```
insert into flight values("1003", "AI-1656", "Mumbai", "Chennai");
```

```
insert into flight values("1004", "AI-1412", "Delhi", "Amristar");
```

```
insert into flight values("1005", "AI-1786", "Delhi", "Ayodhya");
```

```
select * from flight;
```

```
create table reservation (PNR varchar(15), TICKET varchar(20), aadhar  
varchar(20), name varchar(20), nationality varchar(30), flightname varchar(15),  
flightcode varchar(20), source varchar(30), dest varchar(30), ddate  
varchar(20));
```

```
select * from reservation;
```

```
create table cancel(pnr varchar(20), name varchar(40), cancelno varchar(20),  
fcode varchar(20), ddate varchar(30));
```

```
select * from cancel;
```