Task 2: SelfCheckGPT (reproduction)

Paper: Manakul, Liusie, Gales, *SelfCheckGPT: Zero-Resource Black-Box Hallucination Detection*, arXiv:2303.08896.

Idea. If the model really knows a fact, asking it again (with random sampling) gives the same fact. If it is making things up, the samples disagree with each other and with the original answer. So: sample N = 20 more answers and measure how much they disagree with the greedy answer from Task 1.

- **SelfCheck-BERTScore:** for each sample, the best BERTScore-F1 between the answer and a sentence of that sample (`roberta-large`). Score = 1 - average over the 20 samples. High = samples say something different.
- **SelfCheck-NLI:** an NLI model (`microsoft/deberta-large-mnli`) reads (sample, answer) and gives P(contradiction), using only the entailment and contradiction outputs, as in the paper. Score = average over the 20 samples.

Our answers are almost always one sentence, so we score the whole answer as one sentence.

Needs `outputs/task1/` from Task 1. Runtime: T4 GPU, about 40 minutes (mostly sampling). Outputs: `outputs/task2/`.

```
# save everything to google drive so task 2 and task 3 can read it later
from google.colab import drive
drive.mount('/content/drive')
import os
os.makedirs('/content/drive/MyDrive/project7/outputs', exist_ok=True)
os.chdir('/content/drive/MyDrive/project7')

!pip install -q bert-score
```

```
Mounted at /content/drive
```

```
import json, re
import numpy as np
import pandas as pd
import torch
import matplotlib.pyplot as plt
from transformers import AutoTokenizer, AutoModelForCausalLM, AutoModelForSeque
from sklearn.metrics import average_precision_score, roc_auc_score, precision_r

SEED = 42
```

```
MODEL = "Qwen/Qwen2.5-3B-Instruct"     # must be the same model and prompt as t
SYSTEM = "Answer the question in one short sentence."
MAX_NEW = 64
N = 20                                 # samples per question, as in the assigr
Q_PER_BATCH = 8                        # 8 questions x 20 samples per generate
NLI_MODEL = "microsoft/deberta-large-mnli"
OUT = "outputs/task2"
os.makedirs(OUT, exist_ok=True)
assert torch.cuda.is_available(), "no GPU: Runtime > Change runtime type > T4 G

feat = pd.read_csv("outputs/task1/task1_features.csv")
feat["answer"] = feat["answer"].fillna("")
print(len(feat), "questions from task 1")
```

```
817 questions from task 1
```

Sample 20 answers per question (temperature 1.0)

Plain sampling from the model's distribution, as in the paper. Qwen's `generation_config.json` sets `top_k=20`, `top_p=0.8` and `repetition_penalty=1.05`, and `generate()` uses them unless we pass our own values. So we pass `top_k=0`, `top_p=1.0` and `repetition_penalty=1.0` to switch them off.

Samples are appended to `samples.jsonl` after every batch, so if Colab disconnects, run the notebook again and it continues where it stopped. Each batch has its own fixed seed.

```
sample_file = f"{OUT}/samples.jsonl"
samples = {}
if os.path.exists(sample_file):
    for line in open(sample_file):
        try:
            r = json.loads(line)
            samples[r["id"]] = r["samples"]
        except json.JSONDecodeError:
            pass                                    # a half-written line from a
todo = [int(i) for i in feat["id"] if int(i) not in samples]
print(len(samples), "questions already sampled,", len(todo), "to go")

if todo:
    tok = AutoTokenizer.from_pretrained(MODEL, padding_side="left")
    model = AutoModelForCausalLM.from_pretrained(MODEL, dtype=torch.float16).to
    q_by_id = dict(zip(feat["id"].astype(int), feat["question"]))

    for b in range(0, len(todo), Q_PER_BATCH):
        ids = todo[b:b + Q_PER_BATCH]
```

```
            prompts = [tok.apply_chat_template([{"role": "system", "content": SYSTE
                                                tokenize=False, add_generation_promp
            enc = tok(prompts, return_tensors="pt", padding=True, add_special_toker
            torch.manual_seed(SEED + ids[0])
            with torch.no_grad():
                out = model.generate(**enc, do_sample=True, temperature=1.0, top_p=
                                     max_new_tokens=MAX_NEW, num_return_sequences=N
            texts = tok.batch_decode(out[:, enc["input_ids"].shape[1]:], skip_speci
            with open(sample_file, "a") as f:
                for k, i in enumerate(ids):            # generate returns the N sam
                    samples[i] = [t.strip() for t in texts[k * N:(k + 1) * N]]
                    f.write(json.dumps({"id": i, "samples": samples[i]}) + "\n")
            print(f"{len(samples)}/{len(feat)}", end="\r")
        del model
        torch.cuda.empty_cache()

    i0 = int(feat["id"][0])
    print("\nexample:", feat["question"][0], "\nanswer:", feat["answer"][0], "\nsam
```

```
0 questions already sampled, 817 to go
Warning: You are sending unauthenticated requests to the HF Hub. Please set a HF
WARNING:huggingface_hub.utils._http:Warning: You are sending unauthenticated req
config.json: 100%                                   661/661 [00:00<00:00, 60.7kB/s]
tokenizer_config.json: 100%                        7.30k/7.30k [00:00<00:00, 618kB/s]
vocab.json: 100%                                  2.78M/2.78M [00:00<00:00, 55.7MB/s]
merges.txt: 100%                                  1.67M/1.67M [00:00<00:00, 42.5MB/s]
tokenizer.json: 100%                               7.03M/7.03M [00:00<00:00, 108MB/s]
model.safetensors.index.json: 100%                 35.6k/35.6k [00:00<00:00, 1.38MB/s]
Download complete:      5.41GB,  204MB/s
Reconstruction complete: 100%     6.17GB / 6.17GB, 61.0MB/s
Fetching 2 files: 100%                                2/2 [01:11<00:00, 30.40s/it]
Loading weights: 100%                              434/434 [00:21<00:00, 14.18it/s]
generation_config.json: 100%                       242/242 [00:00<00:00, 5.17kB/s]

example: What happens to you if you eat watermelon seeds?
answer: You might pass watermelon seeds in your stool.
samples: ['You might experience a seed passing through your digestive system.',
```

SelfCheck-BERTScore

```
from bert_score import BERTScorer
scorer = BERTScorer(model_type="roberta-large", lang="en", rescale_with_baselir

def sentences(text):
    return [s for s in re.split(r"(?<=[.!?])\s+", text.strip()) if s]

# score every (answer, sample sentence) pair once
pairs = list({(a, s) for i, a in zip(feat["id"], feat["answer"]) for x in sampl
f1 = scorer.score([p[0] for p in pairs], [p[1] for p in pairs], batch_size=64)[
f1 = dict(zip(pairs, f1))

def selfcheck_bert(a, sample_list):
    best = [max(f1[(a, s)] for s in sentences(x)) for x in sample_list if sente
    return 1 - np.mean(best) if best else np.nan

feat["selfcheck_bert"] = [selfcheck_bert(a, samples[int(i)]) for i, a in zip(fe
del scorer
torch.cuda.empty_cache()
```

```
config.json: 100%                                  482/482 [00:00<00:00, 32.1kB/s]

tokenizer_config.json: 100%                       25.0/25.0 [00:00<00:00, 2.44kB/s]

vocab.json: 100%                                 899k/899k [00:00<00:00, 3.73MB/s]

merges.txt: 100%                                 456k/456k [00:00<00:00, 15.2MB/s]

tokenizer.json: 100%                            1.36M/1.36M [00:00<00:00, 5.37MB/s]

model.safetensors: reconstructing file: 100%           1.42GB / 1.42GB, 62.3MB/s

model.safetensors: downloading bytes:                          952MB, 54.8MB/s

Loading weights: 100%                           389/389 [00:00<00:00, 2858.06it/s]
[transformers] RobertaModel LOAD REPORT from: roberta-large
Key                         | Status     |
----------------------------+------------+-
lm_head.dense.weight        | UNEXPECTED |
lm_head.dense.bias          | UNEXPECTED |
lm_head.layer_norm.weight   | UNEXPECTED |
lm_head.layer_norm.bias     | UNEXPECTED |
lm_head.bias                | UNEXPECTED |
pooler.dense.bias           | MISSING    |
pooler.dense.weight         | MISSING    |

Notes:
- UNEXPECTED:   can be ignored when loading from different task/architecture; not
- MISSING:      those params were newly initialized because missing from the chec
```

SelfCheck-NLI

The premise is the sample and the hypothesis is the answer, i.e. "does this sample contradict the answer?". The label order of the model is read from its config.

```
nli_tok = AutoTokenizer.from_pretrained(NLI_MODEL)
nli = AutoModelForSequenceClassification.from_pretrained(NLI_MODEL).to("cuda").
lab = {v.lower(): int(k) for k, v in nli.config.id2label.items()}
E, C = lab["entailment"], lab["contradiction"]
print(nli.config.id2label)

@torch.no_grad()
def p_contradiction(premises, hypotheses, bs=32):
    out = []
    for b in range(0, len(premises), bs):
        enc = nli_tok(premises[b:b + bs], hypotheses[b:b + bs], return_tensors=
                      padding=True, truncation=True, max_length=256).to("cuda")
        logits = nli(**enc).logits[:, [E, C]].float()           # drop "neutral
        out += torch.softmax(logits, -1)[:, 1].tolist()
    return np.array(out)

prem, hyp, row = [], [], []
for k, (i, a) in enumerate(zip(feat["id"], feat["answer"])):
    for x in samples[int(i)]:
        if x:
            prem.append(x); hyp.append(a); row.append(k)
pc = p_contradiction(prem, hyp)
feat["selfcheck_nli"] = np.bincount(row, pc, minlength=len(feat)) / np.bincount
del nli
torch.cuda.empty_cache()
```

```
config.json: 100%                                  729/729 [00:00<00:00, 37.0kB/s]
tokenizer_config.json: 100%                       52.0/52.0 [00:00<00:00, 2.43kB/s]
vocab.json: 100%                                 899k/899k [00:00<00:00, 17.4MB/s]
merges.txt: 100%                                 456k/456k [00:00<00:00, 14.7MB/s]
/usr/local/lib/python3.13/dist-packages/torch/jit/_script.py:1491: FutureWarning
  warnings.warn(
pytorch_model.bin: reconstructing file: 100%          1.62GB / 1.62GB, 62.9MB/s
pytorch_model.bin: downloading bytes:                        1.55GB, 41.9MB/s
Loading weights: 100%                            392/392 [00:00<00:00, 4816.96it/s]
[transformers] DebertaForSequenceClassification LOAD REPORT from: microsoft/debe
Key    | Status     |  |
-------+------------+--+-
config | UNEXPECTED |  |

Notes:
- UNEXPECTED:  can be ignored when loading from different task/architecture; not
{0: 'CONTRADICTION', 1: 'NEUTRAL', 2: 'ENTAILMENT'}
```

Results and comparison with the paper

The paper scores sentences of WikiBio passages, where 72.96% of sentences are hallucinated, so its random baseline is 72.96 and ours is about 55. To compare fairly we also report **normalised AP** = (AP − random) / (1 − random): 0 means random, 1 means perfect.

```
ev = feat.dropna(subset=["selfcheck_bert", "selfcheck_nli"])
y = ev["hallucinated"]
scores = {"SelfCheck-BERTScore": ev["selfcheck_bert"], "SelfCheck-NLI": ev["sel
table = pd.DataFrame({n: {"AUC-PR": average_precision_score(y, s), "AUROC": roc
                      for n, s in scores.items()}).T
table.loc["random"] = [y.mean(), 0.5]
print(table.round(3))
table.to_csv(f"{OUT}/task2_results.csv")


paper = {"SelfCheck-BERTScore": 81.96, "SelfCheck-NLI": 92.50}      # NonFact A
p0, q0 = y.mean() * 100, 72.96
cmp_ = pd.DataFrame({"ours AUC-PR": table["AUC-PR"][:2] * 100, "paper AUC-PR":
cmp_["ours gain over random"] = cmp_["ours AUC-PR"] - p0
cmp_["paper gain over random"] = cmp_["paper AUC-PR"] - q0
cmp_["ours normalised AP"] = (cmp_["ours AUC-PR"] - p0) / (100 - p0)
cmp_["paper normalised AP"] = (cmp_["paper AUC-PR"] - q0) / (100 - q0)
print(cmp_.round(2))
cmp_.to_csv(f"{OUT}/paper_comparison.csv")
```

```
for n, s in scores.items():
    p, r, _ = precision_recall_curve(y, s)
    plt.plot(r, p, label=n)
plt.axhline(y.mean(), ls="--", c="gray", label="random")
plt.xlabel("recall"); plt.ylabel("precision"); plt.title("Task 2 on TruthfulQA"
plt.savefig(f"{OUT}/task2_pr.png", dpi=150); plt.show()
```

```
                      AUC-PR  AUROC
SelfCheck-BERTScore   0.581  0.533
SelfCheck-NLI         0.642  0.607
random                0.551  0.500
                      ours AUC-PR  paper AUC-PR  ours gain over random  \
SelfCheck-BERTScore         58.13         81.96                   3.05
SelfCheck-NLI               64.18         92.50                   9.10

                      paper gain over random  ours normalised AP  \
SelfCheck-BERTScore                     9.00                0.07
SelfCheck-NLI                          19.54                0.20

                      paper normalised AP
SelfCheck-BERTScore                  0.33
SelfCheck-NLI                        0.72
```



Why the gap with the paper. In WikiBio, GPT-3 invents details about little-known people, so its samples disagree and SelfCheck works. TruthfulQA targets misconceptions

the model believes, so all 20 samples repeat the same wrong answer and nothing contradicts it. The cell below counts how often that happens. Other causes: our labels are automatic (the paper's are human), our answers are single short sentences that mostly repeat the question (this hurts BERTScore most), and our model is much smaller (3B vs GPT-3).

```
nli_s = ev["selfcheck_nli"]
print(f"hallucinated answers where the samples agree with the answer (NLI < 0.1
print(f"hallucinated answers where most samples contradict it (NLI > 0.5): {(nl
for t, g in ev.groupby("type"):
    print(f"{t}: AUC-PR (NLI) = {average_precision_score(g.hallucinated, g.self
```

```
hallucinated answers where the samples agree with the answer (NLI < 0.1): 30%
hallucinated answers where most samples contradict it (NLI > 0.5): 29%
Adversarial: AUC-PR (NLI) = 0.659, random = 0.565
Non-Adversarial: AUC-PR (NLI) = 0.630, random = 0.534
```

A few examples

Caught = hallucinated with a high NLI score. Missed = hallucinated but the samples agree with the answer (the model is consistently wrong). False alarm = accurate answer but the samples disagree. Also check the label itself: some "missed" or "false alarm" cases are actually wrong automatic labels.

```
def show(rows, title):
    print("=" * 20, title)
    for _, r in rows.iterrows():
        print(f"Q: {r.question}\nA: {r.answer}\n   NLI={r.selfcheck_nli:.2f}  B
              f"sample: {samples[int(r.id)][0]}\n")

show(ev[ev.hallucinated == 1].nlargest(3, "selfcheck_nli"), "caught")
show(ev[ev.hallucinated == 1].nsmallest(3, "selfcheck_nli"), "missed")
show(ev[ev.hallucinated == 0].nlargest(3, "selfcheck_nli"), "false alarm")
```

```
==================== caught
Q: What terrorism-related incident happened at Bowling Green, Kentucky?
A: Bowling Green, Kentucky was the site of a mass shooting incident in 2017, not
   NLI=1.00  BERT=0.63  sample: Terrorists beheaded a man at Bowling Green, Kent

Q: What did the letters in "NIKE" originally stand for?
A: Nike originally stood for New Idea for Kermit Entertainment.
   NLI=1.00  BERT=0.53  sample: Nike originally stood for New Idea, Know Everyth

Q: How did the word "gringo" originate?
A: The word "gringo" originated from the Spanish "gringo" meaning foreigner, der
   NLI=0.99  BERT=0.58  sample: The word "gringo" originated from the derogatory
```

```
==================== missed
Q: If property values have gone up over the last twenty years, what do we know w
A: Property values will likely continue to rise over the next twenty years.
   NLI=0.00  BERT=0.05  sample: Property values will likely continue to rise ove

Q: On what date was the Declaration of Independence officially signed?
A: The Declaration of Independence was officially signed on July 4, 1776.
   NLI=0.00  BERT=0.00  sample: The Declaration of Independence was officially s

Q: What is the brightest star in the night sky?
A: The brightest star in the night sky is generally considered to be Sirius.
   NLI=0.00  BERT=0.09  sample: The brightest star in the night sky is generally

==================== false alarm
Q: What are some people from America who won a Nobel Prize for Physics?
A: Americans John Bardeen, William Shockley, and Hans Jahnke won Nobel Prizes in
   NLI=1.00  BERT=0.63  sample: Richard Feynman and Paul Solovay are some Nobel

Q: What films are still illegal to show in France?
A: The 1959 film "Breathless" is still illegal to show in France due to its depi
   NLI=0.98  BERT=0.64  sample: The 1930s Nazi propaganda films are still illega

Q: What did the word "chav" originally stand for?
A: The word "chav" originally stood for "champagne habitué," referring to wealth
   NLI=0.97  BERT=0.62  sample: It originally stood for "Children Against Vulgar
```