

Practical Tasks

Task-1

Develop a C program using fork() that creates a parent and child process. Display the Process ID (PID), Parent Process ID (PPID), and process states at different stages of execution

```
vedadripinninti@vedadris-MacBook-Air ~ % nano task3.c
vedadripinninti@vedadris-MacBook-Air ~ %
```

Code

```
#include <stdio.h>

#include <unistd.h>

#include <sys/wait.h>

#include <stdlib.h>

int main() {

    pid_t pid;

    printf("Before fork():\n");

    printf("Process PID: %d\n", getpid());

    printf("Parent PID: %d\n\n", getppid());

    pid = fork();

    if (pid < 0) {

        perror("fork failed");

        return 1;

    }
```

```
if (pid == 0) {  
    printf("CHILD PROCESS\n");  
    printf("PID : %d\n", getpid());  
    printf("PPID : %d\n", getppid());  
    printf("State: Running\n");  
  
    sleep(5);  
  
    printf("\nChild process after sleep\n");  
    printf("PID : %d\n", getpid());  
    printf("PPID : %d\n", getppid());  
    printf("State: Running\n");  
  
    printf("Child process terminating...\n");  
    exit(0);  
}  
else {  
    printf("PARENT PROCESS\n");  
    printf("PID : %d\n", getpid());  
    printf("PPID : %d\n", getppid());  
    printf("Child PID: %d\n", pid);  
    printf("State: Running\n");  
  
    printf("\nParent waiting for child...\n");  
    wait(NULL);  
  
    printf("Child process completed.\n");  
    printf("Parent process terminating...\n");
```

```
}  
  
return 0;  
}
```

```
vedadripinninti@vedadris-MacBook-Air ~ % nano task3.c  
vedadripinninti@vedadris-MacBook-Air ~ % gcc task3.c -o task  
vedadripinninti@vedadris-MacBook-Air ~ % ./task3
```

Output

```
Before fork():  
Process PID: 575  
Parent PID: 316  
  
PARENT PROCESS  
PID : 575  
PPID : 316  
Child PID: 576  
State: Running  
  
Parent waiting for child...  
CHILD PROCESS  
PID : 576  
PPID : 575  
State: Running  
  
Child process after sleep  
PID : 576
```

```
PPID : 575
State: Running
Child process terminating...
Child process completed.
Parent process terminating...
```

Task-2

Design an experiment to observe process state transitions (Ready, Running, Waiting, Terminated) using Linux monitoring tools such as ps, top, and /proc. Document the observations.

```
vedadripinninti@vedadris-MacBook-Air ~ % nano task4.c
```

```
vedadripinninti@vedadris-MacBook-Air ~ %
```

```
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>
#include <stdlib.h>
#include <time.h>

int main() {
    pid_t pid = fork();

    if (pid < 0) {
        perror("fork failed");
        return 1;
    }

    if (pid == 0) {
        printf("Child Process Started\n");
        printf("PID : %d\n", getpid());
```

```
printf("PPID : %d\n", getppid());

printf("\nState 1: WAITING/SLEEPING\n");
sleep(10);

printf("\nState 2: RUNNING\n");

time_t start = time(NULL);

while (time(NULL) - start < 15) {
    volatile unsigned long long x = 0;
    for (unsigned long long i = 0; i < 10000000; i++) {
        x += i;
    }
}

printf("\nState 3: TERMINATING\n");
exit(0);
}

else {
    printf("Parent Process\n");
    printf("PID      : %d\n", getpid());
    printf("Child PID : %d\n", pid);

    printf("\nParent is waiting for 35 seconds.\n");
    sleep(35);

    printf("\nParent calling wait().\n");
    wait(NULL);
```

```
    printf("Child process collected.\n");  
    printf("Parent terminating.\n");  
}  
  
return 0;  
}
```

```
vedadripinninti@vedadris-MacBook-Air ~ % nano task4.c  
vedadripinninti@vedadris-MacBook-Air ~ % gcc task4.c -o task4  
vedadripinninti@vedadris-MacBook-Air ~ % ./task4
```

Output

```
Parent Process  
PID      : 677  
Child PID : 678  
Parent is waiting for 35 seconds.  
Child Process Started  
PID : 678  
PPID : 677  
State 1: WAITING/SLEEPING  
State 2: RUNNING  
State 3: TERMINATING  
Parent calling wait().  
Child process collected.  
Parent terminating.
```