

EDS Lab Assignments

Practical :- 3

Name: Vedant Deshmukh

PRN: 202501040046

3.1.1 Numpy Array Operations

Problem Statement:

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`
- The shape of the array using `shape`
- The total number of elements in the array using `size`

Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers `r` and `c`, representing the number of rows and the number of columns.
- The next `r` lines contain `c` space-separated integers representing the elements of the array, entered row by row.

Output Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

Code:

```
import numpy as np
rows, cols = map(int, input().split())
elements = []

for _ in range (rows):
    elements.extend(map(int, input().split()))

array = np.array(elements).reshape(rows, cols)
print(array)
print(array.ndim)
print(array.shape)
print(array.size)
```

Output:

CODETANTRA

Home Learn Anywhere

202501040046@mitaoe.ac.in Support Logout

3.1.1. Numpy Array Operations

03:52

Write a Python program to create a NumPy array based on user input and display the following:

- The created NumPy array.
- The number of dimensions of the array using `ndim`.
- The shape of the array using `shape`.
- The total number of elements in the array using `size`.

Assume all input elements are valid integers.

Input Format:

- The first line contains two space-separated integers, `r` and `c`, representing the number of rows and the number of columns.
- The next `r` lines contain `c` space-separated integers representing the elements of the array, entered row by row.

Output Format:

- The created NumPy array (printed as a 2D array).
- An integer representing the number of dimensions of the array.
- A tuple representing the shape of the array.
- An integer representing the total number of elements in the array.

Note: Use `reshape()` function to reshape the input array with the specified number of rows and columns.

Sample Test Cases

numpyarr...

Submit

Debugger

```
1 import numpy as np
2 rows, cols = map(int, input().split())
3 elements = []
4 for _ in range(rows):
5     elements.extend(map(int, input().split()))
6 array = np.array(elements).reshape(rows, cols)
7 print(array)
8 print(array.ndim)
9 print(array.shape)
10 print(array.size)
11
```

Average time

0.005 s

4.58 ms

Maximum time

0.009 s

9.00 ms

2 out of 2 shown test case(s) passed

10 out of 10 hidden test case(s) passed

Test case 1

Debug

Expected output

Actual output

3 4

3 4

1 2 3 4

1 2 3 4

5 6 7 8

5 6 7 8

9 10 11 12

9 10 11 12

[[1 2 3 4]]

[[1 2 3 4]]

[[5 6 7 8]]

[[5 6 7 8]]

Terminal

Test cases

< Prev

Reset

Submit

Next >

3.2.1 Numpy: Matrix Operations

Problem Statement:

The given code takes two 3×3 matrices, matrix_a, and matrix_b, as input from the user and converts them into NumPy arrays.

Task:

You are required to compute and display the results of the following matrix operations:

1. **Addition** (matrix_a + matrix_b)
2. **Subtraction** (matrix_a – matrix_b)
3. **Element-wise Multiplication** (matrix_a * matrix_b)
4. **Matrix Multiplication** (matrix_a · matrix_b)
5. **Transpose of Matrix A**

Input Format:

- The user will input 3 rows for matrix_a, each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for matrix_b, each containing 3 integers separated by spaces.

Output Format:

The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

Code:

```
import numpy as np

# Input matrices
print("Enter Matrix A:")
matrix_a = np.array([list(map(int, input().split())) for i in range(3)])

print("Enter Matrix B:")
matrix_b = np.array([list(map(int, input().split())) for i in range(3)])

# Addition
addition_result = matrix_a + matrix_b
print("Addition (A + B):")
print(addition_result)

# Subtraction
```

```
subtraction_result = matrix_a - matrix_b
print("Subtraction (A - B):")
print(subtraction_result)
```

```
# Multiplication (element-wise)
elementwise_multiplication_result = matrix_a * matrix_b
print("Element-wise Multiplication (A * B):")
print(elementwise_multiplication_result)
```

```
# Matrix multiplication (dot product)
matrix_multiplication_result = np.dot(matrix_a, matrix_b)
print("A dot B:")
print(matrix_multiplication_result)
```

```
# Transpose
transpose_a = matrix_a.T
print("Transpose of A:")
print(transpose_a)
```

Output:

3.2.1. Numpy: Matrix Operations

The given code takes two 3×3 matrices, `matrix_a`, and `matrix_b`, as input from the user and converts them into NumPy arrays.

Task:
You are required to compute and display the results of the following matrix operations:

1. Addition (`matrix_a + matrix_b`)
2. Subtraction (`matrix_a - matrix_b`)
3. Element-wise Multiplication (`matrix_a * matrix_b`)
4. Matrix Multiplication (`matrix_a . matrix_b`)
5. Transpose of Matrix A

Input Format:

- The user will input 3 rows for `matrix_a`, each containing 3 integers separated by spaces.
- Similarly, the user will input 3 rows for `matrix_b`, each containing 3 integers separated by spaces.

Output Format:
The program should display the results of the operations in the following order:

1. The result of Addition.
2. The result of Subtraction.
3. The result of Element-wise Multiplication.
4. The result of Matrix Multiplication.
5. The Transpose of Matrix A.

Sample Test Cases

matrixOp.py

```
1 import numpy as np
2
3 # Input matrices
4 print("Enter Matrix A:")
5 matrix_a = np.array([list(map(int, input().split())) for i in range(3)])
6
7 print("Enter Matrix B:")
8 matrix_b = np.array([list(map(int, input().split())) for i in range(3)])
9
10 Add=matrix_a+matrix_b
11 # Addition
12 print("Addition (A + B):")
13 print(Add)
14 # Subtraction
15 sub=matrix_a-matrix_b
16 print("Subtraction (A - B):")
17 print(sub)
18 # Multiplication (element-wise)
19 multi=matrix_a*matrix_b
20 print("Element-wise Multiplication (A * B):")
```

Average time: 0.008 s, Maximum time: 0.010 s
2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1

Expected output	Actual output
Enter Matrix A: 1 2 3	Enter Matrix A: 1 2 3
4 5 6	4 5 6
7 8 9	7 8 9
Enter Matrix B: 1 1 1	Enter Matrix B: 1 1 1

Terminal | Test cases

< Prev | Next >

3.2.2 Numpy: Horizontal and Vertical Stacking of Arrays

Problem Statement:

You are given two arrays arr1 and arr2. You need to perform horizontal and vertical stacking operations on them using NumPy.

- **Horizontal Stacking:** Stack the two matrices horizontally (side by side).
- **Vertical Stacking:** Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

Code:

```
import numpy as np

# Input matrices
print("Enter Array1:")
arr1 = np.array([list(map(int, input().split())) for i in range(3)])

print("Enter Array2:")
arr2 = np.array([list(map(int, input().split())) for i in range(3)])

# Perform horizontal stacking (hstack)
a = np.hstack((arr1, arr2))
print("Horizontal Stack:")
print(a)

# Perform vertical stacking (vstack)
b = np.vstack((arr1, arr2))
print("Vertical Stack:")
print(b)
```

Output:

CODETANTRA

HomeLearn Anywhere

202501040046@mitaoe.ac.inSupportLogout

3.2.2. Numpy: Horizontal and Vertical Stacking of Arrays

0.517

You are given two arrays `arr1` and `arr2`. You need to perform horizontal and vertical stacking operations on them using NumPy.

- Horizontal Stacking**: Stack the two matrices horizontally (side by side).
- Vertical Stacking**: Stack the two matrices vertically (one below the other).

Input Format:

- The program should first prompt the user to input two 3x3 arrays.
- Each array consists of 3 rows, and each row contains 3 space-separated integers.
- The user will input the two arrays row by row.

Output Format:

- The program should display the result of the Horizontal Stack (side-by-side stacking) of the two arrays.
- The program should then display the result of the Vertical Stack (one below the other) of the two arrays.

Sample Test Cases

stacking.py

```
1 import numpy as np
2
3 # Input matrices
4 print("Enter Array1:")
5 arr1 = np.array([list(map(int, input().split())) for i in range(3)])
6
7 print("Enter Array2:")
8 arr2 = np.array([list(map(int, input().split())) for i in range(3)])
9
10 # Perform horizontal stacking (hstack)
11 a=np.hstack((arr1,arr2))
12 print("Horizontal Stack:")
13 print(a)
14 # Perform vertical stacking (vstack)
15 b=np.vstack((arr1,arr2))
16 print("Vertical Stack:")
17 print(b)
```

Average time0.009 s9.25 ms

Maximum time0.014 s14.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 114 ms

Debug

Expected output

Actual output

Enter Array1:
1 2 3
4 5 6
7 8 9
Enter Array2:
4 5 6

Enter Array1:
1 2 3
4 5 6
7 8 9
Enter Array2:
4 5 6

Terminal

Test cases

< Prev

Reset

Submit

Next >

3.2.3 Numpy: Custom Sequence Generation

Problem Statement:

Write a Python program that takes the following inputs from the user:

- Start value: The starting point of the sequence.
- Stop value: The sequence should end before this value.
- Step value: The increment between each number in the sequence.

The program should then generate a sequence using numpy based on these inputs and print the generated sequence.

Input Format:

- The user will input three integer values: start, stop, and step, each on a new line.

Output Format:

- The program should print the generated sequence based on the input values.

Code:

```
import numpy as np
# Take user input for the start, stop, and step of the sequence
start = int(input())
stop = int(input())
step = int(input())
# Generate the sequence using np.arange()
a = np.arange(start, stop, step)
# Print the generated sequence
print(a)
```

Output:

The screenshot displays the CodeTANTRA IDE interface. On the left, the problem statement for '3.2.3. Numpy: Custom Sequence Generation' is shown, detailing the requirements for a Python program that generates a sequence using numpy.arange(). The input format specifies three integer values (start, stop, step) on separate lines, and the output format requires printing the generated sequence. Below the problem statement is a 'Sample Test Cases' section.

The main editor area shows the following Python code:

```
1 import numpy as np
2
3 # Take user input for the start, stop, and step of the sequence
4 start = int(input())
5 stop = int(input())
6 step = int(input())
7
8 # Generate the sequence using np.arange()
9 print(np.arange(start, stop, step))
10 # Print the generated sequence
11
```

At the bottom right, the test runner indicates that all tests passed:

- Average time: 0.007 s, Maximum time: 0.010 s
- 2 out of 2 shown test case(s) passed
- 2 out of 2 hidden test case(s) passed

Test case 1 details:

Expected output	Actual output
3	3
18	18
2	2
[3 5 7 9]	[3 5 7 9]

Test case 2 is also marked as passed. The interface includes navigation buttons at the bottom: < Prev, Reset, Submit, and Next >.

3.2.4 Numpy: Arithmetic and Statistical Operations, Mathematical Operations and Bitwise Operators

Problem Statement:

You are given two arrays A and B. Your task is to complete the function `array_operations`, which will convert these lists into NumPy arrays and perform the following operations:

1. Arithmetic Operations:

- Compute the element-wise sum, difference, and product of the two arrays.

2. Statistical Operations:

- Calculate the mean, median, and standard deviation of array A.

3. Bitwise Operations:

- Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: $A_i \text{ OR } B_i$).

Input Format:

- The first line contains space-separated integers representing the elements of array A.
- The second line contains space-separated integers representing the elements of array B.

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

Code:

```
import numpy as np

def array_operations(A, B):
    # Convert A and B to NumPy arrays
    A = np.array(A)
    B = np.array(B)

    # Arithmetic Operations
    sum_result = A + B
    diff_result = A - B
    prod_result = A * B

    # Statistical Operations
    mean_A = np.mean(A)
    median_A = np.median(A)
```

```
std_dev_A = np.std(A)
```

```
# Bitwise Operations
```

```
and_result = A & B
```

```
or_result = A | B
```

```
xor_result = A ^ B
```

```
# Output results with one space between each element
```

```
print("Element-wise Sum:", ' '.join(map(str, sum_result)))
```

```
print("Element-wise Difference:", ' '.join(map(str, diff_result)))
```

```
print("Element-wise Product:", ' '.join(map(str, prod_result)))
```

```
print(f"Mean of A: {mean_A}")
```

```
print(f"Median of A: {median_A}")
```

```
print(f"Standard Deviation of A: {std_dev_A}")
```

```
    print("Bitwise AND:", ' '.join(map(str, and_result)))
```

```
print("Bitwise OR:", ' '.join(map(str, or_result)))
```

```
print("Bitwise XOR:", ' '.join(map(str, xor_result)))
```

```
A = list(map(int, input().split())) # Elements of array A
```

```
B = list(map(int, input().split())) # Elements of array B
```

```
array_operations(A, B)
```

Output:

3.2.4. Numpy: Arithmetic and Statistical Operations, Mathematical Operations, Bitwise Operators

You are given two arrays A and B . Your task is to complete the function `array_operations`, which will convert these lists into NumPy arrays and perform the following operations:

- Arithmetic Operations:**
 - Compute the element-wise sum, difference, and product of the two arrays.
- Statistical Operations:**
 - Calculate the mean, median, and standard deviation of array A .
- Bitwise Operations:**
 - Perform bitwise AND, bitwise OR, and bitwise XOR on the arrays (ex: A_1 OR B_1).

Input Format:

- The first line contains space-separated integers representing the elements of array A .
- The second line contains space-separated integers representing the elements of array B .

Output Format:

- For each operation (arithmetic, statistical, and bitwise), print the results in the specified format as shown in sample test cases.

Sample Test Cases

```
1 import numpy as np
2
3 def array_operations(A, B):
4
5     # Convert A and B to NumPy arrays
6     A = np.array(A)
7     B = np.array(B)
8
9     # Arithmetic Operations
10    sum_result = A+B
11    diff_result = A-B
12    prod_result = A*B
13
14    # Statistical Operations
15    mean_A = np.mean(A)
16    median_A = np.median(A)
17    std_dev_A = np.std(A)
18
19    # Bitwise Operations
20    and_result = A & B
21    or_result = A | B
```

Test Results:

Test Case	Expected output	Actual output
Test case 1	1 2 3 4	1 2 3 4
Test case 2	5 6 7 8	5 6 7 8
Test case 3	Element-wise Sum: 6 8 10 12	Element-wise Sum: 6 8 10 12
Test case 4	Element-wise Difference: -4 -4 -4 -4	Element-wise Difference: -4 -4 -4 -4
Test case 5	Element-wise Product: 5 12 21 32	Element-wise Product: 5 12 21 32
Test case 6	Mean of A: 2.5	Mean of A: 2.5

3.2.5 Numpy: Copying and Viewing Arrays

Problem Statement:

The given code takes a list of integers as input and converts it into a NumPy array.

Your task is to complete the code by:

- Creating a view of the `original_array` and assigning it to `view_array`.
- Creating a copy of the `original_array` and assigning it to `copy_array`.

After completing these steps, observe how modifying the view affects the `original_array`, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:
Original array after modifying view: **<original_array>**
View array: **<view_array>**
- After modifying the copy:
Original array after modifying copy: **<original_array>**
Copy array: **<copy_array>**

Code:

```
import numpy as np
inputlist = list(map(int,input().split(" ")))

# Original array
original_array = np.array(inputlist)

# Create a view
view_array = original_array.view()

# Create a copy
copy_array = original_array.copy()

# Modify the view
view_array[0] = 99
print("Original array after modifying view:", original_array)
print("View array:", view_array)

# Modify the copy
copy_array[1] = 88
print("Original array after modifying copy:", original_array)
print("Copy array:", copy_array)
```

Output:

3.2.5. Numpy: Copying and Viewing Arrays

The given code takes a list of integers as input and converts it into a NumPy array. Your task is to complete the code by:

- Creating a view of the original_array and assigning it to view_array.
- Creating a copy of the original_array and assigning it to copy_array.

After completing these steps, observe how modifying the view affects the original_array, while modifying the copy does not.

Input Format:

- A single line of space-separated integers.

Output Format:

- After modifying the view:

Original array after modifying view: <original_array>
View array: <view_array>

- After modifying the copy:

Original array after modifying copy: <original_array>
Copy array: <copy_array>

Sample Test Cases

copyAnd...

```
1 import numpy as np
2
3 inputlist = list(map(int,input().split(" ")))
4
5 # Original array
6 original_array = np.array(inputlist)
7
8 # Create a view
9 view_array = original_array.view()
10
11 # Create a copy
12 copy_array = original_array.copy()
13
14 # Modify the view
15 view_array[0] = 99
16 print("Original array after modifying view:", original_array)
17 print("View array:", view_array)
18
19 # Modify the copy
20 copy_array[1] = 88
```

Average time

0.004 s

3.50 ms

Maximum time

0.006 s

6.00 ms

2 out of 2 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1

Expected output

10 20 30 40 50 60 70 80

Original array after modifying view: [99 20 30 40 50 60 70 80]

View array: [99 20 30 40 50 60 70 80]

Original array after modifying copy: [99 20 30 40 50 60 70 80]

Copy array: [10 88 30 40 50 60 70 80]

Actual output

10 20 30 40 50 60 70 80

Original array after modifying view: [99 20 30 40 50 60 70 80]

View array: [99 20 30 40 50 60 70 80]

Original array after modifying copy: [99 20 30 40 50 60 70 80]

Copy array: [10 88 30 40 50 60 70 80]

3.2.6 Searching, Sorting, Counting, Broadcasting

Problem Statement:

The given code in the editor takes a single array, array1, as space-separated integers as input from the user.

Additionally, it takes the following inputs:

- search_value: The value to search for in the array.
- count_value: The value to count its occurrences in the array.
- broadcast_value: The value to add for broadcasting across the array.

You need to complete the code to perform the following operations:

- 1. Searching:** Find the indices where search_value appears in array1 and print these indices.
- 2. Counting:** Count how many times count_value appears in array1 and print the count.
- 3. Broadcasting:** Add broadcast_value to each element of array1 using broadcasting, and print the resulting array.
- 4. Sorting:** Sort array1 in ascending order and print the sorted array.

Input Format:

1. A single line containing space-separated integers representing array1.
2. An integer search_value represents the value to search for in the array.
3. An integer count_value represents the value to count in the array.
4. An integer broadcast_value represents the value to add to each element of the array.

Output Format:

1. The indices where search_value occurs in array1.
2. The count of occurrences of count_value in array1.
3. The array after adding the broadcast_value to each element.
4. The sorted array.

Code:

```
import numpy as np

# Input array from the user
array1 = np.array(list(map(int, input().split())))

# Searching
search_value = int(input("Value to search: "))
count_value = int(input("Value to count: "))
broadcast_value = int(input("Value to add: "))

# Find indices where value matches in array1
a = np.where(array1 == search_value)[0]
print(a)
```

```
# Count occurrences in array1
b = np.count_nonzero(array1 == count_value)
print(b)
```

```
# Broadcasting addition
c = array1 + broadcast_value
print(c)
```

```
# Sort the first array
d = np.sort(array1)
print(d)
```

Output:

The screenshot displays the CodeTANTRA IDE interface. The left sidebar contains a table of contents for a chapter on NumPy, with '3.2.5. Numpy: Searching, Sorting, Counting, Broadcasting' selected. The main editor area shows a Python script with the following code:

```
1 import numpy as np
2
3 # Input array from the user
4 array1 = np.array(list(map(int, input().split()))))
5
6 # Searching
7 search_value = int(input("Value to search: "))
8 count_value = int(input("Value to count: "))
9 broadcast_value = int(input("Value to add: "))
10
11 # Find indices where value matches in array1
12 a=np.where(array1==search_value)[0]
13 print(a)
14 # Count occurrences in array1
15 b=np.count_nonzero(array1==count_value)
16 print(b)
17 # Broadcasting addition
18 c=array1+broadcast_value
19 print(c)
20 # Sort the first array
21 d=np.sort(array1)
22 print(d)
```

Below the code editor, there is a 'Terminal' tab and a 'Test cases' tab. The 'Test cases' tab is active, showing a list of sample test cases:

- 1. A single line containing space-separated integers representing array1.
- 2. An integer search_value represents the value to search for in the array.
- 3. An integer count_value represents the value to count in the array.
- 4. An integer broadcast_value represents the value to add to each element of the array.

The bottom of the IDE shows navigation buttons: < Prev, Reset, Submit, and Next >.

3.2.7 Student Data Analysis and Operations

Problem Statement:

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details:** Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students:** Determine the total number of students in the dataset.
- **Print all student roll numbers:** Extract and print the roll numbers of all students.
- **Print Subject 1 marks:** Extract and print the marks of all students in Subject 1.
- **Find minimum marks in Subject 2:** Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3:** Identify the highest marks in Subject 3.
- **Print all subject marks:** Display the marks of all students for each subject.
- **Find total marks of students:** Compute the total marks for each student across all subjects.
- **Find the average marks of each student:** Compute the average marks for each student.
- **Find average marks of each subject:** Compute the average marks for all students in each subject.
- **Find average marks of Subject 1 and Subject 2:** Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3:** Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of the student with maximum marks in Subject 3:** Identify the student with the highest marks in Subject 3 and print their roll number.
- **Find the roll number of the student with minimum marks in Subject 2:** Identify the student with the lowest marks in Subject 2 and print their roll number.
- **Find the roll number of students who scored 24 marks in Subject 2:** Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
- **Find the count of students who got less than 40 marks in Subject 1:** Count the number of students who scored less than 40 marks in Subject 1.
- **Find the count of students who got more than 90 marks in Subject 2:** Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored ≥ 90 in each subject:** Count the number of students who scored 90 or more marks in each subject.
- **Find the count of subjects in which each student scored ≥ 90 :** Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order:** Sort and print the marks of students in Subject 1 in ascending order.

- **Print students who scored between 50 and 90 in Subject 1:** Display students who scored marks between 50 and 90 in Subject 1.
- **Find index positions of students who scored 79 in Subject 1:** Identify the index positions of students who scored exactly 79 marks in Subject 1.

Code:

```
import numpy as np
```

```
a = np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
```

```
roll = a[:, 0].astype(float)
```

```
s1 = a[:, 1]
```

```
s2 = a[:, 2]
```

```
s3 = a[:, 3]
```

```
# 1. Print all student details
```

```
print("All student Details:\n", a)
```

```
# 2. print total students
```

```
print("Total Students:", len(a))
```

```
# 3. Print all student Roll numbers
```

```
print("All Student Roll Nos", roll)
```

```
# 4. Print subject 1 marks
```

```
print("Subject 1 Marks", s1)
```

```
# 5. print minimum marks of Subject 2
```

```
print("Min marks in Subject 2", np.min(s2))
```

```
# 6. print maximum marks of Subject 3
```

```
print("Max marks in Subject 3", np.max(s3))
```

```
# 7. Print All subject marks
```

```
print("All subject marks:", a[:, 1:])
```

```
# 8. print Total marks of students
```

```
total = s1 + s2 + s3
```

```
print("Total Marks", total)
```

```
# 9. print average marks of each student
```

```
print(np.round(total/3, 1))
```

```
# 10. print average marks of each subject
```

```
print("Average Marks of each subject", np.mean(a[:, 1:], axis = 0))
```

```
# 11. print average marks of S1 and S2
```

```

print("Average Marks of S1 and S2", np.mean([s1, s2], axis = 1))

# 12. print average marks of S1 and S3
print("Average Marks of S1 and S3", np.mean([s1, s3], axis = 1))

# 13. print Roll number who got maximum marks in Subject 3
print("Roll no who got maximum marks in Subject 3", float(roll[np.argmax(s3)]))

# 14. print Roll number who got minimum marks in Subject 2
print("Roll no who got minimum marks in Subject 2", float(roll[np.argmin(s2)]))

# 15. print Roll number who got 24 marks in Subject 2
print("Roll no who got 24 marks in Subject 2", roll[s2 == 24].astype(float).reshape(1, -1))

# 16. print count of students who got marks in Subject 1 < 40
print("Count of students who got marks in Subject 1 < 40", np.sum(s1 < 40))

# 17. print count of students who got marks in Subject 2 > 90
print("Count of students who got marks in Subject 2 > 90:", np.sum(s2 > 90))

# 18. print count of students in each subject who got marks >= 90
print("Count of students in each subject who got marks >= 90:", np.sum(a[:, 1:] >= 90, axis = 0))

# 19. print count of subjects in which each student got marks >= 90
print("Roll no:", roll)
print("Count of subjects in which student got marks >= 90:", np.sum(a[:, 1:] >= 90, axis = 1))

# 20. Print S1 marks in ascending order
print(np.sort(s1))

# 21. Print S1 marks >= 50 and <= 90
print(a[(s1 >= 50) & (s1 <= 90)].astype(float))
print(a.astype(float))

# 22. Print the index position of marks 79
print(np.where(s1 == 79))

```

Output:

3.2.7. Student Data Analysis and Operations

Write a Python program that takes the file name of a CSV file containing student details, including roll numbers and their marks in three subjects as input, reads the data, and performs the following operations:

- **Print all student details:** Display the complete details of all students, including roll numbers and marks for all subjects.
- **Find total students:** Determine the total number of students in the dataset.
- **Print all student roll numbers:** Extract and print the roll numbers of all students.
- **Print Subject 1 marks:** Extract and print the marks of all students in Subject 1.
- **Find minimum marks in Subject 2:** Identify the lowest marks in Subject 2.
- **Find maximum marks in Subject 3:** Identify the highest marks in Subject 3.
- **Print all subject marks:** Display the marks of all students for each subject.
- **Find total marks of students:** Compute the total marks for each student across all subjects.
- **Find the average marks of each student:** Compute the average marks for each student.
- **Find average marks of each subject:** Compute the average marks for all students in each subject.
- **Find average marks of Subject 1 and Subject 2:** Compute the average marks for Subject 1 and Subject 2.
- **Find average marks of Subject 1 and Subject 3:** Compute the average marks for Subject 1 and Subject 3.
- **Find the roll number of the student with maximum marks in Subject 3:** Identify the student with the highest marks in Subject 3 and print their roll number.
- **Find the roll number of the student with minimum marks in Subject 2:** Identify the student with the lowest marks in Subject 2 and print their roll number.
- **Find the roll number of students who scored 24 marks in Subject 2:** Identify students who obtained exactly 24 marks in Subject 2 and print their roll numbers.
- **Find the count of students who got less than 40 marks in Subject 1:** Count the number of students who scored less than 40 marks in Subject 1.
- **Find the count of students who got more than 90 marks in Subject 2:** Count the number of students who scored more than 90 marks in Subject 2.
- **Find the count of students who scored >=90 in each subject:** Count the number of students who scored 90 or more marks in each subject.
- **Find the count of subjects in which each student scored >=90:** Determine how many subjects each student scored 90 or more marks in.
- **Print Subject 1 marks in ascending order:** Sort and print the marks of students in Subject 1 in ascending order.
- **Print students who scored between 50 and 90 in Subject 1:** Display students who scored marks between 50 and 90 in Subject 1.
- **Find index positions of students who scored 79 in Subject 1:** Identify the index positions of students who scored exactly 79 marks in Subject 1.

Note: Fill in the missing code to perform the above-mentioned operations.

Sample Test Cases

Operation...

```
1 import numpy as np
2
3 a = np.loadtxt("Sample.csv", delimiter=',', skiprows=1)
4
5 print("All student Details:\n", a)
6
7 total_students = a.shape[0]
8 print("Total Students:", total_students)
9
10 roll_numbers = a[:, 0]
11 print("All Student Roll Nos", roll_numbers)
12
13 subject_1_marks = a[:, 1]
14 print("Subject 1 Marks", subject_1_marks)
15
16 min_marks_subject_2 = np.min(a[:, 2])
17 print("Min marks in Subject 2", round(min_marks_subject_2, 1))
18
19 max_marks_subject_3 = np.max(a[:, 3])
20 print("Max marks in Subject 3", round(max_marks_subject_3, 1))
21
22 print("All subject marks:", a[:, 1:])
23
24 total_marks = np.sum(a[:, 1:], axis=1)
25 print("Total Marks", total_marks)
26
```

Average time

0.010 s

10.00 ms

Maximum time

0.010 s

10.00 ms

1 out of 1 shown test case(s) passed

Test case 1

10 ms

Debug

Test cases

Expected output

All student Details:

[[301...67...77...88...]

[302...78...88...77...]

[303...45...56...89...]

[304...88...98...45...]

[305...78...88...99...]

**** ** ** *

Actual output

All student Details:

[[301...67...77...88...]

[302...78...88...77...]

[303...45...56...89...]

[304...88...98...45...]

[305...78...88...99...]

**** ** ** *

Terminal

Test cases

< Prev Reset Submit Next >