

Database Transactions and Query Processing

1. Collections of operations that form a single logical unit of work are called _____

- a) Views
- b) Networks
- c) Units
- d) Transactions**

2. The “all-or-none” property is commonly referred to as _____

- a) Isolation
- b) Durability
- c) Atomicity**
- d) None of the mentioned

3. Which of the following is a property of transactions?

- a) Atomicity
- b) Durability
- c) Isolation
- d) All of the mentioned**

4. Execution of transaction in isolation preserves the _____ of a database

- a) Atomicity
- b) Consistency**
- c) Durability
- d) All of the mentioned

5. Which of the following systems is responsible for ensuring durability?

a) Recovery system

b) Atomic system

c) Concurrency control system

d) Compiler system

6. Which of the following is not a transaction state?

a) Active

b) Partially committed

c) Failed

d) Compensated

7. The execution sequences in concurrency control are termed as _____

a) Serials

b) Schedules

c) Organizations

d) Time tables

8. The scheme that controls the interaction between executing transactions is called as _____

a) Concurrency control scheme

b) Multiprogramming scheme

c) Serialization scheme

d) Schedule scheme

9. The deadlock in a set of transaction can be determined by

- a. Read-only graph**
- b. Wait graph
- c. Wait-for graph
- d. All of the mentioned

10 A deadlock exists in the system if and only if the wait-for graph contains a _____.

- a. Cycle**
- b. Direction
- c. Bi-direction
- d. Rotation

11 _____ rollback requires the system to maintain additional information about the state of all the running transactions.

- a. Total
- b. Partial**
- c. Time
- d. Commit

12. A transaction for which all committed changes are permanent is called:

- a. atomic
- b. consistent
- c. isolated
- d. durable**

13. In this instance, dirty reads are disallowed, while nonrepeatable reads and phantom reads are allowed.

a. Read committed

b. Read uncommitted

c. Repeatable read

d. Serializable

14. A transaction may not always complete its execution successfully. Such a transaction is termed

a. Aborted

b. Terminated

c. Closed

d. All of the mentioned

15. Transaction management ensures _____ and _____ properties.

a. Atomicity and Integrity

b. Atomicity and Durability

c. Atomicity and Abstraction

d. None of these

16. _____ is an interface between low level database and application program.

a. Database Associator

b. Database Server

c. Database Manage

d. None of these

17. Who detects the failure of the system and restore the database to consistent state ?

- a. Database Administrator
- b. Application Programmer
- c. Naive User
- d. Storage Manager**

18. Which of the following is the preferred way to recover a database after a transaction in progress terminates abnormally?

- a. Rollback**
- b. Rollforward
- c. Switch to duplicate database
- d. Reprocess transactions

19. Which of the following is the preferred way to recover a database after a system failure?

- a. Rollback
- b. Rollforward
- c. Switch to duplicate database**
- d. Reprocess transactions

20. A shared lock allows which of the following types of transactions to occur?

- a. Delete
- b. Insert
- c. Read**
- d. Update

21. A transaction that performs only one operation is called as a _____

a) Partial schedule

b) Complete schedule

c) Dependent schedule

d) Independent schedule

22. The phenomenon in which one failure leads to a series of transaction rollbacks is called as _____

a) Cascading rollback

b) Cascadeless rollback

c) Cascade cause

d) None of the mentioned

23. State true or false: Every cascadeless schedule is also recoverable

a) True

b) False

24. Which of the following are the advantages of transaction concurrency?

a) Increased throughput

b) Increased utilization

c) Reduces average response time

d) All of the mentioned

25. If a schedule is equivalent to a serial schedule, it is called as a _____

a) Serializable schedule

b) Equivalent schedule

c) Committed schedule

d) None of the mentioned

26. Which of the following is not a type of a schedule?

- a) Partial schedule
- b) Dependent schedule
- c) Recoverable schedule
- d) None of the mentioned**

27. If a transaction has obtained a _____ lock, it can read but cannot write on the item

- a) Shared mode**
- b) Exclusive mode
- c) Read only mode
- d) Write only mode

28. A transaction can proceed only after the concurrency control manager _____ the lock to the transaction

- a) Grants**
- b) Requests
- c) Allocates
- d) None of the mentioned

29. The situation where no transaction can proceed with normal execution is known as _____

- a) Road block
- b) Deadlock**
- c) Execution halt
- d) Abortion

30. The log is a sequence of _____ recording all the update activities in the database.

a) Log records

b) Records

c) Entries

d) Redo

31. The current copy of the database is identified by a pointer, called _____ which is stored on disk.

a) Db-pointer

b) Update log

c) Update log records

d) All of the mentioned

32. If a transaction does not modify the database until it has committed, it is said to use the _____ technique.

a) Deferred-modification

b) Late-modification

c) Immediate-modification

d) Undo

33. In the _____ phase, the system replays updates of all transactions by scanning the log forward from the last checkpoint.

a) Repeating

b) Redo

c) Replay

d) Undo

34. Which of the following is not a recovery technique?

- a. Deferred update
- b. Immediate update
- c. Two-phase commit**
- d. Recovery management

35. Checkpoints are a part of

- a. Recovery measures**
- b. Security measures
- c. Concurrency measures
- d. Authorization measures

36. deals with soft errors, such as power failures.

- a. system recovery
- b. media recovery
- c. database recovery
- d. failure recovery**

37. Which commands are used to control which users have which privilege over which objects ?

- a. QUE and QUIST
- b. GRANT and REVOKE**
- c. CASECADE and MVD
- d. None of the above

38. Which of the following are steps in query processing?

- a) Parsing and translation
- b) Optimization
- c) Evaluation
- d) All of the mentioned**

39. A sequence of primitive operations that can be used to evaluate a query are called as _____

- a) Query evaluation algebra
- b) Query evaluation plan**
- c) Query evaluation primitive
- d) Query evaluation engine

40. Sorting of relations that do not fit in memory is called as _____

- a) Internal sorting
- b) External sorting**
- c) Overflow sorting
- d) Overload sorting

41. A system is in a _____ state if there exists a set of transactions in which every transaction is waiting for another transaction in the set.

- a) Deadlock**
- b) Starved
- c) Isolated
- d) None of the mentioned

42. Which of the following is not a method in deadlock handling

- a) Deadlock prevention
- b) Deadlock detection
- c) Deadlock recovery
- d) Deadlock distribution**

43. Deadlocks can be prevented using

- a) Preemption and transaction rollbacks
- b) Wait and die scheme
- c) Wound-wait scheme
- d) All of the mentioned**

44. State true or false: Wait die scheme is a non-preemptive technique

- a) True**
- b) False

45. Lock timeouts have which of the following advantages?

- a) Unnecessary rollbacks do not occur
- b) Transactions do not starve
- c) It is easy to implement
- d) All of the mentioned**

46. The _____ graph describes deadlocks precisely

- a) Wound wait graph
- b) Wait die graph
- c) Wait for graph**
- d) None of the mentioned

47. How do we generally recover from a deadlock?

- a) By aborting all the transactions
- b) By rolling back all the transactions
- c) By rolling back only a selected number of transactions**
- d) None of the mentioned

48. State true or false: Partial rollback is not possible.

- a) True
- b) False**

49. Which of the following steps must be taken while choosing a victim?

- a) Avoiding starvation
- b) Number of transactions involved in rollback
- c) Data items used by the transaction
- d) All of the mentioned**

50. Which of the following cannot be used to implement a timestamp

- a) System clock
- b) Logical counter
- c) External time counter**
- d) None of the mentioned

51. A logical counter is _____ after a new timestamp has been assigned

- a) Incremented**
- b) Decremented
- c) Doubled
- d) Remains the same

52. W-timestamp(Q) denotes?

- a) The largest timestamp of any transaction that can execute write(Q) successfully**
- b) The largest timestamp of any transaction that can execute read(Q) successfully
- c) The smallest timestamp of any transaction that can execute write(Q) successfully
- d) The smallest timestamp of any transaction that can execute read(Q) successfully

53. R-timestamp(Q) denotes?

- a) The largest timestamp of any transaction that can execute write(Q) successfully
- b) The largest timestamp of any transaction that can execute read(Q) successfully**
- c) The smallest timestamp of any transaction that can execute write(Q) successfully
- d) The smallest timestamp of any transaction that can execute read(Q) successfully

54. A _____ ensures that any conflicting read and write operations are executed in timestamp order

- a) Organizational protocol
- b) Timestamp ordering protocol**
- c) Timestamp execution protocol
- d) 802-11 protocol

55. The default timestamp ordering protocol generates schedules that are

a) Recoverable

b) Non-recoverable

c) Starving

d) None of the mentioned

56. State true or false: The Thomas write rule has a greater potential concurrency than the timestamp ordering protocol

a) True

b) False

57. Which of the following timestamp based protocols generates serializable schedules?

a) Thomas write rule

b) Timestamp ordering protocol

c) Validation protocol

d) None of the mentioned

58. In timestamp ordering protocol, suppose that the transaction T_i issues $\text{read}(Q)$ and $TS(T_i) < W\text{-timestamp}(Q)$, then

a) Read operation is executed

b) Read operation is rejected

c) Write operation is executed

d) Write operation is rejected

59. In timestamp ordering protocol, suppose that the transaction T_i issues $\text{write}(Q)$ and $\text{TS}(T_i) < W\text{-timestamp}(Q)$, then

a) Read operation is executed

b) Read operation is rejected

c) Write operation is executed

d) Write operation is rejected

60. _____ is a procedural extension of Oracle – SQL that offers language constructs similar to those in imperative programming languages.

a) SQL

b) PL/SQL

c) Advanced SQL

d) PQL

61. _____ combines the data manipulating power of SQL with the data processing power of Procedural languages.

a) PL/SQL

b) SQL

c) Advanced SQL

d) PQL

62. _____ has made PL/SQL code run faster without requiring any additional work on the part of the programmer.

a) SQL Server

b) My SQL

c) Oracle

d) SQL Lite

63. A line of PL/SQL text contains groups of characters known as

a) Lexical Units

b) Literals

c) Textual Units

d) Identifiers

64. We use _____ name PL/SQL program objects and units.

a) Lexical Units

b) Literals

c) Delimiters

d) Identifiers

65. A _____ is an explicit numeric, character, string or Boolean value not represented by an identifier.

a) Comments

b) Literals

c) Delimiters

d) Identifiers.

66. If no header is specified, the block is said to be an _____ PL/SQL block.

a) Strong

b) Weak

c) Empty

d) Anonymous

67. _____ is a sequence of zero or more characters enclosed by single quotes.

a) Integers literal

b) String literal

c) String units

d) String label

68. In _____ the management of the password for the account can be handled outside of oracle such as operating system.

a) Database Authentication

b) Operating System Authentication

c) Internal Authentication

d) External Authentication

69. In _____ of Oracle, the database administrator creates a user account in the database for each user who needs access.

a) Database Authentication

b) Operating System Authentication

c) Internal Authentication

d) External Authentication

70. Consider money is transferred from (1)account-A to account-B and (2) account-B to account-A. Which of the following form a transaction?

a) Only 1

b) Only 2

c) Both 1 and 2 individually

d) Either 1 or 2

71. A transaction is delimited by statements (or function calls) of the form _____

a) Begin transaction and end transaction

b) Start transaction and stop transaction

c) Get transaction and post transaction

d) Read transaction and write transaction

72. Identify the characteristics of transactions

a) Atomicity

b) Durability

c) Isolation

d) All of the mentioned

73. Which of the following has “all-or-none” property?

a) Atomicity

b) Durability

c) Isolation

d) All of the mentioned

74. The database system must take special actions to ensure that transactions operate properly without interference from concurrently executing database statements. This property is referred to as

a) Atomicity

b) Durability

c) Isolation

d) All of the mentioned

75. The property of a transaction that persists all the crashes is

- a) Atomicity
- b) Durability**
- c) Isolation
- d) All of the mentioned

76. _____ states that only valid data will be written to the database.

- a) Consistency**
- b) Atomicity
- c) Durability
- d) Isolation

77. Transaction processing is associated with everything below except

- a) Producing detail summary or exception reports
- b) Recording a business activity
- c) Confirming an action or triggering a response**
- d) Maintaining a data

78. The Oracle RDBMS uses the ____ statement to declare a new transaction start and its properties.

- a) BEGIN
- b) SET TRANSACTION**
- c) BEGIN TRANSACTION
- d) COMMIT

79. ____ means that the data used during the execution of a transaction cannot be used by a second transaction until the first one is completed.

- a) Consistency
- b) Atomicity
- c) Durability
- d) Isolation**

80. The most widely used structure for recording database modification is called as _____

- a) Log**
- b) List
- c) Queue
- d) Stack

81. An update log record describes a _____ database write

- a) Single**
- b) Double
- c) Triple
- d) Quadruple

82. Which of the following fields does the update log record have?

- a) Transaction identifier
- b) Data-item identifier
- c) Old value
- d) All of the mentioned**

83. The unique identifier of the transaction that performed the write operation is called as _____

a) Transaction identifier

b) Data-item identifier

c) Old value

d) New value

84. The value of the data item prior to the write is called as _____

a) Transaction identifier

b) Data-item identifier

c) Old value

d) New value

85. If a transaction does not modify the database until it has committed it is said to use a _____ modification technique

a) Deferred

b) Immediate

c) More than one of the mentioned

d) None of the mentioned

86. We say that a transaction has been _____ when its commit log record has been output to stable storage.

a) Locked

b) Completed

c) Committed

d) Released

87. State true or false: Using checkpoints reduces overhead

a) True

b) False

88. A _____ checkpoint is a checkpoint where transactions are allowed to perform updates even while buffer blocks are being written out.

a) Temporary

b) Fuzzy

c) Permanent

d) Recovery

89. If the database modifications occur while the transaction is still active, the transaction is said to use the _____ modification technique

a) Deferred

b) Immediate

c) More than one of the mentioned

d) None of the mentioned

90. A collection of data designed to be used by different people is called a/an

a) Organization

b) Database

c) Relationship

d) Schema

91. Which of the following is the oldest database model?

- a) Relational
- b) Deductive
- c) Physical
- d) Network**

92. Which of the following schemas does define a view or views of the database for particular users?

- a) Internal schema
- b) Conceptual schema
- c) Physical schema
- d) External schema**

93. Which of the following is an attribute that can uniquely identify a row in a table?

- a) Secondary key
- b) Candidate key**
- c) Foreign key
- d) Alternate key

94. Which of the following are the process of selecting the data storage and data access characteristics of the database?

- a) Logical database design
- b) Physical database design**
- c) Testing and performance tuning
- d) Evaluation and selecting

95. Which of the following terms does refer to the correctness and completeness of the data in a database?

- a) Data security
- b) Data constraint
- c) Data independence
- d) Data integrity**

96. The relationship between DEPARTMENT and EMPLOYEE is a

- a) One-to-one relationship
- b) One-to-many relationship**
- c) Many-to-many relationship
- d) Many-to-one relationship

97. A table can be logically connected to another table by defining a

- a) Super key
- b) Candidate key
- c) Primary key**
- d) Unique key

98. If the state of the database no longer reflects a real state of the world that the database is supposed to capture, then such a state is called

- a) Consistent state
- b) Parallel state
- c) Durable state
- d) Inconsistent state**

99. Ensuring isolation property is the responsibility of the

a) Recovery-management component of the DBMS

b) Concurrency-control component of the DBMS

c) Transaction-management component of the DBMS

d) Buffer management component in DBMS

100. _____ allow concurrent transactions to read (SELECT) a resource.

A. Update locks

B. Shared locks

C. Exclusive Locks

D. All of the mentioned