

Bigtree Entertainment Pvt. Ltd.

VistaRemote - Interface Document

Compiled by
Viraj Patel
&
Praveen Bodhuna

© Bigtree Entertainment Pvt. Ltd.
Ground Floor, Wajeda House,
Behind Gazebo House,
Gulmohar Cross Road No. 7,
Juhu Scheme, Mumbai - 400049.
Phone: +91 (22) 6508 8960

Date	Wed, Oct 18, 2023
Document Version	23.10.18.3
Module Version	23.10.18.3
Platform	.NET Class Library
Description	VistaRemote is a component used to integrate 3 rd party software with VISTA Cinema Software.

Table of Contents

Properties.....	4
strTransId.....	4
intBookId / strBookId / strBookIdEx.....	5
lngAuditNumber.....	6
strSeatInfo.....	7
strPrintData.....	8
colA.....	9
curTotal.....	11
curTicketsTotal.....	12
curFoodTotal.....	13
curBookingFee.....	14
intException.....	15
strException.....	16
intExceptionEx.....	17
intPrintCount.....	18
Functions / Methods.....	19
blnSetSettings.....	19
strGetSettings.....	20
strGetValue.....	21
blnInitBook.....	22
strBookingStatus.....	23
blnBookingVerify.....	24
blnAddSeats.....	25
blnSetBookingFee.....	26
blnAddConcessions.....	27
blnCommitBook.....	28
blnCommitBookEx.....	30
blnCancelTrans.....	32
blnContinueTrans.....	33
blnCancelBook.....	34
intSeatsAvail.....	35
blnGetSeatLayout.....	36
blnSetSeats.....	37
blnUnpaidToPaid.....	38
blnGetTicketPrintData.....	39
blnGetBookingPickupStream.....	40
blnBookingCollected.....	41
blnSyncData.....	42
strSeatInfoByArea.....	43
blnTestRemote.....	44
blnSetFnbPickupOrDelivery.....	45
blnMaskBooking.....	46
blnRemoveBookingFee.....	47
blnBookingVerifyEx.....	48
dblGetSessionOccupancy.....	49
blnAddMultiConcessions.....	50
blnAddConcessionsEx.....	51
blnCancelConcessions.....	52
blnSetFnbPickupOrDeliveryEx.....	53
blnRefundTrans.....	54
blnRefundTransEx.....	55
strGetTransactionDataXML.....	56
blnPartialRefund.....	57

blnPartialRefundEx.....	58
strGetOrderStatus.....	59
blnGetSeatStatus.....	60
blnGetGiftCardBalance.....	61
blnValidateVoucher.....	62
blnCommitVoucher.....	63
strGetVersion.....	64
Miscellaneous.....	65
Error Codes and Messages.....	65
Notes.....	66

Properties

strTransId

Summary:

Returns the Temporary Transaction Id (String) of the in process booking. It is a read only property

Property Value:

This property will have temporary Transaction Id after a Booking is initialized until the Booking is committed or cancelled.

Data Type: String

Remarks:

The strTransId property is used to get the Temporary Transaction Id after a successful initialization of a booking. This Temporary Transaction Id is used to refer to this booking in the next call. The Object is itself stateless but allows the 3rd party to maintain the state using this Temporary Transaction Id.

After a booking is initialized the user has to keep track of his booking; because multiple bookings can be in process simultaneously. Thus, the property is used to track the booking that is being done by this user. Id is used by sending it as parameter to other functions which will use it to track the booking and perform the necessary actions on the specified transaction.

The lifespan of the property is limited to the booking process; as soon as a booking is committed or cancelled the transaction Id does not exist in the system.

See Also: [intBookId](#)

intBookId / strBookId / strBookIdEx

Summary:

intBookId - Returns the Numeric Booking Id. It is a read only property

strBookId - Returns the Alpha Booking Id. It is a read only property

strBookIdEx - Returns the Booking Id combined with Cinema Code for uniqueness

Property Value:

Booking Id given by Cinema.

intBookId = 45325

strBookId = I2KJLME

strBookIdEx = SKWB0000045325

Data Type: Int64 / String / String

Remarks

The intBookId property is used to get the Booking Id given by cinema. This Id is available as soon as the first order is added to the Transaction by either executing “blnAddSeats” or “blnAddConcession”. This Booking Id is given to the customer to pickup his / her tickets / concession.

The strBookId property is used to get the Booking Id which can be used to pick up tickets using Vista Kiosk. It is generated along with intBookId. Note that while writing this document, this Booking Id cannot be used to pickup tickets using Vista POS.

It is very important to understand the difference between a Transaction Id (strTransId) and Booking Id (intBookId). Transaction Id has a life cycle ONLY within a transaction. i.e. Between “blnInitBook” and “blnCommitBook” or “blnCancelTrans”. In other words, Transaction Id is NEVER given to a customer.

IngAuditNumber

Summary:

Returns the Transaction Id of VISTA ticketing software.

Property Value:

Transaction Id generated for the particular Booking.

Data Type: Int64

Remarks

Transaction Id is generated ONLY for PAID bookings and can be used for audit purpose.
This ID is never given to the customer as it is of no use to him/her.

strSeatInfo

Summary:

Returns the reserved seat information of the in process booking. It is a read only property

Property Value:

“BAL-A1,A2,STL-C5,C6”

Data Type: String

Remarks

The strSeatInfo property is used to get the reserved seat information. If there are 2 tickets booked for Balcony and 2 tickets for Stalls, the property will hold the details as “BAL-A1,A2,STL-C5,C6”

At any time during the booking process if the user changes the allocated seats the property will reflect the change.

strPrintData

Summary:

Returns the Ticket Printing data as returned by Vista Ticketing Software

Property Value:

String containing the print stream as per the template configured at Cinema.

Data Type: String

Remarks

This property is used while printing tickets. A Ticket template needs to be configured at the Cinema and its print stream generated by that template is stored in this property.

colA

Summary:

It is a collection of areas, which defines the seating layout of the screen.

Property Value:

A Custom Collection and object structure which defines the layout of the show.

Data Type: Collection

Remarks

The colA property is used to get the seating layout of the screen. It gives the status of every seat, as booked, house, current transaction's booking, etc.

The collection can be used to display the layout of the screen and display the allocated seats. This display can be customized to allow the user to change the default allocated seats.

Vista creates a layout in a matrix where screen is always at the bottom. Each Area is a matrix. Vista will provide layout information for all the areas whether they are used in the order or not. Each matrix/area is made up of Rows (Seating Rows like A, B, C, D, etc) and Columns (Seats like 1, 2, 3, 4, etc). If you consider rows and columns are x-axis and y-axis, Vista will provide name and "grid id" for Rows (name to display and number to specify their sequence) and only "grid id" for Seats. Note that these "grid id"s are not the seat numbers but are the position of a seat from the left side of the screen. This way, you can project the gangways in between seats and rows.

"colA" collection contains multiple objects; each is a physical area (e.g. Balcony, Stalls). It also has 2 methods

1. intMinSeatId = This method returns (Int16) the minimum seat id in the matrix.
2. intMaxSeatId = This method returns (Int16) the maximum seat id in the matrix.

"colA" is a collection of object called "objArea". "objArea" has the following properties:

1. strAreaDesc - Short Name of the Area
2. strAreaNum - Area Number (Area Code)
3. strAreaCode - Area Category Code (Area Category Code)

"objArea" has the following method:

1. blnHasCurrentOrder - Returns TRUE if the area has your current order.

"objArea" contains collection of a object called "objRow". "objRow" has the following properties:

1. intGridRowID - Returns the position of the Row from the bottom.
2. strRowPhylID - Returns the name of the Row.

"objRow" contains collection of a object called "objSeat". "objSeat" has the following properties:

1. strGridSeatNum - Returns the position of the Seat from the left.
2. strSeatStatus - Returns the Status of the seat as follows
"0" = Means that this seat is available for user to select

- “1” = Means already sold
- “3” = Means house seat (ideally not available)
- “4” = Means wheel chair or special seat
- “5” = Means that this seat is already selected for current order

How to identify a gangway between 2 rows?

In the collection of Rows, there will be series of objects having sequential “intGridRowID”. In case there is a gangway between 2 rows, the sequence of “intGridRowID” will jump. E.g. For objRow (index = 3), “intGridRowID” is 3 and objRow (index = 4), “intGridRowID” is 5. This means that there is a gangway in between these 2 rows.

How to identify a gangway between 2 seats?

In the collection of Seats, there will be series of objects having sequential “strGridSeatNum”. In case there is a gangway between 2 seats, the sequence of “strGridSeatNum” will jump. E.g. For objSeat (index = 8), “intGridRowID” is 8 and objRow (index = 9), “intGridRowID” is 11. This means that there is a gangway in between these 2 seats.

curTotal

Summary:

Returns the total amount of the in process booking. It is a read only property

Property Value:

Decimal value containing the Total amount of the booking.

Data Type: Decimal

Remarks

The curTotal property is used to get the total amount receivable of the in progress booking. This includes all the values of the in process booking, such as tickets total, booking fee total, concessions total, etc. It is the total amount receivable from the customer.

See Also: curFoodTotal, curBookingFee, curTicketsTotal

curTicketsTotal

Summary:

Returns the total value of tickets of the in process booking. It is a read only property

Property Value:

A total amount of the tickets purchased in this booking.

Data Type: Decimal

Remarks

The curTicketsTotal property is used to get the total value of the tickets in booking. This is used to display the customer the cost of tickets. In addition to this amount there can be Booking Fee applied to the booking. Also, this amount does not include the concession items if any.

See Also: curFoodTotal, curBookingFee, curTotal

curFoodTotal

Summary:

Returns the total value of food/concessions/inventory of the in process booking. It is a read only property

Property Value:

Decimal Value containing the total value of food or concessions ordered.

Data Type: Decimal

Remarks

The curFoodTotal property is used to get the total value of the concessions in booking. This is used to display the customer the cost of concession. In addition to this amount there can be Booking Fee applied to the booking. Also, this amount does not include the tickets if any.

See Also: curTicketsTotal, curBookingFee, curTotal

curBookingFee

Summary:

Returns the total value of booking fee of the in process booking. It is a read only property

Property Value:

Decimal value containing the booking fee for current booking.

Data Type: Decimal

Remarks

The curBookingFee property is used to get the booking fee charged for booking tickets/concessions. This amount is additional to the cost of the tickets/concessions and is payable by customer.

See Also: curTicketsTotal, curFoodTotal, curTotal

intException

Summary:

Returns the numeric code of the error generated during the last execution of any method

Property Value:

An integer containing the exception code.

Data Type: Int64

Remarks

The intException property is used to get the last error code. This is available ONLY for errors occurred during the execution of any methods of VistaRemote.clsBook object.

strException

Summary:

Returns the description of the error generated during the last execution of any method

Property Value:

A string containing the exception message.

Data Type: String

Remarks

The strException property is used to get the last error description. This is available ONLY for errors occurred during the execution of any methods of VistaRemote.clsBook object.

intExceptionEx

Summary:

Returns the extra numeric data of the error generated during the last execution of any method

Value Property:

An integer value containing the numeric data of error generated.

Data Type: Int64

Remarks

The intExceptionEx property is used to get the extra data returned by last error.
e.g. Consider that there are 10 tickets available to book but in a group of 4, 4 and 2.
Now, if the booking is initialized for 5 tickets, an error is generated which passes 4 in intExceptionEx which means that there are only 4 tickets available in continuous block.
Vista will NOT make a booking if it is unable to allocate all the continuous seats.

intPrintCount

Summary:

Returns the print count(Tickets & Voucher) of VISTA ticketing software.

Value Property:

Print count will generate for the paid bookings only.

Data Type: Int64

Remarks

The intPrintCount property is used to set Number of tickets printed in blnBookingCollected method.

Functions / Methods

blnSetSettings

Syntax:

```
clsBook.blnSetSettings(  
    ByVal strSetting As String,  
    ByVal strValue As String  
) As Boolean
```

Summary:

The function is used to set a setting.

Parameters:

strSetting	The setting name whose value is to be updated.
strValue	The settings value for the corresponding setting name.

Returns:

TRUE if successful else FALSE

Remarks:

The function is used to set the values of some settings which are used in booking process. E.g. "ConnectionString", "QueryTimeOut", etc. These settings are set before accessing any function in the DLL.

Properties that can be set:

LicenseType	This property is used to set the license type which is used while doing bookings in VISTA. The property is very important for DLL to work properly and for Bookings to happen under the proper account. The valid license types are: "WWW", "CALL", "IVR", "SMS", "KIOSK", "WUP"
ConnectionString	This property sets the connection string used to connect to the database.
QueryTimeOut	The time out period for database queries.
DebugMode	Can be set to "Verbose" or "None". When Verbose, it will create debug input/output logging for each communication between the remote server and cinema server.
MemberCard	Used to send Member Data information to store in transaction table

See Also: blnGetSettings

strGetSettings

Syntax:

```
clsBook.strGetSettings(  
    ByVal strSetting As String  
) As String
```

Summary:

The function is used to get the value of a setting.

Parameters:

strSetting	The setting name whose value is to be returned.
------------	---

Returns:

Value of the setting as string

Remarks:

The function is used to get the values that have been set for the settings that are required in booking process.

See Also: blnSetSettings

strGetValue

Syntax:

```
clsBook.strGetValue(  
    ByVal strName As String  
) As String
```

Summary:

The function is used to get the value of undefined properties. This command is made to avoid creating numerous properties to this object. Many methods return command specific values which can be accessed via this method. E.g: AddSeats and CommitTrans returns amounts with tax split, now since it is not practical to have so many properties, we have generalized the way to pass this data. You can refer to table below for the list of “strName”

Parameters:

strName	Name of the keyword used to extract value of particular property.
---------	---

Returns:

Value of the property as string

Remarks:

List of properties:

Method(s)	Name	Description
AddSeats	intMaxAvail	Maximum of number of tickets which can be booked for this particular session / area. Only available in case AddSeats returns error 2 or 3
AddSeats	intSeatsAvail	Number of seats available in this session / area
AddSeats AddConcessions CommitBook SetBookingFee	curTicketsTax curFoodTax curBookingFeeTax curTotalTax	Tax values for each type of component
CommitBook	VPGData	Return value from Vista PG component.
BookingStatus	BookingStatus BookingAmountPaid BookingTicketPrinted BookingDateCollected BookingPickupWorkstation BookingPickupUser BookingBookedUser BookingBookedWorkstation	Booking details

blnInitBook

Syntax:

```
clsBook.blnInitBook (
    ByVal strCinemaCode As String
) As Boolean
```

Summary:

The function is used to initialize a booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
---------------	--

Returns:

TRUE if successful else FALSE

Remarks:

This method ONLY initializes the booking process. After execution of this method the booking automatically gets cancelled if not (committed) finalized within some stipulated time. It sets the value of property "strTransId" if it is successful; this property is used to add tickets/concessions to this booking.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
strTransId	intException
	strException
	intExceptionEx

strBookingStatus

Syntax:

```
clsBook.strBookingStatus (
                                ByVal strCinemaCode As String,
                                ByVal lngBookingId As Long
                            ) As String
```

Summary:

The function is used to get the latest status of the Booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	Booking Id for which the Status has to be fetched

Returns:

"" - Error/Not Exists, "P" - Paid Booking, "U" - Unpaid, "I" - In progress, "C" - Cancelled

Remarks:

This method will revert back with the latest status of the Booking specified.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnBookingVerify

Syntax:

```
clsBook.blnBookingVerify (
    ByVal strCinemaCode As String,
    ByVal strKey As String,
    ByVal lngBookingId As Int64,
    ByVal lngSessionId As Int64,
    ByVal strTypeCode As String,
    ByVal intQty As Short,
    ByVal blnPaid As Boolean
) As String
```

Summary:

The function is used to verify the status of the Booking as well as whether the booking was done by the particular application. While booking the application is supposed to pass the “key” which will be used in this method to verify the owner of the booking. Key is the value passed in “Customer Phone” parameter of CommitTrans.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strKey	Value passed in “Customer Phone” parameter of CommitTrans
lngBookingId	Booking Id for which the Status has to be fetched
lngSessionId	Session Code
strTypeCode	Ticket Type / Price code used while booking
intQty	Quantity of tickets booked in this booking
blnPaid	Whether the booking is a PAID booking or not

Returns:

TRUE if the booking matches all the specified parameters else FALSE.

Remarks:

This method is more helpful to verify whether the booking is made by the particular application. All the arguments passed are validated and appropriate error codes are returned in case of any mismatch. FALSE response may mean that the booking was NOT done by this application. This situation comes up since VISTA sometimes reassigns booking numbers to in case it is not used.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnAddSeats

Syntax:

```
clsBook.blnAddSeats (
    ByVal strCinemaCode As String,
    ByVal strTransId As String,
    ByVal lngSessionId As Int64,
    ByVal strTypeCode As String,
    ByVal intQty As Short,
    ByVal blnUserSelectedSeating As Boolean
) As Boolean
```

Summary:

The Function is used to add seats to the transaction.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
lngSessionId	Session Id of the show for which the booking is to be made
strTypeCode	Code the Ticket Type for which the booking is to be made
intQty	Quantity of the Tickets to be booked
blnUserSelectedSeating	Specifies whether the calling application fully handles the Seat Layout (recommended value is FALSE)

Returns:

Returns TRUE if successful else FALSE

Remarks

This method temporarily blocks the specified number of seats. On execution of this function, it blocks the number of seats in vista as specified in intQty parameter and returns the vista booking id which can be used to search the order in vista.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• strTransId (does not change)	• intException
• intBookId	• strException
• strSeatInfo	• intExceptionEx
• curTotal	
• curTicketsTotal	
• curBookingFee	
• intException	
• strException	
• intExceptionEx	

blnSetBookingFee

Syntax:

```
clsBook.blnSetBookingFee (
    ByVal strCinemaCode As String,
    ByVal strTransId As String,
    ByVal curAmount As Decimal,
    ByVal intQty As Short
) As Boolean
```

Summary:

The Function is used to set the Booking Fee to the transaction. Executing this function will override the Booking Fee set earlier by this function or VISTA itself.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
curAmount	Amount to be set as Service Charge (Booking Fee).
intQty	Number of times the above amount is to be calculated for this transaction. In case the amount mentioned is per ticket then this will be the number of tickets in the transaction. In case this amount is per transaction then this will be 1.

Returns:

Returns TRUE if successful else FALSE

Remarks

This method sets the Booking Fee for the Transaction. It will override the earlier booking fee whether it is set by VISTA itself. This method should be executed after ALL the tickets are ordered (blnAddSeats) and before committing (blnCommitBook).

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• strTransId (does not change)	• intException
• curTotal	• strException
• curTicketsTotal	• intExceptionEx
• curBookingFee	
• curFoodTotal	
• intException	
• strException	
• intExceptionEx	

blnAddConcessions

Syntax:

```
clsBook.blnAddConcessions (
    ByVal strCinemaCode As String,
    ByVal strTransId As String,
    ByVal strItemId As String,
    ByVal intQty As Int16
) As Boolean
```

Summary:

The function is used to add concession items to the transaction.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
strItemId	Item code of the concessions / inventory
intQty	Quantity of the Items to be booked

Returns:

Returns TRUE if successful else FALSE

Remarks

This method books the specified item.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• strTransId (does not change)	• intException
• intBookId	• strException
• curTotal	• intExceptionEx
• curFoodTotal	
• intException	
• strException	
• intExceptionEx	

blnCommitBook

Syntax: clsBook.blnCommitBook(
 ByVal strCinemaCode As String,
 ByVal strTransId As String,
 ByVal lngSessionId As Int64,
 ByVal blnPaid As Boolean,
 ByVal strCardNo As String,
 ByVal strCardType As String,
 ByVal sntCardExpiryMonth As Short,
 ByVal sntCardExpiryYear As Short,
 ByVal strCardCVV As String,
 ByVal strCustomerName As String,
 ByVal strCustomerPhone As String,
 ByVal strComments As String,
 ByVal strPickupName As String,
 ByVal strGiftCardData As String,
) As Boolean

Summary: The function is used to commit / complete the booking

Returns: Returns TRUE if successful else FALSE

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
lngSessionId	Session Id of the show for which the booking is to be made
blnPaid	TRUE for Paid Booking, FALSE for Unpaid Booking
strCardNo	Credit Card number
sntCardExpiryMonth	Card Expiry Month
sntCardExpiryYear	Card Expiry Year
strCustomerName	Name of the Card Holder / Customer
strCustomerPhone	Contact number (Phone) of the customer
strComments	Comments
strPickupName	Name of the person who is going to pick up the tickets
strGiftCardData	Vista Gift Card Data

Remarks:

This method commits the temporary booking. After execution of this method the booking is complete. In case the booking is Unpaid then it still can be cancelled at the Cinema or using the “blnCancelBook” method.

String containing Gift card data e.g: |GiftCardNo=100000000036|CardPin=1234|Amount=5000|PayType=0000000017| Note that the payment type code should exist and the amount is in cents/paise so 1200 means Rs. 12 and 4200 means Rs. 42 and 1525 means Rs. 15.25

Properties Affected

<i>When Successful (TRUE)</i>	<i>When Fails (FALSE)</i>
• strTransId	• intException
• intBookId	• strException
• strSeatInfo	• intExceptionEx
• curTotal	
• curFoodTotal	
• curTicketsTotal	
• curBookingFee	
• lngAuditNumber	
• strBookId	

blnCommitBookEx

Syntax: clsBook.blnCommitBookEx(
 ByVal strCinemaCode As String,
 ByVal strTransId As String,
 ByVal lngSessionId As Int64,
 ByVal strCardNo As String,
 ByVal strCardType As String,
 ByVal sntCardExpiryMonth As Short,
 ByVal sntCardExpiryYear As Short,
 ByVal strCardCVV As String,
 ByVal strCustomerName As String,
 ByVal strCustomerPhone As String,
 ByVal strComments As String,
 ByVal strPickupName As String,
 ByVal strMultiPaymentDetails As String
) As Boolean

Summary: The function is used to commit / complete the booking. This method supports multiple payment types for a particular booking.

Returns: Returns TRUE if successful else FALSE

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
lngSessionId	Session Id of the show for which the booking is to be made
strCardNo	Card Number of customer, used for pickup the booking
strCardType	Card Type e.g Visa, Master
sntCardExpiryMonth	Card Expiry Month
sntCardExpiryYear	Card Expiry Year
strCardCVV	Card CVV No, dummy No 123
strCustomerName	Name of the Card Holder / Customer
strCustomerPhone	Contact number (Phone) of the customer
strComments	Comments
strPickupName	Name of the person who is going to pickup the tickets
strMultiPaymentDetails	String with multiple payment types. Refer remarks for details.
strGiftCardData	Vista Gift Card Data

Remarks:

This method commits the temporary booking. After execution of this method the booking is complete. In case the booking is Unpaid then it still can be cancelled at the Cinema or using the “blnCancelBook” method.

String containing multiple payment details. e.g: |PAYTYPE1=M|AMOUNT1=1200|PAYTYPE2=AB00000012|AMOUNT2=4200| Note that the payment type code should exist and the amount is in cents/paise so 1200 means Rs. 12 and 4200 means Rs. 42 and 1525 means Rs. 15.25

String containing Gift card data e.g: |GiftCardNo=100000000036|CardPin=1234|Amount=5000|PayType=0000000017| Note that the payment type code should exist and the amount is in cents/paise so 1200 means Rs. 12 and 4200 means Rs. 42 and 1525 means Rs. 15.25

Properties Affected

<i>When Successful (TRUE)</i>	<i>When Fails (FALSE)</i>
• strTransId	• intException
• intBookId	• strException
• strSeatInfo	• intExceptionEx
• curTotal	
• curFoodTotal	
• curTicketsTotal	
• curBookingFee	
• lngAuditNumber	
• strBookId	

blnCancelTrans

Syntax:

```
clsBook.blnCancelTrans(  
    ByVal strCinemaCode As String,  
    ByVal strTransId As String  
) As Boolean
```

Summary:

The function can be used to cancel the temporary transaction.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method

Returns:

Returns TRUE if successful else FALSE

Remarks

This method cancels the temporary transaction done using the “blnInitBook” method. It also unblocks the seats that were blocked using “blnAddSeats” function.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnContinueTrans

Syntax:

```
clsBook.blnContinueTrans(  
                                ByVal strCinemaCode As String,  
                                ByVal strTransId As String  
    ) As Boolean
```

Summary:

The function allows the user to continue the transaction.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method

Returns:

Returns TRUE if successful else FALSE

Remarks

This function resets the temporary transaction's auto-cancellation timer. This allows the user to continue the transaction for a period longer than the auto-cancellation time.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnCancelBook

Syntax:

```
clsBook.blnCancelBook(  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Int64  
) As Boolean
```

Summary:

The function is used to cancel the booking.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	Booking Id of the UNPAID booking

Returns:

Returns TRUE if successful else FALSE

Remarks

This method cancels the unpaid booking. Paid bookings CANNOT be cancelled / deleted but they can be refunded.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

intSeatsAvail

Syntax:

```
clsBook.intSeatsAvail(  
    ByVal strCinemaCode As String,  
    ByVal lngSessionId As Int64,  
    ByVal strAreaCode As String  
) As Int16
```

Summary:

Function is used to fetch the number of seats available for sales.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made
lngSessionId	Session Id of the show
strAreaCode	Area Category code of the Ticket Type for which the seats availability is to be determined

Returns:

Returns the number of seats available (Int16) for sales.

Remarks

This method returns the number of seats available for sales using VistaRemote object. This means that this figure may be less than the actual availability of seats at the Box Office, which will be as per cinema configuration.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnGetSeatLayout

Syntax:

```
clsBook.blnGetSeatLayout (
    ByVal strCinemaCode As String,
    ByVal strTransId As String,
    ByVal lngSessionId As Int64,
    ByVal blnScreenOnTop As Boolean,
    ByVal strMergeOption As String,
    ByVal strAreaCats As String
) As Boolean
```

Summary:

The function gets the seat layout, along with details of currently blocked seats.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made.
strTransId	Temporary Transaction Id generated by the objInitBook method.
lngSessionId	Session Id of the show.
blnScreenOnTop	Ideally should be FALSE unless specifically told
strMergeOption	Ideally should be BLANK unless specifically told
strAreaCats	Ideally should be BLANK unless specifically told

Returns:

Returns the Collection of Areas, Rows and Seats.

Remarks

This method returns the Layout of the screen in the form of collection using VistaRemote object. This can be used to display the layout of the screen for the user to view the seats allotted by the system.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
Collection of Areas, Rows and Seats.	intException
strGroupSeatsData	strException
	intExceptionEx

blnSetSeats

Syntax:

```
clsBook.blnSetSeats (
    ByVal strCinemaCode As String,
    ByVal strTransId As String,
    ByVal lngSessionId As Int64,
    ByVal strSelectedSeats As String
) As Boolean
```

Summary:

Function can be used to change the default allocated seats.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made.
strTransId	Temporary Transaction Id generated by the objInitBook method.
lngSessionId	Session Id of the show.
strSelectedSeats	The Selected Seats to update the selection of seats against system allotted seating. This is to be in the format: - N selected seats - in quads of Area Category Code, Area Number, Grid Seat Row ID, and Grid Seat Number. E.g. : - 2 0000000001 1 2 3 0000000001 1 2 4

Returns:

Returns true if the VistaRemote is successful in setting the changed seats. And also sets the property strSeatInfo with the newly allotted seats.

Remarks

This method allows the user to select the seats different from those allocated by the system.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
strSeatInfo	intException
	strException
	intExceptionEx

blnUnpaidToPaid

Syntax:

```
clsBook.blnUnpaidToPaid(
    ByVal strCinemaCode As String,
    ByVal lngBookingId As Int64,
    ByVal decAmountPaid As Decimal,
    ByVal strCardNo As String,
    ByVal sntCardExpiryMonth As Short,
    ByVal sntCardExpiryYear As Short
) As Boolean
```

Summary:

The function is used to convert an unpaid booking to paid booking.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made.
lngBookingId	The Booking Number given to user while for Unpaid Booking.
decAmountPaid	Amount Paid For Updating the Booking to Paid Booking
strCardNo	The Card Number of the User
sntCardExpiryMonth	The Card Expiry month.
sntCardExpiryYear	The Card Expiry Year.

Returns:

Returns TRUE when the specified booking is converted from unpaid to paid.

Remarks

This method allows the user to convert the unpaid booking to paid booking. This is a single step method and should NOT be used with any other method as a transaction.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnGetTicketPrintData

Syntax:

```
clsBook.blnGetTicketPrintData(  
    ByVal strCinemaCode As String,  
    ByVal strTransId As String,  
    ByVal strPrinterType As String  
) As Boolean
```

Summary:

Generates the print stream using ticket template as per specified printer type for the transaction.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made.
strTransId	The transaction id returned by InitTrans method.
strPrinterType	Printer Type to be used for Ticket Template

Returns:

Returns TRUE when successful.

Remarks

This method generates print stream and then sets it in strPrintData property.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
strPrintData	intException
	strException
	intExceptionEx

blnGetBookingPickupStream

Syntax:

```
clsBook.blnGetBookingPickupStream(  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Int64,  
    ByVal strPrinterType As String,  
    ByVal strCardNumber As String,  
    ByVal strBarcode As String  
) As Boolean
```

Summary:

Generates the print stream using ticket template as per specified printer type for the booking which is either specified using Booking Id or Card Number or Barcode.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made.
lngBookingId	The Booking Number given to user while Booking.
strPrinterType	Printer Type to be used for Ticket Template
strCardNumber	Optional: Card Number to be used to find the booking
strBarcode	Optional: The barcode to be used to find the booking

Returns:

Returns TRUE when successful.

Remarks

This method generates print stream and then sets it in strPrintData property.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
strPrintData	- intException - strException - intExceptionEx

blnBookingCollected

Syntax:

```
clsBook.blnBookingCollected(  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Int64,  
    ByVal strCardNumber As String,  
    ByVal strBarcode As String,  
    ByVal intPrintCount As Integer,  
    ) As Boolean
```

Summary:

Sets the booking as collected.

Parameters

strCinemaCode	Code of the Cinema where the booking is to be made.
lngBookingId	The Booking Number given to user while Booking.
strCardNumber	Optional: Card Number to be used to find the booking
strBarcode	Optional: The barcode to be used to find the booking
intPrintCount	Number of tickets printed

Returns:

Returns TRUE when the specified booking is flagged as collected.

Remarks

This method allows the user to flag a particular booking as collected.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnSyncData

Syntax:

```
clsBook.blnSyncData(  
    ByVal strCinemaCode As String,  
    ByRef arrOptions(,) As String  
) As Boolean
```

Summary:

This function is used to synchronize the Local (VISTACS) database with Cinema database.

Returns:

Returns TRUE when the Remote is successful in synchronizing the Local (VISTACS) database with the Cinema Database(s) at ALL/SPECIFIED cinema(s).

Remarks

This method has 2 parameters

1. strCinemaCode - This parameter means synchronize only the specified cinema.
2. arrOptions(,) - This parameter will host all the remaining parameters, few of which are optional but not all. The following is the list of these parameters:

arrOptions(x, 0)	arrOptions(x, 1)
strSalesChannel	WWW
strStoredProcedure	spUpdateMyTables
blnOpenSessionsOnly	True

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	• intException
	• strException
	• intExceptionEx

strSeatInfoByArea

Syntax:

```
clsBook.strSeatInfoByArea(  
                                ByVal intAreaNum As Int16  
    ) As String
```

Summary:

The function is used to get the seat information of in-process booking for a particular area.

Parameters

intAreaNum	Area number by which information is to be fetched
------------	---

Returns:

Returns the Seat Information of the in-process booking for a particular area.

Remarks

This method allows the user to fetch the Seat Information for a particular area of the in process booking. If there are two tickets booked for balcony then the data returned by the function will be "A1,A2"

blnTestRemote

Syntax:

```
clsBook.blnTestRemote(  
    ByVal strCinemaCode As String  
) As Boolean
```

Summary:

The function tests the Connectivity with the cinema.

Parameters

strCinemaCode	Cinema Code for which remote connectivity is to be tested
---------------	---

Returns:

Returns “True” if Vista Remote is able to connect to the cinema.

Remarks

This method allows the user to test the connectivity. It accepts the cinema code and if it is successful to connect to the cinema, it returns true.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• strException	• intException
	• strException
	• intExceptionEx

blnSetFnbPickupOrDelivery

Syntax:

```
clsBook.blnSetFnbPickupOrDelivery(  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Int64,  
    ByVal strIsDelivery As String,  
    ByVal strDeliveryTime As String,  
    optional ByVal strComments As String  
) As Boolean
```

Summary:

The function is used to set the FNB pickup or seat delivery flag in Vista.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	The Booking Number given to user while Booking.
strIsDelivery	Whether the FNB is delivery to seat or pickup (Y/N)
strDeliveryTime	Whether the delivery before show(B) or interval(I)
strComments	Optional, any comments for order can be added

Returns:

Returns TRUE if successful else FALSE.

Remarks

This method sets the FNB pickup or seat delivery flag for the Transaction. This method should be executed after ALL the Concessions are ordered (blnAddConcessions) and before committing (blnCommitBook).

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnMaskBooking

Syntax:

```
clsBook.blnMaskBooking(  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Int64,  
    ByVal strSplitSequence As String  
) As Boolean
```

Summary:

The function is used to mask the Booking in Vista.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	The Booking Number given to user while Booking.
strSplitSequence	Sequence of tickets to be split in ' ' separated delimiter

Returns:

Returns TRUE if successful else FALSE, and New booking Id's.

Remarks

This method mask the alphanumeric booking id which is generated by vista and returns new booking id's which is equal to number of split bookings. This method should be executed, when the customer selected for M-Ticket.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• strSplitBookingId	• intException
	• strException
	• intExceptionEx

For Example:

if you send data for split as |1|2,3|, it will return new booking in this order |B7G9A8Q|B26EKW2|.

blnRemoveBookingFee

Syntax:

```
clsBook.blnRemoveBookingFee(  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Int64  
) As Boolean
```

Summary:

The Function is used to remove the Booking fee in Vista.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	The Booking Number given to user while Booking.

Returns:

Returns TRUE if successful else FALSE.

Remarks

This method is used remove booking fee in vista, which is set by blnSetBookingFee method.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	• intException
	• strException
	• intExceptionEx

blnBookingVerifyEx

Syntax:

```
clsBook.blnBookingVerifyEx(  
                                ByVal strCinemaCode As String,  
                                ByVal lngBookingId As Int64  
    ) As Boolean
```

Summary:

The function is used to verify the booking by checking all the transaction table in vista.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	The Booking Number given to user while Booking.

Returns:

Returns TRUE if successful else FALSE.

Remarks

This method is more helpful to verify whether the booking is exists in the vista by checking all the transaction table, to avoid double ticketing.

dblGetSessionOccupancy

Syntax:

```
clsBook.dblGetSessionOccupancy(  
    ByVal strCinemaCode As String,  
    ByVal lngSessionId As Int64  
) As Double
```

Summary:

The function is used to get the occupancy of particular session of cinema in percentage.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngSessionId	Session Id of the show.

Returns:

Returns the occupancy in percentage.

Remarks

This method allows the user to fetch the occupancy information for a particular session of the cinema in percentage.

blnAddMultiConcessions

Syntax:

```
clsBook.blnAddMultiConcessions (
    ByVal strCinemaCode As String,
    ByVal strTransId As string,
    ByVal strItemsOrder As String
) As Boolean
```

Summary:

The function is used to add concession items to the transaction.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
strItemsOrder	This is to be in the format :- N selected Items - in triples of Item Id, Item Quantity and -1. E.g. :- 2 27 1 -1 24 2 -1

Returns:

Returns TRUE if successful else FALSE

Remarks

This method books the specified item.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• strTransId (does not change)	• intException
• intBookId	• strException
• curTotal	• intExceptionEx
• curFoodTotal	
• intException	
• strException	
• intExceptionEx	

blnAddConcessionsEx

Syntax:

```
clsBook.blnAddMultiConcessions (
    ByVal strCinemaCode As String,
    ByVal strTransId As String,
    ByVal strOrderXml As String,
    ByVal blnCancelExisting As Boolean
) As Boolean
```

Summary:

The function is used to add concession items to the transaction.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
strOrderXml	This is to be in the Xml format :- <order><conc><itemid>31</itemid><qty>1</qty><price>-1</price></conc><conc><itemid>29</itemid><qty>1</qty><price>-1</price></conc></order>
blnCancelExisting	Optional: Cancel the existing F&B order, by default it is False.

Returns:

Returns TRUE if successful else FALSE

Remarks

This method books the specified item.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• <i>strTransId</i> (does not change)	• <i>intException</i>
• <i>curTotal</i>	• <i>strException</i>
• <i>curFoodTotal</i>	• <i>intExceptionEx</i>
• <i>intException</i>	
• <i>strException</i>	
• <i>intExceptionEx</i>	

blnCancelConcessions

Syntax:

```
clsBook.blnCancelConcessions (
    ByVal strCinemaCode As String,
    ByVal strTransId As String
) As Boolean
```

Summary:

The function is used to cancel/remove the concession items from the transaction.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method

Returns:

Returns TRUE if successful else FALSE

Remarks

This method cancel/remove the concessions from temporary transaction, which are added using blnAddconcession or blnAddMultiConcessions method.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
• <i>strTransId (does not change)</i>	• <i>intException</i>
• <i>curTotal</i>	• <i>strException</i>
• <i>curFoodTotal</i>	• <i>intExceptionEx</i>
• <i>intException</i>	
• <i>strException</i>	
• <i>intExceptionEx</i>	

blnSetFnbPickupOrDeliveryEx

Syntax:

```
clsBook.blnSetFnbPickupOrDeliveryEx (
    ByVal strCinemaCode As String,
    ByVal lngBookingId As Int64,
    ByVal strIsDelivery As String,
    ByVal strDeliveryTime As String,
    ByVal strBookingDetails As String,
    optional ByVal strComments As String

) As Boolean
```

Summary:

The Function is used to set the FNB pickup or seat delivery flag in Vista.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	Booking Id for which the flag has to be set
strIsDelivery	Whether the FNB is delivery to seat or pickup (Y/N)
strDeliveryTime	Whether the delivery before show(B) or interval(I)
strBookingDetails	To link ticket booking with Fnb booking E.g: BOOKINGID=15645 SESSIONID= ROWID= SEATID= OR BOOKINGID= SESSIONID=36915 ROWID=L SEATID=16 If you want to pass strDeliveryTime as "C"(CounterPickup), then pass parameters as below BOOKINGID= SESSIONID= ROWID= SEATID=
strComments	Optional, any comments for order can be added

Returns:

Returns TRUE if successful else FALSE

Remarks

This method sets the FNB pickup or seat delivery flag for the Transaction and also link with other ticket booking. This method should be executed after ALL the Concessions are ordered (blnAddConcessions).

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnRefundTrans

Syntax:

```
clsBook.blnRefundTrans (
    ByVal strCinemaCode As String,
    ByVal lngBookingId As Int64,
    ByVal strCardNumber As String,
    ByVal strCustomerName As String
) As Boolean
```

Summary:

The Function is used to refund the paid booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	The Booking Number given to user while Booking.
strCardNumber	Optional: Card Number to be used to update in vista.
strCustomerName	Optional: Customer Name to be used to update in vista.

Returns:

Returns TRUE if successful else FALSE

Remarks

This method allows the user to refund the paid bookings which are not yet collected in cinemas.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnRefundTransEx

Syntax:

```
clsBook.blnRefundTrans (
    ByVal strCinemaCode As String,
    ByVal lngBookingId As Int64,
    ByVal strCardNumber As String,
    ByVal strCustomerName As String,
    ByVal blnMultiPayment As Boolean,
    ByVal blnRefundBookingFees As Boolean
) As Boolean
```

Summary:

The Function is used to refund multi payment paid booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	The Booking Number given to user while Booking.
strCardNumber	Optional: Card Number to be used to update in vista.
strCustomerName	Optional: Customer Name to be used to update in vista.
blnMultiPayment	Optional: Refund multi payment in vista, by default it is False.
blnRefundBookingFees	Optional: Refund booking fee in vista, by default it is False.

Returns:

Returns TRUE if successful else FALSE

Remarks

This method allows the user to refund the paid bookings which are not yet collected in cinemas.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

strGetTransactionDataXML

Syntax:

```
clsBook.strGetTransactionDataXML (  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Long  
) As String
```

Summary:

The function is used to get the Transaction details of the Booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	Booking Id for which the Status has to be fetched

Returns:

"" - Error/Not Exists, or return transaction details in XML format.

Remarks:

This method will revert back with the transaction details of the Booking specified.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnPartialRefund

Syntax:

```
clsBook.blnPartialRefund(  
    ByVal strCinemaCode As String,  
    ByVal lngBookingId As Int64,  
    ByVal strTransSeqList As String,  
    ByVal decRefundAmount As Decimal,  
    ByVal strCardNumber As String,  
    ByVal strCustomerName As String,  
    ByVal blnRefundBookingFees As Boolean,  
    ByVal blnRefundInventory As Boolean  
) As Boolean
```

Summary:

The Function is used to partial refund the paid booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	The Booking Number given to user while Booking.
strTransSeqList	Sequence number of transaction to be refunded in ' ' separated delimiter or "" blank will refund whole transaction.
decRefundAmount	Refund amount.
strCardNumber	Card Number to be used to update in vista or blank.
strCustomerName	Customer Name to be used to update in vista or blank.
blnRefundBookingFees	Optional: Refund booking fee in vista, by default it is False.
lnRefundInventory	Optional: Refund Inventory in vista, by default it is False.

Returns:

Returns TRUE if successful else FALSE

Remarks

This method allows the user to partial refund the paid bookings which are not yet collected in cinemas.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnPartialRefundEx

Syntax:

```
clsBook.blnPartialRefund(  
    ByVal strCinemaCode As String,  
    ByVal lngVistaTransNum As Int64,  
    ByVal strTransSeqList As String,  
    ByVal decRefundAmount As Decimal,  
    ByVal strCardNumber As String,  
    ByVal strCustomerName As String,  
    ByVal blnRefundBookingFees As Boolean,  
    ByVal blnRefundInventory As Boolean  
) As Boolean
```

Summary:

The Function is used to partial refund the paid booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngVistaTransNum	The Vista Transaction Number.
strTransSeqList	Sequence number of transaction to be refunded in ' ' separated delimiter or "" blank will refund whole transaction.
decRefundAmount	Refund amount.
strCardNumber	Card Number to be used to update in vista or blank.
strCustomerName	Customer Name to be used to update in vista or blank.
blnRefundBookingFees	Optional: Refund booking fee in vista, by default it is False.
lnRefundInventory	Optional: Refund Inventory in vista, by default it is False.

Returns:

Returns TRUE if successful else FALSE

Remarks

This method allows the user to refund the vista POS transaction's partially or whole at cinema.

Properties Affected

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

strGetOrderStatus

Syntax:

```
clsBook.strGetOrderStatus (
                                ByVal strCinemaCode As String,
                                ByVal lngBookingId As Long
                                ) As String
```

Summary:

The function is used to get the latest status of the concessions booking.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	Booking Id for which the Status has to be fetched

Returns:

"" - Error/Not Exists, or return order status in pipe delimited format.

Example:

|OrderReadyStatus=Y|OrderReadyDateTime=2020-06-14 18:30:15|
OrderDeliveryStatus=N|OrderDeliveryDateTime=|

Remarks:

This method will revert back with the latest status of the concession booking specified.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnGetSeatStatus

Syntax:

```
clsBook.blnGetSeatStatus (
                                ByVal strCinemaCode As String,
                                ByVal strSeatDetails As String
                            ) As Boolean
```

Summary:

The function is used to get the status of the seat, sold or not.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strSeatDetails	Pass the seat details in below format to get the seat status SESSIONID=36915 ROWID=L SEATID=16

Returns:

Returns TRUE if successful else FALSE

Remarks:

This method will revert back with the status of the seat specified.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

blnGetGiftCardBalance

Syntax:

```
clsBook.blnGetGiftCardBalance (
                                ByVal strCinemaCode As String,
                                ByVal strTransId As String,
                                ByVal strCardNo As String,
                                ByVal strCardPin As String
                                ) As Boolean
```

Summary:

The function is used to get the balance of the Vista Gift Card.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
strCardNo	Vista Gift Card Number
strCardPin	Vista Gift Card Pin

Returns:

Returns TRUE if successful else FALSE

Remarks:

This method will revert back with the vista Gift card balance and last 3 transactions.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
curGiftCardBalance	intException
strGiftCardLast3Trans	strException
	intExceptionEx

blnValidateVoucher

Syntax:

```
clsBook.blnValidateVoucher (
    ByVal strCinemaCode As String,
    ByVal strTransId As String,
    ByVal strVoucherBarcode As String,
    ByVal lngSessionId As Int64,
    optional ByVal strVoucherPin As String,
    optional ByVal blnValidateIndividually As Boolean
) As Boolean
```

Summary:

The function is used to validate the Vista voucher code.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
strTransId	Temporary Transaction Id generated by the objInitBook method
strVoucherBarcode	Vista Voucher Barcode.
lngSessionId	Session Id of the show.
strVoucherPin	Vista Voucher Pin.
blnValidateIndividually	True or false, by default false.

Returns:

Returns TRUE if successful else FALSE

Remarks:

This method will revert back with the vista voucher data as below.

|TicketTypeCode=0008|TicketName=SILVER MOVIE VOUCHER|PriceToUse=12500|
RedemptionTicket=Y|PriceFinal=0|ForceBarcode=N|

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
strVoucherData	intException
	strException
	intExceptionEx

blnCommitVoucher

Syntax:

```
clsBook.blnCommitVoucher (
    ByVal strCinemaCode As String,
    ByVal lngBookingId As Long,
    ByVal strVoucherBarcode As String
) As Boolean
```

Summary:

The function is used to get the balance of the Vista Gift Card.

Parameters:

strCinemaCode	Code of the Cinema where the booking is to be made
lngBookingId	Booking Id for which the Status has to be fetched
strVoucherBarcode	Vista Voucher Barcode.

Returns:

Returns TRUE if successful else FALSE

Remarks:

This method will commit the voucher in vista.

Properties Affected:

When Successful (TRUE)	When Fails (FALSE)
	intException
	strException
	intExceptionEx

strGetVersion

Syntax:

```
strGetVersion() As String
```

Summary:

The function returns the version of currently executing VistaRemote.

Returns:

Returns a string representing the version of the vista remote being used.

Remarks

This method allows the user to get the version of Vista Remote. This can be used by the user while logging errors. Such that which version of vista remote is being used could be tracked.

Miscellaneous

Error Codes and Messages

Code	Description
0	Method completed successfully
1	Invalid Command request. This happens only incase cinema is using older version of Vista Sales Server than the minimum required version
2	Not enough seats are available for sale to fulfill request. This means that there are NOT enough seats which can be sold thru this channel.
3	Could not allocate all seats in a contiguous block. This means that the number of seats ordered, are available, but NOT in contiguous block. Vista will NOT book seats in this situation.
4	Parameters passed are not correct. This usually happens because of some data type mismatch or incorrect date format or even maybe because of some incorrect regional settings
5	An unexpected error/database error/component error has occurred. This is a Generic error. The reason can ONLY be found by looking into the Log file at Cinema end.
10	The selected booking could not be found. This means that Vista is unable to find the booking you are trying to change.
11	The selected booking has already been picked up. This means that the tickets, for the booking you are trying to change, have already been picked up by the customer.
13	Could not order concession elements of the ticket package
14	The value of ticket package requested does not match the total value of the package as calculated by server.
15	Unpaid bookings are no longer permitted due to cinema session time/unpaid booking cutoff.
16	Payment was declined OR an error occurred within the Vista Payment component - client must check the Payment Module return strings for details. This will happen only if Vista Payment Module is used for Payment Gateway.
17	The selected booking does not exist
18	The selected booking is not unpaid and cannot be released/cancelled
19	The selected booking has already been released/cancelled
20	There were no elements in the selected transaction liable for refund.
21	Paid orders are NOT permitted when order includes voucher ticket types
22	Requested booking is cancelled
23	Requested booking is unpaid
24	Requested booking is already picked up
25	Requested edit booking already picked up
26	Requested edit booking cancelled
27	Requested edit booking already in edit mode
28	Requested edit booking status changed by another process
29	Client App is not authorized to create unpaid bookings
30	Selling data output is not required - no reference data changes since last output to client
33	Booking is already paid
34	Unpaid booking processed as paid however collected flag could not be set - customer should still receive tickets / vouchers

35	Unpaid booking processing requested but the unpaid booking has not been initialized by calling GetUnpaidBookingPrintStream
50	Invalid Logon details
51	Invalid WorkstationId
52	WorkstationId represented with different clientID
53	ClientID represented with different clientID
54	User Logged in elsewhere

Notes

- The DLL will never raise an exception, so the programmer has to check if the function returns false. And if it does, then he has to check the value of strException to know the error that occurred.
- All the properties are READ-ONLY.
- The sample codes are also available with the package or on request.