Design Style #1 Mealy

Monday, April 19, 2021 7:35 PM

```
LIBRARY ieee;
USE ieee.std_logic_1164.all;
-----------------------------------------------------
ENTITY <entity_name> IS
   PORT ( input: IN <data_type>;
          reset, clock: IN STD_LOGIC;
          output: OUT <data_type>);
END <entity_name>;
-----------------------------------------------------
ARCHITECTURE <arch_name> OF <entity_name> IS
   TYPE state IS (state0, state1, state2, state3, ...);
   SIGNAL pr_state, nx_state: state;
BEGIN
   ---------- Lower section: -----------------------
   PROCESS (reset, clock)
   BEGIN
      IF (reset='1') THEN
         pr_state <= state0;
      ELSIF (clock'EVENT AND clock='1') THEN
         pr_state <= nx_state;
      END IF;
   END PROCESS;
   ---------- Upper section: -----------------------
   PROCESS (input, pr_state)
   BEGIN
      CASE pr_state IS
         WHEN state0 =>
            IF (input = ...) THEN
               output <= <value>;
               nx_state <= state1;
            ELSE ...
            END IF;
         WHEN state1 =>
            IF (input = ...) THEN
               output <= <value>;
               nx_state <= state2;
            ELSE ...
            END IF;
         WHEN state2 =>
            IF (input = ...) THEN
               output <= <value>;
               nx_state <= state3;
            ELSE ...
            END IF;
         ...
      END CASE;
   END PROCESS;
END <arch name>;
```

o/p is written after the o/p.
Since o/p is not state dependent