SP Technical Research Institute of Sweden



PART OF RI. SE

The SP RC Car

Benjamin Vedder
benjamin.vedder@sp.se

2016-07-06, Darmstadt

The SP RC Car



The SP RC Car
Overview

- Positioning:
  - IMU (Accelerometer, Gyroscope, Magnetometer).
  - RTK GPS.
  - Odometry.
- Speed from <1 Km/h to 80 Km/h
- Autopilot.
- Custom user interface.
  - Visualization, remote control, configuration, communication.
  - RTK correction data from different possible sources.
- Fully open source.



The SP RC Car
RTK GPS for accurate positioning

SPP



RTK



The SP RC Car
Hardware Block Diagram



The SP RC Car
Hardware Locations



The SP RC Car
VESC Motor Controller

- Benjamins open source and open hardware spare time project developed during the past 4 years.
- 20 000+ lines of C code in 100+ files.
- 14 threads + interrupts and DMA.
- Cont power: 2000 W
- Peak power: over 5000 W
- Size: 60 x 60 x 20 mm







The SP RC Car
VESC - BLDC Tool GUI



The SP RC Car

Main Controller - front



The SP RC Car
Controller - back



The SP RC Car
RC Car Tool - Main Page



The SP RC Car
Linux Computer Block Diagram



The SP RC Car

RC Car Tool - IMU raw data



The SP RC Car
RC Car Tool - Terminal



The SP RC Car
RC Car Tool - GPS Data



The SP RC Car
RC Car Tool - Configuration



The SP RC Car
RC Car Tool - RTCM correction data



The SP RC Car

RC Car Tool - Real-time plot and track editor for the autopilot





Thank you for your attention!

PART OF RI. SE