



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

Experiment No.7
Implement Circular Linked List ADT.
Name: Vedika Pawar
Roll No:46
Date of Performance:
Date of Submission:
Marks:
Sign:

Experiment No. 7: Circular Linked List Operations

Aim: Implementation of Circular Linked List ADT

Objective:

In circular linked list last node is connected to first node. On other hand circular linked list can be used to implement traversal along web pages.

Theory:

In a circular linked list, the last node contains a pointer to the first node of the list. We can have a circular singly linked list as well as a circular doubly linked list. While traversing a circular linked list, we can begin at any node and traverse the list in

any one direction, forward or backward, until we reach the same node where we started. Thus, a circular linked list has no beginning and no ending.

Inserting a New Node in a Circular Linked List

Case 1: The new node is inserted at the beginning.

Case 2: The new node is inserted at the end.

Deleting a Node from a Circular Linked List

Case 1: The first node is deleted.

Case 2: The last node is deleted.

Insertion and Deletion after or before a given node is same as singly linked list.

Algorithm

Algorithm to insert a new node at the beginning

Step 1: IF AVAIL = NULL

Write OVERFLOW

Go to Step 9 [END OF IF]

Step 2: SET NEW_NODE = AVAIL

Step 3: SET AVAIL = AVAIL → NEXT

Step 4: SET NEW_NODE → DATA = VAL

Step 5: SET PTR = START

Repeat Step 6 while PTR NEXT != START

Step 6: SET PTR = PTR NEXT [END OF LOOP]

Step 7: SET NEW_NODE--> NEXT= START

Step 8: SET PTR-->NEXT = START

Step 9: SET START = NEW_NODE

Step 10: EXIT

Algorithm to insert a new node at the end

Step 1: IF AVAIL = NULL

Write OVERFLOW

Go to Step 11 [END OF IF]

Step 2: SET NEW_NODE = AVAIL

Step 3: SET AVAIL = AVAIL--> NEXT

Step 4: SET NEW_NODE -->DATA = VAL

Step 5: SET NEW_NODE-->NEXT = START

Step 6: SET PTR = START

Step 7: Repeat Step 8 while PTR--> NEXT != START

Step 8: SET PTR = PTR -->NEXT [END OF LOOP]

Step 9: SET PTR -->NEXT = NEW_NODE

Step 10: EXIT

Algorithm to delete the first node

Step 1: IF START = NULL

Write UNDERFLOW

Go to Step 6 [END OF IF]

Step 2: SET PTR = START

Step 3: Repeat Step 4 while PTR--> NEXT != START

Step 4: SET PTR = PTR -->NEXT [END OF LOOP]

Step 4: SET PTR→NEXT = START -->NEXT

Step 5: FREE START

Step 6: EXIT

Algorithm to delete the last node

Step 1: IF START = NULL

Write UNDERFLOW

Go to Step 7 [END OF IF]

Step 2: SET PTR = START [END OF LOOP]

Step 3: Repeat Step 4 and Step 5 while PTR -->NEXT != START

Step 4: SET PREPTR = PTR

Step 5: SET PTR = PTR -->NEXT

Step 6: SET PREPTR-->NEXT = START

Step 7: FREE PTR

Step 8: EXIT

Code:

#include

```
#include

#include

struct node {
int data;

struct node *next;

}; struct node *start = NULL;

struct node *create_cll(struct node *);

struct node *display(struct node *);

struct node *insert_beg(struct node *);

struct node *insert_end(struct node *);

struct node *delete_beg(struct node *);

struct node *delete_end(struct node *);

struct node *delete_after(struct node *);

struct node *delete_list(struct node *);

int main() {

int option;

clrscr();

do {

printf("\n\n *****MAIN MENU *****");

printf("\n 1: Create a list");

printf("\n 2: Display the list");

printf("\n 3: Add a node at the beginning");

printf("\n 4: Add a node at the end");

printf("\n 5: Delete a node from the beginning");

printf("\n 6: Delete a node from the end");

printf("\n 7: Delete a node after a given node");

printf("\n 8: Delete the entire list");

printf("\n 9: EXIT");
```

```
printf("\n\n Enter your option : ");  
scanf("%d", &option);  
switch(option) {  
case 1:  
start = create_cll(start);  
printf("\n CIRCULAR LINKED LIST CREATED");  
break;  
case 2:  
start = display(start);  
break;  
case 3:  
start = insert_beg(start);  
break;  
case 4:  
start = insert_end(start);  
break;  
case 5:  
start = delete_beg(start);  
break;  
case 6:  
start = delete_end(start);  
break;  
case 7:  
start = delete_after(start);  
break;  
case 8:  
start = delete_list(start);  
printf("\n CIRCULAR LINKED LIST DELETED");
```

```

    break;
}
}while(option !=9);

getch();

return 0; }

struct node *create_cll(struct node *start)
{ struct node *new_node, *ptr;

int num;

printf("\n Enter -1 to end");

printf("\n Enter the data : ");

scanf("%d", &num);

while(num!=-1) {

    new_node = (struct node*)malloc(sizeof(struct node));

    new_node -> data = num;

    if(start == NULL) {

new_node -> next = new_node;

start = new_node;

    }

else

{

    ptr = start;

while(ptr -> next != start)

ptr = ptr -> next;

ptr -> next = new_node;

new_node -> next = start;

} printf("\n Enter the data : ");

scanf("%d", &num);

} return start;

```

```

} struct node *display(struct node *start)
{ struct node *ptr; ptr=start;
while(ptr -> next != start) {
    printf("\t %d", ptr -> data);
    ptr = ptr -> next; }
    printf("\t %d", ptr -> data);
return start; }

struct node *insert_beg(struct node *start) {
    struct node *new_node, *ptr;
int num;

    printf("\n Enter the data : ");
    scanf("%d", &num);

new_node = (struct node *)malloc(sizeof(struct node));
    new_node -> data = num;

    ptr = start;

    while(ptr -> next != start)

        ptr = ptr -> next;

    ptr -> next = new_node;

    new_node -> next = start;

    start = new_node;

return start;

} struct node *insert_end(struct node *start) {

    struct node *ptr, *new_node;

int num;

    printf("\n Enter the data : ");
    scanf("%d", &num);

new_node = (struct node *)malloc(sizeof(struct node));

    new_node -> data = num;

```



```

ptr = start;
while(ptr -> next != start)
ptr = ptr -> next;
ptr -> next = new_node;
new_node -> next = start;
return start;
}

struct node *delete_beg(struct node *start) {
struct node *ptr;
ptr = start;
while(ptr -> next != start)
ptr = ptr -> next;
ptr -> next = start -> next;
free(start);
start = ptr -> next;
return start;
} struct node *delete_end(struct node *start) {
struct node *ptr,*preptr;
ptr = start;
while(ptr -> next != start) {
preptr = ptr;
ptr = ptr -> next;
}
preptr -> next = ptr -> next;
free(ptr);
return start;
} struct node *delete_after(struct node *start) {
struct node *ptr, *preptr;

```

```

int val;

printf("\n Enter the value after which the node has to deleted : ");

scanf("%d", &val);

ptr = start;

preptr = ptr;

while(preptr -> data != val) {

preptr = ptr;

ptr = ptr -> next;

} preptr -> next = ptr -> next;

if(ptr == start) start = preptr -> next;

free(ptr);

return start;

} struct node *delete_list(struct node *start) {

struct node *ptr;

ptr = start;

while(ptr -> next != start)

start = delete_end(start);

free(start);

return start;

}

```

Output:

Conclusion:

Write an example of insertion and deletion in the circular linked list while traversing the web pages?

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <string.h>
```

```
// Structure for a web page node in the circular linked list
```

```
struct WebPage {
```

```
    char title[50];
```

```
    struct WebPage* next;
```

```
};
```

```
struct WebPage* current = NULL;
```

```
// Function to insert a new web page
```

```
void insertPage(char title[]) {
```

```
    struct WebPage* newPage = (struct WebPage*)malloc(sizeof(struct WebPage));
```

```
    strcpy(newPage->title, title);
```

```
    if (current == NULL) {
```

```
        current = newPage;
```

```
        newPage->next = newPage; // Make it point to itself in a circular list.
```

```
    } else {
```

```
        newPage->next = current->next;
```

```
        current->next = newPage;
```

```

        current = newPage;

    }

}

// Function to delete the current web page

void deletePage() {

    if (current == NULL) {

        printf("No web page to delete.\n");

        return;

    }

    struct WebPage* nextPage = current->next;

    if (current == current->next) {

        free(current);

        current = NULL;

    } else {

        current->next = nextPage->next;

        free(nextPage);

    }

}

// Function to display the current web page

```

```
void displayCurrentPage() {  
  
    if (current == NULL) {  
  
        printf("No current web page.\n");  
  
    } else {  
  
        printf("Current Page: %s\n", current->title);  
  
    }  
}
```

```
int main() {  
  
    insertPage("Home Page");  
  
    insertPage("About Us");  
  
    insertPage("Contact Us");  
  
  
    displayCurrentPage(); // Displays "Contact Us"  
  
  
  
    deletePage();      // Deletes "Contact Us"  
  
    displayCurrentPage(); // Displays "About Us"  
  
  
  
    deletePage();      // Deletes "About Us"  
  
    displayCurrentPage(); // Displays "Home Page"  
  
  
    return 0;  
}
```

