

Question 10

```
vedsk0831@DESKTOP-83FU7HB:~$ mkdir -p ~/oss
cd ~/oss
nano q10.c
vedsk0831@DESKTOP-83FU7HB:~/oss$ gcc -Wall -Wextra q10.c -o q10
vedsk0831@DESKTOP-83FU7HB:~/oss$ ./q10
Current Directory: /home/vedsk0831/oss

Before export:
OSSP_VAR is not set

Setting OSSP_VAR=Hello_OSSP
After export:
OSSP_VAR = Hello_OSSP

Child Process:
OSSP_VAR = Hello_OSSP

Program completed successfully.
vedsk0831@DESKTOP-83FU7HB:~/oss$ pwd
/home/vedsk0831/oss
vedsk0831@DESKTOP-83FU7HB:~/oss$ echo $OSSP_VAR

vedsk0831@DESKTOP-83FU7HB:~/oss$ |
```

CODE:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <string.h>
```

```
#include <unistd.h>
```

```
#include <sys/wait.h>
```

```
int main()
```

```
{
```

```
    char cwd[1024];
```

```
    /* pwd functionality */
```

```
    if (getcwd(cwd, sizeof(cwd)) != NULL)
```

```
{  
    printf("Current Directory: %s\n", cwd);  
}  
else  
{  
    perror("getcwd");  
}  
  
/* export functionality */  
printf("\nBefore export:\n");  
  
char *value = getenv("OSSP_VAR");  
  
if (value != NULL)  
    printf("OSSP_VAR = %s\n", value);  
else  
    printf("OSSP_VAR is not set\n");  
  
printf("\nSetting OSSP_VAR=Hello_OSSP\n");  
  
if (setenv("OSSP_VAR", "Hello_OSSP", 1) == -1)  
{  
    perror("setenv");  
    return 1;  
}  
  
printf("After export:\n");  
printf("OSSP_VAR = %s\n", getenv("OSSP_VAR"));
```

```
/* Check that child process inherits variable */  
pid_t pid = fork();  
  
if (pid < 0)  
{  
    perror("fork");  
    return 1;  
}  
  
if (pid == 0)  
{  
    printf("\nChild Process:\n");  
    printf("OSSP_VAR = %s\n", getenv("OSSP_VAR"));  
    exit(0);  
}  
  
waitpid(pid, NULL, 0);  
  
printf("\nProgram completed successfully.\n");  
  
return 0;  
}
```