Tcl

=====

Definition

The process of combining all related operations into a single unit and executing them according to the rule "either all operations should succeed or none should succeed" is called Transaction Management.

A transaction is considered a single unit of work and follows the principle:

"Either all or none."

Example: Funds Transfer

Consider a money transfer process between two accounts:

1. **Debit amount from the sender's account**
2. **Credit amount into the receiver's account**

Both operations should be executed as a single transaction.

If the amount is debited from the sender's account successfully, but crediting the receiver's account fails, it may lead to data inconsistency problems.

Types of Transactions

There are two types of transactions:

1. **Local Transactions**
2. **Global Transactions**

1. Local Transactions

In local transactions, all operations of a transaction are executed on the same database.

Example:

Funds transfer from one account to another account where both accounts belong to the same bank.

2. Global Transactions

In global transactions, operations of a transaction are executed on different databases.

Example:

Funds transfer from one account to another account where both accounts belong to different banks.

Acid Properties

==========

In the context of **Database Management Systems (DBMS)**, the term **ACID** refers to a set of properties that ensure database transactions are processed reliably. These properties are crucial for maintaining the integrity and consistency of data, especially when there are system failures, power outages, or multiple transactions occurring simultaneously. **ACID** is an acronym that stands for:

1. **Atomicity**
2. **Consistency**
3. **Isolation**
4. **Durability**

1. Atomicity:

Atomicity ensures that a transaction is treated as a single, indivisible unit. This means that either all the operations of the transaction are successfully completed, or none of them are applied. If any part of the transaction fails, the whole transaction is rolled back.

- **Example Scenario:**
    - Suppose you are transferring money from **Account A** to **Account B** in a banking system.
    - The transaction involves two operations:
        1. Subtracting $100 from **Account A**.
        2. Adding $100 to **Account B**.
    - If the system crashes after subtracting from **Account A** but before adding to **Account B**, the transfer would be incomplete. **Atomicity** ensures that the transaction is fully executed, or not executed at all, and both accounts will remain in a consistent state.
    - If the transaction fails, both operations will be rolled back, and no money will be deducted from **Account A** or added to **Account B**.

2. Consistency:

Consistency ensures that a transaction brings the database from one valid state to another, maintaining all predefined rules, constraints, and data integrity. After a transaction, the database must remain in a valid state.

- **Example Scenario:**
    - Consider a rule that says a bank account balance cannot go below $0.
    - If a transaction tries to withdraw more money than the account holds, the database would be in an inconsistent state. **Consistency** ensures that the transaction is not allowed to proceed unless the integrity of the database (like account balance) is maintained.
    - If the account balance would become negative as a result of the transaction, the database would reject the transaction and maintain consistency.

3. Isolation:

Isolation ensures that the operations of a transaction are isolated from the operations of other concurrent transactions. The effects of one transaction are not visible to others until the transaction is complete. This prevents "dirty reads" or inconsistent data from being accessed by other transactions during the process.

- **Example Scenario:**
    - Imagine two users are accessing the same bank account at the same time:
        - User 1 wants to transfer money from **Account A** to **Account B**.
        - User 2 is trying to check the balance of **Account A** at the same time.
    - If the transactions are not isolated, User 2 could see an intermediate state of **Account A** during the transfer, which could be inaccurate (e.g., the balance may appear to be higher than it should be).
    - **Isolation** ensures that User 2 only sees the final result of the transaction after User 1's transaction is fully completed, maintaining the integrity of the data.

4. Durability:

Durability guarantees that once a transaction has been committed, it will persist, even in the event of a system crash or power failure. The changes made by the transaction are permanently recorded in the database.

- **Example Scenario:**

- After a successful transfer of $100 from **Account A** to **Account B**, the transaction is committed.
- Even if the system crashes immediately after the commit, when the system restarts, the changes (the money transfer) will still be present in the database.
- **Durability** ensures that once a transaction is confirmed, its effects are permanent and not lost.

Summary of ACID Properties in DBMS:

- **Atomicity**: All or nothing.
- **Consistency**: The database remains in a valid state.
- **Isolation**: Transactions do not interfere with each other.
- **Durability**: Committed changes are permanent.

These properties ensure the database maintains its integrity, even when facing issues like system failures or concurrent transactions.

1. COMMIT

Definition

COMMIT is used to **permanently save all changes** made during the current transaction into the database.

Once committed:

- Changes become permanent.
- Other users can see the changes.
- You cannot undo the changes using ROLLBACK.

Syntax

COMMIT;

Example

– Step 1: Create Table

```
CREATE TABLE employees (
  emp_id INT PRIMARY KEY,
  emp_name VARCHAR(50),
```

```
  salary DECIMAL(10,2)
);
– Step 2: Start Transaction
START TRANSACTION;

– Step 3: Insert Records
INSERT INTO employees VALUES (101,'Rahul',45000);
INSERT INTO employees VALUES (102,'Priya',50000);

– Step 4: Commit
COMMIT;
```

Real-Life Example

Imagine you transfer ₹10,000 from your bank account.

- Money deducted from your account
- Money added to receiver's account

Only after both operations succeed, the bank executes:

2. ROLLBACK

Definition

ROLLBACK is used to **undo all changes** made in the current transaction before a COMMIT.

If something goes wrong, rollback restores the database to its previous state.

Syntax

```
Rollback;
```

Example

– Step 1

Start transaction;

– step2

INSERT INTO employees VALUES

(103,'Kiran',60000);

INSERT INTO employees VALUES

(104,'Sneha',70000);

– Step 3

Suppose you inserted wrong data.

Execute

Rollback;

Real-Life Example

Online shopping:

- Product reserved
- Payment failed

Database executes

Rollback;

3. SAVEPOINT

Definition

A **SAVEPOINT** creates a checkpoint inside a transaction.

Instead of rolling back the entire transaction, you can rollback only to a specific savepoint.

Syntax

Savepoint save-point-name;

Rollback to savepoint

ROLLBACK TO savepoint_name;

Commit

Commit;

Example

START TRANSACTION;

-- Increase Rahul's salary

UPDATE employees

SET salary = 48000

WHERE emp_id = 101;

SAVEPOINT s1;

-- Increase Priya's salary

UPDATE employees

SET salary = 53000

WHERE emp_id = 102;

-- Delete Ajay's record

DELETE FROM employees

WHERE emp_id = 105;

SAVEPOINT s2;

-- Update Sneha's salary

```
UPDATE employees
SET salary = 70000
WHERE emp_id = 104;

SELECT * FROM employees;
ROLLBACK TO s2;
SELECT * FROM employees;
COMMIT;
```

MySQL VIEWS

1. What Is a View?

A view is a virtual table in MySQL, built from the result of a stored SELECT statement. It looks and behaves like a regular table when you query it — you can SELECT from it, filter it, and join it — but it does not store any data of its own. Every time a view is queried, MySQL runs its underlying SELECT statement against the real ("base") tables and returns the result.

Think of a view as a saved, reusable query with a name. Instead of typing out a long JOIN every time, you create the view once, then simply run: SELECT * FROM view_name;

```
CREATE VIEW view_name AS
SELECT column1, column2, ...
FROM table_name
WHERE condition;
```

2. Why Do We Need Views?

- **Simplify complex queries:** Hide multi-table JOINs, subqueries, and calculations behind a single, simple table-like name.
- **Reuse query logic:** Write a complex SELECT once and reuse it everywhere — reports, applications, dashboards — without copy-pasting SQL.
- **Data security:** Expose only specific columns or rows to certain users, without granting them access to the full base table.

- **Different perspectives of the same data:** Different departments can have their own tailored 'view' of the same underlying tables.
- **Logical data independence:** If the underlying table structure changes slightly, you can often adjust just the view definition and keep all dependent queries working unchanged.
- **Simplified reporting:** Pre-package aggregations (totals, averages, counts) into a view so business users can query them without knowing SQL joins or GROUP BY.

3. Advantages of Views

- Security: restrict access to sensitive columns (e.g. salary) or sensitive rows (e.g. only a user's own department).
- Simplicity: end users and applications interact with a simple, named virtual table instead of complex SQL.
- Reusability: one view definition can be reused across many reports, applications, and ad-hoc queries.
- Consistency: business logic (calculations, filters) lives in one place, so results are always consistent.
- Maintainability: a business-rule change only needs to be made once, inside the view.
- Custom data presentation: rename or reformat columns, add computed columns, without touching the base table.
- No extra storage cost: a standard view stores no data — only its query definition.

4. What Happens Without Views?

Without views, every application, report, or analyst that needs the same joined/filtered/aggregated data must write out (and maintain) the full SQL logic independently. This leads to duplicated code, inconsistent results when the logic drifts between copies, harder security control, and painful maintenance whenever the business rules or schema change.

Aspect	Without Views	With Views
Repeated complex JOINs	Every report/query rewrites the same 5-table JOIN logic	JOIN logic is written once inside the view

Security	Users need direct table access; hard to hide specific columns/rows	Users query a view that exposes only approved columns/rows
Consistency	Business logic can drift between copies of the same query	Single source of truth — one definition used everywhere
Maintenance	A schema or rule change means updating every copy of the query	Change the view definition once; every consumer gets the update
Readability	Application code full of long, repeated SQL joins	Application code simply does SELECT * FROM view_name
Storage	N/A — no extra storage either way	No extra storage — a view is virtual, not a copy of data

View vs Table

Table	**View**
Physically stores data	Virtual table based on a query
Can store records directly	Usually does not store separate records
Created using CREATE TABLE	Created using CREATE VIEW
Can contain all table data	Can show selected rows/columns
Used for permanent data storage	Mainly used for abstraction, security, and reusable queries

Creating Views

Basic Syntax:

CREATE VIEW view_name AS

SELECT columns

FROM tables

WHERE conditions;

Altering Views

Syntax for ALTER VIEW:

ALTER VIEW view_name AS

SELECT new_columns

FROM new_tables

WHERE new_conditions;

Note: Not all database systems support ALTER VIEW. Some require DROP and CREATE.

Dropping Views

Basic Syntax:

DROP VIEW view_name;

DROP VIEW IF EXISTS view_name; -- Safe drop

5. Real-Time Example: Database & Table Setup

The examples in this guide use a simple company database with two related tables: departments and employees.

```
CREATE TABLE departments (
        dept_id INT PRIMARY KEY AUTO_INCREMENT,
        dept_name VARCHAR(50),
        location VARCHAR(50)
);

CREATE TABLE employees (
        emp_id INT PRIMARY KEY AUTO_INCREMENT,
        emp_name VARCHAR(100),
```

```
    dept_id INT,
    designation VARCHAR(50),
    salary DECIMAL(10,2),
    join_date DATE,
    FOREIGN KEY (dept_id) REFERENCES departments(dept_id)
);
```

Sample Data

```
INSERT INTO departments (dept_name, location) VALUES
('IT','Hyderabad'), ('HR','Bangalore'), ('Finance','Chennai'), ('Sales','Mumbai');

INSERT INTO employees (emp_name, dept_id, designation, salary, join_date)
VALUES
('Rahul',1,'Software Engineer',55000,'2021-06-15'),
('Anita',2,'HR Executive',38000,'2020-03-21'),
('Suresh',4,'Sales Manager',52000,'2019-08-10'),
('Priya',1,'Team Lead',65000,'2022-01-05'),
('Kiran',3,'Finance Analyst',48000,'2018-12-11'),
('Deepika',2,'HR Manager',60000,'2019-10-19');
select*from departments;
select*from employees;
```

6. View Examples

6.1 Basic View — Employee-Department Join

Use case: avoid re-writing the JOIN between employees and departments every time someone needs an employee's department name.

```
CREATE VIEW vw_employee_department AS
SELECT e.emp_id, e.emp_name, e.designation, d.dept_name, d.location
FROM employees e
JOIN departments d ON e.dept_id = d.dept_id;

-- Usage
SELECT * FROM vw_employee_department;
```

TO SHOW THE VIEWS IN A DATABASE;

SHOW FULL TABLES WHERE TABLE_TYPE = 'VIEW';

6.2 Security View — Hiding Salary

Use case: HR generalists should see employee details, but salary must stay restricted to payroll staff only.

```
CREATE VIEW vw_employee_public AS
SELECT emp_id, emp_name, designation, dept_id, join_date
FROM employees;

-- Grant access to the view only, never to the base table
GRANT SELECT ON company.vw_employee_public TO 'hr_user'@'%';
```

6.3 Aggregate / Reporting View — Department Salary Summary

Use case: management wants total and average salary per department without re-writing GROUP BY logic every time.

```
CREATE VIEW vw_department_salary_summary AS
SELECT d.dept_name,
       COUNT(e.emp_id)   AS total_employees,
       SUM(e.salary)     AS total_salary,

       AVG(e.salary) AS average_salary
```

```
FROM employees e
JOIN departments d ON e.dept_id = d.dept_id
GROUP BY d.dept_name;


-- Usage
SELECT * FROM vw_department_salary_summary;
```

Note: because this view uses GROUP BY and aggregate functions, it is read-only — it cannot be used for INSERT, UPDATE, or DELETE.

6.4 Filtered, Updatable View — WITH CHECK OPTION

Use case: an 'IT department only' view that stays consistent even when new rows are added through it.

```
CREATE VIEW vw_it_employees AS
SELECT emp_id, emp_name, designation, dept_id, salary
FROM employees
WHERE dept_id = 1
WITH CHECK OPTION;


-- This succeeds (dept_id matches the view's WHERE clause)
INSERT INTO vw_it_employees (emp_name, dept_id, designation, salary)
VALUES ('Vijay', 1, 'DevOps Engineer', 58000);


-- This fails because dept_id = 2 violates the view's WHERE condition
INSERT INTO vw_it_employees (emp_name, dept_id, designation, salary)
VALUES ('Sneha', 2, 'HR Assistant', 40000);
```

6.5 Computed Column View — Annual Salary

Use case: present a calculated column (annual salary) without altering the base table.

```
CREATE VIEW vw_employee_annual_salary AS
SELECT emp_name, salary AS monthly_salary, salary * 12 AS annual_salary
FROM employees;
```

6.6 Multi-Level View — Built on Another View

Use case: a 'high earners' view built directly on top of the department salary summary view.

```
CREATE VIEW vw_high_paying_departments AS
SELECT dept_name, average_salary
FROM vw_department_salary_summary
WHERE average_salary > 50000;
```

7. Updating Data Through Views

A view is updatable only when MySQL can unambiguously map each row of the view back to exactly one row of one base table. A view becomes non-updatable if it contains any of the following:

- Aggregate functions: SUM(), COUNT(), AVG(), MIN(), MAX()
- GROUP BY or HAVING
- DISTINCT
- UNION or UNION ALL
- Subqueries in the SELECT list that refer to the same base table
- Joins where the modified column doesn't map to a single base table

```
-- Updatable example
UPDATE vw_it_employees
SET salary = 60000
WHERE emp_name = 'Vijay';
```

```
-- Reflected immediately in the base employees table
```

8. Managing Views — ALTER, DROP, SHOW

```
-- View the exact definition of a view
SHOW CREATE VIEW vw_employee_department;

-- Modify an existing view's definition
ALTER VIEW vw_employee_department AS
SELECT e.emp_id, e.emp_name, d.dept_name
FROM employees e
JOIN departments d ON e.dept_id = d.dept_id;

-- Remove a view (base table data is untouched)
DROP VIEW vw_employee_department;

-- List all views in the current database
SELECT table_name
FROM information_schema.views
WHERE table_schema = 'jfs2';
```

9. Types of Views

- **Simple View:** Built from a single table, with no aggregate functions, GROUP BY, or joins. Usually fully updatable.
- **Complex View:** Built from multiple tables using joins, and/or includes aggregate functions, GROUP BY, or subqueries. Often read-only.

- **Updatable View:** A view (simple or a well-formed join) through which INSERT/UPDATE/DELETE can be performed.
- **Read-Only View:** Any view containing aggregates, GROUP BY, DISTINCT, or UNION — data can only be selected, never modified through it.
- **Materialized View (not native to MySQL):** A view whose results are physically stored and periodically refreshed. MySQL does not support this natively — it must be simulated using a real summary table refreshed via a scheduled EVENT or trigger.

10. Interview Questions — Basic Level

Q1. What is a view in MySQL?

A view is a virtual table based on the result of a stored SELECT query. It does not store data itself (in standard MySQL views) — it stores the query definition, and the data is fetched from the underlying base table(s) each time the view is used.

Q2. How do you create a view?

Use the CREATE VIEW statement followed by a SELECT query. Example: CREATE VIEW view_name AS SELECT column1, column2 FROM table_name WHERE condition;

Q3. How do you see the data inside a view?

You query it exactly like a table: SELECT * FROM view_name;

Q4. How do you check the underlying SQL definition of a view?

Use SHOW CREATE VIEW view_name; — this returns the exact CREATE VIEW statement used to define it.

Q5. How do you delete (remove) a view?

Use DROP VIEW view_name; This removes only the view definition, never the underlying table data.

Q6. Does a view store data physically?

No. A standard MySQL view does not store data. It stores only the query. Every time the view is accessed, MySQL re-executes the underlying query against the base table(s).

Q7. What is the main difference between a table and a view?

A table physically stores data on disk, while a view is a stored query that presents data drawn live from one or more tables. Views have no independent storage for rows.

Q8. Can a view be created using multiple tables?

Yes. A view can be based on a JOIN across two or more tables, exactly as a normal SELECT query can.

Q9. Can you use WHERE, GROUP BY, and ORDER BY inside a view definition?

Yes, a view can include WHERE, GROUP BY, HAVING, JOIN, and (with some restrictions in subqueries) ORDER BY clauses, since it is built from any valid SELECT statement.

Q10. Is it possible to rename a view?

MySQL has no direct RENAME VIEW command. The common approach is to create a new view with the desired name using the same SELECT definition, then drop the old view.

11. Interview Questions — Intermediate Level

Q1. What is an updatable view? What restrictions apply?

An updatable view allows INSERT, UPDATE, and DELETE operations that pass through to the base table. A view is updatable only if it has no aggregate functions (SUM, COUNT, AVG, etc.), no GROUP BY/HAVING/DISTINCT, no UNION, and comes from a single table (or a join where the modified columns map to one underlying table).

Q2. What is the WITH CHECK OPTION and why is it used?

WITH CHECK OPTION ensures that any INSERT or UPDATE performed through the view still satisfies the view's WHERE clause. Without it, a user could insert or update a row through a filtered view and the row would then silently disappear from that view's result set.

Q3. Can you insert data into a view? Under what conditions?

Yes, but only if the view is updatable (see above) and the INSERT provides values for all NOT NULL columns of the base table that are not included in the view (or those columns have defaults).

Q4. Does MySQL support materialized views?

Not natively. MySQL views are always virtual — they run the underlying query on every access. To get materialized-view-like behavior, you must manually create a real table and refresh it periodically (e.g. via a scheduled event or trigger), which acts as a workaround.

Q5. Can a view be created on top of another view?

Yes, MySQL allows nested views — a view can be defined using a SELECT that reads from another view. However, deeply nested views can hurt performance and make debugging harder.

Q6. What happens if you drop or alter a base table that a view depends on?

MySQL does not check view dependencies at DROP time. If you drop or rename a column/table used by a view, the view becomes invalid, and querying it will raise an error at execution time (MySQL uses a 'late binding' approach for views).

Q7. Do views improve query performance?

Not directly. A view is essentially a saved query — MySQL still executes the full underlying SELECT (join, filters, aggregation) every time the view is queried. Views improve readability, reusability, and security, not raw execution speed. In fact, deeply nested or poorly written views can slow things down.

Q8. How do you modify an existing view's definition?

Use ALTER VIEW view_name AS SELECT ...; to redefine it, or DROP VIEW followed by CREATE VIEW with the new definition.

Q9. Can indexes be created directly on a MySQL view?

No. Since a standard MySQL view has no physical storage, you cannot create an index directly on it. Performance for a view depends entirely on the indexes that exist on its underlying base tables.

Q10. Can a view include an ORDER BY clause, and does it always take effect?

A view can include ORDER BY, but if the outer query that selects from the view also has its own ORDER BY, the outer ORDER BY takes precedence, and the view's internal ordering may be ignored by the optimizer.

12. Interview Questions — Advanced Level

Q1. How do views help implement security and access control?

Views let you expose only specific columns or rows of a table to certain users (column-level and row-level security), without granting them direct access to the base table. For example, a view can omit a salary column entirely so HR staff can see employee details but not compensation data, and you grant SELECT only on the view, not on the table.

Q2. What are the key limitations of MySQL views?

Views cannot have their own indexes; they cannot use certain constructs (like variables, some subquery forms) that make them non-updatable; performance depends on the underlying query being re-run every time; and MySQL does not validate view dependencies automatically when base tables change.

Q3. Explain MySQL's ALGORITHM=MERGE vs ALGORITHM=TEMPTABLE for views.

MERGE algorithm rewrites the outer query and the view's query into a single query and pushes conditions down to the base tables — this is generally faster and allows the view to be updatable. TEMPTABLE algorithm executes the view's query first into an internal temporary table, then runs the outer query against that temp table — this is often slower and makes the view non-updatable. MySQL uses MERGE whenever possible and falls back to TEMPTABLE when the view contains aggregates, DISTINCT, GROUP BY, UNION, or subqueries in the SELECT list.

Q4. How would you find out which views depend on a specific table?

Query the information_schema.VIEWS table and inspect the VIEW_DEFINITION column (or use information_schema.TABLES together with view metadata) to search for references to the table name. There isn't a single built-in 'dependency' table, so text-searching VIEW_DEFINITION for the table name is the common approach: SELECT table_name, view_definition FROM information_schema.views WHERE view_definition LIKE '%employees%';

Q5. Can a view span multiple databases in MySQL?

Yes. A view's SELECT statement can reference tables from a different database using db_name.table_name syntax, as long as the user creating/using the view has the right privileges on both databases.

Q6. Describe a scenario where a view could hurt performance.

A reporting view that joins several large tables with aggregate functions, built on top of two or three other nested views, forces MySQL to use the TEMPTABLE algorithm and materialize large intermediate result sets in memory or on disk for every single query — even a simple SELECT * FROM view WHERE emp_id = 5 ends up scanning and joining much more data than necessary.

Q7. What is the DEFINER clause in a view, and why does it matter?

When a view is created, MySQL records a DEFINER (the user account that created it). By default, the view executes with the privileges of that definer, not the querying user (SQL SECURITY DEFINER, the default). This lets you grant end users access to a view without granting them any direct privileges on the underlying base tables — the view runs with the definer's higher privileges. SQL SECURITY INVOKER changes this so the view runs with the querying user's own privileges instead.

Q8. Can views support aggregate functions and GROUP BY? Are such views updatable?

Yes, views can include SUM(), COUNT(), AVG(), GROUP BY, and HAVING. However, such views are never updatable — MySQL disallows INSERT/UPDATE/DELETE through any view containing aggregate functions, GROUP BY, HAVING, DISTINCT, or UNION, because there's no unambiguous way to map a change back to a single base-table row.

Q9. How can you achieve materialized-view-like behavior in MySQL, since it isn't supported natively?

Create a real physical 'summary' table that mirrors the view's result, and populate/refresh it periodically using a MySQL EVENT (scheduled job) or a trigger-driven update. Applications query this summary table directly for fast reads, while the refresh job keeps it in sync with the source tables — trading real-time accuracy for read performance.

Q10. If two views are nested (a view built on another view), how does MySQL execute the outer query?

MySQL expands nested views at parse time — the outer view's query is effectively rewritten to substitute the inner view's SELECT definition, then the whole thing is optimized together where possible using the MERGE algorithm. If any level requires TEMPTABLE (e.g. due to aggregation), MySQL materializes that intermediate result first, which can compound performance costs across multiple nesting levels.

13. Real-World Scenario-Based Questions

These questions are commonly asked in interviews to test whether a candidate understands practical, real-world use of views rather than just syntax.

Scenario 1. ***HR staff need to see employee names, designations, and departments, but must NOT see salary information. How would you solve this using views?***

Solution: Create a view that selects only the non-sensitive columns (emp_id, emp_name, designation, dept_id) and excludes salary entirely. Grant HR staff SELECT privilege only on this view — not on the base employees table. They can never query a column that was never included in the view's definition.

Scenario 2. ***Management wants one query that always shows total and average salary per department, without every analyst having to write the same JOIN + GROUP BY each time. How do views help?***

Solution: Create a reporting view (e.g. vw_department_salary_summary) that performs the JOIN between employees and departments with SUM(salary) and AVG(salary) grouped by department, once. Analysts then simply run SELECT * FROM vw_department_salary_summary; getting consistent, up-to-date figures without duplicating the underlying logic in every report or tool.

Scenario 3. ***A 5-table join with complex business logic is copy-pasted into 20 different places in the application. What problem does this cause, and how do views fix it?***

Solution: Duplicating the same complex query in 20 places means every future business-rule change (a new filter, a renamed column, an extra join condition) has to be updated in 20 places, which is error-prone and inconsistent. Wrapping the logic in a single view centralizes it — the application code everywhere simply does SELECT ... FROM the_view, and any future change to the business logic is made once, inside the view definition.

Scenario 4. ***The DBA wants to restrict staff to only certain columns of a sensitive table, without managing column-level GRANTs. How do views solve this?***

Solution: Create a view exposing only the approved columns, and grant privileges on the view instead of the base table. This achieves column-level security without MySQL's more cumbersome column-level GRANT syntax, and it's easy to audit since all restricted access flows through one well-named view.

Scenario 5. ***A view is created with WITH CHECK OPTION and a WHERE clause restricting it to department = 'IT'. A user tries to INSERT a row through this view with department = 'HR'. What happens?***

Solution: The INSERT is rejected by MySQL with an error, because WITH CHECK OPTION enforces that any row inserted or updated through the view must still satisfy the view's WHERE condition (department = 'IT'). Without WITH CHECK OPTION, the insert would silently succeed in the base table but the new HR row would simply not appear when querying the view again.

Scenario 6. ***A view was created using ALGORITHM=TEMPTABLE because it contains a GROUP BY. What's the practical impact for the team using it?***

Solution: The view will always be read-only (no INSERT/UPDATE/DELETE through it), and every SELECT against it forces MySQL to build an internal temporary table first — which is slower than the MERGE approach, especially on large base tables. For a frequently queried report, the team should consider periodically caching the results in a real summary table instead of hitting this view constantly.

Scenario 7. ***A column referenced by a view gets renamed by another team during a migration. What happens to the view, and how would you catch this early?***

Solution: MySQL does not validate views against schema changes at the time the column is renamed — the view keeps its old definition text. The problem only surfaces when someone actually queries the view and gets an 'Unknown column' error. To catch this early, teams should search information_schema.views for references to any column/table before making a breaking schema change, or add automated tests that run SELECT * FROM view_name; against a staging database as part of the migration checklist.

Scenario 8. ***Your reporting dashboard needs fast reads on aggregated sales data, but MySQL views don't cache or materialize results. How would you work around this?***

Solution: Build a real, physical 'materialized view' equivalent: a summary table (e.g. daily_sales_summary) populated by a scheduled MySQL EVENT or an ETL job that runs the aggregate query and stores the results. The dashboard reads from this fast, indexed summary table instead of recomputing the aggregation on every page load, accepting a small refresh-interval delay in exchange for speed.