



08/2023
(Neo)Vim
QWERTY

Shortcut Cheat-Sheet

 - moves the cursor
 - command
 (if red, it enters insert mode)
bol = beginning of line, *eol* = end of line,

UPPER	Esc	ex mode	next Word	end Word	R replace mode	back 'til	copy line	undo line	insert at bol	open above	paste before
lower	command mode	q record macro	w next word	e end word	r replace char	t 'til	y copy ^{1,3}	u undo	i insert mode	o open below	p paste after ¹
		append at <i>eol</i>	substitute line	delete to <i>eol</i>	reverse find char	goto last line	screen top	join lines	help	screen bottom	
	a append	s subst. char	d delete ^{1,3}	f find char	g ⁶	h ←	j ↓	k ↑	l →		
	quit ⁴	back-space	change to <i>eol</i>	visual lines	prev Word	prev find	screen middle				
	Z ⁵	X delete char	C change ^{1,3}	v visual mode	b prev word	n next find	m set mark				

Symbols

: command line	@ play macro	! external filter	& repeat :s
< un-indent ³	> indent ³	= auto format ³	. repeat cmd
(begin sentence) end sentence	{ begin para	} end para
/ find	? reverse find	, reverse t/T/f/F	; repeat t/T/f/F
' goto mark <i>bol</i>	` goto mark	\$ <i>eol</i>	% goto match
- prev line	+ next line	_ <i>bol</i> down	 <i>bol</i> / goto col.
# prev ident	* next ident	^ soft <i>bol</i> ⁷	O <i>bol</i>
1 ²	" ¹	~ toggle case	

Command line:

:w - save,
:q - quit,
:q! - quit without saving,
:e f - open file *f*,
:%s/x/y/g - replace '*x*' by '*y*' filewide,
:h - help,
:new - new file

CTRL commands:

CTRL-R - redo,
CTRL-F/-B - page up/down,
CTRL-E/-Y - scroll line up/down,
CTRL-V - block-visual mode

Visual mode:

Move around and type operator to act on selected region

Notes:

- Use "x before a copy/paste/del command to use that register ('clipboard') (*x*=*a..z*,*) (e.g.: "ay\$ to copy rest of line to reg '*a*')
 2 Type in a number before any action to repeat it that number of times (eg: 2p, d2w, 5i, d4j)
- Duplicate operator to act on current line (dd = delete line, >> = indent line)
- ZZ to save & quit, ZQ to quit without saving
- zt - scroll cursor to top
zb - bottom, zz: center
- gg - top of file,
gf - open file under cursor
- After any initial whitespace at *bol*.