```rust
fn main() {
  // Create a function
  fn say_hello() {
    println!("Hello from a function!");
  }

  say_hello(); // Call the function
}
```

```
Hello from a function!
```

```rust
fn main() {
  fn greet(name: &str) {
    println!("Hello, {}!", name);
  }

  greet("John");
}
```

```
Hello, John!
```

```rust
fn main() {
  fn add(a: i32, b: i32) -> i32 {
    return a + b;
  }

  let sum = add(3, 4);
  println!("Sum is: {}", sum);
}
```

```
Sum is: 7
```

```rust
fn main() {
  fn myFunction() {
    let message = "Hello!";
    println!("{}", message);
  }

  myFunction();

  println!("{}", message); // Error.
Try to remove this line
}
```

```
error[E0425]: cannot find value `message
 --> prog.rs:9:18
  |
9 |   println!("{}", message); // Error.
  |                   ^^^^^^^ not found i

error: aborting due to previous error

For more information about this error, t
```

```rust
fn main() {
  let score = 80;

  if score > 50 {
    let result = "Pass";
    println!("Result: {}", result);
  }

  println!("Result: {}", result); //
Error: result is out of scope here. Try
to remove this line
}
```

```
error[E0425]: cannot find value `result`
 --> prog.rs:9:26
  |
9 |   println!("Result: {}", result); //
  |                          ^^^^^^ not

error: aborting due to previous error

For more information about this error, t
```

```rust
fn main() {
  let x = 5;
  let x = 10;
  println!("x is: {}", x);
}
```

```
x is: 10
```

```rust
fn main() {
  let x = 5;

  {
    let x = 10;
    println!("Inside block: {}", x);
  }

  println!("Outside block: {}", x);
}
```

```
Inside block: 10
Outside block: 5
```