

Code Tracing: read() & readlines()

var	val
lines	['apple banana\n', 'cat dog\n', 'banana apple cat']
outputs	[]

* list of strings!

* this is the output of readlines() for words.txt

enumerate()
i=0,1,2

i=0, line='apple banana\n'

if 0 % 2 == 0:

outputs.append(process_line('apple banana\n'))

→ process_line('apple banana\n')

line='apple banana' * after.strip().lower()

words=['apple', 'banana'] * after.split()

result=[]

w='apple'

✓ starts with 'a'

part='ap'

results=['AP'] * after.upper()

* skip else

w='banana'

0 doesn't start with 'a'

w/in function

w = 'banana'

last = 'a'

result = ['AP', 'bananaa6']

Var	Val
outputs	['AP-bananaa6']

i = 1, line = 'cat dog \n'

if $1 \% 2 \neq 0$

i = 2, line = 'banana apple cat'

if $2 \% 2 == 0$:

outputs.append(process_line('banana apple cat'))

→ process_line('banana apple cat')

line	'banana apple cat'
words	['banana', 'apple', 'cat']
result	[]

w = 'banana'

last = 'a'

result = ['bananaa6']

w = 'apple'

part = 'ap'

result = ['bananaa6', 'AP']

w = 'cat'

last = 't'

result = ['bananaa6', 'AP', 'catt3']

var

val

outputs

['AP-bananaa6',

'bananaa6-AP-catt3']

~~print()~~

AP-bananaa6

bananaa6-AP-catt3