

## MySQL Assignment-2

1. Create the following tables with the given structures and insert sample data as specified:

### SALESPEOPLE:

```
Create table SALESPEOPLE (  
    Snum int(4),  
    Sname varchar(10),  
    City varchar(10),  
    Comm float(3,2)  
);  
Insert into SALESPEOPLE (Snum, Sname, City, Comm) Values  
(1001, 'Peel', 'London', 0.12),  
(1002, 'Serres', 'San Jose', 0.13),  
(1004, 'Motika', 'London', 0.11),  
(1007, 'Rifkin', 'Barcelona', 0.15),  
(1003, 'Axelrod', 'New York', 0.10);
```

### CUSTOMERS:

```
Create table CUSTOMERS (  
    Cnum int(4),  
    Cname varchar(10),  
    City varchar(10),  
    Rating int(4),  
    Snum int(4)  
);  
Insert into CUSTOMERS (Cnum, Cname, City, Rating, Snum) Values  
(2001, 'Hoffman', 'London', 100, 1001),  
(2002, 'Giovanni', 'Rome', 200, 1003),  
(2003, 'Liu', 'San Jose', 200, 1002),  
(2004, 'Grass', 'Berlin', 300, 1002),  
(2006, 'Clemens', 'London', 100, 1001),  
(2008, 'Cisneros', 'San Jose', 300, 1007),  
(2007, 'Pereira', 'Rome', 100, 1004);
```

### ORDERS:

```
Create table ORDERS (  
    Onum int(4),  
    Amt float(7,2),  
    Odate date,  
    Cnum int(4),  
    Snum int(4)  
);
```

```
Insert into ORDERS (Onum, Amt, Odate, Cnum, Snum) Values
(3001, 18.69, '1990-10-03', 2008, 1007),
(3003, 767.19, '1990-10-03', 2001, 1001),
(3002, 1900.10, '1990-10-03', 2007, 1004),
(3005, 5160.45, '1990-10-03', 2003, 1002),
(3006, 1098.16, '1990-10-03', 2008, 1007),
(3009, 1713.23, '1990-10-04', 2002, 1003),
(3007, 75.75, '1990-10-04', 2004, 1002),
(3008, 4723.00, '1990-10-05', 2006, 1001),
(3010, 1309.95, '1990-10-06', 2004, 1002),
(3011, 9891.88, '1990-10-06', 2006, 1001);
```

## Questions

1. Write a select command that produces the order number, amount, and date for all rows in the Orders table.
2. Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.
3. Write a query that displays the Salespeople table with the columns in the following order: city, sname, snum, comm.
4. Write a select command that produces the rating followed by the name of each customer in San Jose.
5. Write a query that will give you all orders for more than Rs. 1,000.
6. Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.
7. Write a query on the Customers table whose output will exclude all customers with a rating  $\leq 100$ , unless they are located in Rome.
8. Write two different queries that would produce all orders taken on October 3rd or 4th, 1990.
9. Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.
10. Write a query that selects all orders except those with zeroes or NULLs in the amt field.
11. Display All Orders Sorted by Amount (Lowest to Highest).
12. Show All Customers Sorted By Rating (Highest to Lowest).
13. Display Salespeople Ordered Alphabetically By Name.
14. List All Orders Taken On October 3rd or 6th, 1990 (Using IN).
15. Display Customers Located in London, Rome, or Berlin (Using IN).
16. Add a New Column 'Phone' to the CUSTOMERS Table.
17. Show Customer Names and Ratings Using Aliases.
18. Display Salesperson Name as 'Salesperson' and Commission as 'Commission (%)'.
19. Show All Customers Whose Names Start With 'C'.
20. Find Orders Where The Customer Number Starts With '20'.
21. Display Salespeople Whose City Name Contains 'on'.
22. Count the Number of Orders With Amount Greater Than Rs. 1000
23. Calculate the Sum of All Order Amounts for Salesperson.
24. Find the Average Rating of Customers Located in London.
25. Find the Minimum Order Amount for Customers in San Jose.
26. Find the Maximum Commission Among Salespeople in London.
27. Find Customers Who Have Placed Orders with Amount More Than Rs. 1000.

28. Write a query that lists each order number, amount, and the corresponding customer's name by using a subquery in the SELECT clause.

**Note:** After solving each query, take a screenshot and upload it to Git.

