

```
SQL> DROP TABLE Agent;
```

Table dropped.

```
SQL> DROP TABLE Orders;
```

Table dropped.

```
SQL> --Q1
```

```
SQL> CREATE TABLE Agent(Agent_code varchar(5), Agent_name varchar(10), Working_area varchar(10), commision number(2,2), Phone_no number, country varchar(10) null);
```

Table created.

```
SQL> CREATE TABLE Orders(Ord_num varchar(3), Ord_amount number, Advance_amount number, Ord_date date, Cust_code varchar(4), Agent_code varchar(5), Description varchar(20) null);
```

Table created.

```
SQL> INSERT INTO Agent VALUES('Ac001','Ramesh','Bangalore',0.15,0331234567,'India');
```

1 row created.

```
SQL> INSERT INTO Agent VALUES('Ac002','Dinesh','Bangalore',0.25,0331234568,'');
```

1 row created.

```
SQL> INSERT INTO Agent VALUES('Ac003','Suresh','Mumbai',0.35,0331234569,'London');
```

1 row created.

```
SQL> INSERT INTO Agent VALUES('Ac004','Kamlesh','Newjersey',0.68,0331234564,'');
```

1 row created.

```
SQL> INSERT INTO Agent VALUES('Ac005','Kartik','Chennai',0.73,0331234563,'India');
```

1 row created.

```
SQL> INSERT INTO Orders VALUES('004', 200, 3000, '15-aug-2020','C004','Ac001','Masala kulcha');
```

```
SQL> INSERT INTO Orders VALUES('007', 600, 5000, '17-sep-2020','C006','Ac003','Biryani');
```

1 row created.

```
SQL> INSERT INTO Orders VALUES('008', 700, 100, '19-feb-2019','C007','Ac005','');
```

1 row created.

```
SQL> INSERT INTO Orders VALUES('009', 10000, 600, '21-march-2010','C009','Ac008','Masala dosa');
```

1 row created.

```
SQL> INSERT INTO Orders VALUES('010', 20, 600, '21-april-2012','C006','Ac005','');
```

1 row created.

```
SQL> SELECT * FROM Agent;
```

AGENT	AGENT_NAME	WORKING_AR	COMMISSION	PHONE_NO	COUNTRY
Ac001	Ramesh	Bangalore	.15	331234567	India
Ac002	Dinesh	Bangalore	.25	331234568	
Ac003	Suresh	Mumbai	.35	331234569	London
Ac004	Kamlesh	Newjersey	.68	331234564	
Ac005	Kartik	Chennai	.73	331234563	India

```
SQL> SELECT * FROM Orders;
```

ORD	ORD_AMOUNT	ADVANCE_AMOUNT	ORD_DATE	CUST	AGENT	DESCRIPTION
004	200	3000	15-AUG-20	C004	Ac001	Masala kulcha
007	600	5000	17-SEP-20	C006	Ac003	Biryani
008	700	100	19-FEB-19	C007	Ac005	
009	10000	600	21-MAR-10	C009	Ac008	Masala dosa
010	20	600	21-APR-12	C006	Ac005	

```
SQL> --a)
```

```
SQL> SELECT Ord_num, Ord_amount, Ord_date, Cust_code, Agent_code FROM Orders WHERE Agent_code in
2 (SELECT Agent_code FROM Agent WHERE Working_area='Bangalore');
```



```
SQL> --a)
SQL> SELECT Ord_num, Ord_amount, Ord_date, Cust_code, Agent_code FROM Orders WHERE Agent_code in
2  (SELECT Agent_code FROM Agent WHERE Working_area='Bangalore');
```

```
ORD ORD_AMOUNT ORD_DATE  CUST AGENT
---
004          200 15-AUG-20 C004 Ac001
```

```
SQL> --b)
SQL> SELECT Ord_num, Ord_amount, Cust_code, Agent_code FROM Orders WHERE Agent_code in
2  (SELECT Agent_code FROM Agent WHERE Agent_name='Ramesh');
```

```
ORD ORD_AMOUNT CUST AGENT
---
004          200 C004 Ac001
```

```
SQL> --Q2
SQL> CREATE TABLE employees(employee_id varchar(3), first_name varchar(10), last_name varchar(10), email varchar(15), phone_number number, hire_date date , job_id varchar(6), salary number, manager_id varchar(5) null, department_id number);
CREATE TABLE employees(employee_id varchar(3), first_name varchar(10), last_name varchar(10), email varchar(15), phone_number number, hire_date date , job_id varchar(6), salary number, manager_id varchar(5) null, department_id number)
*
ERROR at line 1:
ORA-00955: name is already used by an existing object
```

```
SQL> INSERT INTO employees VALUES( '700', 'Hasmukh', 'Patel', 'hp@gmail.com', 7003216160, '15-aug-2020', 'Hp003', 7000, '', 90);
1 row created.
```

```
SQL> INSERT INTO employees VALUES( '800', 'Kamlesh', 'Paul', 'kp@gmail.com', 7003216170, '17-feb-2020', 'Kp004', 8000, '506', 90);
1 row created.
```

```
SQL> INSERT INTO employees VALUES( '900', 'Dinesh', 'Gandhi', 'dp@yahoo', 9136278563, '19-mar-2101', 'Dg006', 20000, '508', 80);
1 row created.
```

```
SQL> INSERT INTO employees VALUES( '701', 'Suresh', 'Modi', 'sm@dg.com', 9187653294, '20-april-2015', 'Sp003', 15000, '', 80);
1 row created.
```



```
SQL> --a)
SQL> SELECT employee_id, manager_id, first_name, last_name FROM employees WHERE manager_id!=null;
```

no rows selected

```
SQL> --b)
SQL> SELECT employee_id, manager_id, first_name, last_name FROM employees WHERE manager_id=null;
```

no rows selected

```
SQL>
SQL> --Q3
SQL> DROP TABLE Orders;
```

Table dropped.

```
SQL> CREATE TABLE salesman(salesman_id varchar(10), name varchar(10), city varchar(10), commision number(2,2));
CREATE TABLE salesman(salesman_id varchar(10), name varchar(10), city varchar(10), commision number(2,2))
*
```

ERROR at line 1:
ORA-00955: name is already used by an existing object

```
SQL> CREATE TABLE Orders(Ord_num varchar(3), Purch_amt number, Ord_date date, Customer_id varchar(5), salesman_id varchar(10));
```

Table created.

```
SQL> INSERT INTO salesman VALUES('si123@06', 'Lakshmi', 'Kolkata', 0.5);
```

1 row created.

```
SQL> INSERT INTO salesman VALUES('si123@09', 'Ganesh', 'London', 0.6);
```

1 row created.

```
SQL> INSERT INTO salesman VALUES('si123@90', 'Dinesh', 'London', 0.3);
```

1 row created.

```
SQL> INSERT INTO salesman VALUES('si123@10', 'Joseph', 'Chennai', 0.6);
```

```
SQL> INSERT INTO salesman VALUES('si123@90', 'Dinesh', 'London', 0.3);
```

```
1 row created.
```

```
SQL> INSERT INTO salesman VALUES('si123@10', 'Joseph', 'Chennai', 0.6);
```

```
1 row created.
```

```
SQL> INSERT INTO salesman VALUES('si123@19', 'Mahesh', 'Hyderabad', 0.65);
```

```
1 row created.
```

```
SQL> INSERT INTO salesman VALUES('si123@26', 'Paul Adam', 'London', 0.1);
```

```
1 row created.
```

```
SQL> INSERT INTO salesman VALUES('si123@67', 'Rahul', 'Delhi', 0.4);
```

```
1 row created.
```

```
SQL> INSERT INTO Orders VALUES('123', 600, '20-aug-2010', '003cd', 'si123@19');
```

```
1 row created.
```

```
SQL> INSERT INTO Orders VALUES('576', 750, '20-feb-2018', '004cd', 'si123@19');
```

```
1 row created.
```

```
SQL> INSERT INTO Orders VALUES('579', 800, '20-may-2012', '004cd', 'si123@26');
```

```
1 row created.
```

```
SQL> INSERT INTO Orders VALUES('600', 60000, '20-jan-2021', '006cd', 'si123@10');
```

```
1 row created.
```

```
SQL> INSERT INTO Orders VALUES('700', 745, '26-jan-2021', '007cd', 'si123@09');
```

```
1 row created.
```

```
SQL> INSERT INTO Orders VALUES('800', 860, '29-jan-2019', '007cd', 'si123@26');
```



1 row created.

SQL>

SQL> SELECT * FROM salesman;

SALESMAN_I	NAME	CITY	COMMISSION
si123@06	Lakshmi	Kolkata	.5
si123@09	Ganesh	London	.6
si123@90	Dinesh	London	.3
si123@10	Joseph	Chennai	.6
si123@19	Mahesh	Hyderabad	.65
si123@26	Paul Adam	London	.1
si123@67	Rahul	Delhi	.4

7 rows selected.

SQL> SELECT * FROM Orders;

ORD	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN_I
123	600	20-AUG-10	003cd	si123@19
576	750	20-FEB-18	004cd	si123@19
579	800	20-MAY-12	004cd	si123@26
600	60000	20-JAN-21	006cd	si123@10
700	745	26-JAN-21	007cd	si123@09
800	860	29-JAN-19	007cd	si123@26

6 rows selected.

SQL> --a)

SQL> SELECT * FROM Orders WHERE salesman_id in
2 (SELECT salesman_id FROM salesman WHERE name='Paul Adam');

ORD	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN_I
800	860	29-JAN-19	007cd	si123@26
579	800	20-MAY-12	004cd	si123@26

SQL> --b)

SQL> SELECT * FROM Orders WHERE salesman_id in



Type here to search



5:17 PM
2/6/2023



2

```
SQL> --a)
SQL> SELECT * FROM Orders WHERE salesman_id in
2 (SELECT salesman_id FROM salesman WHERE name='Paul Adam');
```

ORD	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN_I
800	860	29-JAN-19	007cd	si123@26
579	800	20-MAY-12	004cd	si123@26

```
SQL> --b)
SQL> SELECT * FROM Orders WHERE salesman_id in
2 (SELECT salesman_id FROM salesman WHERE city='London');
```

ORD	PURCH_AMT	ORD_DATE	CUSTO	SALESMAN_I
700	745	26-JAN-21	007cd	si123@09
800	860	29-JAN-19	007cd	si123@26
579	800	20-MAY-12	004cd	si123@26

```
SQL>
```