
VERIQTA

50 Linux Production Failures

Real Incidents, Root Causes, Debugging and Recovery



- ✓ 50 Real Production Failures
- ✓ Symptoms and Evidence
- ✓ Root-Cause Analysis
- ✓ Safe Recovery Steps
- ✓ Prevention and Hardening




@veriqta | @veriqta | @veriqta | @veriqta | @veriqta | @veriqta

VERIQTA

When Healthy Processes Stop Making Progress


1 Uninterruptible D-state Tasks Blocking Shutdown and Recovery

- **What it is:** Processes in D (Uninterruptible Sleep) wait on I/O and can't be killed, which can hang shutdown or maintenance.
- **Key evidence:** `ps -eo pid,stat,cmd | grep ^D`, `wchan`, `dmesg`, storage I/O errors.
- **Fix:** Resolve the I/O cause (e.g., failing disk, NFS, or device), then the D tasks clear.




2 PID Exhaustion Despite Apparently Low CPU and Memory Usage

- **What it is:** The system runs out of process IDs (PIDs) because the PID limit is reached, not because of CPU or memory pressure.
- **Key evidence:** `ps aux | wc -l`, `/proc/sys/kernel/pid_max`, `dmesg` (fork failed).
- **Fix:** Stop the process creating excessive children, clean up zombies, and tune `kernel.pid_max` if needed.



3 Zombie Accumulation Caused by a Parent Process That Never Reaps Children

- **What it is:** Child processes complete but remain as zombies (state Z) because the parent doesn't collect their exit status.
- **Key evidence:** `ps aux | grep ' Z '`, `pstree -p`, check parent process behavior.
- **Fix:** Fix or restart the parent process so it reaps children (e.g., `wait()`), or redesign process handling.



Senior Engineer Takeaway: A system can look healthy (low CPU, free memory) and still be unrecoverable due to stuck I/O, PID exhaustion, or zombies. Always check process state, PID usage, and parent–child behavior.


VERIQTA

CPU Failures That Utilization Graphs Hide

1 CFS Bandwidth Throttling Causing Latency Spikes Below Host CPU Capacity

- **What it is:** The Linux **CFS** (Completely Fair Scheduler) enforces CPU limits (cgroup) and can throttle a process even when the host CPU is not fully used.
- **Key evidence:** `cat /sys/fs/cgroup/cpu.stat` (check `nr_throttled` and `throttled_time`).
- **Fix:** Increase the CPU quota/limit, or adjust a fairer limit for the workload.


```
$ cat cpu.stat
nr_throttled    1250
throttled_time  456780000
```



2 CPU Steal Time Producing False Application Performance Diagnoses

- **What it is:** CPU time taken by the hypervisor (e.g., in VMs) that your OS wanted to use, making the app look slow even when CPU usage looks low.
- **Key evidence:** `mpstat -P ALL 1` or `top` (check the `st` column for steal time).
- **Fix:** Move to a less contended host, right-size the VM, or isolate critical workloads.


```
$ mpstat -P ALL 1
CPU   %usr   %sys   %iowait   %steal
all   12.5    5.1     0.8      28.4
```



3 Runqueue Saturation and Scheduler Latency Despite Acceptable Average CPU

- **What it is:** Too many runnable tasks competing for CPU, which increases scheduling delay and application latency, even if average CPU usage looks fine.
- **Key evidence:** `uptime` (load average), `vmstat 1` (r/running), or `ps -eo state`.
- **Fix:** Identify and reduce competing workloads, tune thread count, or reschedule CPU-intensive jobs.

```
$ uptime
  15:42:10 up 10 days, load average:
  8.52, 7.91, 6.88
```



Senior Engineer Takeaway: CPU can be the bottleneck even when graphs look healthy. Always check throttling (cgroup), steal time (virtualization), and runqueue (scheduling pressure) before concluding.

VERIQTA

The Process That Refuses to Die


1 SIGTERM Ignored or Mishandled During Production Shutdown

- **What it is:** A process keeps running after receiving **SIGTERM** because it ignores the signal or doesn't handle it correctly.
- **Key evidence:** `ps -o pid,stat,cmd -p <PID>`, `kill -TERM <PID>` (no exit), and check logs for signal handling.
- **Fix:** Ensure proper signal handling (e.g., trap **SIGTERM**) or use a graceful shutdown with a timeout, then **SIGKILL** if needed.




2 systemd Restart Storms Caused by Incorrect Unit Dependencies and Policies

- **What it is:** A service restarts repeatedly (rapid loop) due to bad dependencies, misconfiguration, or an aggressive `Restart=` policy.
- **Key evidence:** `systemctl status <service>`, `journalctl -u <service> -f` (showing repeated start/stop), and `systemctl list-dependencies`.
- **Fix:** Correct dependencies (**After=/Requires=**), review `Restart=` and `StartLimit*` settings, and fix the underlying failure.



3 Orphaned Child Processes Retaining Sockets, Locks, or Other Resources

- **What it is:** Child processes continue running after the parent dies, keeping resources (sockets, file locks, ports) in use.
- **Key evidence:** `ps --ppid 1`, `lsof -p <PID>`, `ss -tulpn`) (check open sockets), or `fuser`.
- **Fix:** Configure proper process supervision (e.g., systemd, a process manager), and ensure children exit or are cleaned up on parent failure.



Senior Engineer Takeaway: A process that won't exit often points to signal handling, service policy (systemd), or orphaned children. Always confirm the signal path, service configuration, and resource ownership.

VERIQTA


PAGE 4

Memory Failures Beyond OOMKilled

1 Memory Pressure and Reclaim Stalls Before an Out-of-Memory


- **What it is:** The kernel is under memory pressure and spends excessive time reclaiming memory (eviction, swapping, page cache), causing application stalls even before an OOM kill.
- **Key evidence:** `vmstat 1` (high si/so), `cat /proc/pressure/memory` (high some/full), and rising `kswapd` CPU.
- **Fix:** Reduce memory usage, tune reclaim (e.g., swappiness), or add memory.

```
$ cat /proc/pressure/memory
some avg10=0.35  avg60=0.28
full avg10=0.12  avg60=0.09
```




2 cgroup Memory Limits Triggering Local OOM While the Host Has Available Memory

- **What it is:** A process inside a cgroup (container, systemd slice, or service) hits its memory limit and is OOM-killed, even though the host still has free memory.
- **Key evidence:** `dmesg | grep -i oom`, `cat /sys/fs/cgroup/*/memory.max`, and container logs showing `OOMKilled`.
- **Fix:** Increase the cgroup memory limit, right-size the workload, or tune memory requests/limits (e.g., in Kubernetes).



3 Page-Cache Pressure and Writeback Congestion Producing Unexpected Stalls

- **What it is:** Heavy writes fill the page cache and the kernel struggles to flush data to disk (writeback), causing I/O stalls and application slowdowns.
- **Key evidence:** `vmstat 1` (high dirty/writeback), `cat /proc/meminfo | grep -E "Dirty|Writeback"`, and high disk I/O wait (`iostat -x 1`).
- **Fix:** Reduce write rate, improve disk throughput, tune dirty_ratio/dirty_background_ratio, or move heavy writes to faster storage.




```
$ grep -E "Dirty|Writeback" /proc/meminfo
Dirty:        1532680 kB
Writeback:     842400 kB
```

Senior Engineer Takeaway: OOMKilled is the last stage of a memory problem. Monitor memory pressure, cgroup limits, and writeback early to prevent application stalls and unexpected kills.


VERIQTA

Hidden Kernel Resource Exhaustion

1 Slab Growth and Unreclaimable Kernel Memory Exhausting Usable Capacity

- **What it is:** Kernel memory used by caches (slab) grows abnormally and cant be reclaimed, reducing available memory for applications.
- **Key evidence:** `slabtop`, `cat /proc/slabinfo`, or `dmesg` showing slab growth (e.g., `dentry`, `inode`, `kmalloc`).
- **Fix:** Identify the growing slab cache, find the workload causing it (..g., excessive files or connections), then tune or restart the service.

```
$ slabtop -o
  OBJS    CACHE          SIZE    USED
  452K    dentry         320M    305M
  298K    inode_cache    288M    276M
```



2 File Descriptor Exhaustion Despite Sufficient System-Wide Capacity

- **What it is:** A process hits its per-process file descriptor (FD) limit even though the system still has available FDs.
- **Key evidence:** `lsof -p <PID> | wc -l`, `cat /proc/<PID>/limits`, and errors like "Too many open files" in logs.
- **Fix:** Increase the process limit (e.g., via `ulimit` or systemd `LimitNOFILE=`) and fix FD leaks in the application.


```
$ cat /proc/1234 limits | grep files
  Max open files            1024         1024
```



3 Inotify Watch or Instance Limits Silently Breaking File-Watching Services

- **What it is:** The system hits the inotify limit (watches or instances), so new file watches fail, causing services (e.g., sync, build, or config reload) to stop working.
- **Key evidence:** Errors like "No space left on device" in logs, and check with `sysctl fs.inotify.*` and `inotifywatch -v`.
- **Fix:** Increase limits (e.g., `fs.inotify.max_user_watches` and `fs.inotify.max_user_instances`), then reload `sysctl` and validate the service.

```
$ sysctl fs.inotify.max_user_watches
  fs.inotify.max_user_watches = 8192
$ sysctl fs.inotify.max_user_instances
  fs.inotify.max_user_instances = 128
```



Senior Engineer Takeaway: Kernel resources (slab, file descriptors, inotify) can run out without high CPU or memory usage. Always monitor kernel caches, per-process limits, and inotify usage for early signals.

When Disk Space Lies

1 Deleted Log Files Still Consuming Disk Space Through Open File Descriptors

- **What it is:** A log file is deleted (rm) but the process still has it open, so the disk space remains in use until the process closes it.
- **Key evidence:** `du` shows lower usage, but `df -h` still shows the disk as full.
- **Fix:** Find the process holding the file, then restart or signal it to close the file descriptor.

```
$ lsof | grep deleted
java    1234    /var/log/app.log
(deleted)
```



2 Inode Exhaustion on a Filesystem With Significant Free Byte Capacity

- **What it is:** The filesystem runs out of inodes (file entries) even though there is still free disk space (bytes) available.
- **Key evidence:** File creation fails with "No space left on device", and `df -h` shows free space, but `df -i` shows 100% inode usage.
- **Fix:** Identify and remove unnecessary small files (e.g., old caches, temp files), or increase inode capacity during provisioning.


```
$ df -h /data
Filesystem    Size  Used  Avail  Use%
/dev/sdb1     100G   40G    60G   40%
$ df -i  /data
Filesystem  Inodes  IUsed  IFree  IUse%
/dev/sdb1    6.4M   6.4M      0   100%
```



3 Reserved Filesystem Blocks Causing Non-Root Writes to Fail Early

- **What it is:** Filesystems (e.g., ext4) reserve a percentage of disk space (default ~5%) for root, so non-root users can hit "No space left on device" before the disk is actually full.
- **Key evidence:** `df -h` shows ~95% usage, non-root writes fail, but root can still write.
- **Fix:** Review and adjust the reserved space (e.g., `tune2fs -m 1 /dev/sdb1` to set 1%) if appropriate for the workload.

```
$ tune2fs -l /dev/sdb1 | grep reserved
Reserved block count:       524288
Reserved block percentage:  5%
```



Senior Engineer Takeaway: Disk space can be misleading. Always check open files (lsof), inode usage (df -i), and reserved blocks (tune2fs) before assuming the disk is actually full.


VERIQTA

Storage Latency That Looks Like an Application Bug

1 I/O Queue Saturation and Tail Latency Hidden Behind Average Disk Metrics

- **What it is:** The storage I/O queue becomes saturated (too many pending I/O requests), causing high tail latency (e.g., p99) while average disk metrics still look healthy.
- **Key evidence:** High queue depth (`iostat -x`), high await/latency at p95/p99, and growing I/O wait (`%iowait`) on the host.
- **Fix:** Reduce I/O concurrency, tune the queue (e.g., `nr_requests`), optimize writes (e.g., batching), or move the workload to faster storage.


```
$ iostat -x 1
Device    r/s    w/s    await    aqu-sz
sdb       12     458    120.5    32.18
```



2 Filesystem Journal or Metadata Contention Delaying Unrelated Writes

- **What it is:** Heavy journal activity or metadata operations (create, delete, rename, chmod) can block or slow down seemingly unrelated writes.
- **Key evidence:** High journal I/O, many metadata operations, and latency spikes during file creations or deletions.
- **Fix:** Reduce metadata churn, tune the journal (e.g., `commit=`), or separate workloads to another filesy$men or disk.

```
$ iostat -x 1
Device    r/s    w/s    await    %util
sdb       88     920    85.3     98.7
```



3 Synchronous Writes and Flush Barriers Exposing Storage Latency Under Transaction Load

- **What it is:** Workloads that use synchronous writes (e.g., `fsync`, `O_SYNC`) or flush barriers force data to be committed to disk, exposing the storage's real latency, especially under high transaction load.
- **Key evidence:** Spikes in write latency, high `fsync` time (e.g., via `strace` or app metrics), and increased I/O wait during heavy transactions.
- **Fix:** Reduce unnecessary synchronous writes, use batching or async writes, tune mount options (e.g., `noatime`, `data=ordered`), or upgrade to faster storage (e.g., NVMe).

```
$ strace -T -e fsync -p 1234
fsync(3)    = 0   <0.482731>
fsync(3)    = 0   <0.517903>
```



Senior Engineer Takeaway: A healthy average I/O metric can hide serious latency problems. Always check queue depth, tail latency (p95/p99), journal/metadata activity, and synchronous writes when diagnosing slow applications.

VERIQTA

Filesystem Failures That Threaten Recovery

1 Filesystem Remounted Read-Only After Detected Storage or Metadata Errors

- **What it is:** The filesystem is automatically remounted read-only (ro) by the kernel when it detects storage, journal, or metadata errors to prevent further data corruption.
- **Key evidence:** `dmesg` or `journalctl` showing errors (e.g., "EXT4-fs error", "remounting filesystem read-only").
- **Fix:** Investigate the root cause (disk, I/O, or filesystem errors), repair the filesystem (e.g., `fsck` in maintenance mode), and restore to read-write (rw).

```
$ mount | grep '/data'
/dev/sdb1 on /data type ext4 (ro,
errors=remount-ro)
```



2 NFS Hard-Mount Stalls Leaving Processes Blocked During Remote Storage Failure


- **What it is:** An NFS hard mount keeps retrying indefinitely when the remote server becomes unavailable, causing processes to block (e.g., I/O hangs, high D-state).
- **Key evidence:** Processes in D (uninterruptible) state (`ps`/`top`), and the mount shown as `hard` in `mount` or `/etc/fstab`.
- **Fix:** Restore the NFS server, or use a more resilient mount (e.g., `soft`, `timeo`, `retrans`, or `nfsvers`), and add monitoring and alerts.

```
$ mount | grep nfs
nfs-server:/export /mnt/nfs nfs
(rw,hard)
```



3 OverlayFS Copy-Up and Writable-Layer Exhaustion Disrupting Containerized Workloads

- **What it is:** OverlayFS copies files from the read-only image layer to the writable layer (copy-up) when modified. If the writable layer fills up (e.g., Docker/container runtime), containers can fail or become unstable.
- **Key evidence:** "No space left on device" errors inside the container, high usage in the container storage path, and OverlayFS in `mount` output.
- **Fix:** Free space (e.g., clean logs, unused layers), increase storage, or set quotas/limits and regular cleanup policies (e.g., `docker system prune`).




```
$ df -h /var/lib/docker
Filesystem      Size  Used  Avail  Use%
/dev/nvme0n1p1  50G   49G   1.0G   98%
```

Senior Engineer Takeaway: Filesystem failures can silently block writes, hang processes, or stop containers. Always check mount state, kernel logs, and storage usage before attempting recovery.


VERIQTA

TCP Failures Beyond Connection Refused

1 SYN Backlog Saturation Causing Intermittent Connection Establishment Failures

- **What it is:** The TCP SYN backlog (queue of half-open connections) fills up during high or bursty traffic, so new connection attempts are dropped or time out.
- **Key evidence:** Rising "SYN_RECV" connections, backlog overflows in logs (e.g., "Possible SYN flooding"), or connection timeouts under load.
- **Fix:** Increase the backlog (e.g., net.core.somaxconn, tcp_max_syn_backlog), use SYN cookies (tcp_syncookies=1), and tune the service and load balancer.


```
$ ss -n state syn-recv | wc -l
  4521
```



2 Ephemeral Port Exhaustion Disrupting Outbound Connections

- **What it is:** The system runs out of ephemeral (source) ports needed for outbound connections, so new connections fail even though the service and network are healthy.
- **Key evidence:** Errors like "Cannot assign requested address", "address not available", or a large number of connections in ESTABLISHED/TIME_WAIT using the ephemeral port range.
- **Fix:** Expand the port range (e.g., net.ipv4.ip_local_port_range), reduce connection churn, enable connection pooling, and tune TIME_WAIT handling.


```
$ sysctl net.ipv4.ip_local_port_range
net.ipv4.ip_local_port_range = 32768 60999
```



3 TIME_WAIT Accumulation and Unsafe Socket-Reuse Assumptions During High Churn

- **What it is:** A large number of connections remain in TIME_WAIT after closing, consuming resources and exhausting ports under high connection churn.
- **Key evidence:** Many sockets in TIME_WAIT (e.g., via `ss` or `netstat`), increasing port usage, and intermittent connection failures.
- **Fix:** Reduce unnecessary connection churn (e.g., use keep-alive/connection pooling), and tune TIME_WAIT (e.g., tcp_fin_timeout, tcp_tw_reuse where appropriate and safe).

```
$ ss -tan state time-wait | wc -l
  18654
```



Senior Engineer Takeaway: TCP can fail for reasons beyond "connection refused." Always check the SYN backlog, ephemeral ports, and TIME_WAIT when diagnosing connection issues.

VERIQTA

The Network Is Up, but Requests Still Fail

1 Conntrack Table Exhaustion Dropping Otherwise Valid Traffic

- **What it is:** The connection tracking (conntrack) table runs out of entries, so new or existing flows are dropped even though the network and service are up.
- **Key evidence:** High conntrack usage (e.g., > 90%), log messages like "nf_conntrack: table full, dropping packet", or intermittent connection failures.
- **Fix:** Increase the conntrack table size (e.g., net.netfilter.nf_conntrack_max), reduce unnecessary long-lived connections, and tune timeouts (e.g., nf_conntrack_tcp_timeout).

```
$ cat /proc/sys/net/netfilter/
  nf_conntrack_count
  1048576
$ cat /proc/sys/net/netfilter/
  nf_conntrack_max
  1048576
```



2 Path MTU Discovery Failure Creating Selective Hangs for Larger Requests

- **What it is:** Path MTU Discovery (PMTUD) fails to find the correct MTU, often because ICMP "Fragmentation Needed" messages are blocked, causing large requests to hang or timeout.
- **Key evidence:** Small requests work (e.g., curl), but larger payloads (e.g., file upload, large API calls) hang; ICMP type 3 (fragmentation needed) not seen along the path.
- **Fix:** Allow ICMP (type 3, code 4), set a safe MTU (e.g., 1400–1500) on affected interfaces, or clamp MSS (e.g., --clamp-mss-to-pmtu) for TCP traffic.


```
$ tracepath -n example.com
 1:   10.0.0.1              pmtu 1500
 2:   192.0.2.1             pmtu 1500
 3:   198.51.100.10         pmtu 1400
```



3 Asymmetric Routing Interacting With Reverse-Path Filtering and Dropped Packets

- **What it is:** Traffic takes different paths for outbound and inbound flows (asymmetric routing), and reverse-path filtering (rp_filter) drops legitimate return packets.
- **Key evidence:** Requests leave the host but responses never arrive; counters increase for dropped packets; rp_filter is set to strict (1).
- **Fix:** Use loose rp_filter (2) or disable it (0) where appropriate (e.g., net.ipv4.conf.all.rp_filter=2), or fix the routing to make paths symmetric.

```
$ sysctl net.ipv4.conf.all.rp_filter
  net.ipv4.conf.all.rp_filter = 1
```



Senior Engineer Takeaway: A healthy network (ping up, interface up) can still fail requests due to conntrack limits, MTU discovery issues, or asymmetric routing with reverse-path filtering. Always verify the full path and kernel network settings.


VERIQTA

DNS, TLS and Hidden Dependency Failures

1 DNS Resolver Timeouts and Search-Domain Expansion Amplifying Application Latency

- **What it is:** DNS lookups timeout or become slow, and search-domain expansion causes multiple unnecessary queries, increasing application latency.
- **Key evidence:** Repeated DNS queries (e.g., multiple A/AAAA lookups) and high DNS resolution time in logs, traces, or metrics.
- **Fix:** Configure correct DNS settings (e.g., resolv.conf, ndots, search domains), reduce unnecessary search domains, and use a reliable, low-latency DNS resolver (e.g., systemd-resolved, CoreDNS, or a corporate DNS).

```
$ cat /etc/resolv.conf
nameserver 10.0.0.2
search svc.cluster.local example.com
options ndots:5
```



2 Certificate Renewal Succeeds, but the Running Service Still Serves an Expired Certificate

- **What it is:** The certificate is renewed (e.g., by Certbot or an automated process), but the running application keeps using the old, expired certificate.
- **Key evidence:** The new certificate exists on disk (valid dates), but the service still presents the expired certificate to clients (e.g., via openssl s_client).
- **Fix:** Reload or restart the service to load the new certificate (e.g., systemctl reload nginx), and ensure the renewal process includes a reload hook.

```
$ openssl x509 -in /etc/ssl/certs/app.crt \
  -noout -dates
notBefore=Oct 10 00:00:00 2026 GMT
notAfter=Oct 10 00:00:00 2027 GMT
```



3 Clock Drift or Time Synchronization Failure Breaking TLS, Authentication, and Distributed Coordination

- **What it is:** The system clock drifts or is not synchronized, causing TLS validation failures, authentication issues (e.g., tokens, Kerberos, OIDC), and problems in distributed systems (e.g., etcd, consul, or clustering).
- **Key evidence:** TLS "certificate not yet valid" or "certificate has expired" errors, token validation failures, or cluster nodes marked unhealthy.
- **Fix:** Ensure reliable time synchronization using NTP or chrony (e.g., configure chronyd or systemd-timesyncd), and monitor clock drift (e.g., timedatectl).

```
$ timedatectl status
Local time:    Tue  Nov 10 10:24:31 UTC
NTP service:   active
System clock synchronized: yes
```



Senior Engineer Takeaway: Failures in DNS, TLS, or system time often look like application issues. Always check name resolution, certificate reloads, and clock synchronization when diagnosing unexplained failures.


VERIQTA

systemd and Boot-Time Failure Chains

1 Boot Blocked or Degraded by Remote Mount Dependencies and Timeout Behavior

- **What it is:** The boot process can stall or become slow when a remote filesystem (e.g., NFS, SMB, or cloud storage) is required and does not respond within the expected time.
- **Key evidence:** systemd shows mount units in "activating (start)" or "failed" state, with timeout errors in the logs (e.g., "Timed out waiting for device").
- **Fix:** Make remote mounts non-blocking (e.g., nofail, x-systemd.automount), set sensible timeouts (e.g., x-systemd.mount-timeout), and avoid hard dependencies in the boot chain.


```
$ systemctl status remote-data.mount
● remote-data.mount - /mnt/data
   Loaded: loaded (/etc/fstab; generated)
   Active: failed (Result: timeout)
      Job: mount /mnt/data
```



2 systemd Service Sandboxing or Resource Limits Breaking an Otherwise Valid Application

- **What it is:** systemd can restrict a service using sandboxing (e.g., ProtectSystem, ProtectHome, NoNewPrivileges) or resource limits (e.g., MemoryMax, CPUQuota), which can cause a working application to fail.
- **Key evidence:** The service fails to start or exits with permission denied, read-only filesystem, or resource limit errors (e.g., "Operation not permitted" or "cgroup memory limit exceeded").
- **Fix:** Review and adjust the unit file (e.g., loosen sandboxing, increase limits), test with systemctl edit, and validate with the service logs.

```
$ systemctl status app.service
● app.service - My Application
   Active: failed (Result: exit-code)
  ExecStart=/usr/local/bin/app (code=exited, 1)
```



3 Journald Storage Pressure or Rate Limiting Obscuring Critical Incident Evidence

- **What it is:** The system journal (journald) can hit storage limits or rate limits, causing older logs to be rotated away or new logs to be dropped, hiding key evidence during incidents.
- **Key evidence:** journalctl shows messages like "Suppressed X messages" or logs are missing around the time of failure, and journal storage is near or at its configured limit.
- **Fix:** Increase or adjust journal storage (e.g., SystemMaxUse, SystemMaxFileSize), tune rate limiting (e.g., RateLimitBurst/Interval), and ship important logs to external storage (e.g., rsyslog, Loki, or a SIEM).

```
$ journalctl -u app.service
Nov 10 10:20:01 systemd[1]: app.service failed
Nov 10 10:20:01 systemd-journald[123]:
    Suppressed 487 messages in 10s
```



Senior Engineer Takeaway: Boot, service, and logging issues often form a chain of failures. Always check systemd dependencies, service limits, and journald storage and rate limits when diagnosing production issues.

Security Controls That Resemble Outages

1 SELinux or AppArmor Denials Mistaken for Filesystem Permission Errors

- **What it is:** SELinux (or AppArmor) can block actions (e.g., file access, execution, or network) based on security policy, often looking like a normal permission error (e.g., "Permission denied").
- **Key evidence:** audit logs (e.g., ausearch, audit.log) show "AVC denied" (SELinux) or AppArmor "DENIED" entries.
- **Fix:** Confirm the security policy (e.g., getenforce, aa-status), adjust the policy (e.g., setenforce 0 for testing, or update AppArmor/SELinux rules), and retest.

```
$ ausearch -m avc -ts recent
$ grep "AVC denied" /var/log/audit/audit.log
$ getenforce
  Enforcing
```



2 Linux Capabilities and NoNewPrivileges Preventing Required Privileged Operations

- **What it is:** Linux capabilities (e.g., CAP_NET_BIND_SERVICE, CAP_SYS_ADMIN) and NoNewPrivileges can restrict privileged actions, even when running as root inside a container or service.
- **Key evidence:** Operations fail with "Operation not permitted" or "Permission denied" despite root, and capability checks show missing or blocked capabilities.
- **Fix:** Grant only the required capabilities (e.g., --cap-add), review NoNewPrivileges (e.g., --security-opt=no=new-privileges), and follow the least-privilege principle.


```
$ capsh --print | grep Current
  Current: = cap_chown,cap_net_bind_service
$ grep NoNewPrivileges /proc/self/status
  NoNewPrivileges: 1
```



3 Namespace and cgroup Boundaries Misleading Host-versus-Container Troubleshooting

- **What it is:** Namespaces (PID, NET, MNT, UTS etc.) and cgroups isolate containers from the host, so what works on the host may fail inside the container (e.g., different PIDs, network, mounts, or resource limits).
- **Key evidence:** Resource, process, or network differences between host and container (e.g., different view of /proc, interfaces, or cgroup limits in /sys/fs/cgroup).
- **Fix:** Inspect the container's namespace and cgroup context (e.g., nsenter, docker exec, cat /sys/fs/cgroup), and validate limits and resources from inside the container.

```
$ nsenter --target <pid> --mount --net --pid
$ cat /sys/fs/cgroup/memory.max
  1073741824
```



Senior Engineer Takeaway:


Security controls (SELinux/AppArmor), capabilities, and namespace/cgroup isolation can block or change behavior in ways that look like outages. Always check security policy, privileges, and container boundaries during incident analysis.

When Load Average Misleads Engineers

1 Elevated Load Average Driven by Blocked Tasks Rather than CPU Execution

- **What it is:** A high load average (e.g., 4.00, 6.50) can result from many tasks in uninterruptible sleep (D state) waiting on I/O (e.g., disk, network, or filesystem), not from high CPU usage.
- **Key evidence:** High load average with low CPU utilization, and multiple processes in D state (e.g., "D" in ps or "uninterruptible sleep" in top).
- **Fix:** Identify the blocking resource (e.g., I/O, NFS, storage), remove the bottleneck (e.g., recover storage, fix network, or unstick the mount), and verify the load average returns to normal.

```
$ uptime
  16:24:51 up 12 days,  3:10,  2 users,
  load average: 6.50, 6.12, 5.87
$ top
  Cpu(s): 2.4% us, 1.1% sy, 96.5% id
$ ps -eo state,pid,cmd | grep '^D'
  D    3421   java
  D    3470   rsync
  D    3512   python
```



2 Memory or I/O Pressure Stalls Detected Through Pressure Stall Information (PSI)

- **What it is:** Pressure Stall Information (PSI) shows when tasks are stalled due to resource pressure (CPU, memory, or I/O) before traditional metrics (e.g., CPU %, memory %) or alerts show a problem.
- **Key evidence:** Non-zero "some" or "full" stall times in PSI (e.g., /io/pressure or /memory/pressure), indicating contention and delayed progress.
- **Fix:** Check PSI metrics, find the resource under pressure (e.g., memory reclaim, I/O backlog), reduce contention (e.g., tune I/O, add memory, or limit noisy processes), and monitor until PSI returns near zero.

```
$ cat /proc/pressure/io
  some avg10=12.34 avg60=8.21 avg300=5.03
  full avg10=0.67 avg60=0.45 avg300=0.22
$ cat /proc/pressure/memory
  some avg10=9.12 avg60=6.33 avg300=4.01
  full avg10=1.04 avg60=0.73 avg300=0.31
```



Senior Engineer Takeaway: A high load average does not always mean high CPU usage. Use task state and PSI to confirm if the system is stalled by I/O or memory pressure and fix the actual bottleneck.

Concurrency Failures That Survive Restarts

1 Advisory File Locks and Competing Service Instances Causing Apparent Deadlocks

- **What it is:** Advisory file locks (e.g., flock, fcntl) are cooperative locks, and multiple service instances can still compete for the same resource, leading to apparent deadlocks or long waits.
- **Key evidence:** Processes stuck on file lock operations (e.g., "F" state in ps, or blocked in flock/fcntl) even after a service restart.
- **Fix:** Identify the locking process (e.g., lsof, fuser, or /proc/locks), ensure only one active instance (e.g., systemd/restart policy, leader lock), and use timeouts and lock cleanup.

```
$ lsof /var/run/app.lock
COMMAND   PID  USER   TYPE  NAME
app      4281  app    FWR   /var/run/app.lock
$ cat /proc/locks | grep app.lock
1: POSIX  ADVISORY  WRITE  4281  08:01:12345
/var/run/app.lock
```



2 Futex Contention and Thread-Pool Starvation Causing Growing Request Queues

- **What it is:** Futex (fast userspace mutex) contention occurs when many threads wait on the same lock, and a saturated thread pool can prevent new work from being processed, causing request queues to grow even when CPU usage is low.
- **Key evidence:** High futex waits (e.g., in strace or perf) and a growing request queue with low CPU utilization (e.g., via top, htop, or application metrics).
- **Fix:** Identify the contention (e.g., perf top, strace -f -e futex), right-size the thread pool (e.g., worker/connection limits), reduce lock contention (e.g., finer-grained locks), and add queue and latency monitoring.

```
$ top
Cpu(s): 4.2% us, 1.1% sy, 94.7% id
$ strace -f -e futex -p 4281
futex(0x7f8c1a4b3000, FUTEX_WAIT, ...) = 0
futex(0x7f8c1a4b3000, FUTEX_WAIT, ...) = 0
...
```



Senior Engineer Takeaway: Restarts do not always fix concurrency issues. Check for lingering file locks, competing instances, futex contention, and thread-pool limits when requests are stuck or queues keep growing.

VERIQTA

Kernel and Network Stack Failure Escalation

1 NIC Receive Queue Overflow or Softirq Saturation Causing Packet Drops

- **What it is:** The network interface card (NIC) receive queue (RX queue) can become full, or the kernel's softirq (e.g., NET_RX) can become saturated, causing packet drops before the application sees the traffic.
- **Key evidence:** Increasing RX drop counters on the NIC, high softirq usage (ksoftirqd), and normal application logs (even though traffic is missing).
- **Fix:** Identify the bottleneck (e.g., ethtool, /proc/softirqs), increase RX queue size or RPS/RSS parallelism, and balance IRQ/softirq load across CPUs.

```
$ ethtool -S eth0 | egrep 'rx_(drop|miss)'
  rx_dropped: 12489
  rx_missed_errors: 317
$ cat /proc/softirqs | grep NET_RX
  NET_RX:  154328  992411  843210  129337
```



2 Kernel Soft Lockups or Driver Faults Producing Intermittent Host Unresponsiveness

- **What it is:** A kernel soft lockup occurs when a CPU is stuck in the kernel for too long (e.g., a loop, blocking driver, or hardware issue), while driver faults can cause intermittent freezes, high latency, or partial host unresponsiveness.
- **Key evidence:** Kernel messages showing "soft lockup", "hung task", or driver errors (e.g., in dmesg), often with periods of high system latency or stalled workloads.
- **Fix:** Check kernel logs (dmesg / journalctl), identify the offending driver or task, update or roll back the driver/kernel if needed, and validate hardware health.

```
$ dmesg | egrep -i 'soft lockup|hung task|driver'
[ 3124.209] watchdog: BUG: soft lockup -
 CPU#2 stuck for 22s! [kworker/2:1:1234]
[ 3124.915]  e1000e 0000:03:00.0:
 Tx timeout, resetting adapter
```




Senior Engineer Takeaway: Network drops and host freezes can start at the kernel and driver level. Always check NIC queues, softirq load, and kernel logs when traffic disappears or the host becomes intermittently unresponsive.

The Host Is Healthy, but the Service Is Not

1 Load Balancer Health Checks Reporting Healthy While Application Worker Pools Are Exhausted

- **What it is:** The load balancer (LB) health check can return "healthy" because the host and the application endpoint (e.g., /health) respond, even though the application worker pool (e.g., threads, processes, or connection pool) is exhausted and cannot handle real traffic.
- **Key evidence:** LB shows the instance as healthy, but requests are slow, queued, or timing out (e.g., 5xx, increased latency, or growing request backlog).
- **Fix:** Make health checks represent real service readiness (e.g., check worker pool status, queue depth, or dependencies), set sensible thresholds, and remove instances when the service is not actually ready.


```
$ curl -sS http://app:8080/health
{"status":"ok"}
$ curl -sS http://app:8080/metrics | grep worker
app_worker_pool_in_use 100
app_worker_pool_max    100
app_request_queue_depth 428
```



2 Retry Amplification Across Services Turning a Small Dependency Slowdown into a Fleet-Wide Incident

- **What it is:** When a dependency (e.g., database, API, or cache) slows down, multiple services retry aggressively (often with low timeouts and high retry counts), increasing traffic and load, which worsens the slowdown and can cause a wide-scale outage.
- **Key evidence:** Spike in request volume, higher retry rates, increasing latency, and cascading failures across multiple services.
- **Fix:** Use bounded retries (e.g., max retries), exponential backoff with jitter, timeouts, and circuit breakers to stop retry storms and contain the impact.

```
$ curl -sS http://app:8080/metrics | egrep
  "retry_total|request_latency_seconds"
 service_retry_total 15876
 request_latency_seconds_p95 4.82
```



Senior Engineer Takeaway: A healthy host does not guarantee a healthy service. Make health checks meaningful and control retries with timeouts, backoff, and circuit breakers to prevent small slowdowns from becoming major outages.

Recovery Actions That Make Incidents Worse

1 Restarting a Degraded Service Triggers Cache Cold Starts, Reconnection Storms, and Higher Dependency Load

- What it is: Restarting a slow or degraded service can clear its in-memory cache, force many clients to reconnect at once, and increase load on downstream dependencies (e.g., database, API, or queues).
- Key evidence: After a restart, you see a surge in connection attempts, cache miss rates, and higher load on dependent services.
- Fix: Before restarting, validate impact (cache, connections, and dependencies), use a gradual restart (e.g., rolling or canary), and monitor for load spikes.

```
$ systemctl restart app.service
$ watch -n2 'curl -s http://app:8080/metrics |
  egrep "cache_miss|connections|dependency_load"'
cache_miss_rate  0.76
active_connections  4821
dependency_load  0.89
```



2 Automated Remediation Repeatedly Restarts Healthy Instances Because of Poor Health Checks

- What it is: Automation (e.g., auto-healing, watchdog, or orchestration) can keep restarting healthy instances when health checks are too strict, misconfigured, or do not reflect real application readiness.
- Key evidence: Instances restart repeatedly even though the service is actually healthy (e.g., frequent restarts in logs and short uptime).
- Fix: Redesign health checks (e.g., check real readiness, add a grace period, and use multiple signals), and set restart limits with backoff (e.g., exponential backoff).


```
$ kubectl get pods -w
NAME                READY   RESTARTS   AGE
app-7f9d8c9-abc     1/1     5          12m
app-7f9d8c9-def     1/1     6          14m
```



3 Restoring from a Valid Backup Fails to Meet Recovery Objectives Due to Untested Consistency and Dependency Order

- What it is: A backup may be valid (e.g., completes and is readable), but the restore can still fail to meet RTO/RPO because application data, state, and dependent services (DB, queue, cache) were not restored and started in the correct order.
- Key evidence: The application starts, but functions are broken (e.g., errors, missing data, or failed dependencies).
- Fix: Test full recovery regularly, verify application consistency, and document and automate the correct restore order (e.g., DB → cache → queue → app).

```
$ ./restore.sh --backup backup_2026-11-12.tar.gz
$ systemctl start app.service
$ journalctl -u app.service -n 5
  ERROR: database not ready
  ERROR: missing cache data, retrying...
  ERROR: dependency (queue) unavailable
```



Senior Engineer Takeaway: Recovery actions can make an incident worse when you restart without impact analysis, use poor health checks, or restore without testing consistency and dependency order.

Production Incident Command: Evidence Before Action

1 Cross-System Incident Exercise

- A cross-system incident exercise combining several failures from the notebook (e.g., network, app, dependency) to practice a full production response.

2 Distinguish the Failure Type

- Clearly identify and separate:
  - Host failure (OS, kernel, resources)
  - Application failure (service, code, worker, config)
  - Dependency failure (DB, API, cache, DNS, etc.).

3 Establish Blast Radius and Correlate Changes

- Determine the blast radius (impacted services, users, regions) and correlate recent changes (deployments, config, scaling, network) with the incident timeline.

4 Interpret Key Signals and Metrics

- Use and interpret: PSI (pressure), vmstat (CPU/memory/I/O), ss (sockets/connections), journalctl (service logs), dmesg (kernel/driver events), and service-level metrics (latency, error rate, throughput).

5 Choose the Right Intervention

- Select the most appropriate action based on evidence and risk:
  - Rollback (revert a change)
  - Traffic isolation (quarantine the fault)
  - Failover (shift to a healthy target)
  - Restart (recover a degraded service)
  - Capacity intervention (scale up/out).


6 Establish Recovery and Verify

- Define clear recovery criteria (e.g., error rate, latency, queue depth, PSI) and verify that mitigation fully restores service without creating secondary failures (e.g., new bottlenecks, cascading retries, resource exhaustion).

Incident Scenario (Example)

- Traffic latency spike and rising errors.
- DB dependency slowdown.
- Application worker pool exhaustion.
- Autoscaler adds capacity, but recovery remains unstable.

Investigation Workflow



Key Evidence Sources

```
$ cat /proc/pressure/{cpu,memory,io}   # PSI
$ vmstat 1 5                           # System load
$ ss -s                                # Socket summary
$ journalctl -u app.service -n 200     # Service logs
$ dmesg -T | tail -n 50                #Kernel/driver events
$ curl -s http://app/metrics           #Service-level metrics
```

Response Decision Matrix (Guide)

Condition (Evidence)	Action
Bad deploy / config change	Rollback
Dependency degraded (DB, API, cache)	Traffic isolation or failover
Service degraded (safe to recover)	Restart
Sustained high load / saturation	Capacity intervention (scale up/out)
Widespread or multi-service impact	Failover (to healthy region/cluster)

Senior Engineer Takeaway: Run an evidence-driven incident response: understand the failure, measure the impact, choose the right action, and verify full and safe recovery.

Senior Linux Production Readiness Assessment

1	Final Scenario-Based Engineering Examination	A final, real-world Linux production assessment that evaluates your ability to investigate, stabilize, and recover complex incidents.
2	Five Ambiguous Production Incidents with Competing Hypotheses	Analyze five realistic incidents where multiple plausible root causes exist, requiring evidence, elimination, and clear justification.
3	Command-Output Interpretation and Evidence-Based Reasoning	Interpret real command outputs (e.g., vmstat, ss, journalctl, dmesg, PSI) and use the evidence to identify the most likely root cause.
4	Risk Assessment for Destructive or Disruptive Recovery Commands	Evaluate the impact and risk of recovery actions (e.g., service restart, process kill, filesystem repair, cache flush) and choose the safest effective option.
5	Recovery Decisions Under Availability and Data-Integrity Constraints	Make recovery decisions that restore service quickly while preserving availability, preventing data loss, and meeting production objectives.
6	Prevention Plans Covering Observability, Capacity, Automation, and Failure Containment	Propose a practical prevention plan, including improved observability (metrics, logs, traces), capacity and performance controls, automation (health checks, remediation), and failure containment (isolation, limits, blast radius).

Assessment Flow



Senior Engineer Takeaway: Bring together investigation, decision-making, risk management, recovery, and prevention to demonstrate production readiness in a real-world Linux environment.