

ANNEXURE A

WIRELESS NETWORK VULNERABILITY ASSESSMENT REPORT

Case Studies 1–10

This report assesses the principal wireless, authentication, segmentation, monitoring, access-control, and data-protection weaknesses associated with the ten assigned case studies. Recommendations are framed as defensive security controls suitable for a vulnerability assessment report.

1. TJX Companies Wireless Network Breach, 2005–2007

1. Incident Overview

The incident involved unauthorized wireless access to a retail network where weak WEP protection, inadequate wireless controls, and insufficient segmentation exposed payment-card environments.

2. Identified Vulnerabilities

- Obsolete WEP encryption and weak wireless protection
- Insufficient authentication and access control
- Inadequate separation of wireless users from payment systems
- Limited wireless monitoring and rogue-access-point detection
- Insufficient protection of sensitive payment-card data

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

1. Replace WEP with WPA2-Enterprise or WPA3-Enterprise using 802.1X and certificate-backed authentication.
2. Segment guest, corporate, POS, and payment-card networks using VLANs, firewalls, and least-privilege ACLs.
3. Deploy wireless IDS/IPS and continuously detect rogue or unauthorized access points.
4. Encrypt payment data in transit and at rest, minimize stored cardholder data, and apply PCI DSS controls.

5. Centralize authentication, logging, alerting, vulnerability management, and periodic wireless assessments.

5. Overall Risk Rating

High

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

2. Lowe's Wireless Network Intrusion, 2003

1. Incident Overview

A compromised retail wireless connection reportedly provided a path toward central corporate systems, illustrating the danger of connecting store wireless networks too closely to sensitive enterprise and point-of-sale environments.

2. Identified Vulnerabilities

- Weak wireless authentication
- Insufficient wireless isolation
- Inadequate firewall boundaries between store and corporate systems
- Insufficient POS segmentation
- Limited intrusion detection and centralized access management

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

6. Use enterprise WPA2/WPA3 with 802.1X and unique identities rather than shared wireless credentials.
7. Place POS systems in isolated, tightly controlled network segments.
8. Use firewalls between wireless, store, POS, and corporate networks with deny-by-default rules.
9. Deploy IDS/IPS and centralized security monitoring for unusual lateral movement.
10. Apply centralized identity, privileged-access management, logging, and regular access reviews.

5. Overall Risk Rating

Critical

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

3. Firesheep and Public Wi-Fi Session Hijacking, 2010

1. Incident Overview

Firesheep demonstrated that users on the same open wireless network could capture unencrypted session cookies and impersonate authenticated users when applications failed to protect the entire session with HTTPS.

2. Identified Vulnerabilities

- Open wireless networks exposing traffic to nearby clients
- Session cookies transmitted without adequate encryption
- Incomplete HTTPS enforcement
- Missing or weak HSTS
- Insufficient client isolation and security awareness

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

11. Enforce HTTPS across every authenticated page and resource and redirect HTTP to HTTPS.
12. Use HSTS with an appropriate policy and secure cookie attributes such as Secure and HttpOnly; use SameSite where appropriate.
13. Enable wireless client isolation so connected users cannot directly communicate with each other.
14. Recommend or provide VPN protection for sensitive activity on untrusted networks.
15. Educate users to verify HTTPS/certificate warnings and avoid transmitting sensitive information over untrusted Wi-Fi.

5. Overall Risk Rating

High

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

4. DarkHotel Attacks Through Hotel Wi-Fi Networks

1. Incident Overview

The DarkHotel campaign illustrated how compromised or untrusted hotel networks can be used to target selected guests with fraudulent software-update prompts and malware.

2. Identified Vulnerabilities

- Weak guest authentication and captive-portal trust
- Potential DNS or traffic manipulation
- Insufficient guest-network segmentation
- Third-party management and privileged access risks
- Insecure software-update delivery or inadequate signature validation
- Insufficient malware and network monitoring

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

16. Isolate guest Wi-Fi from hotel administration, POS, surveillance, and building-management networks.
17. Secure captive portals with HTTPS, strong certificates, minimal data collection, and protected administrative interfaces.
18. Use DNS security controls and monitor for unexpected DNS changes or malicious domains.
19. Require signed software updates and endpoint verification; never trust update prompts solely because they appear on a hotel network.
20. Restrict third-party access with MFA, least privilege, time-limited accounts, logging, and periodic review.
21. Deploy wireless monitoring, endpoint detection, and centralized incident response.

5. Overall Risk Rating

Critical

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

5. Marriott Wi-Fi Deauthentication Incident, 2014

1. Incident Overview

The incident concerned use of equipment to transmit Wi-Fi deauthentication messages that disrupted guests' personal hotspots, demonstrating an availability risk associated with unprotected 802.11 management frames.

2. Identified Vulnerabilities

- Management frames vulnerable to spoofed deauthentication
- Wireless availability and interference risk
- Insufficient wireless intrusion detection/prevention
- Inadequate acceptable-use governance
- Potential regulatory and legal exposure

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

22. Use Protected Management Frames (802.11w/PMF) where supported.
23. Prefer WPA3 configurations that require or strongly support PMF according to the deployment and client capabilities.
24. Deploy wireless IDS/IPS capable of detecting abnormal deauthentication and interference patterns.
25. Define acceptable-use policies that clearly prohibit deliberate disruption of guest communications.
26. Maintain documented authorization, testing, escalation, and incident-response procedures for wireless security tools.
27. Assess regulatory requirements and legal consequences before deploying controls that can affect third-party communications.

5. Overall Risk Rating

High

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

6. Fake Wi-Fi Networks at the Republican National Convention, 2016

1. Incident Overview

A security experiment using fake open wireless networks showed that many users would connect to familiar-looking or attractive SSIDs, creating opportunities for traffic interception, identity exposure, and credential theft.

2. Identified Vulnerabilities

- Users trusting SSIDs without verification
- Automatic reconnection to previously seen networks
- Open Wi-Fi and deceptive captive portals
- Evil-twin access points
- Weak certificate validation and user awareness
- Lack of VPN enforcement

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

28. Disable automatic connection to open or unknown networks on managed devices.
29. Use WPA2/WPA3 Enterprise for organizational networks and device certificates where practical.
30. Deploy rogue-AP and evil-twin detection at event venues.
31. Use VPN enforcement or secure enterprise connectivity for managed devices on untrusted networks.
32. Train participants to verify network names, captive portals, and certificate warnings.
33. Provide a clearly communicated official SSID and help channel for reporting suspicious networks.

5. Overall Risk Rating

High

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

7. Wi-Fi Attacks Against Anti-Doping Officials, 2016

1. Incident Overview

The reported campaign targeting officials using hotel and event Wi-Fi demonstrates the risk of credential theft and unauthorized access to sensitive organizational and medical information during international travel.

2. Identified Vulnerabilities

- Exposure to untrusted hotel/event Wi-Fi
- Credential theft risk
- Insufficient MFA or device authentication
- Weak endpoint protection
- Insecure VPN configuration
- Inadequate travel-security procedures
- Risk to sensitive and medical information

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

34. Require phishing-resistant MFA for important accounts where possible.
35. Use device certificates and managed endpoints to strengthen device authentication.
36. Require secure VPN or zero-trust access for sensitive internal applications over public networks.
37. Harden endpoints with EDR, full-disk encryption, patching, application control, and secure configuration.
38. Apply strict travel-security procedures, including avoiding unknown Wi-Fi and reporting suspicious prompts.
39. Encrypt sensitive data and enforce least privilege, retention limits, and access logging.

5. Overall Risk Rating

Critical

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

8. Attempted OPCW Wi-Fi Intrusion, 2018

1. Incident Overview

The attempted close-access operation highlighted that enterprise wireless signals can extend beyond physical boundaries and that attackers may position equipment near facilities to target wireless authentication or access.

2. Identified Vulnerabilities

- RF exposure beyond the physical perimeter
- Enterprise Wi-Fi authentication risks
- Improper 802.1X/EAP certificate validation
- Rogue-device and rogue-AP detection gaps
- Insufficient wireless intrusion prevention
- Physical-security weaknesses

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

40. Use WPA2-Enterprise or WPA3-Enterprise with 802.1X and strong EAP methods.
41. Validate server certificates correctly on all managed clients to prevent credential exposure to rogue authentication servers.
42. Perform RF surveys to identify signal leakage outside controlled areas.
43. Deploy wireless IDS/IPS to identify rogue APs, suspicious clients, and unusual RF behavior.
44. Integrate wireless alerts with physical surveillance and security response.
45. Use network-access control to verify device identity and security posture before granting access.

5. Overall Risk Rating

Critical

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

9. Australian Airport and In-Flight Evil-Twin Case, 2024

1. Incident Overview

The reported Australian case involved alleged creation of fake Wi-Fi access points imitating legitimate networks, illustrating how passengers can be tricked into connecting and disclosing personal information.

2. Identified Vulnerabilities

- SSID impersonation and evil-twin access points
- Automatic connection to remembered networks
- Fraudulent captive portals
- Certificate-warning bypass by users
- Passenger data exposure
- Insufficient rogue-AP detection and response

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

46. Use a clearly published official SSID and avoid relying on SSID appearance as the only trust signal.
47. Configure managed devices not to auto-connect to untrusted open networks.
48. Monitor airport/airline wireless space for rogue APs and impersonated SSIDs.
49. Use HTTPS everywhere and ensure captive portals do not request unnecessary sensitive information.
50. Provide passenger guidance explaining how to verify official Wi-Fi and report suspicious portals.
51. Create staff procedures for rapid identification, containment, evidence preservation, and escalation of rogue APs.

5. Overall Risk Rating

High

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.

10. Network Rail Public Wi-Fi Portal Compromise, 2024

1. Incident Overview

The reported incident involved unauthorized content appearing on public Wi-Fi landing pages after misuse of a legitimate administrator account, highlighting the importance of privileged-access security and supplier controls.

2. Identified Vulnerabilities

- Compromise or misuse of a legitimate privileged account
- Insufficient privileged-access management
- Weak or missing MFA
- Third-party supplier access risks
- Insufficient logging and account monitoring
- Weak change approval and configuration control
- Incident-response gaps

3. Vulnerability Assessment

Area	Assessment	Risk
Wireless / Network Access	Review encryption, authentication, RF exposure, and whether wireless clients can reach sensitive systems.	High
Segmentation / Access Control	Verify isolation of guest, corporate, POS, administrative, and sensitive environments using firewalls and least privilege.	High
Monitoring	Check centralized logging, rogue-AP detection, IDS/IPS, alerting, and response procedures.	Medium–High
Data / Credential Protection	Assess encryption, session/credential protection, MFA, endpoint controls, and sensitive-data handling.	High

4. Recommended Security Controls

- 52. Require MFA for all administrative and supplier accounts, preferably phishing-resistant methods.
- 53. Use PAM with least privilege, just-in-time access, session recording, and regular entitlement reviews.
- 54. Separate administrative interfaces from public Wi-Fi user networks.
- 55. Implement formal change approval, version control, configuration baselines, and rollback procedures.
- 56. Centralize logs and alert on unusual administrator login locations, times, and configuration changes.
- 57. Review third-party access contracts, credentials, monitoring, and offboarding procedures.
- 58. Maintain an incident-response playbook for public-portal compromise and service suspension.

5. Overall Risk Rating

High

6. Conclusion

The assessment shows that wireless security cannot be treated as an isolated access-layer issue. Strong encryption and authentication must be combined with segmentation, endpoint protection, monitoring, secure application protocols, privileged-access controls, and an effective incident-response process.