

AUTO-TUNE: FINDING AN OPTIMAL DISTANCE THRESHOLD FOR INFERRING HIV TRANSMISSION CLUSTERS

Steven Weaver^{1*}, Vanessa Davila Conn², Hannah Verdonk¹, Joel Wertheim³,
and Sergei L. Kosakovsky Pond¹

¹ Center for Viral Evolution, Temple University, Philadelphia, PA, USA

² Center for Research in Infectious Diseases, National Institute of Respiratory Diseases, Mexico City, Mexico

³ Department of Medicine, University of California, San Diego, CA

Correspondence*:
Steven Weaver
sweaver@temple.edu

2 ABSTRACT

3 Choosing an appropriate distance threshold is an important part of inferring a transmission net-
4 work to determine the relative growth of clusters within a localized epidemic. This distance
5 threshold determines how close two consensus sequences must be in order for a link to be
6 created between them in the network. Using a distance threshold that is too high can result in a
7 network with many unnecessary links, making it difficult to interpret and analyze. On the other
8 hand, using a distance threshold that is too low can result in a network with too few links, which
9 may not capture key insights into rapidly growing clusters among patients with shared attributes
10 that could benefit from public health intervention measures.

11 Here, we present a heuristic scoring approach for tuning a distance threshold by associating
12 each tested threshold against the maximal number of clusters created across all thresholds and
13 the difference between the ratio (R_{12}) of the largest cluster in the network to the second largest
14 cluster at each iteration. The number of clusters is normalized between $[0, 1]$ then gated via a
15 Gompertz function transform. Meanwhile, the distribution of all R_{12} ratios are converted to Z
16 scores, and normalized relative to the largest positive Z score across all candidate distances.
17 The priority score is the sum of aforementioned two components.

18 Published research using the HIV-TRACE software package frequently use the default thresh-
19 old of 1.5% for HIV pol gene sequences. We apply our scoring heuristic to outbreaks with different
20 characteristics, such as regional or temporal variability, and demonstrate the utility of using the
21 scoring mechanism's suggested distance threshold to identify clusters exhibiting risk factors that
22 would have otherwise been more difficult to identify. For example, while we found that a 1.5%
23 distance threshold is typical for US-like epidemics, recent outbreaks like the CRF07_BC subtype
24 among men who have sex with men (MSM) in China has been found to have a lower optimal
25 threshold of 0.5% to better capture the transition from injected drug use (IDU) to MSM as the pri-
26 mary risk factor. Alternatively, in communities surrounding Lake Victoria, where there has been
27 sustained transmission for several years, we found that a larger distance threshold is suitable to

capture a more risk factor diverse populace with sparse sampling over a longer period of time. Such identification may allow for more informed intervention action by respective public health officials.

Keywords: molecular epidemiology, HIV, network, transmission cluster, surveillance

1 INTRODUCTION

Choosing an appropriate distance threshold is an important part of using a transmission network to track the spread of a contagious disease. This distance threshold determines how close two individuals must be in order for a link to be created between them in the network.

Using a distance threshold that is too small can result in a network with many unnecessary links, making it difficult to interpret and analyze. On the other hand, using a distance threshold that is too large can result in a network with too few links, making it difficult to accurately track the spread of the disease.

To ensure that the transmission network is useful and informative, it is important to carefully consider the appropriate distance threshold. This may vary depending on the specific disease and the context in which it is spreading. For example, a highly contagious respiratory illness may require a smaller distance threshold than a less contagious illness that is primarily spread through direct contact.

In general, the goal is to strike a balance between having enough links to accurately track the spread of the disease, while not having so many links that the network becomes difficult to interpret. This can be achieved through careful analysis and consideration of the specific disease and context.

Overall, choosing an appropriate distance threshold is an important step in using a transmission network to track the spread of a contagious disease. It can help ensure that the network is useful and informative, and can ultimately aid in efforts to control and prevent the spread of the disease.

2 METHODS

2.1 Scoring Heuristic Procedure

Network threshold selection procedure proceeds as follows:

1. For each candidate threshold d_L , in increasing order, ranging from the smallest genetic distance in the dataset, up to either the largest distance or a predetermined maximal threshold, we compute two network statistics: R_{12} , the ratio of the largest cluster to the second largest cluster, and C – the number of clusters in the network.
2. A priority score is assigned to each d_L . This score measures two properties of the threshold: Does R_{12} jump at d_L ? How far is the number of clusters C at d_L from the maximal number of clusters over all threshold values? Let there be N overall d_L candidate values, and assume we are examining the i th candidate, d_L^i with $W < i \leq N - W$ (W is a positive integer defined below).
 - a. The R_{12} jump is computed by looking at the normalized ratio of the mean R_{12} values computed over the leading window $d_L^{i+1} \dots d_L^{i+W}$ and the trailing window $d_L^{i-W} \dots d_L^{i-1}$. The width of the window, W , is defined as $((\lfloor \frac{N}{100} \rfloor, 3), 30)$. The distribution of ratios is converted to Z scores, and normalized relative to the largest positive Z score across all candidate distances, yielding the jump component of the score.

- 63 b. The number of clusters, C_i at threshold d_L^i is first normalized to $[0, 1]$ through $\frac{C_{max}-C_i}{C_{max}-C_{min}}$ and next
 64 gated via a Gompertz function transform $1 - e^{-e^{-25x+3}}$. This function provides an ad hoc means
 65 for penalizing having too few clusters relative to the maximum over all ranges. For example, a
 66 threshold that yields 95% of the maximal number of clusters receives a score of 0.996, while a
 67 threshold that yields 85% - a score of 0.376.
- 68 c. The priority score for d_L^i is the sum of the two components defined in (a) and (b).
- 69 3. The threshold with the highest priority score will be selected as the suggested automatic distance
 70 threshold, if the score is high enough (1.9 or more), and either of the two conditions hold.
- 71 a. No other thresholds have priority scores of 1.9 or higher
- 72 b. If other thresholds have priority scores of 1.9 or higher, then the range of thresholds represented by
 73 these options is small (no more than $\log(N)$ times the mean step between successive d_L^i).
- 74 4. If no single threshold can be selected in step 3, then the one with the highest priority score is suggested,
 75 and an inspection of the plot like the one on the analyze page is recommended to ensure that the
 76 threshold is sensible.

77 2.2 Assortativity

78 Degree-weighted homophily (DWH) is a measure of similarity between nodes in a network based on
 79 their attributes (such as demographic characteristics or behaviors) and their degree (i.e., the number of
 80 connections they have to other nodes in the network). It is used to quantify the extent to which nodes
 81 with similar attributes tend to be connected to each other more frequently than would be expected by
 82 chance. DWH is calculated as the ratio of the observed number of connections between nodes with similar
 83 attributes to the expected number of connections between such nodes, based on their degree.

84 In mathematical terms, it is defined as:

$$DWH = \frac{W_M + W_C - 2W_X}{\frac{d_{in}}{nodes_{in}^2} + \frac{d_{out}}{nodes_{out}^2}} \quad (1)$$

85 Where

- 86 • W_M : Weight of in-group connections
- 87 • W_C : Weight of out-group connections
- 88 • W_X : Weight of cross-group connections
- 89 • d_{in} : In-group degree
- 90 • d_{out} : Out-group degree
- 91 • $nodes_{in}$: number of in-group nodes
- 92 • $nodes_{out}$: number of out-group nodes

93 DWH ranges from -1 to 1. A DWH value of 0 indicates that there is no more homophily than expected
 94 with chance, while a value of 1 indicates that there is perfect homophily (e.g. Birds always link to birds,
 95 and only birds). A value of -1 is achieved for perfectly disassortative networks (e.g. Bird never linking
 96 with another bird).

97 DWH is used in social network analysis and in the study of how different attributes are related to the
 98 formation of connections between individuals. It is used as a way to measure the similarity of attributes

between individuals in a network. Additionally, randomization is performed by shuffling attribute labels among nodes, then performing DWH computation. This is useful in creating a null distribution of DWH scores under random mixing. A panmictic range is reported by shuffling attributes multiple times and reporting the minimum and maximum score.

2.3 Implementation

The software implementation involves a step-by-step process that utilizes the HIV-TRACE suite of packages. It starts with calculating pairwise distances with the tn93 tool and a supplied multiple sequence alignment. This generated pairwise distances are supplied to the hivnetworkcsv script while providing the -A keyword argument. A brief outline of the software's implementation are as follows

1. Calculate pairwise distances: The user first calculates the pairwise distances using the tn93 fast pairwise distance calculator, providing the necessary threshold value and the input FASTA file. The command for this step is

```
1 tn93 -t 0.030 pol.fasta > pairwise_distances.15.tn93.csv
```

Please note that the threshold should include the maximal range one is intending to test.

2. Compute distance threshold scores: The hivnetworkcsv script is then executed with the required input file, format, and autotune option to generate a tab-separated output file, as shown below

```
1 hivnetworkcsv -i pairwise_distances.15.tn93.csv -f plain -A 0 > autotune_report.tsv
```

3. Visualize the report: Users can upload the generated autotune_report.tsv file to <http://autotune.datamonkey.org/analyze> for visualization and further analysis of the data. This web-based platform provides an interactive environment to explore scores and other metrics across the range of tested outputs.

4. Run HIV-TRACE: Once AUTO-TUNED threshold(s) are settled upon after review, the user runs the HIV-TRACE command with the appropriate input FASTA file, distance threshold, and other required arguments. The output is saved as a JSON file. An example command is

```
1 hivtrace -i ./INPUT.FASTA -a resolve -r HXB2.prrt -t < autotune_threshold > -m 500 -g .05
  ↪> hivtrace.results.json
```

2.3.1 Optional : Compute Assortativity Metrics

5. Annotate results: The hivnetworkannotate script is used to annotate the results obtained from the HIV-TRACE step with attributes. The script takes the JSON results file, node attributes file, schema file, and a resolve flag as input.

```
1 hivnetworkannotate -n hivtrace.results.json -a node_attributes.json -g schema.json -r
```

For more information, users can refer to the hivnetworkannotate documentation.

6. Analyze the results with DWH: After the results file has been annotated, the user can proceed to the assortativity page, <http://autotune.datamonkey.org/assortativity>, for further analysis of the output.

AUTO-TUNE is readily accessible on GitHub as part of the hivclustering repository (<https://github.com/veg/hivclustering>). It is integrated into the command-line interface of the software as the -A or -auto-profile argument. hivclustering is a key component of the HIV-TRACE suite of tools, a resource for the inference, analysis and visualization of HIV transmission networks.

The Degree Weighted Homophily (DWH) calculation tool, an integral component of the assortativity step, is developed using TypeScript, a statically typed superset of JavaScript that ensures robustness and scalability. In an effort to promote accessibility and ease of integration, the DWH tool is packaged and distributed through the Node Package Manager (NPM), enabling researchers and developers to conveniently incorporate this advanced analytical tool into their own projects and workflows. DWH can be used in-browser or as a command line tool, allowing researchers and developers to employ the tool in an interactive command-line interface or integrate it into larger software applications, thus catering to a diverse array of technical needs and preferences. Instructions for usage and installation is found on Github (<https://github.com/veg/dwh>).

The described workflow offers a systematic approach to analyze potential distance thresholds for one's data with AUTO-TUNE, from calculating pairwise distances to visualizing and annotating results.

2.4 Visualization

Visualizations of AUTO-TUNE results are accessible at <http://autotune.datamonkey.org/analyze>. It is a dynamic and interactive web-based platform that offers visualization and analysis of results generated by AUTO-TUNE. The website provides a comprehensive view of the data by generating various plots across candidate distance thresholds. These include a score plot, allowing users to identify trends and anomalies across the full range of thresholds. Additionally, it generates a graph showing the number of clusters across candidate thresholds, one of the components that contribute to the score. The site also includes an R1/R2 plot that displays the ratio of the largest cluster to the second largest cluster across candidate thresholds, which is the other metric that contributes to the scoring heuristic.

An assortativity tool is available at <http://autotune.datamonkey.org/assortativity>, and is an advanced analytical tool engineered to facilitate the calculation of Degree Weighted Homophily (DWH) values. It utilizes the DWH NPM package to generate a tabular representation of DWH values corresponding to each value for a selected attribute annotation, providing an exhaustive examination of the interrelationships for the field. A notable feature is the computation of the panmictic range, which involves a label permutation test to generate the null distribution of DWH values. This feature establishes a comparative baseline that aids in determining the significance of homophily versus what would be expected by chance. Lastly, the site also provides a plot of the fraction of pairwise connections, normalized by degree, for each value pertinent to the selected field. This visual depiction facilitates an intuitive comprehension of the distribution and interconnections within the dataset.

The site aims to offer a user-friendly interface for data visualization, playing an important role in interpreting and understanding AUTO-TUNE's output data. The visualization code is available on Github (<https://github.com/stevenweaver/autotune-app/>).

2.5 Data curation and analysis

3 RESULTS

3.1 Middle Tennessee, Seattle, and Alberta

3.2 Comparison with Prior Publications Citing HIV-TRACE

3.3

3.4 Effect on Subsampling Density

4 DISCUSSION

CONFLICT OF INTEREST STATEMENT

183 The authors declare that the research was conducted in the absence of any commercial or financial
184 relationships that could be construed as a potential conflict of interest.

AUTHOR CONTRIBUTIONS

185 The Author Contributions section is mandatory for all articles, including articles by sole authors. If an
186 appropriate statement is not provided on submission, a standard one will be inserted during the production
187 process. The Author Contributions statement must describe the contributions of individual authors referred
188 to by their initials and, in doing so, all authors agree to be accountable for the content of the work. Please
189 see here for full authorship criteria.

FUNDING

190 Details of all funding sources should be provided, including grant numbers if applicable. Please ensure to
191 add all necessary funding information, as after publication this is no longer possible.

ACKNOWLEDGMENTS

192 This is a short text to acknowledge the contributions of specific colleagues, institutions, or agencies that
193 aided the efforts of the authors.

SUPPLEMENTAL DATA

194 Supplementary Material should be uploaded separately on submission, if there are Supplementary Figures,
195 please include the caption in the same file as the figure. LaTeX Supplementary Material templates can be
196 found in the Frontiers LaTeX folder.

DATA AVAILABILITY STATEMENT

197 The datasets [GENERATED/ANALYZED] for this study can be found in the [NAME OF REPOSITORY]
198 [LINK].

REFERENCES

- 199 Bbosa, N., Ssemwanga, D., and Kaleebu, P. (2020). Short Communication: Choosing the Right Pro-
200 gram for the Identification of HIV-1 Transmission Networks from Nucleotide Sequences Sampled
201 from Different Populations. *AIDS research and human retroviruses* 36, 948–951. doi:10.1089/AID.
202 2020.0033
- 203 Brenner, B. G., Ibanescu, R.-I., Osman, N., Cuadra-Foy, E., Oliveira, M., Chaillon, A., et al. (2021). The
204 Role of Phylogenetics in Unravelling Patterns of HIV Transmission towards Epidemic Control: The
205 Quebec Experience (2002-2020). *Viruses* 13, 1643. doi:10.3390/v13081643
- 206 Chato, C., Kalish, M. L., and Poon, A. F. Y. (2020). Public health in genetic spaces: a statistical framework
207 to optimize cluster-based outbreak detection. *Virus Evolution* 6, veaa011. doi:10.1093/ve/veaa011

208 Dalai, S. C., Junqueira, D. M., Wilkinson, E., Mehra, R., Kosakovsky Pond, S. L., Levy, V., et al. (2018).
209 Combining Phylogenetic and Network Approaches to Identify HIV-1 Transmission Links in San Mateo
210 County, California. *Frontiers in Microbiology* 9, 2799. doi:10.3389/fmicb.2018.02799
211 Ding, X., Chaillon, A., Pan, X., Zhang, J., Zhong, P., He, L., et al. (2022). Characterizing genetic trans-
212 mission networks among newly diagnosed HIV-1 infected individuals in eastern China: 2012–2016.
213 *PLOS ONE* 17, e0269973. doi:10.1371/journal.pone.0269973. Publisher: Public Library of Science
214 H, Y., H, W., Y, X., L, H., Y, L., Q, L., et al. (2021). Acquisition and transmission of HIV-1 among
215 migrants and Chinese in Guangzhou, China from 2008 to 2012: Phylogenetic analysis of surveillance
216 data. *Infection, genetics and evolution : journal of molecular epidemiology and evolutionary genetics*
217 *in infectious diseases* 92. doi:10.1016/j.meegid.2021.104870. Publisher: Infect Genet Evol
218 Liu, M., Han, X., Zhao, B., An, M., He, W., Wang, Z., et al. (2020). Dynamics of HIV-1 Molecular
219 Networks Reveal Effective Control of Large Transmission Clusters in an Area Affected by an Epidemic
220 of Multiple HIV Subtypes. *Frontiers in Microbiology* 11, 604993. doi:10.3389/fmicb.2020.604993
221 Rhee, S.-Y., Magalis, B. R., Hurley, L., Silverberg, M. J., Marcus, J. L., Slome, S., et al. (2019). National
222 and International Dimensions of Human Immunodeficiency Virus-1 Sequence Clusters in a Northern
223 California Clinical Cohort. *Open Forum Infectious Diseases* 6, ofz135. doi:10.1093/ofid/ofz135
224 Sivay, M. V., Hudelson, S. E., Wang, J., Agyei, Y., Hamilton, E. L., Selin, A., et al. (2018). HIV-1
225 diversity among young women in rural South Africa: HPTN 068. *PloS One* 13, e0198999. doi:10.
226 1371/journal.pone.0198999
227 Yan, H., He, W., Huang, L., Wu, H., Liang, Y., Li, Q., et al. (2020). The Central Role of Nondisclosed Men
228 Who Have Sex With Men in Human Immunodeficiency Virus-1 Transmission Networks in Guangzhou,
229 China. *Open Forum Infectious Diseases* 7, ofaa154. doi:10.1093/ofid/ofaa154

TABLES

Table 1. Homophily Comparison

Dataset	Art’s Threshold Avg. Homophily	AUTO-TUNE Avg. Homophily
TN	0.0079	0.0147
Seattle	0.0259	0.0348
Canada	-0.0536	-0.0448

Table 2. Paper Comparison

PMID	Country	Collection Date	Threshold Used	AUTO-TUNE
29975689	South Africa	2011-2015	2.5%	2.584%
30574123	USA	1997-2008	2%	1.848%
32500089	China	2008-2015	0.5%	0.675%
32693608	Uganda	2009-2016	1.5%	1.707%
33281803	China	2000-2016	0.5%/0.7%	0.676%
33901684	China	2008-2012	1.5%	1.215%
34452506	Canada	1996-2017	1.5%/2.5%	0.547%
31041344	USA	1997-2017	1.5%	0.927%

5 FIGURE CAPTIONS