

# Contents

<b>What We've Got</b>	<b>2</b>
<b>DSE</b>	<b>2</b>
1    dse-sub1 . . . . .	2
2    dse-sub2 . . . . .	2
<b>Agent</b>	<b>2</b>
<b>Target</b>	<b>2</b>
1    target-sub1 . . . . .	2
2    target-sub2 . . . . .	2
3    target-sub3 . . . . .	2

## What We've Got

- Pretty good DSE extraction results. [1].
- Better than [2]'s Agent extraction results.
- Strange and very bad Target extraction results.

## DSE

### 1 Hyperparameter Tuning

### 2 Train with different Wordvector


## Agent

## Target

### 1 Using the Original RNN Structure

### 2 Merge the Input Labels

### 3 Multitasking



**Figure 1:** *Multitask RNN*



## Bibliography

- [1] Ozan Irsoy and Claire Cardie, Opinion Mining with Deep Recurrent Neural Networks, In *Proceedings of the Conference on Empirical Methods in Natural Language Processing*, 720–728, 2014, Doha, Qatar, <http://aclweb.org/anthology/D14-1080> [2](#)
- [2] Bishan Yang and Claire Cardie, Joint inference for fine-grained opinion extraction, 2013, In *Proceedings of ACL* [2](#)