



We will:

1. introduce main building blocks of Vehicle as a programming language



We will:

- 1. introduce main building blocks of Vehicle as a programming language
- 2. get to practice working with Vehicle



We will:

- 1. introduce main building blocks of Vehicle as a programming language
- 2. get to practice working with Vehicle
- 3. use the ACAS Xu benchmark to show Vehicle's verification work flow



We will:

- 1. introduce main building blocks of Vehicle as a programming language
- 2. get to practice working with Vehicle
- 3. use the ACAS Xu benchmark to show Vehicle's verification work flow
- 4. identify PL problems that are resolved by **Vehicle**

Recap: four PL problems



- Interoperability properties are not portable between training/counter-example search/ verification.
- Interpretability code is not easy to understand.
- Integration properties of networks cannot be linked to larger control system properties.
- E^G Embedding gap little support for translation between problem space and input space.

Recap: ACAS Xu




A collision avoidance system for unmanned autonomous aircraft.

Inputs:

- ightharpoonup Distance to intruder, ρ
- Angle to intruder, θ
- Intruder heading, φ
- ► Speed, *v_{own}*
- ► Intruder speed, *v_{int}*

Outputs:

- Clear of conflict
- Strong left
- Weak left
- ► Weak right
- Strong right



ACAS Xu



Definition (ACAS Xu: Property 3)

If the intruder is directly ahead and is moving towards the ownship, the score for COC will not be minimal.

$$1500 \leq \rho \leq 1800 \ \land -0.06 \leq \theta \leq 0.06 \ \land \psi \geq 3.10 \ \land v_{own} \geq 980 \ \land v_{int} \geq 960$$

$$\Rightarrow$$

$$\exists a \in \{SL, L, R, SR\}. f(\theta, \rho, \varphi, v_{own}, v_{int})_{COC} < f(\theta, \rho, \varphi, v_{own}, v_{int})_{a}$$

Types



Let us build the ACAS Xu specification.

We start with types of input and output vectors, as well as types of ACAS Xu networks

```
type InputVector = Vector Rat 5
type OutputVector = Vector Rat 5

@network
acasXu : InputVector -> OutputVector
```

The Vector type represents a mathematical vector, or in programming terms can be thought of as a fixed-length array.

Values



Types for values are automatically inferred by **Vehicle**. For example, we can declare the number π and its type will be inferred as rational:

pi = 3.141592



<u>Problem</u>: The trained ACAS Xu network assumes that the inputs and outputs are normalised to values (roughly) between -2 and 2.



<u>Problem</u>: The trained ACAS Xu network assumes that the inputs and outputs are normalised to values (roughly) between -2 and 2.

However, we want to write our specifications over the original units! (e.g. m/s)



<u>Problem</u>: The trained ACAS Xu network assumes that the inputs and outputs are normalised to values (roughly) between -2 and 2.

However, we want to write our specifications over the original units! (e.g. m/s)

This is an instance of the common problem space / input space mismatch



<u>Problem</u>: The trained ACAS Xu network assumes that the inputs and outputs are normalised to values (roughly) between -2 and 2.

However, we want to write our specifications over the original units! (e.g. m/s)

This is an instance of the common problem space / input space mismatch

Being able to write specifications about the problem space is a feature that distinguishes **Vehicle** from other neural network verifiers platforms.

Vector normalisation

For clarity, we define a new type synonym for unnormalised input vectors which are in the problem space.

```
type UnnormalisedInputVector = Vector Rat 5
```

Next we define the range of the inputs that the network is designed to work over.

```
minimumInputValues : UnnormalisedInputVector
minimumInputValues = [0.0, -pi , -pi , 100.0, 0.0]

maximumInputValues : UnnormalisedInputVector
maximumInputValues = [60261.0, pi, pi, 1200.0, 1200.0]

meanScalingValues : UnnormalisedInputVector
meanScalingValues = [19791.091, 0.0, 0.0, 650.0, 600.0]
```

Vector manipulation



An alternative method to vector definition is to use the 'foreach' constructor, which is used to provide a value for each 'index i'.

```
minimumInputValues : UnnormalisedInputVector
minimumInputValues = foreach i . 0
```

Let us see how 'foreach' works with vector indexing.

We can now define the normalisation function that takes an input vector and returns the unnormalised version.

```
normalise : UnnormalisedInputVector -> InputVector
normalise x = foreach i .
  (x ! i - meanScalingValues ! i) / (maximumInputValues ! i)
```

Vector manipulation



An alternative method to vector definition is to use the 'foreach' constructor, which is used to provide a value for each 'index i'.

```
minimumInputValues : UnnormalisedInputVector
minimumInputValues = foreach i . 0
```

Let us see how 'foreach' works with vector indexing.

We can now define the normalisation function that takes an input vector and returns the unnormalised version.

```
normalise : UnnormalisedInputVector -> InputVector
normalise x = foreach i .
   (x ! i - meanScalingValues ! i) / (maximumInputValues ! i)
... our first acquaintance with functions!
```



```
<name> : <type> <name> [<args>] = <expr>
```

Functions make up the backbone of the Vehicle language.



```
<name> : <type> <name> [<args>] = <expr>
```

Functions make up the backbone of the **Vehicle** language.

```
validInput : UnnormalisedInputVector -> Bool
validInput x = forall i .
  minimumInputValues ! i <= x ! i <= maximumInputValues ! i</pre>
```



```
<name> : <type> <name> [<args>] = <expr>
```

Functions make up the backbone of the Vehicle language.

```
validInput : UnnormalisedInputVector -> Bool
validInput x = forall i .
  minimumInputValues ! i <= x ! i <= maximumInputValues ! i</pre>
```

Our first acquaintance with predicates and quantifiers!

One of the main advantages of **Vehicle** is that it can be used to state and prove specifications that describe the network's behaviour over an infinite set of values.



Function Composition: Exercise

What are the types of functions 'acasXu' and 'normalise':

```
normAcasXu : UnnormalisedInputVector -> OutputVector
normAcasXu x = acasXu (normalise x)
```

Let's verify ACAS Xu!



```
distanceToIntruder = 0
                        -- measured in metres
angleToIntruder
                       -- measured in radians
intruderHeading
                  = 2 -- measured in radians
speed
                  = 3 -- measured in metres/second
intruderSpeed
                        -- measured in meters/second
clearOfConflict = 0
weakLeft
weakRight
strongLeft
               = 3
strongRight
               = 4
```

The fact that all vector types come annotated with their size means that it is impossible to mess up indexing into vectors, e.g. if you changed 'distanceToIntruder = 0' to 'distanceToIntruder = 5' the specification would fail to type-check.

Matthew Daggitt , Wen Kokke (online) , Ekaterina Komendantskaya • Neural Network Verification With Vehicle: Chapter 2 - Getting Started

Property 3



If the intruder is <u>directly ahead</u> and is moving towards the ownship, the score for COC will not be minimal.

Property 3



If the intruder is <u>directly ahead</u> and is moving towards the ownship, the score for COC will not be minimal.

```
directlyAhead : UnnormalisedInputVector -> Bool
directlyAhead x =
  1500 <= x ! distanceToIntruder <= 1800 and
  -0.06 <= x ! angleToIntruder <= 0.06</pre>
```

Property 3



If the intruder is <u>directly ahead</u> and is moving towards the ownship, the score for COC will not be minimal.

```
directlyAhead : UnnormalisedInputVector -> Bool
directlyAhead x =
  1500 <= x ! distanceToIntruder <= 1800 and
  -0.06 <= x ! angleToIntruder <= 0.06</pre>
```

Exercise!

1. Can you identify whether the specification is written in terms of input space or problem space? How do you know? Matthew Daggitt , Wen Kokke (online) , Ekaterina Komendantskaya • Neural Network Verification With Vehicle: Chapter 2 - Getting Started

Property 3



If the intruder is directly ahead and is <u>moving towards</u> the ownship, the score for COC will not be minimal.

Property 3



If the intruder is directly ahead and is <u>moving towards</u> the ownship, the score for COC will not be minimal.



If the intruder is directly ahead and is moving towards the ownship, the score for COC will not be minimal.



If the intruder is directly ahead and is moving towards the ownship, the score for COC will not be minimal.

```
minimalScore : Index 5 -> UnnormalisedInputVector -> Bool
minimalScore i x =
   forall j . i != j => normAcasXu x ! i < normAcasXu x ! j</pre>
```



If the intruder is directly ahead and is moving towards the ownship, the score for COC will not be minimal.

```
minimalScore : Index 5 -> UnnormalisedInputVector -> Bool
minimalScore i x =
   forall j . i != j => normAcasXu x ! i < normAcasXu x ! j</pre>
```

Exercise!

1. What kind of domain 'forall' ranges over? Is it finite or infinite?



If the intruder is directly ahead and is moving towards the ownship, the score for COC will not be minimal.



If the intruder is directly ahead and is moving towards the ownship, the score for COC will not be minimal.



If the intruder is directly ahead and is moving towards the ownship, the score for COC will not be minimal.

Exercise!

- 1. Can you guess the purpose of the '@property' syntax?
- 2. What kind of domain 'forall' ranges over? Is it finite or infinite?

How to run Vehicle



Checklist

- 1. Vehicle and Marabou are installed.
- 2. navigate to examples/chapter2/acasXu in the tutorial repo.

How to run Vehicle



Checklist

- 1. Vehicle and Marabou are installed.
- 2. navigate to examples/chapter2/acasXu in the tutorial repo.

Verifier limitations



Vehicle is very expressive...

Matthew Daggitt , Wen Kokke (online) , Ekaterina Komendantskaya • Neural Network Verification With Vehicle: Chapter 2 - Getting Started

Verifier limitations



Vehicle is very expressive... but most verifiers can only solve **linear** specifications with **non-alternating quantifiers**.


Verifier limitations




Vehicle is very expressive... but most verifiers can only solve **linear** specifications with **non-alternating quantifiers**.

What does Vehicle do when you write such a specification?





























Secondary type systems...



These secondary type-systems not possible without:

- A modular type-checker that is generic over the set of builtin types.
- Backtracking instance search.
- Automatic generalisation over unsolved metas and instance constraints.
- ▶ Dependent types (for operations over provenance information stored in the types).

Secondary type systems...




These secondary type-systems not possible without:

- A modular type-checker that is generic over the set of builtin types.
- Backtracking instance search.
- Automatic generalisation over unsolved metas and instance constraints.
- ▶ Dependent types (for operations over provenance information stored in the types).

The user is expected to make very little use of these features!

What we've seen in this chapter ...





Concluding Exercise



Which of the four PL problems we addressed?

- Interoperability properties are not portable between training/counter-example search/verification.
- Interpretability code is not easy to understand.
- Integration properties of networks cannot be linked to larger control system properties.
- E^G Embedding gap little support for translation between problem space and input space.



ACAS Xu Property 1 gives an idea how the *embedding gap* can arise not only when we reason about inputs, but also the outputs of networks!



ACAS Xu Property 1 gives an idea how the *embedding gap* can arise not only when we reason about inputs, but also the outputs of networks!

Definition (ACAS Xu: Property 1)

If the intruder is distant and is significantly slower than the ownship, the score of a COC advisory will always be below a certain fixed threshold:

$$(\rho \ge 55947.691) \land (v_{own} \ge 1145) \land (v_{int} \le 60)$$
 \Rightarrow the score for COC is at most 1500

where the neural network outputs are scaled as follows: given an element x of the output vector, we scale it as: $\frac{x-7.518884}{373.94992}$.



ACAS Xu Property 1 gives an idea how the *embedding gap* can arise not only when we reason about inputs, but also the outputs of networks!

Definition (ACAS Xu: Property 1)

If the intruder is distant and is significantly slower than the ownship, the score of a COC advisory will always be below a certain fixed threshold:

$$(\rho \ge 55947.691) \land (v_{own} \ge 1145) \land (v_{int} \le 60)$$
 \Rightarrow the score for COC is at most 1500

where the neural network outputs are scaled as follows: given an element x of the output vector, we scale it as: $\frac{x-7.518884}{373.94992}$.

- ► Can you formalise Property 1 in Vehicle?
- ► Can you spot the embedding gap, this time concerning the network's output?