

Installing the Sidecar

🕒 6 minute read ✖ page test

Injection

In order to take advantage of all of Istio's features, pods in the mesh must be running an Istio sidecar proxy.

The following sections describe two ways of injecting the Istio sidecar into a pod:

enabling automatic Istio sidecar injection in the pod's namespace, or by manually using the `istioctl` command.

When enabled in a pod's namespace, automatic injection injects the proxy configuration at pod creation time using an admission controller.

Manual injection directly modifies configuration, like deployments, by adding the proxy configuration into it.

If you are not sure which one to use, automatic injection is recommended.

Automatic sidecar injection

Sidecars can be automatically added to applicable Kubernetes pods using a mutating webhook admission controller provided by Istio.

While admission controllers are enabled by default, some Kubernetes distributions may disable them. If this is the case, follow the instructions to turn on admission controllers.

When you set the `istio-injection=enabled` label on a namespace and the injection webhook is enabled, any new pods that are created in that namespace will automatically have a sidecar added to them.

Note that unlike manual injection,

automatic injection occurs at the pod-level. You won't see any change to the deployment itself. Instead, you'll want to check individual pods (via `kubectl describe`) to see the injected proxy.

Deploying an app

Deploy sleep app. Verify both deployment and pod have a single container.

```
$ kubectl apply -f @samples/sleep/sleep.yaml@
$ kubectl get deployment -o wide
```

NAME	READY	UP-TO-DATE	AVAILABLE	AGE	CONTAINERS
sleep	1/1	1	1	12s	sleep
					curlimages/curl
					app=sleep

```
$ kubectl get pod
```

NAME	READY	STATUS	RESTARTS
sleep-8f795f47d-hdcgs	1/1	Running	0
			42s

Label the default namespace with `istio-injection=enabled`

```
$ kubectl label namespace default istio-injection=enabled --overwrite
$ kubectl get namespace -L istio-injection
```

NAME	STATUS	AGE	ISTIO-INJECTION
default	Active	5m9s	enabled
...			

Injection occurs at pod creation time. Kill the running pod and verify a new pod is created with the injected sidecar. The original pod has `1/1 READY` containers, and the pod with injected sidecar has `2/2 READY` containers.

```
$ kubectl delete pod -l app=sleep
$ kubectl get pod -l app=sleep
pod "sleep-776b7bcdcd-7hpnk" deleted
```

NAME	READY	STATUS	RE
STARTS AGE			
sleep-776b7bcdcd-7hpnk	1/1	Terminating	0
1m			
sleep-776b7bcdcd-bhn9m	2/2	Running	0
7s			

View detailed state of the injected pod. You should see the injected `istio-proxy` container and corresponding volumes.

```
$ kubectl describe pod -l app=sleep
```

```
...
Events:
  Type    Reason      Age   From          Message
  ----    -
  ...
  Normal  Created     11s   kubelet       Created container istio-init
  Normal  Started     11s   kubelet       Started container istio-init
  ...
  Normal  Created     10s   kubelet       Created container sleep
  Normal  Started     10s   kubelet       Started container sleep
  ...
  Normal  Created     9s    kubelet       Created container istio-proxy
  Normal  Started     8s    kubelet       Started container istio-proxy
```

Disable injection for the `default` namespace and verify new pods are created without the sidecar.

```
$ kubectl label namespace default istio-injection-
$ kubectl delete pod -l app=sleep
$ kubectl get pod
namespace/default labeled
pod "sleep-776b7bcdcd-bhn9m" deleted
```

NAME	READY	STATUS	RE
STARTS AGE			
sleep-776b7bcdcd-bhn9m	2/2	Terminating	0
2m			
sleep-776b7bcdcd-gmvnr	1/1	Running	0
2s			

Controlling the injection policy

In the above examples, you enabled and disabled injection at the namespace level. Injection can also be controlled on a per-pod basis, by configuring the `sidecar.istio.io/inject` label on a pod:

Resource	Label	Enal

Namespace	istio-injection	enabl
Pod	sidecar.istio.io/inject	"true

If you are using control plane revisions, revision specific labels are instead used by a matching `istio.io/rev` label. For example, for a revision named `canary`:

Resource	Enabled label	
Namespace	istio.io/rev=canary	istio-inj
Pod	istio.io/rev=canary	sidecar..

If the `istio-injection` label and the `istio.io/rev` label are both present on the same namespace, the `istio-injection` label will take precedence.

The injector is configured with the following logic:

1. If either label is disabled, the pod is not injected
2. If either label is enabled, the pod is injected
3. If neither label is set, the pod is injected if `.values.sidecarInjectorWebhook.enableNamespacesByDefault` is enabled. This is not enabled by default, so generally this means the pod is not injected.

Manual sidecar injection

To manually inject a deployment, use `istioctl kube-inject`:

```
$ istioctl kube-inject -f @samples/sleep/sleep.yaml  
@ | kubectl apply -f -  
serviceaccount/sleep created  
service/sleep created  
deployment.apps/sleep created
```

By default, this will use the in-cluster configuration. Alternatively, injection can be done using local copies of the configuration.

```
$ kubectl -n istio-system get configmap istio-sidecar-injector -o=jsonpath='{.data.config}' > inject-config.yaml  
$ kubectl -n istio-system get configmap istio-sidecar-injector -o=jsonpath='{.data.values}' > inject-values.yaml  
$ kubectl -n istio-system get configmap istio -o=jsonpath='{.data.mesh}' > mesh-config.yaml
```

Run `kube-inject` over the input file and deploy.

```
$ istioctl kube-inject \
  --injectConfigFile inject-config.yaml \
  --meshConfigFile mesh-config.yaml \
  --valuesFile inject-values.yaml \
  --filename @samples/sleep/sleep.yaml@ \
  | kubectl apply -f -
serviceaccount/sleep created
service/sleep created
deployment.apps/sleep created
```

Verify that the sidecar has been injected into the sleep pod with 2/2 under the READY column.

```
$ kubectl get pod -l app=sleep
```

NAME	READY	STATUS	RESTARTS
sleep-64c6f57bc8-f5n4x	2/2	Running	0

24s

Customizing injection

Generally, pod are injected based on the sidecar injection template, configured in the `istio-sidecar-injector` configmap. Per-pod configuration is available to override these options on individual pods. This is done by adding an `istio-proxy` container to your pod. The sidecar injection will treat any configuration defined here as an override to the default injection template.

Care should be taken when customizing these settings, as this allows complete customization of the resulting `Pod`, including making changes that cause the sidecar container to not function properly.

For example, the following configuration customizes a variety of settings, including lowering the CPU requests, adding a volume mount, and adding a `preStop` hook:

```
apiVersion: v1
kind: Pod
metadata:
  name: example
spec:
  containers:
    - name: hello
      image: alpine
    - name: istio-proxy
      image: auto
      resources:
        requests:
          cpu: "100m"
  volumeMounts:
    - mountPath: /etc/certs
      name: certs
  lifecycle:
    preStop:
      exec:
        command: ["sleep", "10"]
  volumes:
    - name: certs
      secret:
        secretName: istio-certs
```


In general, any field in a pod can be set. However, care must be taken for certain fields:

- Kubernetes requires the `image` field to be set before the injection has run. While you can set a specific image to override the default one, it is recommended to set the `image` to `auto` which will cause the sidecar injector to automatically select the image to use.
- Some fields in `Pod` are dependent on related settings. For example, CPU request must be less than CPU limit. If both fields are not configured together, the pod may fail to start.

Additionally, certain fields are configurable by `annotations` on the pod, although it is recommended to use the above approach to customizing settings.

Custom templates

(experimental)



This feature is experimental and subject to change, or removal, at any time.

Completely custom templates can also be defined at installation time. For example, to define a custom template that injects the `GREETING` environment variable into the `istio-proxy` container:


```
apiVersion: install.istio.io/v1alpha1
kind: IstioOperator
metadata:
  name: istio
spec:
  values:
    sidecarInjectorWebhook:
      templates:
        custom: |
          spec:
            containers:
              - name: istio-proxy
                env:
                  - name: GREETING
                    value: hello-world
```

Pods will, by default, use the `sidecar` injection template, which is automatically created. This can be overridden by the `inject.istio.io/templates` annotation. For example, to apply the default template and our customization, you can set `inject.istio.io/templates=sidecar,custom`.

In addition to the `sidecar`, a `gateway` template is provided by default to support proxy

injection into Gateway deployments.