Online Tuning of Storage Ring Nonlinear Dynamics

and Fast ORM Measruement at SIRIUS

Optics Tuning and Corrections for Future Colliders Workshop

CERN, June 27, 2023



Matheus M. S. Velloso

Brazilian Synchrotron Light Laboratory (LNLS/CNPEM)

Gleb Wataghin Institute of Physics (IFGW/UNICAMP)

on behalf of the LNLS Accelerator Physics Group

Introduction

Online tuning of storage ring non-linear dynamics

Fast ("AC") Measurement of Orbit Response Matrix

SIRIUS storage ring

4th generation storage ring based Synchrotron Light Source with 250 pm rad emittance. Designed, built and operated by the Brazilian Synchrotron Light Laboratory (LNLS), at the Brazilian Center for Research in Energy and Materials (CNPEM), Campinas, Brazil.

Parameter		Currently	Phase I
Energy	E_0	3 GeV	
Current	I_0	100 mA	350 mA
Operation mode		Top-up	
Lifetime	τ	15 h	> 10 h
RF Cavities		1 NC	2 SC + HC
RF Voltage	$\hat{V}_{\mathrm{rf}}$	1.5 MV	3.0 MV
RF Frequency	f_{rf}	499.667 MHz	
Harmonic Number	h	864	
Momentum compaction factor	α	1.6×10^{-4}	
Energy Spread	σ_δ	8.5×10^{-4}	
Bunch length	σ_z	2.5 mm	12 mm
Energy loss p/ turn	U_0	470 keV	870 keV

SIRIUS Lattice and Optics

20×5BA lattice, with 5-fold symmetric high (A) and low (B, P) betatron functions sections: 1 Superperiod = A-B-P-B





Introduction

Online tuning of storage ring non-linear dynamics

Fast ("AC") Measurement of Orbit Response Matrix

Off-axis injection scheme



RCDS Dynamic Aperture Optimization Setup

Robust conjugate direction search (RCDS) for DA optimization:

- objective function:
  - avg. injection efficiency of 5 pulses @ 2 Hz ($\sigma \approx 1\%$)
  - beam steered to the DA border to reduce efficiency
  - kick resilience optimization $\not\Longrightarrow$ injection efficiency optimization
- available knobs: 21 sextupole families
  - chromaticity response matrix nullspace singular-vectors (13, 17 knobs)
  - 13 free families + 6 compensation families
- Tuning in 3 machine working points: higher fractional tunes to reduce amplification factors and improve orbit stability

More details:
M. M. S. Velloso, M. B. Alves, L. Liu, X. R. Resende, F. H. de Sá, and X. Huang, in *Proc. IPAC'23* Venezia, 05 2023, pp. 3222-3226
About RCDS:
X. Huang, J. Corbett, J. Safranek, J. Wu, *Nucl. Instr. Meth.*, vol 726, pp.77-83, 2013.
X. Huang, J. Safranek, *Phys. Rev. ST Accel. Beams*, vol 18, p.18

SIRIUS sextupole families

achromatic	SFA0, SDA0, SFB0, SDB0, SDP0, SFP0
chromatic	SDA1, SFA1, SDA2, SFA2, SDA3, SDB1, SFB1 SDB2, SFB2, SDB3, SFP1, SDP1, SDP2, SFP2 SDP3

Tuning at $\nu_x = 49.08, \nu_y = 14.14$ (Working Point 1)



Tuning at $\nu_x = 49.08, \nu_y = 14.14$ (Working Point 1)





Tuning at $\nu_x = 49.08, \nu_y = 14.14$ (Working Point 1)





configuration	injection efficiency [%]	lifetime @ 60 mA
ref-config	88 ± 8	21 hrs
run 1	91 ± 1	
run 2	98 ± 1	20 hrs
run 3	87 ± 3	

Tuning at $\nu_x = 49.08, \nu_y = 14.14$ (Working Point 1)





configuration	injection efficiency [%]	lifetime @ 60 mA
ref-config	88 ± 8	21 hrs
run 1	91 ± 1	
run 2	98 ± 1	20 hrs
run 3	87 ± 3	



Tuning at $\nu_x = 49.20, \nu_y = 14.25$ (Working Point 2)



Tuning at $\nu_x = 49.20, \nu_y = 14.25$ (Working Point 2)





Tuning at $\nu_x = 49.20, \nu_y = 14.25$ (Working Point 2)





configuration	injection efficiency [%]	lifetime @ 60 mA
non-optimized	51 ± 1	18 hrs
run 1	79 ± 3	21 hrs
run 2	65 ± 1	

Tuning at $\nu_x = 49.20, \nu_y = 14.25$ (Working Point 2)





configuration	injection efficiency [%]	lifetime @ 60 mA
non-optimized	51 ± 1	18 hrs
run 1	79 ± 3	21 hrs
run 2	65 ± 1	



Tuning at $\nu_x = 49.16, \nu_y = 14.22$ (Working Point 3)



Tuning at $\nu_x = 49.16, \nu_y = 14.22$ (Working Point 3)





Tuning at $\nu_x = 49.16, \nu_y = 14.22$ (Working Point 3)





configuration	injection efficiency [%]	lifetime @ 60 mA
non-optimized		
optimized	93 ± 3	19.5 hrs

Tuning at $\nu_x = 49.16, \nu_y = 14.22$ (Working Point 3)





configuration	injection efficiency [%]	lifetime @ 60 mA
non-optimized		
optimized	93 ± 3	19.5 hrs



Orbit stability improvements

WP 3 contributed for SIRIUS recent achievement of reaching $< 1\%$ σ_x and $< 4\%$ σ_y orbit rms variations in the horizontal and vertical planes, respectively.



L. Liu *et al.*, "Status of SIRIUS operation with users", presented at the IPAC'23, Venice, Italy, May 2023, paper WEOGA2.

Courtesy of Daniel Tavares

Summary

- Oline tuning with RCDS is effective at optimizing injection efficiency
- optimizing injection efficiency $\not\Rightarrow$ larger kick resiliency/larger phase portrait areas

Introduction

Online tuning of storage ring non-linear dynamics

Fast ("AC") Measurement of Orbit Response Matrix

AC ORM Measurement



M.M.S. Velloso, M.B. Alves, and F.H. de Sá, "Fast Orbit Response Matrix Measurement via Sine-Wave Excitation of Correctors at SIRIUS", in *Proc. IPAC'22*, Bangkok, Thailand, Jun. 2022, pp. 425–428.

- Fitting to i-th BPM data $u_i(t_j)$:

$$\begin{bmatrix} \cos(2\pi f_1 t_1) & \sin(2\pi f_1 t_1) & \dots \\ \cos(2\pi f_1 t_2) & \sin(2\pi f_1 t_2) & \dots \\ \vdots & \vdots & \\ \cos(2\pi f_1 t_n) & \sin(2\pi f_1 t_n) & \dots \end{bmatrix} \begin{bmatrix} b_{i1} \\ c_{i1} \\ \vdots \\ b_{im} \\ c_{im} \end{bmatrix} = \begin{bmatrix} u_i(t_1) \\ u_i(t_2) \\ \vdots \\ u_i(t_n) \end{bmatrix}$$

- Expected beam motion

$$\Delta u_i(t_n) = \sum_j a_{i,j} \sin(2\pi f_j t_n + \phi_{i,j})$$

$$a_{i,j} = \sqrt{b_{i,j}^2 + c_{i,j}^2}, \quad \phi_{i,j} = \mathrm{atan2}(b_{i,j}, c_{i,j}) \in (-\pi, \pi]$$

- ORM elements:

$$M_{ij} = \mathrm{sgn}(\phi_{i,j}) \frac{a_{i,j}}{\Delta\theta_j},$$

Measurements at SIRIUS storage ring

SIRIUS BPMs-CMs circuit

- 160 BPMs
- $n_x = 120$ CHs, $n_y = 160$ CVs,
  $n = n_x + n_y = 280$ CMs

Measurements at SIRIUS storage ring

SIRIUS BPMs-CMs circuit

- 160 BPMs
- $n_x = 120$ CHs, $n_y = 160$ CVs,
  $n = n_x + n_y = 280$ CMs

Measurement Procedure

- At each one of the **20 sectors**,
  - **6 CHs** $f_x = 3, 7, 13, 19, 29, 37$ Hz
  - **8 CVs** $f_y = 5, 11, 17, 23, 31, 41, 47, 59$ Hz
  - prime frequencies to easily distinguish nonlinear harmonics
  - 5 µrad strength, during 4 seconds.
  - integer number of oscillations, orthogonal harmonics
- The complete measurement
  - 30 mins for DC method
  - $2.5 - 3$ mins AC method

Measurements at SIRIUS storage ring

SIRIUS BPMs-CMs circuit

- 160 BPMs
- $n_x = 120$ CHs, $n_y = 160$ CVs,
  $n = n_x + n_y = 280$ CMs

Measurement Procedure

- At each one of the **20 sectors**,
  - **6 CHs** $f_x = 3, 7, 13, 19, 29, 37$ Hz
  - **8 CVs** $f_y = 5, 11, 17, 23, 31, 41, 47, 59$ Hz
  - prime frequencies to easily distinguish nonlinear harmonics
  - 5 µrad strength, during 4 seconds.
  - integer number of oscillations, orthogonal harmonics
- The complete measurement
  - 30 mins for DC method
  - $2.5 - 3$ mins AC method

Measurements at SIRIUS storage ring

SIRIUS BPMs-CMs circuit

- 160 BPMs
- $n_x = 120$ CHs, $n_y = 160$ CVs, $n = n_x + n_y = 280$ CMs

Measurement Procedure

- At each one of the **20 sectors**,
  - **6 CHs** $f_x = 3, 7, 13, 19, 29, 37$ Hz
  - **8 CVs** $f_y = 5, 11, 17, 23, 31, 41, 47, 59$ Hz
  - prime frequencies to easily distinguish nonlinear harmonics
  - 5 µrad strength, during 4 seconds.
  - integer number of oscillations, orthogonal harmonics
- The complete measurement
  - 30 mins for DC method
  - $2.5 - 3$ mins AC method



Thank you!

matheus.velloso@lnls.br

M. M. S. Velloso is supported by the São Paulo Reseach Foundation (FAPESP) via Grant #2022/04162-4

CNPEM
Brazilian Center for Research
in Energy and Materials

MINISTRY OF
SCIENCE TECHNOLOGY
AND INNOVATION